

EB-PU2113W

13,000-Lumen 3LCD Laser Projector with 4K Enhancement



Premium large venue laser projector with 4K Enhancement¹.









Incredible color — Epson® 3-chip 3LCD technology produces 13,000 lumens of equal white and color brightness²

WUXGA with 4K Enhancement¹ — accepts 4K content and delivers up to 4.6 million pixels on-screen for an incredibly crisp and vibrant image

Long-lasting laser light source — 20,000-hour virtually maintenance-free laser light source³

Simplified installation — 9 optional powered lenses (sold separately), including an ultra short throw .35 throw lens with unique zero offset design, provide enhanced flexibility and convenience during installation

Engineered for reliability — hermetically sealed optical engine offers high dust resistance while filterless cabinet and liquid cooling system support easy, low-maintenance operation

Outstanding image quality — high native contrast ratio produces deep blacks; frame interpolation delivers realistic moving images; HDR support⁴ and scene adaptive gamma correction for true-to-life images

Fast installation — built-in NFC functionality⁵ to streamline multi-projector installations using the easy-to-use Epson Projector Configuration Tool (EPCT)⁶ mobile app for Android™ and iOS®

Optional attachable PixAlign™ camera — provides access to powerful features, including projector stacking assist function⁷, tiling assist⁷ for edge blends, color calibration⁸ and screen matching⁸

Simple Blending and Simple Stacking functions⁸ — for fast blending or stacking of two projectors using a remote controller instead of conventional setup with a PC and router; requires optional attachable PixAlign camera⁸

Optional attachable PixAlign™ camera — provides access to powerful features, including projector stacking assist function⁷, blending assist⁷ for edge blends, color calibration⁸ and screen matching⁸ from the projector menu or Epson Projector Professional Tool (EPPT) app⁹



EB-PU2113W 13,000-Lumen 3LCD Laser Projector with 4K Enhancement¹

Specifications

Projection System High-aperture Epson 3LCD 3-chip technology

Projection Method Front/rear/ceiling mount **Driving Method** Poly-Silicon TFT Active Matrix Pixel Number 2,304,000 dots (1920 x 1200) x 3

Signal Input Maximum Display Resolution: 4096 x 2160 (resizing display): Display Resolution: 1920 x 1200 pixels Native Resolution WUXGA with 4K Enhancement (1920 x 1200 x 2)

Resolution on Screen WUXGA with 4K Enhancement¹/ 4.6 million pixels

Aspect Ratio Supports 4:3, 16:10, 16:9*, 21:9* * With vertical image shift control within letterbox area.

Pixel Arrangement Cross stripe Color Brightness² Color Light Output: 13,000 lumens White Brightness² White Light Output: 13,000 lumens

Contrast Ratio 2,500,000:1 (Dynamic Contrast: On) **Brightness Uniformity (Typical)** 85% Color Reproduction Up to 1.07 billion colors Keystone Correction Vertical: ±45 degrees;

Horizontal: ±30 degrees Illumination Technology Laser Diode

Projection Lens (Standard)

Visit Epson.com for information on optional lenses.

Standard Lens ELPLM15 (sold separately)

Type Powered shift/focus/zoom **F-Number** 2.0 - 2.1

Focal Length 14.8 mm - 17.7 mm **Zoom Ratio** Optical Zoom: 1.0 - 1.6 Throw Ratio Range 1.57 - 2.56 Lens Shift Vertical: ±60%; Horizontal: ±18%

Other Features

Operating Temperature 32 °F to 122 °F (0 °C to 50 °C) Power Supply Voltage $100 \text{ V} - 240 \text{ V} \text{ AC} \pm 10\%, 50 \text{ Hz} - 60 \text{ Hz}$ **Power Consumption**

886 W (Normal/Custom) 646 W (Quiet/Extended) 2.0 W Standby (Network Standby)

0.4 W Standby (Energy Saving)

Fan Noise 34 dB (Normal Mode); 29 dB (ECO)

IP Rating IP5X10

Security Security cable hole, lens lock, Kensington® lock provision, wireless LAN unit lock

Video I/O

Input Signal Input Video Signal (HDMI®, DVI-D and HDBaseT® ports) 480i/480p/576i/576p/720p/1080i/1080p/3840 x 2160/

Auto Power On Signal Detection on HDMI/Plug-In Detection (HDMI, VGA 15-pin)

Sleep Mode Yes (with timer) **HDMI CEC Control** Yes

Interfaces

HDMI x 1 (HDCP 2.3) HDBaseT x 1 DVI-D x 1 VGA x 1

Variable Audio Out: Mini Stereo x 1 USB Type-B x 1 USB Type-A x 2 (5 V, 2.0 A)

USB Type-A for Wireless LAN (optional) Serial: RS-232c x 1 (9-pin) Remote Mini Stereo

Network: RJ-45



Dimensions (W x D x H)

Including Feet 23.1" x 19.4" x 8.6' Weight 52.4 lb (23.8 kg)

Remote Control

Features Power, Source Search Selection, Lens Shift/Zoom/ Focus, Test Pattern Selection, A/V Mute, Freeze, User ID, Auto Aspect, Color Mode, Number, Page Up and Down, E-Zoom, Volume, Help, Menu, Enter, ESC and Pointer Functions

Operating Angle

Front: Right/Left: 60 to +60; Upper/Lower: +30 to 30 degrees Rear: Right/Left: 30 to +30; Upper/Lower: +40 to +10 degrees **Operating Distance** 98 ft

Eco Features

RoHS compliant

End-of-life options available¹¹

Epson America, Inc. is a SmartWay® Transport Partner12

Limited Warranty and Service

Warranty Three-year limited or 20,000 hours, whichever comes first in the U.S. and Canada

Service Toll-free telephone support, Monday through Friday Epson ConnectionSM

Pre-Sales Support (U.S. and Canada): 800-463-7766 Website: www.epson.com

Epson PreferredSM Plus Extended Service Plan

EPPPRJPUE5

3-Year Upgrade to Next-Business-Day Whole Unit Exchange¹³ for Years 1-3 EPPPRJPU3

5-Years Next-Business-Day Whole Unit Exchange 13 for Years 1-5

Other extended service plans may be available

What's Included

EB-PU2113W projector, power cable, remote control with 2 batteries, cable cover, user guide and warranty sheet

Ordering Information

EB-PU2113W V11HA65920 Ultra Short Throw Lens (ELPLX02S) V12H004X0B Ultra Short Throw Lens - White (ELPLX02WS) V12H004Y0B Short Throw #1 Zoom Lens (ELPLU03S) V12H004UA3 V12H004U04 Short Throw #2 Zoom Lens (ELPLU04) Wide Throw #2 Zoom Lens (ELPLW06) V12H004W06 Wide Throw #3 Zoom Lens (ELPLW08) V12H004W08 Middle Throw #2 Zoom Lens (ELPLM15) V12H004M0F Middle Throw #3 Zoom Lens (ELPLM10) V12H004M0A V12H004M0B Middle Throw #4 Zoom Lens (ELPLM11) Long Throw Zoom Lens (ELPLL08) V12H004L08 Rigging Frame (ELPMB59) V12H996A01 Wireless LAN Module (ELPAP11) V12H005A02 Projector Ceiling Mount (ELPMB67) V12HA54010 Suspension Adapter (ELPFP15) V12HA55010 PixAlign Camera (ELPEC01) V12HA46010

1 4K Enhancement Technology shifts each pixel to surpass Full HD resolution on screen. 2 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. 3 No required maintenance for the light source for up to 20,000 hours. Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m3 of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period. | 4 HDR performance available with select third-party devices. For more information, see www.epson.com/hdrcompatibility | 5 NFC requires use of a device that includes NFC and may require additional software. | 6 Epson Projector Configuration Tool app for Android and iOS. Internet connection required for download; data usage fee may apply. | 7 Requires Epson external camera or built-in camera for each projector and the Epson Projector Professional Tool app. | 8 Using separate camera for each projector. | 9 Mac® and PC only. |
10 IP5X-certified optical engine and laser light source module in accordance with IEC standard 60529. | 11 For convenient and reasonable recycling options, visit www.epson.com/recycle | 12 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency. | 13 Product comes with a 3-year limited warranty with the option to purchase Extended Service Plans up to a total of 5 years of continuous coverage. Extended Service Plan must be purchased within 90 days of hardware purchase. See individual service plan for details. Expedited shipping not available in all areas. Orders must be placed and processed by 1 p.m. Pacific Time, Monday through Friday, excluding holidays.

See the latest innovations from Epson Business Solutions at www.epson.com/forbusiness



Epson America, Inc. 3131 Katella Ave., Los Alamitos, CA 90720 **Epson Canada Limited** 185 Renfrew Drive, Markham, Ontario L3R 6G3 www.epson.com

Specifications and terms are subject to change without notice. EPSON is a registered trademark of Seiko Epson Corporation. PixAlign is a trademark of Epson America, Inc. and Epson Connection and Epson Preferred are service marks of Epson America, Inc. Mac is a trademark of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google LLC. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2023 Epson America, Inc CPD-62051R3 11/23

Contact:	