POINT-OF-SALE PRINTER
TM-T88VII

EPSON

TM-T88VII

Wall Mount   Compact   Auto Cutter   Print

FAST BILLING MEETS LEGENDARY RELIABILITY

Accelerate your billing and cut back on long queues with Epson's latest TM-T88VII thermal receipt printer. With fast print speeds and flexible connectivity options, the TM-T88VII is ideal for high-volume environments in hospitality, retail, grocery, banking and more. Low power consumption and an advanced paper-saving function[1] helps reduce your environmental impact. With Epson's TM Utility app, setting up an Epson bill printer is easy and the vertical mounting kit provides a range of flexible configurations.

High Performance
Fast print speeds of 500 mm/s[2] with high-speed auto-cutter for fast transactions.

Integrated Connectivity
The printer can be dynamically shared by PC-POS terminals, tablets, and mobile devices as well as cloud servers.

POS Peripheral Support
Supports POS peripherals including barcode scanners, payment terminals and customer displays.

*1 Paper savings depend on the text and graphics printed on the receipt.
*2 Under standard test conditions.

SPECIFICATIONS
TM-T88VII

EPSON

MODEL NUMBER	TM-T88VII	
SKU Numbers	C31CJ57712	C31CJ57722
Connectivity	USB+LAN+SERIAL	USB+LAN+PARALLEL
Printing Technology	Thermal Line Printing	
Printing Method	500 mm / sec	
Max. Printing Speed	108 x 108 dpi	
Print Resolution	79.5 + 0.5 mm / 57.5 + 0.5 mm	
Paper Width		
Print Width	80 mm Setting: 72 mm (Left Margin: 2.65 mm & Right Margin: 4.85 mm)	
	58 mm Setting: 52.5 mm (Left Margin: 2.65 mm & Right Margin: 2.35 mm)	
Print Font		
Font	80 mm Setting: Font-A (48 characters / line), Font-B (64 characters / line)	
	58 mm Setting: Font-A (35 characters / line), Font-B (46 characters / line)	
Barcode Fonts	Yes, supports 1D and 2D Barcode symbols	
UTF-8 Fonts Support	Yes, supported	
Character Set	95 alphanumeric characters, 18 international sets, 128 x 43	
	pages extended graphics	
Character Structure	Special Font A: 12 x 24 dots	
	Special Font B: 9 x 24 dots	
Paper Guide Spacer	Yes, for 58 mm Paper roll (Auto Sensing) and 40 mm roll (Manual Setting)	
Sensors	Paper End, Cover Open, Near End Sensor	
Paper Load	Drop in Paper Loading	
Roll Specifications	Diameter: 108 mm (4.02"), Thickness: Max 0.103 mm	
Auto-cutter Type	V Cutter type (Partial Cut) - One uncut point in center	
Auto-cutter Life	3 Million Cuts - One Point un-cut on the left edge150 km	
Printhead Life	200 km	
Reliability (MTBF & MCBF)	360,000 Hours & 70 Million Lines	
Colour	EBCK (Epson Black)	
Options	Wall Mount Kit, External Buzzer	
Interface	Standard : USB, Ethernet (10/100 Base TX), RS-232C Serial;	
	Connectivity for Cash Drawer / Optional External Buzzer	
Power		
Power Supply	DC +24 Volts External Power Supply (PS-190)	
Acoustic Noise	52 dBA	
General Information		
Printer Driver	Epson Advanced Printer Driver 6 for TM-L 100 (APD),TM Virtual Port Driver	
NV Area	Graphics Area 384 KB, Bit Image Memory 1 KB	
Audible Alert	Built-in buzzer, optional external buzzer	
Sensors	Paper End, Cover Open, Near End Sensor	
Software	TM Utility (iOS, Android & Windows),	
	TM Deployment Tool, Monitoring Tool	
Overall Dimensions		
(W x D x H)	140 mm x 148.5 mm x 207 mm	
Weight	1.6 kg	
Warranty	1 year	

TM-T88VII
Dimensions & Weight
Weight: 1.6 kg (3.53 lbs)

207 mm
140 mm
148.5 mm

Information correct as of March 2025.

Dealer's Stamp

Epson Helpline: For product info or service - 1800 425 0011
For service: 1800 123 001 600 or 1860 3000 1600 (9 am - 6 pm) (Mon- Sat)
Email: pos@eid.epson.co.in

www.epson.co.in

eClean
e-Waste to e-Clean
call . clear . clean

EPSON SERVICE