

BrightLink[®] 536Wi Interactive WXGA 3LCD Projector



Product shown with optional wall mount. Sold separately.

The short-throw interactive projector for collaboration in any classroom.

Up to 3x Higher Color Brightness¹, and reliable performance — 3LCD, 3-chip technology

One measurement of brightness is not enough — look for both high color brightness and high white brightness. The BrightLink 536Wi has:

Color/Interactive Brightness: 3,400 lumens²

White/Interactive Brightness: 3,400 lumens²

Easy-to-use, interactive teaching tool — fully integrated, dual pen-based interactivity³ transforms any wall or existing whiteboard into an interactive display

Large, engaging presentations, even in small spaces — built-in short-throw lens projects images 53" up to 116" from less than 4' away with virtually no glare or shadows

Convenient collaboration for BYOD classrooms — wirelessly share⁴ and compare students' work from multiple devices, simultaneously, with Moderator device management software⁵

PC-free annotations — write on images projected directly from an iPad[®], iPhone[®], iPod[®], Android device, document camera or Blu-ray Disc[®] player, no computer necessary

Includes 1-year subscription and support for SMART Learning Suite — SMART Notebook[®], SMART amp[™], SMART lab[™], SMART Learning Suite Online and more

Wireless projection from an array of devices — project from iPad, iPhone, Android tablets and smartphones with the free Epson iProjection[™] App⁴ (wireless module sold separately)

Long-lasting, low-cost lamps — up to 10,000 hours in ECO Mode⁶



Specifications

Projection System Epson 3LCD, 3-chip technology
Projection Method Front/wall mount
Driving Method Epson Poly-silicon TFT Active Matrix
Pixel Number 1,024,000 dots (1280 x 800) x 3
Color Brightness² Color Light Output: 3400 lumens
White Brightness² White Light Output: 3400 lumens
Interactive Color Brightness²
 Color Light Output: 3400 lumens
Interactive White Brightness²
 White Light Output: 3400 lumens
Aspect Ratio 16:10
Native Resolution 1280 x 800 (WXGA)
Resize 640 x 480 (VGA), 800 x 600 (SVGA), 1024 x 768 (XGA),
 1152 x 864 (SXGA), 1280 x 960 (SXGA2), 1280 x 1024 (SXGA3),
 1366 x 768 (WXGA 60-2), 1440 x 900 (WXGA+),
 1400 x 1050 (SXGA+), 1600 x 1200 (UXGA)
Lamp Type 215 W UHE
Lamp Life⁶ Up to 10,000 hours (ECO Mode), Up to 5000 hours
 (Normal Mode)
Throw Ratio Range 0.48 – 0.65
Size (projected) 53" – 116" without wall mount, 68" – 113"
 with wall mount
Keystone Correction (manual) Vertical: ± 7 degrees,
 Horizontal: ± 5 degrees
Mac® Connectivity Projector is Mac compatible via USB, DVI
 to HDMI® or VGA adapter (not included)
Contrast Ratio Up to 16,000:1
Color Reproduction Up to 1.07 million colors

Projection Lens

Type Digital zoom/Manual focus
F-number 1.6
Focal Length 6.4 mm
Zoom Ratio Digital zoom 1.0 – 1.35

Other

Display Performance NTSC: 480 lines, PAL: 576 lines
 (Depends on observation of the multi-burst pattern)
Input Signal NTSC/NTSC4.43/PAL/M-PAL/N-PAL/PAL60/
 SECAM
Speaker 16 W mono
Operating Temperature 41° ± 95° F (5° ± 35° C)
Power Supply Voltage 100 – 240 V ±10%, 50/60 Hz
Power Consumption 315 W (Normal Mode), 230 W (ECO
 Mode), 1.90 W (Communication On), 0.22 W (Communication Off)
Fan Noise 37 dB (Normal Mode), 29 dB (ECO Mode)
Security Kensington security lock port, padlock and security
 cable hole, password protect function

Interactive Specifications

Interactive Area 68" to 113" diagonal (16:10, WXGA) wall
 mounted; 53" to 116" without mount
Interactive Modes Computer interactivity/input: Interactive
 and Whiteboard modes, Dual user PC-free annotations
Calibration Method Automatic or Manual
System Compatibility Epson Easy Interactive Driver:
 Windows® and Linux: no driver required, Macintosh®:
 Mac OS X® 10.3.9, 10.4.x, 10.5.x, 10.6.x, 10.7.x, 10.8.x
 (Included in the box. Also available for unlimited download at
 Epson.com support page)
Input Input device: digital pen; Number of pens included: one,
 Technology: infrared, 940 nm

Interfaces

Computer/component video: D-sub 15 pin x 2,
 S-video: Mini DIN x 1, Composite-video: RCA
 (Yellow) x 1, Audio in: RCA x 1 (L and R), Mini
 stereo x 2, USB connector: Type B x 1, (USB
 display, audio and pen control), USB connector:
 Type A x 1, (USB memory/document camera),
 HDMI x 1, RJ-45 x 1, Serial: RS-232C x 1,
 Monitor out: D-sub 15 pin x 1, Audio out: Mini
 stereo x 1, Microphone: Mini stereo x 1, Wireless
 LAN USB port: 802.11 b/g/n (optional module
 sold separately)



Interactive Specifications (continued)

Pen Specifications Size: 6.4" L x .9" W, Weight: 1.1 oz (without
 battery), Power: AA battery, rechargeable, Compatible battery
 types: SANYO Eneloop®, HR-3UTG/HR-3UTGA (Eneloop batteries
 and charger included), Manganese dry cell, Alkaline dry cell,
 PC-free annotations, PC free annotation tools: Yes, PC-free
 annotation sources (devices not, included): document cameras,
 DVD/Blu-ray player, iPod/iPad devices⁴
Requirements for Computer Interactivity Connection to the
 computer: USB

Interactive Software

Epson Easy Interactive Tools for Windows and Macintosh
 System Compatibility: Microsoft® Windows XP SP2, Windows
 XP SP3 (Home Edition/Professional), Windows Vista®, Windows
 Vista SP1, Windows Vista SP2 (All editions except for Starter),
 Windows 7 SP1 (All editions except for Starter), Windows 8,
 Mac OS X 10.5/10.6/10.7

Optional Software

SMART Notebook
 Windows: Pentium® 4 processor or better, 2GB of RAM, 2.5GB
 of free hard disk space for SMART® education software
 installation (an additional 600MB is required for complete Gallery
 installation), Windows XP SP3, Windows 7 SP1 or Windows 8
 operating system
 Macintosh: Intel® Core™ 2 Duo processor or better 2GB of RAM,
 2GB of free hard disk space for SMART education software
 installation (an additional 600MB is required for complete Gallery
 installation), Mac OS X 10.7 or 10.8 operating system, software
MimioStudio
 Windows: Windows XP, Windows Vista, Windows 7 or Windows 8
 Pentium II 750 MHz+ processor or equivalent, 512MB RAM
 minimum (1GB RAM recommended), 350MB free disk space
 (English), 800MB (Multi-language), Internet connection
 Macintosh: Mac 10.6, 10.7, 10.8 or 10.9, Intel processors,
 1GHz, 512MB RAM minimum (1GB RAM recommended),
 350MB free disk space (English), 900MB (Multi-language),
 Internet connection

Dimensions (W x D x H)

Including feet: 13.6" x 11.7" x 6.2"
Excluding feet: 13.6" x 11.7" x 4.1"
Weight 8.5 lb.

Remote Control

Features Source search, video, LAN, computer, USB, power,
 aspect, color mode, volume, e-zoom, A/V mute, freeze, menu,
 page up and down, help, auto, mouse functions, user, esc,
 Pen mode
Operating Angle Right/left: ± 30 degrees
 Upper/lower: 10 to ± 70 degrees
Operating Distance 19.7 ft (6 m)

Eco Features

RoHS compliant, Recyclable product⁷, Epson America, Inc. is a
 SmartWay® Transport Partner⁸

Support

The Epson ConnectionSM
 Pre-sales support U.S. and Canada 800-463-7766
 Internet websites www.epson.com www.epson.com/brightlink

Service Programs

Two-year projector limited warranty, Epson Road Service
 program, PrivateLine® dedicated toll-free support (U.S. and
 Canada only) and 90-day limited lamp warranty

What's in the Box

BrightLink 536Wi projector, interactive pen A (orange),
 USB cable, Easy Interactive software, user's guide CD,
 rechargeable batteries and charger, quick setup guide,
 power cord, computer cable (VGA), projector remote control,
 batteries, user manual CD, projector software CD, Quick Setup
 Sheet, PrivateLine support card, password protection sticker
 and lens cover

Ordering Information

BrightLink 536Wi	V11H670022
Genuine Epson lamp	V13H010L87
Replacement air filter	V13H134A47
Mimio Studio Interactive Software	V12HMSS020
Interactive pen A (orange)	V12H666010
Interactive pen B (blue)	V12H667010
Interactive pen tips	V12H668010
Short-throw wall mount (ELPMB27)	V12H706020

¹ Color brightness (color light output) in brightest mode, measured by a third-party lab in accordance with IDMS 15.4. Color brightness will vary depending on usage conditions. Top-selling Epson 3LCD projectors versus top-selling 1-chip DLP projectors based on PMA Research sales data for Dec. 2015 through Nov. 2016. ² Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. ³ Includes one pen. Additional pens optional. ⁴ For wireless functionality, including via the Epson iProjection App, the projector must be configured on a network, either through the Ethernet port on the projector (check model specifications for availability) or via a wireless connection. Check your owner's manual to determine if a wireless LAN module must be purchased separately to enable a wireless connection. Not all Epson projectors are able to be networked. The Epson iProjection App does not support all files and formats. See www.epson.com for details. ⁵ Moderator feature is part of EasyMP® Multi-PC Projection software. ⁶ Lamp life will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time. ⁷ For convenient and reasonable recycling options, visit www.epson.com/recycle ⁸ SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.

Epson America, Inc.
 3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada Limited
 185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com
 www.epson.ca

Specifications and terms are subject to change without notice. EPSON and EasyMP are registered trademarks, EPSON Exceed Your Vision is a registered logomark and Epson iProjection is a trademark of Seiko Epson Corporation. BrightLink and PrivateLine are registered trademarks and Epson Connection is a service mark of Epson America, Inc. iPad, iPhone, iPod, Mac, Macintosh and OS X are trademarks of Apple, Inc., registered in the U.S. and other countries. Android is a trademark of Google Inc. Microsoft, Windows and Windows Vista are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2018 Epson America, Inc. Com-SS-Oct-13 CPD-52679R1 3/18

Contact:

