

LARGE FORMAT PHOTO PRINTER
SURECOLOR™ SC-P8530D

EPSON

AMPLIFY YOUR IDEAS WITH TOP-CLASS PRINT QUALITY.



Transform your ideas into striking true-to-life prints with Epson's Pro Photo Graphic Printer.

Nothing beats seeing life injected into your ideas, turning them into picturesque prints in vivid and vibrant colours with top-class accuracy. Equipped with the Epson's proprietary PrecisionCore MicroTFP printheads, the Epson SureColor™ SC-P8530D photographic printer take pride in their precise and reliable print productivity, along with the colour-accurate reproduction with Epson genuine UltraChrome™ PRO 6 inks. With high installation flexibility and seamless printing workflow, increase your print efficiency today!



IT'S IN THE DETAILS.



**ULTRACHROME
PRO 6 INK**



Highest Standards in Print

The additional grey ink in the UltraChrome™ Pro 6 inks offers smooth and natural colour gradation in every print.

Installation Flexibility

Flat top design allows for easy placement of printer in challenging and narrow spaces, giving businesses more options in installation.

Boosted Efficiency

Improved print speeds and continuous automatic printing with dual rolls help ensure high productivity with minimal downtime.

SPECIFICATIONS

SURECOLOR™ SC-P8530D

MODEL NUMBER		SC-P8530D	
Printing Technology		PrecisionCore™ Inkjet Technology, Variable-Sized Droplet Technology	
Printing Method		PrecisionCore MicroTFP® Printhead	
Print Head		9,600 Nozzles	
Nozzle Configuration		Pk:1,600, Mk:1,600	
Black		C:1,600, M:1,600, Y:1,600, Gray:1,600	
Colour			
Maximum Resolution		2,400 x 1,200 dpi	
Minimum Ink Droplet Volume		3.5pl	
Printing Specifications			
Print Speed - B0 Size*		Speed	Quality
*Premium Glossy Photo Paper 170gsm		152 sec	281 sec
Print Speed (Poster) - B0 Size*			
*Premium Glossy Photo Paper 170gsm		N/A	281 sec
Margin		Top/Bottom: Min. 3mm ¹ / Right/Left: Min. 0mm ¹	
Roll Paper		Top: Min. 3mm ¹ / Bottom: Min. 12.7mm ¹ / Right/Left: Min. 0mm ¹	
Cut Sheet			
Ink System		Pigment Ink	
Ink Type		UltraChrome Pro 6 Ink	
Ink Brand Name		Cyan, Magenta, Yellow, Gray, Photo Black, Matte Black	
Colour		350, 700 ml	
Ink Capacity		Ink Cartridge	
Ink Case			
Paper Handling		Roll (Double Roll), Cut Sheet (Manual Feed), Poster Board (Manual Feed)	
Paper Path		Friction Feed	
Paper Feed Method		Max. 170 mm ²	
Maximum Roll Diameter		12.5kg	
Maximum Roll Weight		254 – 1,118 mm	
Paper Width (Roll)		203 – 1,118 mm	
Paper Width (Cut Sheet)		0.07 – 0.8 mm	
Paper Thickness (Roll)		Cut Sheet: 0.07 – 0.8 mm / Poster Board: 0.8 – 1.5 mm	
Paper Thickness (Manual)		91 m ³	
Maximum Printable Length		254 mm (10"), 300 mm (11.8"), 330 mm (13"), 356 mm (14"), 406 mm (16"), 432 mm (17"), 500 mm (19"), 508 mm (20"), 515 mm (20.3"), 594 mm (23"), 610 mm (24"), 700 mm (27.5"), 728 mm (28.6"), 841 mm (33"), 914 mm (36"), 1030 mm (40.5"), 1188 mm (44")	
Borderless Sizes		The remaining amount is managed by the barcode printed on roll paper	
Roll Paper Remaining			
Connectivity		SuperSpeed USB ⁴ , 100BASE-TX /1000BASE-T/IEEE802.11b/g/n/ac, USB memory stick ⁵	
Interface		ESC/P raster, HP-GL/2 ⁶ , HP RTL ⁶ , Adobe PostScript 3, Adobe PDF 1.7	
Printer Language		Yes	
USB Direct Print		4GB	
Memory		SSD 960GB	
HDD (Optional)			
Operating System		Windows 10, 8.1, 8, 7, Windows Vista, Windows XP (32bit/64bit)	
PC System Requirement		Windows Server 2019/2016/2012 R2/2012/2008 R2/2008/2003 R2/2003 SP2 or later	
Mac System Requirement		Mac OS X 10.6.8 or later, Mac OS 11 or later	
Utility Software		Windows - Printer driver - EpsonNet Setup - EpsonNet Print - EpsonNet Config SE - EPSON manuals - Manual Launcher - LFP Print Plug-in for Office - PS Driver - PS Folder	
Bundled in CD		Windows - Epson Media Installer - EpsonNet SetupManager - Epson Device Admin - Epson Edge Dashboard - Epson Print Layout - Epson Print Automate - Epson Edge Print (Option) - Epson Print Admin (Option) - Order Controller (Option)	
Web Delivery		Mac - Printer driver - EpsonNet Config SE - EPSON manuals - Epson Media Installer - Epson Edge Dashboard - Epson Print Layout - PS Driver iOS/Android - Epson Smart Panel	
Electrical Specifications		AC 100 – 240 V, 50/60 Hz	
Voltage		AC 100 V 3.4 AAC 100 - 240 V 3.4 - 1.6 A	
Rated Current		Operating: Approx. 70 W, Ready: Approx. 32 W,	
Power Consumption		Sleep: Approx. 2.0 W, Standby: Approx. 0.3 W	
Environmental Conditions		Operating: 10°C to 35°C / Storage: -20°C to 40°C	
Temperature		Operating: 20% to 80% (no condensation), Storage: 5% to 85% (no condensation)	
Humidity			
Dimensions & Weight		1,848 x 975 x 829 mm	
Dimension (W x H x D)		Approx. 155 kg	
Weight			

Dimensions and Weight

SC-P8530D

Weight: Approx. 155 kg



WHAT'S IN THE BOX

- Printer
- Initial ink cartridge
- AC power cable
- Setup guide
- Software CD-ROM
- Maintenance box

OPTIONS

Roll Feed Spindle (44") (C12C936171)
Production Stacker (44") (C12C937131)
SSD Unit (C12C936671)

CONSUMABLE

Ink Cartridge		
CYAN	350ml	C13T48Y200
Gray	350ml	C13T48YE00
Matte Black	350ml	C13T48Y800
Magenta	350ml	C13T48Y300
Photo Black	350ml	C13T48Y100
Yellow	350ml	C13T48Y400
Cyan	700ml	C13T48R200
Gray	700ml	C13T48RE00
Matte Black	700ml	C13T48R800
Magenta	700ml	C13T48R300
Photo Black	700ml	C13T48R100
Yellow	700ml	C13T48R400
Maintenance Tank		C13S210115
Borderless Maintenance Box		C13S210116
Printer Cutter Blade		C13S210117
Cleaning Stick		C13S090013

© 2025 Epson India Pvt. Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON is registered trademark of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.

Dealer's Stamp

Information correct as of May 2025.

¹ Might differ depends on applications/media.

² Depending on the thickness of the paper. It is larger than the available outer diameter size. If roll paper is used, please confirm that it is within the outside diameter range

³ Printable length is limited depending on restrictions of operating systems or applications.

⁴ Compatible with the USB 3.0 Specification.

⁵ Incompliant for USB memory with an encryption or utility function. Non-guarantee to connected through USB memory reader/writer or extension cable.

⁶ It is recommended to do test before purchasing printer if HP-GL/2 or HP RTL direct print is used, because support is dependent on the application or data used.

EPSON INDIA PVT. LTD.

11th Floor, Godrej Centre, Hebbal, Survey No. 26, Bellary Road, Sahakar Nagar, Byatarayanapura, Bangalore 560 092, Karnataka.
Tel: 080-6939 5000 Fax: 080-6939 5005

Regional Offices:

Ahmedabad 4037 0075, Chennai 4905 5177, Coimbatore 98942 19200, Ernakulam 4012 315, Hyderabad 4857 0032, Jaipur 4923 119, Kolkata 4603 4714/15/29/30, Mumbai 3079 8200, New Delhi 4107 3101, 4752 2414, Pune 2998 0641



Epson Helpline: For product info or service - 1800 425 0011
For service: 1800 123 001 600 or 1860 3000 1600 (9 am - 6 pm) (Mon - Sat)
Email: ifp@epson-india.in

www.epson.co.in

DISCLAIMER: While efforts have been made to provide accurate information, there could be errors, which may have crept in. In the event of any discrepancy, the Product Operating Instructions supplied with products shall be the authentic reference point. Features, specifications, dimensions, weight and prices mentioned are subject to change without prior notice. Actual products may differ slightly in appearance to illustrations/pictures provided.