
INKJET COLOUR LABEL PRINTER COLORWORKS™ C7510G





Epson understands the need and importance of efficient industrial labelling which is often hindered by the hassle of outsourcing colour label printing to Print Service Providers. Introducing Epson's first industrial colour label printer with PrecisionCore[™] printhead technology that functions outstandingly in a high-mix environment. Make the right choice towards greater productivity.





ENGINEERED FOR BUSINESS

Hassle-free Colour Labels On-demand Print high quality, customised colour labels in-house easily without keeping an inventory of pre-printed labels.



Used with approved media, labels are GHS (Globally Harmonised System) certified for chemical labelling.

Precision and Clarity

Epson's revolutionary PrecisionCore printhead delivers consistency and accuracy especially on small text, graphics and barcodes.

The ColorWorks C7510G label printer returns control to you with higher quality works and swifter print speeds. The label printer features Epson's revolutionary PrecisionCore technology, which is engineered to deliver precise printing quickly.



Hassle-free Colour Labels On-demand

Designed to meet the needs of customers, the C7510G colour label printer leads the ColorWorks Series in print volume and is capable of high-mix applications. It allows you to produce multiple colour label variations from blank labels, eliminating the traditional two-step label printing process. It simplifies the print process to improve product identification and productivity whilst eliminating your excess inventory.

GHS-compliant

Meet your regulatory requirements within the chemical industry with GHS-compliant labels. The C7510G label printer prints with UltraChrome™ DL ink*, which when accompanied by certified media, delivers printouts that adhere to GHS standard and are BS5609 certified.



Prescription label



Product packaging label



GHS-compliant label

*In the progress of BS5609 certified (as at September 2015).

Precision and Clarity



Featuring PrecisionCore printhead technology, Epson's most advance printhead architecture, it is the driving force behind Epson's lead in both quality and quantity output. This translates to a reliable colour label printer that delivers both consistency and swift printing to meet your needs.

Clarity in Printing



UltraChrome DL ink ensures printouts on glossy and other media stays clear and crisp with easy-to-read text and along with the appropriate media, printouts are smudge, fade and water resistant.

Epson pigment ink



Epson pigment ink is not water soluble and firmly binds to media fibers, resisting water and other moisture.

Dye-based ink



Conventional dye-based ink is water soluble so printouts can be negatively affected by water and other moisture.

Astounding Print Speed

With a print speed of up to 300mm/sec, you can swiftly print full colour labels, rivalling speeds of incumbent thermal monochrome printers.

The C7510G label printer executes roll-to-roll operations with the option of a take-up-unit ensuring that overall productivity is increased.




Selective Ink Cartridge Replacement

The C7510G label printer functions with consolidation of individual CMYK ink cartridges which mean ink wastage is now a thing of the past. Only replace empty ink cartridges to fully maximise cost savings and greatly reduce production time.



Nozzle Verification Technology (NVT)

The C7510G label printer produces consistent and reliable quality printouts every time with minimal user intervention through its NVT that works behind the scenes to detect and revive blocked nozzles back to maximum operating performance.



Nozzle Verification Technology



With Nozzle Verification Technology



Without Nozzle Verification Technology

SP ECI FIC ATION S COLORWORKS ™ C75 10G



394mm (15.5")

597mm (23.5")

> 293mm (11.54")

403mm (15.87")

MODEL NUMBER		C7510G		Dimensions & Weight
Print Technology	Technology	PrecisionCo re TFP * with Nozzle Verification Technology		C7510G
	Colour	 Four-colour printing, individual ink cartridge (UltraCh rome™ DL pigment ink: C, M, Y, K)		Weight: 37.0kg (81.57lb
Ink Cartridge	Colour	Cyan, Magenta, Yellow, Black		
	Model	SJIC31P(C), SJIC31P(M), SJIC31P(Y), SJIC31P(K)		
Print Resolution		1200 x 600 dpi		a trion
Printing Width		4.1" (104mm) max.		
Print Speed		300mm/s		
Interfaces		US 2.0 High-Speed, Ethe rnet 10/100 BASE-T		
Print Font		Fixed font: Sans serif, OCR-A, OCR-B, Symbol. Scalable font: Sans serif.		
		User can download scalable fonts to the printer		
Ba rcode Font (Printer Driver Built-in) Media Sou rce Media Types		Ba rcode: UPC-A, UPC-E, JAN13(EAN), JAN8(EAN), Code39, IT F, Codaba r, Code93, Code128,		
		GS1-128, GS1 DataBar Omnidi rectional, GS1 DataBar Truncated, GS1 DataBar Limited,		391mm
		GS1 DataBar Expanded		(15.4")
		Two-dimensional symbols: PDF417, QR Code, GS1 DataBar Stacked, GS1 Omnidi rectional, GS1		
		DataBar Expanded Stacked, DataMatrix, Aztec Code, Mic roPDF417, Mic ro QR Code, Maxi Code		Take-up Unit
		Roll-fed, Fanfold		Weight: 4.25kg (9.37lb)
		Plain, Matte, Gloss y, Synthetic		
Paper Specifications		Width	Thickness	- 120
Media Form	4010	waa	1110011033	12
Roll	Full-page Label (BM)	Label Width: 46 ~ 108mm	Plain Label Matter Label Synthetic Labels	- Kalles
NUI			Plain Label, Matte Label, Synthetic Label: 0.129 ~ 0.236mm	
	Die-cut Label (Gap)	Backing Paper Width: 50 ~ 112mm		
Fanfold	Die-cut Label (BM)		Glossy Label: 0.167 to 0.182mm	- VEZ
Fantoid	Die-cut Label (Gap)		Plain Label, Matte Label: 0.161 ~ 0.164mm	
	Die-cut Label (BM)			
External Roll Diameter		Max. 203.2mm		222mm >> * (8.74")
Paper Co re Exte rnal Diameter		Internal Diameter: 76.2 ± 0.5mm		(0.7.1)
Number of Folds		External Diameter: 82.2mm or mo re		
Number of Folds		Fanfold Paper: 750 or less		
Winding Direction		Face Out		
Autocutter Life		Die-cut Label	Full-page Label	
		Plain, Matte, Glossy: 1,500,000 cuts	Plain: 750,000 cuts	
		Synthetic: 500,000 cuts	Matte: 200,000 cuts	
			Glossy: 300,000 cuts	
		Synthetic: 100,000 cuts		
Temperatu re / Humidity Printing Storage		5 to 32°C / 20 - 80% RH Humidity		
		-20 to 60°C / 5 - 85% RH Humidity		© 2017 Epson India Pvt. Ltc
Overall Dimensions		597 x 391 x 394mm		Reproduction in part or in wh
Mass		Approx. 37.0kg (81.57lb) - Printer (without ink)		permission from Epson, is st
Power Supply				and EXCEED YOUR VISION of Seiko Epson Corporation.
Power Consumption Printing Standby		50 - 60W (average printing)		and other company names u
		4.1 - 4.4W		identification purposes only a or registered trademarks of t
Rated Voltage		AC 100 - 240 VAC		Epson disclaims any and all
Rated F requency		50 - 60Hz		Print samples shown are sim
EMC Standa rds		VCCI Class A, FCC Class A, ICES-003 Class A, CE Marking, AS/NZS CISPR22 Class A, CCC, KC, EAC,		and product availability are s notice and may vary between
		Ukraine EMC		with local Epson offices for n
Safety Standa rds		UL60950-1/CSA C22.2 No.60950-1, EN60950-1, CCC, KC, EAC, BSMI, Ukraine Safety Standa rd		Apple, iPad and iPhone are t
Operating System		Microsoft Windows 8.1 (32-bit, 64-bit), Windows 8 (32-bit, 64-bit), Windows 7 SP1 (32-bit, 64-bit),		registered in the U.S. and ot
		Windows Vista SP2 (32-bit, 64-bit), Windows XP SP3 (32-bit), Windows Server 2012 R2,		service mark of Apple Inc.
		Windows Server 2012, Windows Server 2008 R2, Windows Server 2008 (32-bit, 64-bit),		Android is a trademark of Go
		Windows Server 2003 R2 (32-bit)		

India Pvt. Ltd. All Rights Reserved. part or in whole, without the written n Epson, is strictly prohibited. EPSON OUR VISION are registered trademarks Corporation. All other products names bany names used herein are for irposes only and are the trademarks ademarks of their respective owners. s any and all rights in those marks. hown are simulations only. Specifications ailability are subject to change without vary between countries. Please check offices for more information.

iPhone are trademarks of Apple Inc., U.S. and other countries. App Store is a Apple Inc.

lemark of Google Inc.

Information correct at time of printing Printed December 2017

EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A, No.1, Murphy Road, Ulsoor, Bangalore - 560 008. Tel: 080-30515000 Fax: 080-30515005

Regional Offices:

Ahmedabad - 33148500/01, Chennai - 3967 7500, Cochin - 4012 315, Coimbatore - 98942 19200, Kolkata - 6500 9370/77, Mumbai - 3079 8200, New Delhi - 3312 0300/01, Pune - 3028 6000/05, Hyderabad - 6463 9640/41



EPSON SERVICE

Epson Helpline: For product info or service - 1800 425 0011 For service - 1860 3000 1600 (9AM - 6PM) (Mon - Sat) www.epson.co.in Dealer's Stamp