LARGE FORMAT TECHNICAL PRINTERS SURECOLOR™ SC-T5730DM/T7730DM

EPSON



Exceptional performance, spectacular precision, and true-to-life colours from your SureColor™ printer.

Be ready to amplify your ideas and showcase them in spectacular precision with Epson's SureColorTM all-in-one multi-function technical printers SC-T5730DM and SC-T7730DM. Equipped with PrecisionCoreTM MicroTFP® printheads for precise printing and vivid colour-accurate prints using the UltraChromeTM XD3 inks, it brings top-class accuracy and efficiency in every print. In addition, versatile printing capabilities, the printers come equipped with user-friendly functions and secured management for businesses to enjoy a seamless printing process. Get ready to be mesmerised by the exceptional line printing accuracy and top-class efficiency.





MODEL NUMBER	SC-T5730DM	SC-T7730DM	Dimensions and Weight
SKU Code	C11CH82402		SC-T5730DM
Printer Width Printing Technology	91.44 cm (36")	111.76 cm (44")	Weight: Approx. 150 kg
Printing rechinology Print Head	PrecisionCore™ MicroTFP® Printhead		
Nozzle Configuration	9,600 Nozzles (400 nozzles x 24 channels x	x 1 head)	
Maximum Resolution	2,400 x 1,200 dpi		tracm
Minimum Ink Droplet Volume	3.5 pl		Bereite Harrison
_ine Accuracy	±0.1% or ±0.26 mm		and the same of th
Minimum Line Width	0.08 mm ⁻¹ (0.02 mm ⁻²) A0 Size	B0 Size	_ 975 mi
Print Speed	Plain Paper: 25 sec (Draft), 32 sec (Speed)	Plain Paper: 35 sec (Draft), 46 sec (Speed)	
	184 sec (High Quality)	258 sec (High Quality)	
	Premium Glossy Photo Paper 170 gsm:	Premium Glossy Photo Paper 170 gsm:	
	108 sec (Speed), 184 sec (Quality),	152 sec (Speed), 281 sec (Quality),	1,645 mm 499 mm
	417 sec (Max Quality)	614 sec (Max Quality)	_
CAD	A1 Landscape Size	soc 600v600 dpi Lipo Draw/Speed: 23 soc	
	Plain Paper 300x600 dpi Line Draw/Draft: 16 sec, 600x600 dpi Line Draw/Speed: 23 sec A0 Size		SC-T7730DM
	Plain Paper 300x600 dpi Line Draw/Draft: 28 sec, 600x600 dpi Line Draw/Speed: 43 sec		Weight: Approx. 166 kg
Poster	A0 Size	B0 Size	
	Plain Paper 300x600 dpi	Premium Glossy Photo Paper 170 gsm:	
	EPSON Vivid/Speed: 32 sec	1200x1200 dpi, EPSON Standard (sRGB)/	DECE
Scanning		Quality: 281 sec	humananananananananananananananananananan
ight Source	Dual LED		975
Optical Resolution	600 dpi		978
can Speed (200 dpi)	4.5 ips (Colour) / 10 ips (Mono)		
Maximum Scan Length	30.5 m		
Scan Accuracy	±0.1% Soon to Notwork Folder/FTD Soon to Email Soon to Mamory Davido		1 848 mm 499 mi
Scan Features	Scan to Network Folder/FTP, Scan to Email, Scan to Memory Device, Scan to Computer (Document Capture Pro), Scan to Computer (WSD)		1,848 mm 499 m
Copying	Scarrto Computer (Document Capture F10)	, Scar to Computer (WSD)	-
Scaling	25 to 755%		
Maximum Copies	99 copies		INK CARTRIDGE
nk System			- 350 mL
nk Type	UltraChrome™ XD3 Pigment Ink	Photo Plack	- Photo Black C13T50Y100
Colours Paper Handling	Cyan, Magenta, Yellow, Red, Matte Black, F	TIOTO DIACK	- Cyan C13T50Y20
Paper Path	Roll (Double Roll), Cut Sheet (Manual Feed), Poster Board (Manual Feed)		Magenta C13T50Y300 Yellow C13T50Y400
Maximum Roll Diameter/Weight	2/3" Core, Max. 170 mm/12.5 kg		_ Matte Black C13T50Y80
Paper Width	Roll: 254 – 914 mm	Roll: 254 – 1,118 mm	Red C13T50YF00
	Cut Sheet: 203 – 914 mm	Out Sheet: 203 – 1,118 mm	700 mL
Margin (Roll Paper)*³ Margin (Cut Sheet)*³	Top, Bottom: Min. 3 mm right, left: Min. 0 m	nm at left. Min. 0 mm	- Photo Black C13T50R100
Media Thickness	Top: Min. 3 mm, Bottom: Min. 12.7 mm right, left: Min. 0 mm Roll: 0.07 mm – 0.8 mm		- Cyan C13T50R200
	Cut Sheet: 0.07 mm – 0.8 mm		Magenta C13T50R300 Yellow C13T50R400
	Poster Board: 0.8 mm - 1.5 mm		Yellow C13150R400 Matte Black C13T50R800
Borderless Width Sizes (mm) Connectivity	914, 841, 728, 700, 610, 594, 515, 508,	1118, 1030, 914, 841, 728, 700, 610,	Red C13T50RF00
	500, 432, 406, 356, 330, 300, 254	594, 515, 508, 500, 432, 406, 356, 330,	
		300, 254	-
onnectivity nterface	USB 3.0, Ethernet (100BASE-TX/1000BASI	F-T) Wi-Fi (IFFF802 11b/g/p)	
Vi-Fi Direct	Wi-Fi Direct (Simple AP)		© 2024 Enson India But Ltd. All Bights Bases and
ISB Host	Yes ⁻⁴		 © 2024 Epson India Pvt. Ltd. All Rights Reserved Reproduction in part or in whole, without the
JSB Direct Print	Supported Format: PDF, TIFF, JPEG, HP-GL/2, HP RTL		written permission from Epson, is strictly prohibite
Control Panel	4.3" Touch Screen ESC/D restor, HD CL /0"5, HD DTL '5, Adoba Doct Script 3, Adoba DDE 1.7		 EPSON is registered trademark of Seiko Epson Corporation. All other products names and other
Printer Languages Mobile Solutions	ESC/R raster, HP-GL/2 ⁻⁵ , HP RTL ⁻⁵ , Adobe PostScript 3, Adobe PDF 1.7 Epson Smart Panel, Apple AirPrint		 company names used herein are for identification
Memory	Epson Smart Panel, Apple AirPrint Physical: 6 GB (Printer) + 4 GB (Adobe PostScript unit) + 3 GB (Scanner) + 960 GB (SSD)		purposes only and are the trademarks or registere trademarks of their respective owners. Epson
Tion of y	Virtual memory for HP-GL/2": 128 GB, Sca		disclaims any and all rights in those marks. Print
oftware Information			 samples shown are simulations only. Specification and product availability are subject to change
Supported OS	Windows XP, Vista, 7, 8, 8.1, 10, 11		without notice and may vary between countries.
		Windows Server 2003 SP2 or later, 2008, 2012, 2016, 2019, 2022	
loctrical Specifications	Mac OS X 10.6.8 or later		information.
lectrical Specifications oltage	AC 100-240 V 50/60 Hz		Apple, iPad and iPhone are trademarks of Apple
onage Rated Current	3.4-1.6 A		 Inc., registered in the U.S. and other countries. Ap Store is a service mark of Apple Inc.
Power Consumption	Operating: Approx. 90 W / Ready: Approx. 44 W / Sleep: Approx. 2.0 W		
<u> </u>	Standby: Approx. 0.3 W		Android is a trademark of Google Inc.
nvironmental Conditions	0 " 1000	1000	Doglar's Stame
emperature	Operating: 10°C to 35°C, Storage: -20°C to 40°C		Dealer's Stamp -
Humidity Sound Pressure	Operating: 20% to 80% (no condensation), Storage: 5% to 85% (no condensation) Operating: Approx. 50 dB(A)		
Sound Pressure Sound Power	Operating: Approx. 50 dB(A) Operating: Approx. 6.6 dB(A)		
Vhat's In The Box	Printer, Initial ink cartridge, AC power cable,	Setup quide,	
	Software CD-ROM, Maintenance box		

*1 ISO/IEC 24790, Single weight matte paper, CAD/Line Drawing, Speed, High Speed=Off, Finest Detail=On. *2 Addressable. *3 It differs depend on applications/media. *4 Not supported for USB memory with an encryption or security function. Not-guarantee connected through USB memory reader/writer or extension cable. *5 It is recommended to do test before purchasing printer if HP-GL/2 or HP RTL direct print is used, because whether supported or not depends on application or data.

Information correct at time of printing. Printed January 2024

975 mm

EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A, No.1, Murphy Road, Ulsoor, Bangalore - 560 008. Tel: 080-4566 5000 Fax: 080-4566 5005

Scan the QR code to contact an Epson representative close to you.







CONTACT EPSON TODAY! EMAIL: pravin@eid.epson.co.in

Epson Helpline: For product info or service - 1800 425 0011
For service: 1800 123 001 600 or 1860 3000 1600 (9 am - 6 pm) (Mon - Sat)
Email: Ifp@epson-india.in www.epson.co.in