A3+ MULTIFUNCTION ECOTANK PRINTER TO BOOST PRODUCTIVITY & PROFITS.



Get fully flexible and customisable print solutions for your business with the Epson L15180 EcoTank colour printer, and the M15180 EcoTank monochrome printer. Powered by Heat-Free Technology, these printers increase productivity with ultra-high page yield and consistent fast speed printing of up to 25 ipm. Printouts are sharp, crisp and water resistant from our 4-colour pigment ink which is suitable for business printing. Secure the access of your devices through authentication and apply printing control to reduce cost of printing."

























Built for Business

Improve productivity with ultra-high page yield and consistent fast print speed of up to 25 ipm, delivering prints of impeccable quality from our 4-colour pigment ink.

Open Platform Enabled**

Manage your printers with Epson Print Admin or integrate with compatible third party print management solutions.

Heat-Free Technology

Enjoy high speed quality printing at lower power consumption with Epson PrecisionCore Heat-Free Technology

SPECIFICATIONS

Product Name Printer Type	L15180 Print, Scan, Copy and Fax with ADF	M15180 Print, Scan and Copy with ADF	Dimensions & Weight L15180
Printing		Think, Ocarraina Copy With ADF	Weight: 21.0 kg
Printing Technology Nozzle Configuration	PrecisionCore Printhead 800 x 1 nozzles each (Black, Cyan, Magenta, Yellow)	800 x 1 nozzles each (Black)	
Print Direction Maximum Resolution	Bi-directional printing 4800 x 1200 dpi	4800 x 2400 dpi	EPSON .
Minimum Ink Droplet Volume	3.8 pl	4000 X 2400 aþi	· · · · · · · · · · · · · · · · · · ·
Print Speed ^{*1} Draft Text - Memo, A4 (Black ^{#1} / Colour ^{#2})	Up to 32 ppm / 32 ppm	Up to 32 ppm	1
ISO 24734, A4 (Black / Colour) ISO 24734, A3 (Black / Colour)	Simplex: Up to 25 ipm / 25 ipm Duplex: Up to 21 ipm / 21 ipm Simplex: Up to 13.5 ipm / 13.5 ipm Duplex: Up to 10 ipm / 10 ipm	Simplex: Up to 25 ipm Duplex Up to 16 ipm Simplex: Up to 13.5 ipm Duplex Up to 10 ipm	0
First Page Out Time A4 (Black / Colour)	Simplex: Up to 5.5 sec / 5.5 sec Duplex: Up to 11.0 sec / 11.5 sec	Simplex: Up to 5.5 sec Duplex: Up to 11.0 sec	500
Photo Default ⁻² - 10 x 15 cm / 4 x 6"*3 (Border / Borderless)	Approx. 26 sec per photo / 27 sec per photo	-	515 mm (19.7 (20.3")
Printer Language Emulation	ESC/P-R PCL5 / PCL6 / PostScript3 / PDF (ver1.7)		
Automatic 2-sided printing	Yes (up to A3)		M15180
Copying Copy Speed			Weight: 20.2 kg
ISO 29183, A4 (Black / Colour), Flatbed	Simplex: Up to 23 ipm / 23 ipm	Simplex: Up to 23 ipm	
ISO 24735, A4 (Black / Colour), ADF Maximum Copies from Standalone	Duplex: Up to 19 ipm / 19 ipm 999 copies	Simplex: Up to 22.5 ipm Duplex: Up to 15.5 ipm	TPSON
Reduction / Enlargement Maximum Copy Resolution	25 - 400%, Auto Fit Function 600 x 600 dpi		3
Maximum Copy Size	<u>АЗ</u>		
Scanning Scanner Type	Flatbed colour image scanner		
Sensor Type	CIS		. ≥
Optical Resolution Maximum Scan Area	1200 x 2400 dpi 297 x 431.8 mm		515 mm 500 (19.7
Scan Features Colour	Scan to Memory Device, Scan to Network Folder / FTP, Scan to Email, Scan to Co. 48-bit input, 24-bit output	mputer (Epson ScanSmart), Scan to Computer (WSD)	(20.3")
Grayscale	16-bit input, 8-bit output		
Black & White Scanner Bit Depth	16-bit input, 1-bit output		*1 Print speed (Pages Per Minute) is
Scan Speed (Flatbed / ADF (Simplex) /			calculated when printed on A4 plain paper in the fastest mode,
ADF (Duplex)) Monochrome 200dpi	Flatbed: 5 sec, ADF (Simplex / Duplex): Up to 26.0 ipm / 11.5 ipm		10 x 15 cm photo print speed when printed on Epson Premium Glossy Photo
Colour 200dpi Fax Function	Flatbed: 10 sec, ADF (Simplex / Duplex): Up to 9.0 ipm / 6.0 ipm		Paper. Print speed may vary depending on system configuration, print mode,
Type of Fax	Walk-up black-and-white and colour fax capability	<u>-</u>	document complexity, software, type of paper used and connectivity. Print speed
Receive Memory / Page Memory Error Correction Mode	6MB, Up to 550 pages (ITU-T No.1 chart) ITU-T T.30		does not include processing time on host computer.
Fax Speed (Data Transfer Rate) Fax Resolution	Up to 33.6 kbps, Approx. 3 sec/page Up to 200 x 200 dpi	-	
Transmission Paper Size	Op to 200 x 200 api		
Flatbed ADF	A5, A4, A3, B5, B4, Half Letter, Letter, Legal, 11 x 17" A5, A4, A3, B5, B4, Half Letter, Letter, Legal, 11 x 17"	-	THE STATE OF THE S
Receiving Paper Size	Half Letter, A5, B5, A4, Letter, Legal, B4, 11 x 17", A3, A3+	-	Williamson a Billion of State
Speed Dial / Group Dial Fax Features	Up to 200 numbers, 199 groups PC Fax (Transmission / Receive), Automatic Redial, Address Book, Transmi	t	#1 #2 #3
	Reservation, Broadcast Fax (Mono only), Polling Reception, Fax Preview, Fax to E-mail, Memory Reception, Fax to Folder, Automatic 2-sided Fax		Black Text Colour Photo 4f
ADF Function	64-95 a/m²		*2 When printed on Epson Premium Glossy
Support Paper Thickness Paper Capacity	64-95 g/m² 50 pages (80 g/m²)		Photo Paper. *3 Default mode in accordance with ISO7779
Card Slot / USB Host Function USB Host	USB Host (Scan to memory device / Storage function)		for MFPs.
Direct Print Paper Size	A6, A5, A4, A3, A3+, B6, B5, B4, 10 x 15 cm, 16:9 wide, 13 x 18 cm, #10, DL,	06, C4, 16K, Indian-Legal, Letter, 8.5 x 13", Legal, 8K	
Supported Formats (Direct Print) Paper Handling	PEG, TIFF, PDF		
Paper Feed Method	Friction feed		© 2024 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole,
Number of Paper Trays Paper Hold Capacity	3 (Front 2, Rear 1)		without the written permission from Epson, is strictly prohibited. EPSON and EXCEED
Input Capacity	Cassette 1: 250 sheets (80 g/m²), 50 sheets of Premium Glossy Photo Paper Cassette 2: 250 sheets (80 g/m²)	Cassette 1: 250 sheets (80 g/m²) Cassette 2: 250 sheets (80 g/m²)	YOUR VISION are registered trademarks
Output Capacity	Rear Tray: 50 sheets (80 g/m²), 20 sheets of Premium Glossy Photo Paper 125 sheets (80 g/m²), 20 sheets of Premium Glossy Photo Paper		of Seiko Epson Corporation. All other products names and other company names
Paper Size	A6, A5, A4, B6, B5, Half Letter, Executive, 16K, Indian-Legal, Letter, 8.5 x 13", Legal 8.5 x 14" (216 x 356 mm), 4 x 6", 5 x 7",		used herein are for identification purposes
Maximum Paper Size	8 x 10", 16:9 wide, Envelopes #10, DL, C6, C4 215.9 x 6000 mm (8.5 x 236.2")		only and are the trademarksor registered trademarks of their respective owners. Epson
Print Margin	0 mm top, left, right, bottom via custom settings in printer driver (except plain paper) ³		disclaims any and all rights in those marks. Print samples shown are simulations only.
Interface USB	USB 2.0		Specifications and product availability are subject to change without notice and may
Network Network Protocol	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct (8 connections) TCP/IPv4, TCP/IPv6, LPD, IPP, PORT9100, WSD		vary between countries. Please check with
Network Management Protocols	SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SNTP, SLP,		local Epson offices for more information.
Security Functions Epson Open Platform	Limit Access Function, PIN No. Certification, LDAP Address Book, IP Address Yes	ess Filtering, Panel Admin Mode	Apple, iPad and iPhone are trademarks of
Mobile and Cloud Printing			Apple Inc., registered in the U.S. and other countries. App Store is a service mark of
Epson Connect Other Mobile Solutions	Epson Smart Panel, Epson iPrint, Epson Email Print, Remote Print Driver, S Apple AirPrint, Mopria Print Service	Scan to Cloud	Apple Inc.
Control Panel			
LCD Screen Printer Software	4.3" TFT Colour Touch LCD		
Software Support	Epson ScanSmart (Win / Mac)		Android is a trademark of Google Inc.
Operating System Compatibility	Windows XP / Vista / 7 / 8 / 8.1 / 10 Windows Server 2003 / 2008 / 2012 / 2016 / 2019		Dealer's Stamp
Electrical Specifications	Mac OS X 10.6.8 or later		
Rated Voltage	AC 220 - 240 V		
Rated Frequency Power Consumption	50 - 60 Hz		
Operating	20 W	21 W	
Standby Sleep	10.3 W 0.9 W	9.9 W 0.8 W	Information correct at time of printing Printed December 2024
Power Off Typical Electricity Consumption (TEC) Number	0.2 W 0.15 kWh	0.2 W 0.14 kWh	
	OFFO WAIT	O	

EPSON INDIA PVT. LTD.

PC Printing / Black

11th Floor, Godrej Centre, Hebbal, Survey No.26, Bellary Road, Sahakar Nagar, Byatarayanapura, Bangalore 560 092, Karnataka. Tel: 080 6939 5000. Fax: 080 6939 5005



6.7B(A), 52dB(A)

Ahmedabad 4037 0075, Chennai 4905 5177, Coimbatore 98942 19200, Ernakulam 4012 315, Hyderabad 4857 0032, Jaipur 4923 119, Kolkata 4603 4714/15/29/30, Mumbai 3079 8200, New Delhi 4107 3101, 4752 2414, Pune 2998 0641

350 mm (13.8")

500 mm