

EB-770Fi



Project your vision, with a Full HD interactive large screen display up to 100" that will enhance engagement, learning and productivity.

Whatever the size of class or meeting room, unrestricted and interactive learning sessions are possible with this bright, compact and affordable touch-display solution.

The EB-770Fi's bright image, scalable up to 100", is clearly visible from every angle and at a distance, and content can easily be shared or streamed directly from multiple devices for the ultimate collaborative experience.

The EB-770Fi is a step up from the EB-770F, with added interactive features.

Interactive technology enables two digital pens to be used on the display simultaneously (finger touch available through optional accessory FT01). Presentations can be controlled and brought to life with on-screen annotations, while a variety of convenient built-in tools support productivity. An optional Epson visualiser camera can be controlled via the display, projecting documents or objects from a desk for the whole room to see in incredible detail.

With a 4,100 lumens laser-light source, combined with 3LCD technology, it produces a large, bright and vibrant display up to 100", clearly visible from all angles and at a distance.

Versatile wired and wireless connectivity options, including screen mirroring via Miracast™, allows participants to effortlessly share content from their PCs or mobile devices.

The experience is immersive and user-friendly.

The ultra short throw lens allows safe, unobtrusive positioning above the display, enabling presenters free access to interact without casting shadows.

Unlike a flat-panel display, there is no heavy, breakable, glass panel to create disruptive, reflected blind spots from certain angles; and presenters are not subjected to LCD panel direct blue light radiation.

DATASHEET / BROCHURE



KEY FEATURES

- **Interactive FHD display for any room**
49-100" UST display for unrestricted viewing (no shadows/reflections)
- **Bright and energy efficient laser**
4,100lm CLO with 3LCD technology for brighter colours at only 205W
- **Effortless connectivity options**
Auto-on, wired / wireless display with USB 2A output for smart sticks
- **Simple to use and built to last**
Virtually maintenance free with 5-year, 12,000hr warranty
- **Document camera compatibility**
Create and record a live, totally immersive lesson or presentation

EPSON

PRODUCT SPECIFICATIONS

TECHNOLOGY	
Projection System	3LCD Technology, RGB liquid crystal shutter
LCD Panel	0.62 inch with C2 Fine
IMAGE	
Color Light Output	4,100 Lumen- 2,800 Lumen (economy) In accordance with IDMS15.4
White Light Output	4,100 Lumen - 2,800 Lumen (economy) In accordance with ISO 21118:2020
Resolution	1080p
High Definition	Full HD
Aspect Ratio	16:9
Contrast Ratio	Over 5,000,000:1
Light source	Laser
Laser Light source	20,000 hours Durability High, 30,000 hours Durability Eco
Keystone Correction	Manual vertical: $\pm 3^{\circ}$, Manual horizontal $\pm 3^{\circ}$
Colour Video Processing	10 Bits
2D Vertical Refresh Rate	192 Hz - 240 Hz
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Throw Ratio	0.25 - 0.35:1
Zoom	Digital, Factor: 1 - 1.35
Lens	Optical
Screen Size	60 inches - 100 inches
Projection Lens F Number	1.6
Projection Lens Focal Length	3.7 mm
Projection Lens Focus	Manual
Offset	5 : 1
CONNECTIVITY	
Interfaces	USB 2.0-A (2x), USB 2.0 Type B (Service Only) (2x), RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11a/b/g/n/ac, Wi-Fi Direct, VGA in (2x), VGA out, HDMI in (3x), Composite in, Miracast, Jack plug out, Jack plug in (3x), Microphone input, Sync. in, Sync. out, Multi-Touch interface (optional)
Network Protocol	HTTPS, IPv4, IPv6, SNMP, ESC/VP.net, PJLink
ADVANCED FEATURES	
Security	Kensington lock, Control panel lock, Password lock, Padlock, Security cable hole, Wireless LAN unit lock, Wireless LAN security, Password protection
Other features	21:9 aspect ratio support, A/V mute, Arc Correction, Auto Power On, Auto source search, Built-in speaker, CEC compatible, Digital zoom, Direct Power on/off, Document Camera Compatible, Dual Pen Support, Easy OSD pre-setting, Email notification, Finger-touch support, Home Screen, Horizontal and vertical keystone correction, Image Shift, Instant on/off, Interactive, Interactive Home Screen, Interactive OSD menu, Mail notification function, Microphone input, Network administration, Network projection, OSD copy function, PC Interactive, PC free annotation, Projection App for Chromebook, Quick Corner, Schedule Function, Screen Mirroring, Screen share, Split-Screen-Function, Ultra-wide display (16:6), Web Control, Web Remote, Whiteboard sharing function, Wireless LAN capable, iProjection App, iProjection set-up by QR code
Interactivity	Yes - pen and finger-touch
Video Color Modes	Blackboard, Cinema, Dynamic, Presentation, sRGB, DICOM SIM
Projector control	via: Crestron Integrated Partner, Crestron RoomView, Extron IP Link, AMX Device Discovery, Control4 Simple Device Discovery Protocol

EB-770Fi

WHAT'S IN THE BOX

- Power cable
- Pen Holder/Stand
- Interactive pens
- 2 x Pen tip(Teflon)
- 4 x Pen tip(Felt)
- USB cable
- Remote control incl. batteries
- Quick Start Guide

PRODUCT SPECIFICATIONS

EB-770Fi

GENERAL

Power consumption	197 Watt - On mode power consumption (Normal) 263 Watt (Peak), 199 Watt (Eco), 0.5 Watt (Energy saving standby)
Heat Dissipation	895 BTU/hour (max)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Product dimensions	356 x 395 x 133 mm (Width x Depth x Height)
Product weight	6 kg
Noise Level	Normal: 37 dB (A) - Economy: 27 dB (A)
Supported Temperature	Storage -10° C - 60° C
Supported Humidity	Operation 20% - 80%, Storage 10% - 90% If the projector is suspended from a ceiling or wall mount and installed in an environment with heavy oil smoke or places where oils or chemicals are volatilized, places where a lot of smoke or bubbles are used for event staging, or where aroma oils are frequently burned, it can make certain parts of our products susceptible to a material degradation which over time could break and cause the projector to drop from the ceiling. If you are concerned about the environment in which your projector is installed, or if you have any other questions, please contact our support department and they can provide additional assistance.
Included Software	Easy Interactive Tools, EasyMP Multi PC Projection, Epson Projector Management
Options	Air filter, Finger Touch Unit, Finger Touch Unit Wall Bracket, Pen tip(Felt), Pen tip(Teflon), Visualiser camera, WP System - ELPWP10, Wall mount, Wireless LAN unit, Wireless transmitter - ELPWT01
Loudspeaker	16 Watt
Room Type / Application	Meeting room / Classroom
Positioning	Ceiling Mounted, Desktop, Wall Mounted
Colour	White

OTHER

Warranty	3 years or 20,000 hours whichever is ealier
----------	---

OPTIONAL ACCESSORIES

EB-770Fi

- ELPFT01 - Finger Touch Unit
V12H007A24
- ELPMB63 - Finger Touch Wall Bracket for ELPFT01
V12HA05A09
- Interactive Pen - ELPPN05A - Orange - EB-6xxWi/Ui / 14xxUi
V12H773010
- Interactive Pen - ELPPN05B - Blue - EB-6xxWi/Ui / 14xxUi
V12H774010
- Wall Mount - ELPMB62 - EB-7xx / EB-8xx
V12HA06A06
- Adapter - ELPAP11 Wireless LAN (5GHz)
V12H005A01
- Air Filter - ELPAF60 - EB-7XX / EB-L2xx Series
V13H134A60

LOGISTICS INFORMATION

SKU	V11HA78056
Country of Origin	Philippines

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners.
Product information is subject to change without prior notice.

EPSON INDIA PVT. LTD.

11th Floor, Godrej Centre, Sy No-26, Bellary
Road, Hebbal, Sahakar Nagar,
Byatarayanapura, Bengaluru – 560092
Tel: 080-4566 5000 Fax: 080-4566 5005

Regional Offices:

Ahmedabad 4037 0075, Chennai 3967 7500, Ernakulam 4012 315, Coimbatore 99620 00969
Hyderabad 4857 0032, Jaipur 0141 4923119, Kolkata 4603 4714/15/29/30, Mumbai 3079 8200
New Delhi 4107 3101, 4752 2414, 4226 3483, 4215 1033, Pune 3028 6000.



Epson Helpline: Epson Helpline: For product info or service – 1800 425 0011
For service: 1800 123 001 600 or 1860 3000 1600 (9 am – 6 pm) (Mon – Sat)
Email: emp@eid.epson.co.in

www.epson.co.in

EPSON