LARGE FORMAT PRINTERS SURECOLOR™ SC-R5030L

EPSON



SureColor™ SC-R5030L













Introducing 6-colour Resin Ink Technology

The SureColor™ SC-R5030L signage printer features Epson's UltraChrome™ RS Resin Inks for stunning prints with a low environmental impact, thus increasing the scope of applications. High ink capacity enables non-stop printing. User-replaceable printheads ensure minimal downtime. Advanced heating and the printheads' amazing durability helps maintain colour consistency every time.





SPECIFICATIONS SURECOLOR™ SC-R5030L



Printing Technology

Printhead: Advanced PrecisionCoreTM TFP® 12-channel drop on demand, inkjet printhead with ink-repelling coating technology

Ink Type: UltraChrome TM RS ink; 6-colours (C, M, Y, K, LC, LM) and optimiser Nozzle configuration: Colour and monochrome heads; 1,600 nozzles x 2

Droplet technology: Variable droplet technology Maximum Resolution: 1200 x 2400 dpi Printer Language / Drivers: Epson ESC / P® raster

Epson Ink Supply System

Ink supply tank fill volume: 1,500 mL x 2 (each colour); 6 colours total

Ink pack shelf life: 2 years from printed production date

Printer is designed for use with Epson ink packs only, not third-party ink systems

Roll Media Handling

Single roll-to-roll: 163 cm (64") wide, Media core: 5.1 cm (2") or 7.6 cm (3") core diameter

Maximum roll diameter: Up to 24.9 cm (9.8"), Maximum roll weight: Up to 45 kg

Media thickness: 1 mm thick, Take-up reel: Fully automatic "wind in" or "wind out" with tension control

Printable Area and Accuracy

Maximum paper width: Up to 163 cm (64"), Minimum paper width: Up to 30 cm (11.8"),

Left / Right Margins: 0.51 cm (0.20"), 101.6 cm (0.40") total, Maximum Printable Width: Up to 161.5 cm (63.6")

Production speed[^]

Vinyl & Wall covering: 15~27.1 m 2 / h Vinyl: 9.5~29.5 m 2 / h Coated Paper: 9.5~20.9 m 2 / h Film: 5.2~6.6 m 2 / h

General

Dimensions (W x D x H): 294.9 cm (116.1") x 104.5 cm (41.1") x 177.4 cm (69.8"), Weight: 449 kg Acoustic noise level: Approx. 66.1 dB, Operating temperature: 59 $^{\circ}$ F to 86 $^{\circ}$ F (15 $^{\circ}$ C to 30 $^{\circ}$ C)

Relative humidity: Operating 20 - 80% (no condensation), Operating (recommended): 40 - 60% (no condensation)

Printer requires two outlets, voltage: AC 200 - 240 V, frequency: 50 / 60 Hz current: 16 A x 2

Power consumption (printing): Approx. 4.6 kW, standby: approx. 220 W, sleep mode: approx. 44 W, power off: approx. 1 W

Printer Interface

Hi-Speed USB 2.0 (1 port), 1000 Base-T Ethernet (1 port),

Operating systems supported Windows® 10 and 8.1,

Epson Edge Print minimum PC requirements: 2 GHz CPU, 2 GB RAM, 120 GB HDD, DVD-ROM or internet connection, Recommended PC specifications: 3 GHz or higher quad core CPU, 8 GB RAM, 500 GB SSD, and high-speed internet connection

Dimensions & Weight

Weight: 425 Kg (936 lbs) 177.4 cm (69.8") 104.5 cm (41.1")

Ink Supply Units 1500 mL x 2

Black	C13T45R100
Cyan	C13T45R200
Magenta	C13T45R300
Yellow	C13T45R400
Light Cyan	C13T45R500
Light Magenta	C13T45R600
Optimiser	C13T45R700
Maintenance Liquid	C13T45R800

Optional Accessories

Media edge plate	C12C935321
Media cleaner brush	C12C936031
Thermal sheet	C12C936551
Cleaning liquid,1500	C13T45X100
Wiper unit	C13S210100
Waste ink bottle	C13S210071
Cleaning kit	C13S210103
Cleaning stick	C13S090013
Clean room wiper	C13S090016

© 2025 Epson India Pvt. Ltd. All Rights
Reserved. Reproduction in part or in whole,
without the written permission from Epson,
is strictly prohibited. EPSON is registered
trademark of Seiko Epson Corporation. All other
products names and other company names
used herein are for identification purposes only
and are the trademarks or registered trademarks
of their respective owners. Epson disclaims
any and all rights in those marks. Print samples
shown are simulations only. Specifications
and product availability are subject to change
without notice and may vary between countries.
Please check with local Epson offices for more
information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.

Information correct as of April 2025

EPSON INDIA PVT. LTD.

11th Floor, Godrej Centre, Hebbal, Survey No.26, Bellary Road, Sahakar Nagar, Byatarayanapura, Bangalore 560 092, Karnataka. Tel: 080-6939 5000 Fax: 080-6939 5005

Scan the QR code to contact an Epson representative close to you.



CONTACT EPSON TODAY! EMAIL: pravin@eid.epson.co.in





Epson Helpline: For product info or service - 1800 425 0011

For service: 1800 123 001 600 or 1860 3000 1600 (9 am - 6 pm) (Mon - Sat)

Email: Ifp@epson-india.in

www.epson.co.in

Dealer's Stamp

[^] Figures are print speed only based on operation with Epson Edge Print. They do not include provisions for image processing, transfer, drying and/or post production. Results may vary with alternative RIP software and may not be applicable to all media types and/or applications.