

T3-B All-in-One SCARA Robot

Robots

SCARA



Value without compromise. The ultimate slide alternative.

Easy to install, plus fast integration — installs in minutes, unlike complex linear-slide systems; requires less time and money for system integration

All-in-One solution — includes built-in controller with power for end-of-arm tooling, all in one space-saving structure

Value without compromise — offers the same intuitive software, powerful features and reliability found in Epson's most advanced robots, providing incredible value at an affordable cost

Space-saving design with built-in controller — controller conveniently housed in the robot's base helps save critical floorspace

Easy to use — intuitive and feature-packed Epson RC+® development software makes it easy to create powerful solutions; also comes with Epson RC+ Express, enabling new users to develop robotic solutions with little to no programming experience necessary

Runs on 110 V or 220 V power — low wattage and power consumption; no special panel or plug required

Built-in power for end-of-arm tooling — eliminates the need for an external power source

Integrated vision guidance option — designed specifically for robot guidance; makes it easy to automate simple applications when vision is required

No battery required for encoder — minimizes downtime and reduces overall cost of ownership

Other integrated options — teach pendant, IntelliFlex™ parts feeding, fieldbus master and slave interface boards available, including EtherNet/IP and Add on Instructions for easy integration with Allen-Bradley PLCs



Model Name		T3-B SCARA Robot
Model Number		T3-B401SS
Mounting Type		Tabletop
Arm Length	Joint #1 plus Joint #2	400 mm
Repeatability	Joints #1 - 2	± 0.020 mm
	Joint #3	± 0.020 mm
	Joint #4	± 0.02 deg
Payload	Rated	1 kg
	Max.	3 kg
Standard Cycle Time ¹		0.52 sec
Max. Motion Range	Joint #1	± 132 deg
	Joint #2	± 141 deg
	Joint #3	150 mm
	Joint #4	± 360 deg
Allowable Moment of Inertia (Joint #4)	Rated	0.003 kg·m ²
	Max.	0.010 kg·m ²
Joint #3 Down Force	Max.	83 N
User Electric Lines	Hand I/O: IN6/OUT4 D-Sub 15pin User I/O: IN18/OUT12	
User Pneumatic Lines	ø6 mm x2, ø4 mm x1	
Brakes	Z-Axis only	
Power	AC 100 - 240 V Single Phase	
Power Consumption	0.66 kVa	
Power Cable Length	5 m	
Weight (cables not included)	16 kg: 35 lb	
Applicable Controller	Built in	
Safety Standards	CE Marking	
What's in the Box	T3-B robot, Robot power cable, Epson RC+ software and Epson RC+ Express software, E-Stop unit with cable, T3-B Robot System Safety & Installation Manual, Connector set (I/O, hand I/O and safety circuit connectors)	
Options		
	Integrated Vision Guidance	Available
	OCR (for use with Vision Guide)	R12NZ920H3
	IntelliFlex Parts Feeding	Available
	Epson RC+ 7.0 API	R12NZ920AE
	TP3 – Teach Pendant	R12NZ900N3
	TP2 – Teach Pendant	R12NZ9005P
	GUI Builder 7.0	R12NZ900AH
	External Control Point (ECP) Option	R12NZ920AF
	Ethernet/IP Fieldbus I/O (Slave)	R12NZ900TH
	Ethernet/IP Fieldbus I/O (Master)	R12NZ900NZ
	DeviceNet Fieldbus I/O (Slave)	R12NZ900TE
	DeviceNet Fieldbus I/O (Master)	R12NZ900NX
	EtherCAT Fieldbus I/O (Slave)	R12NZ900TX
	Profibus Fieldbus I/O (Slave)	R12NZ900TF
	Profibus Fieldbus I/O (Master)	R12NZ900NY
	PROFINET Fieldbus I/O (Slave)	R12NZ900TG
	CC Link Fieldbus I/O (Slave)	R12NZ900TD
	Epson Add on Instructions for Allen-Bradley	R19NZ911A5
	Z-Axis Tool Coupler	RE001063-1
	Tool Mounting Plate (for use with Tool Coupler)	R12NZ90035
	Camera Mounting Bracket	R12NZ9003D

Support

Customer Service
(562) 290-5920
service@robots.epson.com

Applications Support
(562) 290-5930
applications@robots.epson.com

Sales Inquiries
(562) 290-5997
info@robots.epson.com

¹ Cycle time based on round-trip arch motion (300 mm horizontal, 25 mm vertical) with 1 kg payload (path coordinates optimized for maximum speed).

See the latest innovations from Epson® Business Solutions at www.epson.com/forbusiness

Better Products for a Better Future®
eco.epson.com



Epson America, Inc.
3131 Katella Ave., Los Alamitos, CA 90720

Epson Canada Limited
185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com
www.epson.ca

Specifications and terms are subject to change without notice. EPSON and Epson RC+ are registered trademarks, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. IntelliFlex is a trademark of Epson America, Inc. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2021 Epson America, Inc. Com-SS-Oct-13 CPD-61647 12/21

Contact: