WorkForce Enterprise WF-C20750



With print speeds of up to 75ppm this eco-responsible MFP offers impressive reliability and high print yields, reducing operational costs

Print up to 100,000 pages in mono or 50,000 in colour without changing the supplies. This reliable, low maintenance 4-in-1 device offers high-speed performance, superior image quality, all with significant sustainability advantages over laser models.

Superior quality at high speeds

The WorkForce Enterprise WF-C20750 delivers superior image quality at print speeds of up to 75ppm and a first copy out time (FCOT) of 5.4 seconds.

Super high ink yield

Print up to 100,000 pages in mono or 50,000 in colour without changing the ink supplies. This means there is even less need for user intervention. Through fewer consumables and supplies, it also produces less waste. With low power consumption, the overall environmental impact of printing is cut dramatically.

Robust, high-end finishing capability

With advanced finishing such as booklet finisher and hole punch options, this device offers advanced finishing capability. It also offers a high paper capacity of up to 5,350 pages, increasing productivity further.

Heat-free technology

Epson Heat-Free Precision Core Technology requires no heat to warm up when it is switched on or awoken from sleep, which significantly reduces energy consumption. This allows Epson's Heat-Free inkjets to deliver an exceptional FCOT compared to laser technology.

Advanced software solution compatibility

A variety of software solutions can be integrated into existing IT infrastructure to improve efficiency. This includes Epson's new Epson Remote Services (ERS) which offers cloud-based device monitoring and management system that delivers advanced remote diagnostics for Epson business products.

DATASHEET / BROCHURE



KEY FEATURES

- Faster performance Fast FCOT of 5.4 seconds and print speeds of up to 75ppm
- High capacity ink yield Users can print up to 100,000 pages in mono or 50,000 in colour without changing the ink supplies
- Improved finishing capability Advanced finishing such as booklet finisher and hole punch options
- **Powerful scanning capability** Thin paper support and improved scanning quality
- Works with Epson Remote Services Cloud based, advanced diagnosis of Epson printers and MFPs



PRODUCT SPECIFICATIONS

TECHNOLOGY			
Printing Method	PrecisionCore™ Micro TFP printhead 8,676 Nozzles Black, 8,676 Nozzles per Color		
Nozzle Configuration			
Minimum Droplet Size	3.5 pl DURABrite™ Pro Office Departmental		
Ink Technology			
Category			
All-in-One Functions	Print, Scan, Copy		
PRINT			
First Page Out	Monochrome 5.4 Seconds, Colour 5.4 Seconds		
Printing Speed ISO/IEC 24734	75 pages/min Monochrome, 75 pages/min Colour		
Duplex Printing Speed	75 A4 Pages/min Monochrome, 75 A4 Pages/min Colour		
ISO/IEC 24734			
Printing Speed ISO/IEC 24734	45 pages/min Monochrome, 45 pages/min Colour		
(A3)			
Maximum Printing Speed	75 pages/min Monochrome (plain paper 75 g/m²), 75 pages/min Colour (plain paper 75 g/m²)		
Printing Resolution	600 x 2,400 DPI		
Printing Volume	400,000 pages per month		
	The maximum number of printed pages per month based on the performance capabilities of		
	the printer, including ISO rated print speeds and paper handling capabilities.		
Recommended Duty Cycle	8,000 - 100,000 pages per month		
Colours	Black, Cyan, Yellow, Magenta		
SCAN			
Double-sided scanning	Yes		
Scanning Speed	60 ipm (Monochrome, Single-sided, 300 dpi, ADF); 60 ipm (Colour, Single-sided, 300 dpi,		
	ADF); 110 ipm (Monochrome, Double-sided, 300 dpi, ADF); 110 ipm (Colour, Double-sided,		
	300 dpi, Automatic Document Feeder);		
Optical Resolution	600 DPI x 600 DPI (Horizontal x Vertical)		
Optical Resolution (ADF)	600 DPI x 600 DPI (Horizontal x Vertical)		
Advanced document	Scan to Email, Scan to FTP, Scan to USB, Computer (Epson Document Capture Pro), USB		
integration	Memory Device / Card		
Output formats	BMP, JPEG, TIFF, multi-TIFF, PDF, PNG		
Scanner type	Contact image sensor (CIS)		
Optical Resolution	600 DPI x 600 DPI (Horizontal x Vertical)		
FAX OPTION			
FAX OPTION Type of fax	Walk-up black and white and colour fax capability		
	Walk-up black and white and colour fax capability Up to 33.6kbps / Approx. 3 sec/page		
Type of fax			
Type of fax Fax Transmission Speed	Up to 33.6kbps / Approx. 3 sec/page		
Type of fax Fax Transmission Speed Error correction mode	Up to 33.6kbps / Approx. 3 sec/page CCITU/ITU Group3 fax with Error Correction Mode		

Preview, Polling Reception

WorkForce Enterprise WF-C20750

WHAT'S IN THE BOX

- Information sheet
- Power cable
- User guide

PRODUCT SPECIFICATIONS

WorkForce Enterprise WF-C20750

_

COPY		
Copy Speed	Up to 75 ipm Black, Up to 75 ipm Colour	
	*Simplex ADF 600 x 600 dpi (ISO/ IEC 24735)	
Copy resolution (dpi)	600 x 1200	
Reduction / Enlargement	25 % - 400 %	
Maximum number of copies	9,999	
Maximum Copy Size	A3	
0.0111/071/071/		
CONNECTIVITY Network Printing Protocols	IPP I DP Port 9100 WSD	
-	IPP, LDP, Port 9100, WSD	
Network Management Protocols	SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNTP, SLP, WSD, LLTD, Ping, SNMP 2.0c, SNMP 3.0	
Network Protocol		
	IPv4, IPv6	
Network Scanning Protocols	WSD-Scan, FTP	
Interraces	10 Base-T, Ethernet interface (100 Base-TX / 10 Base-T), Gigabit ethernet interface, Ethernet	
	Interface (1000 Base-T/ 100-Base TX/ 10-Base-T), Wireless LAN IEEE 802.11a/b/g/n, Wi-Fi	
WI AN Coourity	Direct, USB 1.1 Type A, USB 2.0 Type A, USB 3.0 Type B, Near Field Communication (NFC)	
WLAN Security	WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP), WPA PSK (AES)	
Network Protocol	TCP/IPv4, TCP/IPv6, TCP, HTTP, HTTPS, IPv4, IPv6, IPSEC, SSL/TLS	
PAPER / MEDIA HANDLING		
Paper Formats	A3, A4, Postcard, A3+, A5, A6, B4, B5, B6, C4 (Envelope), C5 (Envelope), C6 (Envelope), DL	
	(Envelope), Executive, Letter, Legal, HLT, No. 10 (Envelope), User defined, SRA3	
Automatic Document Feed	150 pages	
Compatible Paper Weight	60 g/m ² - 350 g/m ²	
Duplex	Yes (A4/A3, plain paper)	
Standard Paper input	2,350 Sheets Standard, 150 Sheets MP tray, 550 Sheets paper tray	
Output Tray Capacity	550 Sheets	
Maximum paper input	5,350	
Number of paper trays	4	
PAPER FEED RASF		
Paper Input Name	RASF	
Paper Formats	A3+, A3, A4, A5, A6, B4, B5, B6, C4 (Envelope), C5 (Envelope), C6 (Envelope), DL (Envelope),	
r upor r officio	Letter, 20 x 25 cm, HLT, User defined, SRA3	
Custom sizes	Min 55x 330 mm to Max 127x 1,200 mm	
Compatible paper weight	60 g/m ² - 350 g/m ²	
Paper Capacity 1	150 80gsm	
Media type	100 bogani	
	Plain Paper, Recycled Paper, Colour Paper, Letterhead	
	Plain Paper, Recycled Paper, Colour Paper, Letterhead	
PAPER FEED C1		
PAPER FEED C1 Paper Input Name	C1	
PAPER FEED C1 Paper Input Name Paper Formats	C1 A3, A4, A5, B4, B5, Letter, HLT, Executive	
PAPER FEED C1 Paper Input Name Paper Formats Custom sizes	C1 A3, A4, A5, B4, B5, Letter, HLT, Executive Min 140x 297 mm to Max 182x 432 mm	
PAPER FEED C1 Paper Input Name Paper Formats Custom sizes Compatible paper weight	C1 A3, A4, A5, B4, B5, Letter, HLT, Executive Min 140x 297 mm to Max 182x 432 mm 60 g/m ² - 160 g/m ²	
PAPER FEED C1 Paper Input Name Paper Formats Custom sizes Compatible paper weight Paper Capacity 1	C1 A3, A4, A5, B4, B5, Letter, HLT, Executive Min 140x 297 mm to Max 182x 432 mm 60 g/m ² - 160 g/m ² 550 80gsm	
PAPER FEED C1 Paper Input Name Paper Formats Custom sizes Compatible paper weight	C1 A3, A4, A5, B4, B5, Letter, HLT, Executive Min 140x 297 mm to Max 182x 432 mm 60 g/m ² - 160 g/m ²	
PAPER FEED C1 Paper Input Name Paper Formats Custom sizes Compatible paper weight Paper Capacity 1	C1 A3, A4, A5, B4, B5, Letter, HLT, Executive Min 140x 297 mm to Max 182x 432 mm 60 g/m ² - 160 g/m ² 550 80gsm	
PAPER FEED C1 Paper Input Name Paper Formats Custom sizes Compatible paper weight Paper Capacity 1 Media type	C1 A3, A4, A5, B4, B5, Letter, HLT, Executive Min 140x 297 mm to Max 182x 432 mm 60 g/m ² - 160 g/m ² 550 80gsm	
PAPER FEED C1 Paper Input Name Paper Formats Custom sizes Compatible paper weight Paper Capacity 1 Media type PAPER FEED C2-C4	C1 A3, A4, A5, B4, B5, Letter, HLT, Executive Min 140x 297 mm to Max 182x 432 mm 60 g/m ² - 160 g/m ² 550 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead	
PAPER FEED C1 Paper Input Name Paper Formats Custom sizes Compatible paper weight Paper Capacity 1 Media type PAPER FEED C2-C4 Paper Input Name	C1 A3, A4, A5, B4, B5, Letter, HLT, Executive Min 140x 297 mm to Max 182x 432 mm 60 g/m ² - 160 g/m ² 550 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead C2-C4	
PAPER FEED C1 Paper Input Name Paper Formats Custom sizes Compatible paper weight Paper Capacity 1 Media type PAPER FEED C2-C4 Paper Input Name Paper Formats	C1 A3, A4, A5, B4, B5, Letter, HLT, Executive Min 140x 297 mm to Max 182x 432 mm 60 g/m ² - 160 g/m ² 550 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead C2-C4 A3, A4, A5, B4, B5, Letter, HLT	
PAPER FEED C1 Paper Input Name Paper Formats Custom sizes Compatible paper weight Paper Capacity 1 Media type PAPER FEED C2-C4 Paper Input Name Paper Formats Custom sizes	C1 A3, A4, A5, B4, B5, Letter, HLT, Executive Min 140x 297 mm to Max 182x 432 mm 60 g/m ² - 160 g/m ² 550 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead C2-C4 A3, A4, A5, B4, B5, Letter, HLT Min 140x 297 mm to Max 182x 432 mm	
PAPER FEED C1 Paper Input Name Paper Formats Custom sizes Compatible paper weight Paper Capacity 1 Media type PAPER FEED C2-C4 Paper Input Name Paper Formats Custom sizes Compatible paper weight	C1 A3, A4, A5, B4, B5, Letter, HLT, Executive Min 140x 297 mm to Max 182x 432 mm 60 g/m ² - 160 g/m ² 550 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead C2-C4 A3, A4, A5, B4, B5, Letter, HLT Min 140x 297 mm to Max 182x 432 mm 60 g/m ² - 160 g/m ²	
PAPER FEED C1 Paper Input Name Paper Formats Custom sizes Compatible paper weight Paper Capacity 1 Media type PAPER FEED C2-C4 Paper Input Name Paper Formats Custom sizes Compatible paper weight Paper Capacity 1 Media type	C1 A3, A4, A5, B4, B5, Letter, HLT, Executive Min 140x 297 mm to Max 182x 432 mm 60 g/m ² - 160 g/m ² 550 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead C2-C4 A3, A4, A5, B4, B5, Letter, HLT Min 140x 297 mm to Max 182x 432 mm 60 g/m ² - 160 g/m ² 550 80gsm	
PAPER FEED C1 Paper Input Name Paper Formats Custom sizes Compatible paper weight Paper Capacity 1 Media type PAPER FEED C2-C4 Paper Input Name Paper Formats Custom sizes Compatible paper weight Paper Capacity 1 Media type PAPER FEED LCT	C1 A3, A4, A5, B4, B5, Letter, HLT, Executive Min 140x 297 mm to Max 182x 432 mm 60 g/m ² - 160 g/m ² 550 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead C2-C4 A3, A4, A5, B4, B5, Letter, HLT Min 140x 297 mm to Max 182x 432 mm 60 g/m ² - 160 g/m ² 550 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead	
PAPER FEED C1 Paper Input Name Paper Formats Custom sizes Compatible paper weight Paper Capacity 1 Media type PAPER FEED C2-C4 Paper Input Name Paper Formats Custom sizes Compatible paper weight Paper Capacity 1 Media type PAPER FEED LCT Paper Input Name	C1 A3, A4, A5, B4, B5, Letter, HLT, Executive Min 140x 297 mm to Max 182x 432 mm 60 g/m ² - 160 g/m ² 550 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead C2-C4 A3, A4, A5, B4, B5, Letter, HLT Min 140x 297 mm to Max 182x 432 mm 60 g/m ² - 160 g/m ² 550 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead LCT	
PAPER FEED C1 Paper Input Name Paper Formats Custom sizes Compatible paper weight Paper Capacity 1 Media type PAPER FEED C2-C4 Paper Input Name Paper Formats Custom sizes Compatible paper weight Paper Capacity 1 Media type PAPER FEED LCT Paper Input Name Paper Formats Paper Formats	C1 A3, A4, A5, B4, B5, Letter, HLT, Executive Min 140x 297 mm to Max 182x 432 mm 60 g/m ² - 160 g/m ² 550 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead C2-C4 A3, A4, A5, B4, B5, Letter, HLT Min 140x 297 mm to Max 182x 432 mm 60 g/m ² - 160 g/m ² 550 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead	
PAPER FEED C1 Paper Input Name Paper Formats Custom sizes Compatible paper weight Paper Capacity 1 Media type PAPER FEED C2-C4 Paper Input Name Paper Formats Custom sizes Compatible paper weight Paper Capacity 1 Media type PAPER FEED LCT Paper Input Name Paper Formats Compatible paper weight	C1 A3, A4, A5, B4, B5, Letter, HLT, Executive Min 140x 297 mm to Max 182x 432 mm 60 g/m ² - 160 g/m ² 550 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead C2-C4 A3, A4, A5, B4, B5, Letter, HLT Min 140x 297 mm to Max 182x 432 mm 60 g/m ² - 160 g/m ² 550 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead LCT A4, Letter 60 g/m ² - 160 g/m ²	
PAPER FEED C1 Paper Input Name Paper Formats Custom sizes Compatible paper weight Paper Capacity 1 Media type PAPER FEED C2-C4 Paper Input Name Paper Formats Custom sizes Compatible paper weight Paper Capacity 1 Media type PAPER FEED LCT Paper Input Name Paper Formats Paper Formats	C1 A3, A4, A5, B4, B5, Letter, HLT, Executive Min 140x 297 mm to Max 182x 432 mm 60 g/m ² - 160 g/m ² 550 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead C2-C4 A3, A4, A5, B4, B5, Letter, HLT Min 140x 297 mm to Max 182x 432 mm 60 g/m ² - 160 g/m ² 550 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead	

PRODUCT SPECIFICATIONS

PAPER FEED DUPLEX			
Paper Input Name Duplex			
Compatible paper weight	60 g/m² - 160 g/m²		
GENERAL			
Energy Use	160 Watt (standalone copying, ISO/IEC 24712 pattern), 1.7 Watt (sleep mode), 76 Watt		
	(Ready), 0.1 Watt (Power off), TEC 0.44 kWh/week		
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz		
Product dimensions	674 x 757 x 1,243 mm (Width x Depth x Height)		
Product weight	177.1 kg		
Compatible Operating	Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X		
Systems	10.12.x, Mac OS X 10.13.x, Mac OS X 10.6.8, Windows 10 (32/64 bit), Windows 7 (32/64 bit),		
	Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2003 R2 x64, Windows Server		
	2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit),		
	Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or later, XP		
	Professional x64 Edition SP2		
Sound Power	Operation: 7.5 B (A)		
Noise	Operation: 60 dB (A)		
Power supply	220V, 240V		
ADDITIONAL FEATURES			
Features	Touchscreen		
Panel	Type: Color, Touchscreen, Diagonal: 22.7 cm		
Media Handling	Duplex (A4/A3, plain paper)		
Security Functions	Limit access function with Epson Web Config, Secure confidential printing with PIN code		
	release, LDAP Address Book, IPsec, IEEE802.1x, SSL (Server authentication), Panel Admin		
	Mode		
OTHER FEATURES			
Emulations	PCL5c, PCL6, PostScript 3, PDF 1.7, ESC/P, ESC/P-R, PCL5e, ESC/Page, ESC/Page-Colour		

WorkForce Enterprise Staple Cartridge for Booklet Finisher	C12C935411
 WorkForce Enterprise Staple Cartridge for Staple Finisher 	C12C935401
 WorkForce Enterprise WF-C20750 Black Ink 	C13T02S100 50,000 pages
 WorkForce Enterprise WF-C20750 Cyan Ink 	C13T02S200 50,000 pages
 WorkForce Enterprise WF-C20750 Magenta Ink 	C13T02S300 50,000 pages
 WorkForce Enterprise WF-C20750 Yellow Ink 	C13T02S400 50,000 pages
Maintenance box	C13T671300

OPTIONAL ACCESSORIES

- Cassette Lock C12C933231
- WorkForce Enterprise Booklet Finisher C12C935071
- WorkForce Enterprise Staple Finisher C12C935501
- WorkForce Enterprise Saddle Unit C12C935821
- WorkForce Enterprise Finisher Bridge Unit C12C935101
- WorkForce Enterprise 2/4 Hole Punch Unit C12C935171
- Super G3/G3 Fax Board C12C934491
- EpsonNet 10/100/1000Base Tx Int C12C934471
- 3000-Sheet High Capacity Paper Tray C12C933231




EXCEED YOUR VISION

Epson Hong Kong Limited

Unit 715-723, 7/F Trade Square, 681 Cheung Sha Wan Road, Cheung Sha Wan, Kowloon, H.K. *Please call our sales hotlines for demonstration at our showroom

WorkForce Enterprise WF-C20750

INK YIELD DATA



*Approx. page yield based on ISO/IEC 24711/24712 or ISO/ IEC 29102/29103. Actual yield will vary depending on images printed and usage conditions.

Epson Authorized Customer Service Centre Wah Fung Computer Services Ltd. Unit 901, 9/F, Westin Centre, 26 Hung To Road, Kwun Tong, Kowloon, Hong Kong

: (852) 2827 8211 HK Technical Hotline : (852) 2827 8911 Macau Hotline (853) 2850 8065 URL: www.epson.com.hk

HK Sales Hotline