



The Epson SureColor™ SC-S80670 is Epson's next generation, high-performance, eco-solvent signage printer. It incorporates the latest printing technologies, which include precision media feeding system and dual-performance PrecisionCore™ TFP® printheads - to confidently meet the most demanding jobs. Equipped with the widest colour gamut in the S series range, the SC-S80670 is built to astound with true-to-life colours in every brilliant printout.











Dual Printheads 2 Years Warranty

Epson Genuine Inks

Environmentally

0 COLOURS 0 INKS MAX.	ULTRACHROME™ GS3 INK		$\textbf{PRECISIONCORE}^{\text{\tiny{TM}}}$	PRINT SPEEDS SQM/HR		
			PER COLOUR	TFP® PRINTHEAD	HIGH QUALITY**	PRODUCTION**
		163 cm (64)	700 mL*	Dual	13.2	26.8



Outstanding Performance

Print exceedingly vivid colours in outstanding quality with PrecisionCore™ technology and a wide colour gamut.

Steadfast Reliability

Tackle high-volume printing with ease through the newly developed precision media feeding system that allows you to print uninterrupted.





Epson UltraChrome™ GS3 ink is Greenguard Gold certified and meets the French-VOC A+ Class criteria for low chemical emissions

Optimised Design

163 cm (64")

Enjoy hassle-free operations and maintenance with automatic media alignment and setup, along with automated printhead cleaning technology.







MODEL NUMBER		SC-S80670				
SKU No.		C11CE45402				
Printer Width		163 cm (64")				
Printing Te						
Printhead		PrecisionCore™ TFP® Printhead	PrecisionCore™ TFP® Printhead			
Nozzle Configuration		360 x 1 x 2 nozzles each colour (x10)				
Maximum Resolution		1440 x 1440 dpi				
Minimum Inl	Droplet Volume	4.2 pl	4.2 pl			
Print Speed	i					
1 Layer	Colour	Max Speed - 1 pass	Up to 95.1 m²/h (360 x 720 dpi)			
		High Speed - 2 pass (Billboard)	Up to 52.3 m²/h (720 x 720 dpi)			
		Production 1 - 4 pass	Up to 26.8 m²/h (720 x 720 dpi)			
		Production 2 - 6 pass	Up to 18.2 m²/h (720 x 720 dpi)			
	Colour, Colour + White	High Quality - 8 pass	Up to 13.2 m ² /h (720 x 720 dpi)			
		Max Quality 1 - 12 pass	Up to 8.8 m²/h (720 x 1440 dpi)			
		Max Quality 2 - 16 pass	Up to 6.8 m²/h (720 x 1440 dpi)			
		Max Quality 3 - 30 pass	Up to 3.7 m ² /h (720 x 1440 dpi)			
		Max Quality 4 - 48 pass	Up to 2.4 m²/h (1440 x 1440 dpi)			
	Colour + Metallic Silver	Production - 20 pass	Up to 4.2 m²/h (720 x 1440 dpi)			
		High Quality - 36 pass	Up to 2.3 m ² /h (1440 x 1440 dpi)			
2 Layer	Colour + White	Speed - 18 pass	Up to 6.4 m²/h (720 x 720 dpi)			
		Production - 32 pass	Up to 3.5 m ² /h (720 x 1440 dpi)			
		High Quality - 48 pass	Up to 2.4 m ² /h (1440 x 1440 dpi)			
	Colour + Metallic Silver	Production - 40 pass	Up to 1.9 m ² /h (720 x 1440 dpi)			
		High Quality - 72 pass	Up to 1.1 m ² /h (1440 x 1440 dpi)			
3 Layer	Colour + White	Speed - 27 pass	Up to 3.2 m ² /h (720 x 720 dpi)			
-		Production - 48 pass	Up to 1.7 m ² /h (720 x 1440 dpi)			
		High Quality - 72 pass	Up to 1.1 m ² /h (1440 x 1440 dpi)			
Ink System						
Ink Type		Epson UltraChrome™ GS3 Ink Technology with Red				
Colours		10 colours - Cyan, Magenta, Yellow, Black, Light Cyan, Light Magenta, Light Black, Orange, Red,				
		White or Metallic Silver				
Ink Capacity		700 mL (all colours except White and Metallic Silver), 600 mL (White), 350 mL (Metallic Silver)				
Paper Handling		Rear roll feed (2 "/3 " core with max 250 mm diameter and up to 45 kg); Auto take-up reel				
Media Type	3	-	-			
Printable Are	aa	Max printing width: 1616 mm; Side Margin: 5 mm both sides, 10 mm with media holding plates				
Media Width		300 to 1626 mm				
Media Thick		Up to 1 mm				
Heaters		Pre- and Platen- Heater (30 to 50 °C); After-Heater (30 to 55 °C)				
Control Par	nel	6.9 cm (2.7") Colour LCD				
Connectivi						
Printer Interf	•	Hi-speed USB 2.0, 100BASE-TX / 1000	BASE-T			
Printer Lang		Standard: ESC/P raster				
Printer Drive	-	-				
Memory		512 MB main + 128 MB network	512 MB main + 128 MB network			
Software		Standard: CD Installer, Communication Driver, EPSON Manuals Launcher, Operators Guides, General				
Software		Information, Epson Control Dashboard, EpsonNet Config, EpsonNet Setup, EpsonNet Print, Epson Software Updater				
Other Features		Auto Head Alignment Technology (Media feed and Bi-directional), Auto Nozzle Check System, Mail				
		Report System, Custom Paper Backup				
	Operating Requirements					
Power Requirements		Input voltage AC 100 - 240 V 50/60 Hz				
Power Consumption		Operating: Approx. 745 W; Standby: Approx. 445 W w/ heater ON; Sleep: Approx. 13 W; Power Off: Less than 1.8 W				
Recommend	ded Operating					
Temperature & Humidity		15 - 35 °C; 20 - 80 % RH (non-condensing)				
Printer Din						
Dimensions		2,620 x 880 x 1,338 mm (W x D x H) (st	2,620 x 880 x 1,338 mm (W x D x H) (storage)			
Weight		284 kg (without ink)				
Bundled Items		Substrate Support System (C12C932361), SC-S80670 Printer Starter Kit				
Warranty		Standard two years inclusive of parts and printhead				
warranty		otalidaru two years iliciusive di parts and printnead				

Dimensions & Weight SC-S80670

Weight: 284 kg (626.1 lbs) - without ink



Ink Cartridge Compatibility

-	 Black (700 mL) 	C13T892100
-	 Cyan (700 mL) 	C13T892200
-	 Magenta (700 mL) 	C13T892300
-	Yellow (700 mL)	C13T892400
-	Light Cyan (700 mL)	C13T892500
-	Light Magenta (700 mL)	C13T892600
-	 Light Black (700 mL) 	C13T892700
_	 Orange (700 mL) 	C13T892800
_	 Red (700 mL) 	C13T892900
_	O White (600 mL)	C13T892A00
_	Metallic Silver (350 ml.)	C13T802R00

Supplies & Optional Accessories

350 mL Cleaning Cartridge	C13T696000
Maintenance Parts Kit	C13S210044
Ink Cleaner	C13T699300
Cleaning Stick	C13S090013
Clean Room Wiper	C13S090016
Waste Ink Bottle	C13T724000
Additional Print Drying System	C12C932381
Media Holding Guide	C12C932411

© 2023 Epson India Pvt. Ltd. All Rights Reserved.
Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Selko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Information correct as of April 2023.

EPSON INDIA PVT. LTD.

Note: RIP Software required to print

12th Floor, The Millenia, Tower A, No.1 Murphy Road, Ulsoor, Bangalore 560 008 Tel: 080-4566 5000, Fax: 080-4566 5005

Scan the QR code or Click here to contact an Epson representative close to you.



CONTACT EPSON TODAY! EMAIL: pravin@eid.epson.co.in



Epson Helpline: For product info or service - 1800 425 0011 For service: 1800 123 001 600 (9AM - 6PM) (Mon-Sat)

Email: Ifp@epsonindia.in

Dealer's Stamp