

Technical specifications for Epson L6161

Up to 4800 x 1200 dpi optimized resolution on various paper types
Black 33 ppm and Color 20 ppm Black 15 ISO ppm and Color 8 ISO ppm
Black 6.5 ISO ppm and Color 4.5 ppm
DS, Android™),
ia Print Service
11 ISO cpm (black), 5.5 ISO ppm (color)
Color, black/white, draft/normal 1 - 99 copies (without PC)
A4, letter
Cama plana con sensor de líneas CIS de color
21.6 x 29.7 cm (8.5" x 11.7")
1700 1
1200 dpi 1200 x 2400 dpi
9600 x 9600 dpi
48 bit input, 24 bits output
Scanning to computer, scan to the cloud
Hi-Speed USB, Wireless 802.11 b/g/n ⁶ , Wi-Fi Direct ¹¹⁶ , Ethernet (10/100 Mbps)
Windows Vista®/Windows® 7/Windows® 8/8.1/Windows® 10 (32bit/64bit) Windows® XP SP3 (32bit) Windows® XP Professional x64 Edition SP2
Windows" XP SP3 (32Dit) Windows" XP Professional X64 Edition SP2 Windows Server® 2003 SP2 – Windows Server® 2016 ⁷ - Mac OS X 10.6.8 – Mac OS 10.12.x ⁶
Normal (A4, letter, legal), photographic (4" x 6" x 5" x 7", 7.8" x 9.8", A4, letter)
8.5" x 47.2" (21.6 cm x 120 cm)
21.6 cm x 120 cm (8.5" x 47.2")
3.5" x 5.1" (9cm x 13 cm), 3.9" x 5.9" (10 cm x 15 cm), 5.1" x 7.1" (13 cm x 18 cm), 7.9" x 9.8" (20 x 25 cm), letter (21.6 cm x 27.9 cm), legal (21.6 cm x 35.6 cm), A4,
A6, half letter (14 cm x 21.6 cm), executive (18.4 cm x 26.7 cm), user defined (3.5" x 47.2
Supports different Epson papers; Plain paper, bond and photographic
Normal, bond and airmail
150 normal pages, 20 photo pages, 10 envelopes
30 normal pages
1 bottle with black ink: Prints up to 7.500 pages
3 bottles with color inks (Cyan, Magenta, Yellow) Prints up to 6.000 pages' Epson recommends the use of genuine inks to to obtain the best print
performance and quality and to not risk the limited warranty
2.4" LCD color
Epson printer driver, Epson Scan 2
2 years with product registration
Open: 14.8" x 19.8" x 7.36" (37.5 x 50.3 x 18.7 cm) Closed: 14.8" x 13.7" x 7.4" (37.5 cm x 34.7 cm x 18.7 cm)
Closed: 14.8" x 13.7" x 7.4" (37.5 cm x 34.7 cm x 18.7 cm) Weight: 12.79 lb (5.8 kg)
Weight. 12.75 b (5.8 kg)
74
187mm
0 187mm
187mm
13.7" 347mm
13.7 14.8"
13.7* 3/7mm
13.7* 14.8* 375mm Only 12W in operation mode:
11.37 14.8° 375mm

Epson L6161 (110 V) C11CG21301 Epson L6161 (220 V) C11CG21303 Black ink bottle T504120-AL Cyan ink bottle T504220-AL Magenta ink bottle T504420-AL Yellow ink bottle T504420-AL

Product and bottles¹ codes

Identified to the product varies according to the contribution of the space. The operating of the page, the normal BD gram printing according to the contribution of the space. The operating of the page the normal BD gram printing according to the source of the space. The operating of the page the normal BD gram printing according to the source of the page. The normal BD gram printing according to the source of the page. The normal BD gram printing according to the source of the page. The normal BD gram printing according to the source of the page. The normal BD gram printing according to the source of the page. The normal BD gram printing according to the source of the page. The normal BD gram printing according to the source of the page. The normal BD gram printing according to the source of the page. The normal BD gram printing according to the source of the page. The normal BD gram printing according to the source of the page that of the source of the

www.latin.epson.com In Latin America call the local office or your authorized distributor. Subsidiaries Epson:

Argentina S.R.L. (5411) 5167 0300 Chile, S.A. (562) 2484 3400 Colombia LTDA. (571) 523 5000

Centroamérica (506) 2588 7800 México, S.A. de C.V. (5255) 1323 2000 Perú, S.A. (511) 418 0210

Epson Ecuador 1-800-000-044 Venezuela, S.R.L. (58212) 240 11 11 RIF: J-00192669-0

EPSON, EDOTAVK and Expression are registered trademarks, EPSON baceed Your Vision is a registered trademark logo and Better Products for a Better Future and Epson Domect are trademarks registered by Selo Epson Doporation. All offer product and transformers are trademarks and / or registered trademarks of their negocitive companies. Epson resources all rights our threse transfs. Society (2017) Epson America, Inc. COP-LEIOTM 11/177







EcoTank[®] L6161 WIRELESS I PRINT I COPY I SCAN I ETHERNET







IDEAL FOR BUSINESSES AND WORKGROUPS

The wireless multifunctional EcoTank® L6161 gives you the revolutionary cartridge-free printing, with newly designed front-facing tanks, bottles of ink with a keyed and automatic system for easy filling of each color. In addition, the EcoTank® L6161 allows you to print up to 7.500 pages in black¹ or 6.000 pages in color¹. Print hundreds of projects without interruptions, with the Epson genuine ink bottle sets that are equivalent to

about 35 sets of ink cartridges², saving up to 90% in ink with inexpensive replacement bottles³. The EcoTank[®] L6161 prints up to 150 double-sided





WIRELESS PRINTING

Easy printing from computers, tablets and smartphones⁴

sheets and has a 2.4 "color LCD screen. NEW SYSTEM | EcoFit[™] New system easy to fill e-Mail Print Wireless Google Cloud Apple® Airprint® Scan to the cloud Connectivity Print™ and Ethernet PRODUCTIVITY / MULTIFUNCTIONAL 3:1 Front-facing tanks Easy copying and printing with 2.4" color LCD More compact design Scan with great quality 48-bit and ECONOMY AND PEACE OF MIND I INK TANK SYSTEM Peace of mind with 100% Print quickly - up to 33 cartridge-free printing Bottles with EcoFit[™] system Print borderless photos PRINTS UP TO Thousands of prints Save time and paper without interruptions¹ printing costs Automatic double-sided OR 6.000 COLOR PAGES PROFESSIONAL QUALITY **EPSON | GENUINE INKS GUARANTEED QUALITY | EPSON 5TH GENERATION** Excellent quality and value with Epson genuine inks T504420-AL Yellow T504120-AL Black PROFESSIONAL TING TECHNOLOG\ QUALITY AND LIMITED EXTENDED EPSON WARRANTY ENDORSED BY SATISFIED CLIENTS Pigmented black ink bottle of 127 mL. Print up to 7.500 pages in black¹ Print black text with laser quality Color ink bottles of 70 mL each. Print up to 6.000 pages in color¹

25 MILLION PREFER US*

ALWAYS USE GENUINE EPSON INKS PROTECT YOUR PRINTER, PROTECT YOUR INVESTMENT