

# Pro G7500UNL WUXGA 3LCD Projector with 4K Enhancement without Lens

## Brilliant

Color Brightness:  
6,500 lumens<sup>1</sup>

White Brightness:  
6,500 lumens<sup>1</sup>



Shown with lens. Lens sold separately.

## Bright large-venue projector with 4K Enhancement, optional lenses and HDBaseT™

**3x Higher Color Brightness<sup>2</sup> and reliable performance** — 3LCD, 3-chip technology

**One measurement of brightness is not enough** — look for both high color brightness and high white brightness. The Pro G7500UNL has:

**Color Brightness:** 6,500 lumens<sup>1</sup>

**White Brightness:** 6,500 lumens<sup>1</sup>

**Exceptional Full HD widescreen display** — native WUXGA (1920 x 1200) with 4K Enhancement<sup>3</sup> for presentations, videos, digital signage and more

**4K Enhancement Technology<sup>3</sup>** — a revolutionary technology that accepts 4K signal and enhances 1080p for output that surpasses Full HD image quality

**Ten optional interchangeable lenses** — with powered lens shift and lens memory, including an ultra short-throw lens for shallow spaces (sold separately)

**Versatile connectivity** — supports the full range of inputs, including HDBaseT, HDMI®, DVI-D, VGA and 5-BNC, for easy integration with any system

**Advanced collaboration features** — simultaneously project side-by-side from different sources with Split Screen<sup>4</sup>

**Web-based remote management** — control and monitor projector status via a Web browser

**Multi-PC Projection** — connect up to 50 Windows®, Mac®, iOS® or Android™ devices and display up to four screens simultaneously over the network (controlled via the Moderator<sup>5</sup> function from your PC)



# Pro G7500UNL WUXGA 3LCD Projector with 4K Enhancement without Lens

## Specifications

**Projection System** High-aperture Epson® 3LCD, 3-chip technology  
**Projection Method** Front/rear/ceiling mount  
**Driving Method** Poly-silicon TFT Active Matrix  
**Pixel Number** 2,304,000 dots (1920 x 1200) x 3  
**Native Resolution** 1920 x 1200 (WUXGA)  
**Resize** 640 x 480, 800 x 600, 1280 x 1024, 1400 x 1050  
**Aspect Ratio** Supports 4:3, 16:9, 16:10  
**Pixel Arrangement** Cross stripe  
**Color Brightness<sup>1</sup>** Color Light Output: 6,500 lumens  
**White Brightness<sup>1</sup>** White Light Output: 6,500 lumens  
**Contrast Ratio** 50,000:1 (Full White 6,500 lm / Full Black 0 lm)  
**Brightness Uniformity (typical)** 90%  
**Color Reproduction** Up to 1 billion colors  
**Size (projected distance)** 50" - 300"  
**Lens Shift** Vertical: ±67 percent; horizontal: ±30 percent  
**Keystone Correction** Vertical: ±45 degrees; horizontal: ±30 degrees  
**Lamp Type** 400 W UHE  
**Lamp Life<sup>6</sup> (ECO Mode/Normal)** Up to 4,000/3,000 hours

## Projection Lens (Standard, Not Included)

See website for information on optional lenses.

**Type** Powered focus/zoom  
**F-number** 1.70 - 2.30  
**Focal Length** 24.0 mm - 38.2 mm  
**Zoom Ratio** Optical zoom 1 - 1.6x  
**Throw Ratio Range** 1.44 - 2.32

## Other Features

**Operating Temperature** 32° to 113°F (0° to 45°C)  
**Power Supply Voltage** 100 - 240 V ±10%, 50/60 Hz AC  
**Power Consumption**  
 601 W (Normal Mode)  
 498 W (ECO Mode)  
 3.0 W Standby (Communication on)  
 0.5 W Standby (Communication off)  
**Fan Noise** 39 dB (Normal Mode); max. 31 dB (ECO Mode)  
**Security** Security cable hole, lens lock, Kensington lock provision

## Effective Scanning Frequency Range

**Pixel Clock** 13.5 MHz - 162 MHz (up to UXGA 60 Hz)  
**Horizontal** 15 kHz - 92 kHz  
**Vertical** 50 Hz - 85 Hz

## Video I/O

**Display Performance** NTSC: 480 line, PAL: 576 line (depends on observation of the multi-burst pattern)  
**Input Signal** NTSC/NTSC4.43/PAL/M-PAL/N-PAL/PAL60/SECAM/480i/576i/480p/576p/720p/1080i/1080p  
**Pixelworks®** Video Chip 3D Y/C separation, noise reduction motion compensated Interlace-Progressive conversion (2 - 2, 3 - 2 film detection)

## Interfaces

HDBaseT x 1  
 DVI-D x1  
 HDMI x 1  
 Computer: D-sub 15 pin x 1  
 Component Video: BNC x 1  
 Audio-in: Mini stereo x 3  
 Audio Out x 1  
 Network: RJ-45 x 1, 100 Mbps Serial: RS-232c  
 Hardwire remote jack x 1  
 Monitor Out: D-sub 15 pin x 1

## Dimensions (W x D x H)

**Excluding Feet, Lens** 19.88" x 15.04" x 5.67"  
**Weight** 19.6 lb  
**Including Feet, Lens** 19.88" x 15.94" x 6.73"  
**Weight** 28.4 lb

## Remote Control

**Features** Power, source search selection, computer, video, A/V Mute, freeze, user ID, auto, aspect, color mode, number, page up and down, E-zoom, volume, help, menu, enter, esc and pointer functions  
**Operating Angle**  
 Right/left: Front: ± 60 degrees; Rear: ± 30 degrees  
 Upper/lower: Front: ± 20 degrees; Rear: +10 to +50 degrees  
**Operating Distance** 49 ft

## Eco Features

RoHS compliant  
 Recyclable product<sup>7</sup>  
 Epson America, Inc. is a SmartWay® Transport Partner<sup>8</sup>

## Support

**The Epson Connection<sup>SM</sup>**  
 Pre-sales support U.S. and Canada 800-463-7766  
 Internet website [www.epson.com](http://www.epson.com)  
**Service Programs**  
 Limited warranty of 20,000 hours of usage or 3 years, whichever comes first, Epson Road Service program, PrivateLine® dedicated toll-free support (U.S. and Canada only) and 90-day limited lamp warranty

## What's in the Box

Pro G7500UNL projector, power cable, computer cable (VGA), projector remote control with batteries, user manual CD, EasyMP® software CD, Quick Setup Sheet and lens lock screw



## Ordering Information

Pro G7500UNL	V11H750920
Genuine Epson lamp (ELPLP93)	V13H010L93
Replacement air filter (ELPAF30)	V13H134A30
Ultra short-throw zoom Lens	V12H004X01
Short-throw #1 zoom Lens	V12H004U03
Short-throw #2 zoom Lens	V12H004U04
Wide-throw #1 zoom Lens	V12H004W05
Wide-throw #2 zoom Lens	V12H004W06
Middle-throw #1 zoom Lens	V12H004M08
Middle-throw #2 zoom Lens	V12H004M09
Middle-throw #3 zoom Lens	V12H004M10
Middle-throw #4 zoom Lens	V12H004M11
Long-throw zoom Lens	V12H004L08
Quick Wireless Connect key (ELPAP10)	V12H731P02
Epson Ceiling Mount - low ceilings (ELPMB47)	V12H802010
Epson Ceiling Mount - high ceilings (ELPMB48)	V12H803010
Advanced projector ceiling mount with precision gear	ELPMBPRH
Adjustable suspended ceiling channel kit	ELPMBP01
False ceiling plate kit	ELPMBP02
Structural round ceiling plate	ELPMBP03
Adjustable extension column (pipe) 8" - 11"	ELPMBP01
Kensington security lock	ELPSL01
Distribution amplifier	ELPDA01
HDBaseT Transmitter (ELPHD01)	V12H547020
Wireless LAN module (ELPAF10)	V12H731P02
1-year extended warranty	EPPEXPB1
2-year extended warranty	EPFPTB2

<sup>1</sup> Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. <sup>2</sup> Color brightness (color light output) measured in accordance with IDMS 15.4. Color brightness will vary depending on usage conditions. The projectors used by a third-party lab for measuring color brightness were leading Epson 3LCD business and education projectors and leading 1-chip DLP projectors, based on NPD sales data for June 2013 through May 2014 and PMA Research sales data for Q1 through Q3 2013. <sup>3</sup> 4K Enhancement Technology shifts each pixel diagonally by 0.5 pixels to double the resolution and surpass Full HD image quality. <sup>4</sup> Consult your user manual for input combinations. <sup>5</sup> Moderator feature is part of EasyMP Multi-PC Projection software. <sup>6</sup> Lamp life will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time. <sup>7</sup> For convenient and reasonable recycling options, visit [www.epson.com/recycle](http://www.epson.com/recycle) <sup>8</sup> SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.

See the latest innovations from Epson Business Solutions at [www.epson.com/forbusiness](http://www.epson.com/forbusiness)

**Better Products for a Better Future™**  
eco.epson.com



**Epson America, Inc.**  
3840 Kilroy Airport Way, Long Beach, CA 90806

**Epson Canada Limited**  
185 Renfrew Drive, Markham, Ontario L3R 6G3

**www.epson.com**  
**www.epson.ca**

Specifications and terms are subject to change without notice. EPSON and EasyMP are registered trademarks, EPSON Exceed Your Vision is a registered trademark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. PrivateLine is a registered trademark and Epson Connection is a service mark of Epson America, Inc. Mac is a trademark of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google Inc. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2016 Epson America, Inc. Com-SS-Oct-13 CPD-52340 8/16