DOCUMENT CAMERAS ELPDC21/13/07





Cut through the hassle, and get straight to your presentation. Epson's series of document cameras not only captures details with Full HD resolution, its versatile connectivity also gives you great functionality. Furthermore, its compatibility with Epson's interactive projectors allows you to easily manipulate your images without moving away from the screen. For smoother and hassle-free presentations – Epson is the answer.



*Available for ELPDC21 and ELPDC13 only.





ELPDC13



ENGINEERED FOR BUSINESS

Epson's series of Full HD document cameras is engineered to bring your presentations alive. Enjoy seamless integration with Epson's interactive projectors, versatile connectivity and the best in digital imaging, all packed into a sleek and compact design, for impressive presentations.

ELPDC21			
0.00		ELPDC13	
	ELPDC07		
	ELPDC21	ELPDC13	ELPDC07
Key Benefits	Desktop document camera with optical zoom	Desktop document camera with digital zoom	Ultra-portable USB-powered document camera
Effective Pixels	2MP (1920 x 1080 pixels)	2MP (1920 x 1080 pixels)	2MP (1920 x 1080 pixels)
Camera Sensor	1/2.7 inch CMOS Sensor	1/2.7 inch CMOS Sensor	1/2.7 inch CMOS Sensor
Frame-Per-Second (FPS)	30	30	30
Output Resolution	Up to Full HD (1080p)	Up to Full HD (1080p)	Up to Full HD (1080p)
Zoom	10x Digital 12x Optical	16x Digital	8x Digital
Built-in Microphone	Yes	Yes	Yes
AV Recording	Yes	Yes	No
Weight	Approx 2.6 kg	Approx 2.5 kg	Approx 1.0 kg

PARTNERS IN PERFECTION

Epson Ultra-short-throw Interactive Projectors

Compatibility with Epson's ultra! short-throw interactive projectors allows you to easily interact with your images, literally at your fingertips with finger-touch and pen interactivity.




Pair your Epson's document camera with an interactive projector for impressive presentations today.

Realistic and Larger Images

Larger Imaging Sensor

Achieve sharp, clear images with amazing quality and detail in any light with the large imaging sensor, which captures more light per pixel. The ELPDC21 automatically detects the native aspect ratio of projectors and selects the correct output resolution to match.



12x Optical and 10x Digital Zoom


Zoom in on every intricate detail and let students get up close and personal with the subject at hand. The ELPDC21 delivers a unique perspective on any subject with up to 12x optical zoom and 10x digital zoom. Bring lessons alive, right before their eyes, without having to pass around a microscope or photograph.



Large Capture Area

Open students' eyes to a whole new world of possibilities. With a large capture area, the ELPDC21 lets you display virtually any object - from a two-page spread in a textbook to 3D objects or content from your smart devices.









A3



Microscope Support

You can even share organisms under a microscope via the included microscope adapter. Just fit the adapter to any standard microscope eyepiece and bring the smallest particles to the big screen for all to see.

Frame Rate

Watch your presentation come alive with the 30 frames-per-second (fps) video that provides ultra-smooth video performance and minimal delays.






Full HD Image Output

Capture every detail and impress your audiences with brilliant Full HD 1080p resolution.



Versatile Connectivity


Take learning to the next level with engaging multimedia presentations. Output the captured images to any HDMI or VGA display device, as well as to a PC via the USB connections. Enhance any learning experience with attention-grabbing content. You can even capture images and save them to the SD card or connected PC.




Hassle-free Compatibility

Interactive Projector Integration


Enjoy instant interactivity with easy-to-use interactive tools. With PC-less annotation, add notes and diagrams to live images with Epson's interactive projectors. Its compatibility with Epson's interactive projectors gives you ease-of-control to your presentations.



Example 1: Start/stop recording on the big screen



Example 2: Zoom in/out on the big screen



Epson Easy Interactive Tools (EIT) Software

With PC connectivity, users can use the Epson's Interactive Tool (EIT) to annotate on the live image. It is even easier with the Epson interactive projector, which allows users to annotate using the interactive feature.

Portable and Compact

Save on space with the sleek and compact design that conveniently folds into a ready-to-carry unit.



Convenient Features

Split Screen

Split screen capability enables projection of a live video and still image from ab SD card. The versatile remote controller works for both document camera and projector.

Using the split screen, viewers can enjoy both still and moving images.



Camera

Picture in SD Card

Record and Share Lessons

Now, it's easier than ever to capture creative lessons and share them later with other students. Use the document camera and built-in microphone to record classroom demonstrations and projects. Then, play them back for students who missed the class.



Built-in LED Light

The built-in LED light illuminates objects so that you can project objects clearly even if the surrounding area is dimly lit.




Convenient One-touch Control

Enjoy convenient one-touch button to freeze, focus, capture and video record the images.









Realistic and Larger Images

Large Capture Area

Open students' eyes to a whole new world of possibilities. With a large capture area, the ELPDC13 lets you display virtually any object - from a two-page spread in a textbook to 3D objects or content from your smart devices.







Microscope Support

You can even share organisms under a microscope via the included microscope adapter. Just fit the adapter to any standard microscope eyepiece and bring the smallest particles to the big screen for all to see.



16x Digital Zoom

Versatile rotating camera head with intuitive 16x digital zoom and a microscope adapter to provide sharp detail and clear magnification, making it the perfect tool for a dynamic presentation.



Frame Rate

Watch your presentation come alive with the 30 frames-per-second (fps) video that provides ultra-smooth video performance and minimal delays.






Full HD Image Output

Capture every detail and impress your audiences with brilliant Full HD 1080p resolution.



Hassle-free Compatibility

Enjoy instant interactivity with easy-to-use interactive tools. With PC-less annotation, add notes and diagrams to live images with Epson's interactive projectors. Its compatibility with Epson's interactive projectors gives you ease-of-control to your presentations.



Example 1: Start/stop recording on the big screen

Example 2: Zoom in/out on the big screen

Compact and Flexible


Captured images can be easily displayed by adjusting the arm position and camera head of the ELPDC13. This document camera is also space-saving with its sleek and compact design that conveniently folds into a ready-to-carry unit.



ELPDC13

Versatile Connectivity

Take learning to the next level with engaging multimedia presentations. Output the captured images to any HDMI or VGA display device, as well as to a PC via the USB connections. Enhance any learning experience with attention-grabbing content. You can even capture images and save them to the SD card or connected PC.



Convenient Built-in Features

Split Screen

Split screen capability enables projection of a live video and still image from an SD card. The versatile remote controller works for both document camera and projector.

Using the split screen, viewers can enjoy both still and moving images.



Camera

Picture in SD Card

Record and Share Lessons

Now, it's easier than ever to capture creative lessons and share them later with other students. Use the document camera and built-in microphone to record classroom demonstrations and projects. Then, play them back for students who missed the class.



Built-in LED Light

The built-in LED light illuminates objects so that you can project objects clearly even if the surrounding area is dimly lit.




Convenient One-touch Control

Enjoy convenient one-touch button to freeze, focus, capture and video record the images.








Realistic and Larger Images

The ELPDC07 features an 8x digital zoom and a microscope adapter to provide sharp detail and clear magnification, making it the perfect tool for a dynamic presentation.

Open students' eyes to a whole new world of possibilities. With a large capture area, the ELPDC07 lets you display virtually any object - from a one-page spread in a textbook to 3D objects or content from your smart devices. You can even share organisms under a microscopic via the included microscope adapter. Just fit the adapter to any standard microscope eyepiece and bring the smallest particles to the big screen for all to see.



Frame Rate

Watch your presentation come alive with the 30 frames-per-second (fps) video that provides ultra-smooth video performance and minimal delays.





Full HD Image Output


Capture every detail and impress your audiences with brilliant Full HD 1080p resolution.





Hassle-free Compatibility

Enjoy instant interactivity with easy-to-use interactive tools. With PC-less annotation, add notes and diagrams to live images with Epson's interactive projectors. Its compatibility with Epson's interactive projectors gives you ease-of-control to your presentations.



Portable and Compact

Made easy for users to bring along to presentations, this document camera packs conveniently with any main unit without the need of an extra storage bag or compartment.

The ELPDC07 does not require any power adapter and can be easily powered by USB port. Measuring only 60 mm when folded, the document camera is portable, compact and easily carried anywhere and anytime.



Convenient Built-in Features

Now, it's easier than ever to capture creative lessons and share them later with other students. Use the document camera and built-in microphone to record classroom demonstrations and projects. Then, play them back for students who missed the class.

The built-in LED light illuminates objects so that you can project objects clearly even if the surrounding area is dimly lit.

Convenient One-touch Control

Enjoy convenient one-touch button to freeze, focus, capture and video record the images.



SPECIFICATIONS ELPDC21/13/07



MODEL NA	ME	ELPDC21	ELPDC13	ELPDC07
			ELFDOID	
	Specification	01400		
Sensor	Pick-Up Device	CMOS		
	Size	1/2.7"		
	Effective Pixels	2MP Pixels (1920 x 108	30)	
	Native Resolution	1080p (16:9 Aspect Ra		
	Frame Rate	Up to 30 fps	· · /	
lidaa Outau			(CA (1004 - 7/ 0) / M/VCA (1000 - 0)	0) / 10//0
Video Output Display Out			(GA (1024 x 768) / WXGA (1280 x 80	0) / N/A
		HD (1360 x 768) / 1080p (1920 x 1080)		
	HDMI	480p / 720p / 1080p		N/A
	USB-B	VGA / SVGA / XGA / S	KGA / WXGA / 720p / 1080p	VGA / SVGA / XGA / SXGA / 720p /
				WXGA / 1080P
Optical Sys	tems			
_ens	Туре	Optical Zoom / Focus	No Optical Zoom / Focus	
	51			
	F-Number	F = 3.4 - 5	F = 2.0	
Shooting Are	ea	Max 297 x 526 mm at 1	1080p output resolution	Max 273 x 364 mm at XGA output resolution
Zoom		Up to 10x Digital	Up to 16x Digital	Up to 8x Digital
		Up to 12x Optical	, ,	
ocus		Automatic (need to pres	ss "Encus" hutton)	Automatic (need to press "Focus" button),
0000		Focus adjust time: less		Focus adjust time: less than 3 sec
	-		11111 2 3CC	
llumination	1			
Jpper		White LED x 2 (variable	LED light)	
nterface P	ort			
nput	D-Sub 15Pin (VGA)	1 (Black)		N/A
		1 (Blue)		<u>N/A</u>
Dutput	D-Sub 15Pin (VGA)	. ,		
	HDMI	1 (in common with CEC	C control)	N/A
JSB I/O		Туре В х 1		
nternal Micro	ophone	Yes (Monoral)		
Memory I/O		1 (SD / SDHC, No SDX	C support)	N/A
,				[(WPA
Basic Func	non			
reeze		Yes		
Output Sour	ce Select	Yes		N/A
	tness Adjustment	Yes		Yes (using PC App)
5 5	,	Yes		
0 0	ness Control			
Auto Detect	Aspect Ratio	Yes		
Extended F	unction			
Still Image C	anture	Yes (need external SD c	card)	N/A
0				N/A
Video Capture		Yes (w/Audio) (need external SD card)		
Digital Scroll / Pan / Tilt		Yes (available for over 2x digital zoom) (without Zoom window)		
Image File Play / Slideshow		Yes (need external SD card)		N/A
Split Screen		Yes		N/A
Adjustment				I
-		Voc (Auto Claudu D-1	abt Eluoroccont Jacondoccon ¹	Yoc
mage	White Balance		ight, Fluorescent, Incandescent)	Yes
	Focus	Yes (Manual adjustment		Yes
	Focus Lock	Yes	N/A	
	Image Mode	Yes (Normal, Text, Displ	ay)	N/A
	Colour / B&W / Negative	Yes (Colour, Black & Wh		N/A
	0			
	Image Rotation	Yes (0, 180 degrees)		N/A
	Microscope	Yes		
	Noise Reduction	Yes		N/A
unction	HDMI Output		, HDTV (720p), HDTV (1080p)]	N/A
anotion		1 1 1 1 1		
	Output Resolution		768), WXGA (1280 x 800),	N/A
			(GA (1280 x 1024), Full HD (1920 x 1	
	Flicker Reduction	Yes (50 Hz, 60 Hz)		
	Language	Yes		N/A
	Sleep Mode	Yes		N/A
	Sleep Mode Timer	Yes		N/A
	HDMI Link	Yes (On / Off)		N/A
Power	w Voltago	100 - 240 V AC (50/60	Hz)	USB Bus Powered 5 V
		12 V		N/A
Power Supp	, ,			
Power Supp Dutput Voltaç	ge Of AC Power Adapter			Less than 2.5 W
Power Supp Output Voltaç Power Cons	ge Of AC Power Adapter sumption	13 W		
Power Supp Dutput Voltaç Power Cons	ge Of AC Power Adapter			N/A
Power Supp Dutput Voltaç Power Cons Power Cons	ge Of AC Power Adapter sumption	13 W Less than 0.5 W	(0m / 0ft - 2,286m / 7,500ft) (20%	N/A
Power Cons Power Cons Operating 1	ge Of AC Power Adapter sumption sumption (Standby) Temperature	13 W Less than 0.5 W	(0m / 0ft - 2,286m / 7,500ft) (20%	N/A
Power Supp Output Voltag Power Cons Power Cons Operating 1 Dimensions	ge Of AC Power Adapter sumption sumption (Standby) Temperature s	13 W Less than 0.5 W 5 - 35 °C <41 - 95 °F>		N/A 80% humidity, No condensation)
Power Supp Output Voltag Power Cons Power Cons Operating 1 Dimensions Open (D x W	ge Of AC Power Adapter rumption rumption (Standby) Temperature S / x H)	13 W Less than 0.5 W 5 - 35 °C <41 - 95 °F> 502 x 270 x 328 mm	447 x 270 x 317 mm	N/A 80% humidity, No condensation) 76 x 260 x 388 mm
Power Supp Dutput Voltag Power Cons Power Cons Dperating 1 Dimensions Open (D x W	ge Of AC Power Adapter rumption rumption (Standby) Temperature S / x H)	13 W Less than 0.5 W 5 - 35 °C <41 - 95 °F>		N/A 80% humidity, No condensation)
Power Supp Output Voltag Power Cons Power Cons Operating 1 Dimensions Open (D x W Folded (D x	ge Of AC Power Adapter rumption rumption (Standby) Temperature S / x H)	13 W Less than 0.5 W 5 - 35 °C <41 - 95 °F> 502 x 270 x 328 mm 120 x 375 x 122 mm	447 x 270 x 317 mm 120 x 367 x 122 mm	N/A 80% humidity, No condensation) 76 x 260 x 388 mm 76 x 260 x 60 mm
Power Supp Dutput Voltag Power Cons Power Cons Dperating 1 Dimensions Open (D x W Folded (D x Weight	ge Of AC Power Adapter sumption femperature s / x H) W x H)	13 W Less than 0.5 W 5 - 35 °C <41 - 95 °F> 502 x 270 x 328 mm	447 x 270 x 317 mm	N/A 80% humidity, No condensation) 76 x 260 x 388 mm
Power Supp Dutput Voltag Power Cons Power Cons Dperating T Dimensions Dpen (D x W Folded (D x Weight Theft Proof	ge Of AC Power Adapter sumption (standby) Temperature s / x H) W x H)	13 W Less than 0.5 W 5 - 35 °C <41 - 95 °F> 502 x 270 x 328 mm 120 x 375 x 122 mm Approx. 2.6 kg	447 x 270 x 317 mm 120 x 367 x 122 mm	N/A 80% humidity, No condensation) 76 x 260 x 388 mm 76 x 260 x 60 mm
Power Supp Dutput Voltag Power Cons Power Cons Derating 1 Dimensions Open (D x W Folded (D x Weight Theft Proof Kensington I	ge Of AC Power Adapter sumption (sumption (Standby) Femperature s / x H) W x H) Lock	13 W Less than 0.5 W 5 - 35 °C <41 - 95 °F> 502 x 270 x 328 mm 120 x 375 x 122 mm Approx. 2.6 kg Yes	447 x 270 x 317 mm 120 x 367 x 122 mm	N/A 80% humidity, No condensation) 76 x 260 x 388 mm 76 x 260 x 60 mm Approx. 1.0 kg
Power Supp Output Voltac Power Cons Power Cons Operating 1	ge Of AC Power Adapter sumption (sumption (Standby) Femperature s / x H) W x H) Lock	13 W Less than 0.5 W 5 - 35 °C <41 - 95 °F> 502 x 270 x 328 mm 120 x 375 x 122 mm Approx. 2.6 kg	447 x 270 x 317 mm 120 x 367 x 122 mm	N/A 80% humidity, No condensation) 76 x 260 x 388 mm 76 x 260 x 60 mm

LPDC21 / ELPDC13

upplied Accessories

ISB Cable Computer Cable (VGA Cable) xternal AC Power Adapter Remote Control: Yes (with 2 AA Batteries) licroscope Adapter oftware CD-ROM Iser Manual CD-ROM

LPDC07

upplied Accessories ISB Cable licroscope Adapter oft Carrying Case ioftware CD-ROM Iser Manual CD-ROM

LPDC21/ ELPDC13



2024 Epson India Pvt. Ltd. All Rights Reserved. 2024 Epson India Pvt. Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON is registered trademark of Seiko Epson Corporation. All other products names and other company names used herein are or identification purposes only and are the rademarks or registered trademarks of their espective owners. Epson disclaims any and all ights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

pple, iPad and iPhone are trademarks of Apple ic., registered in the U.S. and other countries. pp Store is a service mark of Apple Inc.

ndroid is a trademark of Google Inc.

Dealer's Stamp

EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A, No.1, Murphy Road, Ulsoor, Bangalore – 560 008. Tel: 080–4566 5000 Fax: 080–4566 5005

Regional Offices:

Ahmedabad 3314 8500/01, Chennai 3967 7500, Cochin 4012 315, Coimbatore 98942 19200 Hyderabad 4857 0032, Jaipur 78699 11699, Kolkata 4603 4729, Mumbai 3079 8200 New Delhi 3312 0300, Pune 3028 6000/05,

Information correct at time of printing Printed April 2024.



EPSON

Epson Helpline: For product info or service - 1800 425 0011 For service: 1800 123 001 600 or 1860 3000 1600 (9 am - 6 pm) (Mon - Sat) Email: projector@eid.epson.co.in

www.epson.co.in