

Full detailed report

(ISO/IEC 29183)

Model Stylus NX330

Machine setting

Test Start Date and Time	2011/3/14 , 11:30 am
Tester	T.Onishi
Color or B/W	Color MFD
Configuration (Option)	Option wasn't used
Temperature	24.4 °C
Humidity	24.9 %
Test End Date and Time	2011/3/14 , 2:00 pm

	Pre-set item	Pre-set value
Mode	Output resolution	Default
	Output Quality	Default
	Copying mode	Default
	Auto density adjustment	N/A
	Collating function	N/A
Paper	Paper sending direction	Default
	Paper type setting	Default
Paper path	Paper feeding	Default Paper Feeder
	Paper exit	Standard exit tray
	Output orientation	Default (face up)
Temporary stop	N/A	N/A

Paper	Manufacturer	Fuji Xerox
	Weight	64g/m2
	Size	Letter
	Paper type/Name	PPC/V604

Summary Report

	sFCOT [seconds]	sESAT [ipm]
Color	34	2.6
B&W	18	5.5

Full Report

	Target	sFCOT [seconds]	sEFTP [ipm]			sESAT [ipm]
			1Copy test	1Copy+30 seconds (# copies)	1Copy+4 minutes (# copies)	
Color	A	34	1.7	2.2	2.4	2.5
				3 copies	12 copies	
	B	29	2.0	3.2		4.0
				4 copies		
	C	34	1.7	2.0		2.2
3 copies						
D	38	1.5	1.6		1.8	
			2 copies			
Average		34	1.7	2.2		2.6
B&W	A	17	3.6	4.9	5.7	5.6
				4 copies	25 copies	
	B	17	3.5	5.4		6.2
				5 copies		
	C	18	3.4	4.8		5.5
4 copies						
D	18	3.3	4.4		4.9	
			4 copies			
Average		18	3.4	4.8		5.5