INK TANK SYSTEM PRINTERS L4150/L4160





MIGHTY SAVINGS, COMPACT DESIGN.

Compact and sleek, the new tank design is integrated into the printer to allow the printer to have the smallest footprint* amongst all brands of ink tank printers that use bottled ink refills. Enjoy spill-free refilling with individual bottles which have unique nozzles that fit only into their respective tanks. Auto-duplex printing** affords users up to 50% savings on paper costs by printing automatically on both sides of paper. Remain connected with the option to print wirelessly over network or directly from your mobile devices using Wi-Fi Direct. Rejoice in exceptional print quality with the use of pigment black ink which produces water and smudgeresistant printouts.



L4150



L4160



Ultra-High Page Yield Print

Speed





Wi-Fi

Direct

1-Year Warrantv^



*The total Colour CPP including black ink is 32 paise.



Each printer comes bundled with a starter kit of 1 x 127 mL bottle of black pigment ink and 3 x 70 mL bottles of colour ink.

ENGINEERED FOR BUSINESS

Superior Savings with Auto-Duplex** Save up to 50% on paper cost with auto-duplex function which reduces paper consumption.

Seamless Connectivity Share your printer over Wi-Fi Wi-Fi Dire

Share your printer over Wi-Fi, Wi-Fi Direct, and print on the go via a suite of Epson Connect features.

A4 Size Borderless Printing

Large-size photo printing is made possible with borderless printing up to A4 size.

Presults obtained by comparing published specifications of minimum footprint of all brands of ink tank printers using bottled ink refils against the Epson L4150/4160. Results valid as of July 2017. "Auto-duplex double-sided printing is only available on L4160. "Total Colour Cast Per Print - 20 Paise (XM) + 12 Paise (X) = 32 Paise. Cost Per Print (CPP) is calculated based on quicked Page Yield for Black 7, 500 pages and Composite (Q)anAMagenta/fellow - 6.000 Pages) ink bottles, and MPP of Epson granies ink bottles. Quicked yields are based on the ISO 24711/2471 20 attemts of mixed text and colour graphics with Epson methodology. Dualed yields are based on the replacement ink bottles purchased. Part of the ink from the included bottles is used for printer startup so yields could be lower than those of replacement ink bottles. Actual yields vary due to reasons including images printed, print esting, temperature and humidity. Vields may be lower when printing infrequently or predominantly with one ink colour. Ink is used for both based and colour printing infrequently or predominantly with one ink colour. Ink is used for both based and colour printing. "Source: ID CAsia Pacific Hardcogy Periphenes Taxket 2017 O3. Volume and Value Market stare of AH hiele Hhrites and MPs." Sandard warranty period is one year or 30,000 pages whichered cross fist.

SPECIFICATIONS L4150/4160



MODEL NUMBER	L4150	L4160	Dimensions & Weight
Printer Type	Print, Scan, Copy	Print, Scan, Copy	L4150
Printing		·	Weight: 5.0 kg (11.0 lb)
Printing Technology	On-demand ink jet (piezoelectric)		
Nozzle Configuration			
Print Direction	Bi-directional printing, Uni-directional printing		187 mm
Maximum Resolution	5760 x 1440 dpi (with Variable-Sized Droplet Technology)		(7.4 ")
Minimum Ink Droplet Volume	3 pl		
Print Speed *1			
Draft Text - Memo, A4 (Black #1 / Colour#2)	Up to 33 ppm / 15 ppm		375 mm (13 7 ")
ISO 24734, A4 (Black / Colour)	Up to 10.5 ipm / 5.0 ipm	Up to 10.5 ipm / 5.0 ipm, Duplex: 6.0 ipm / 4.0 ipm	375 mm (13.7 ") (14.8 ")
Photo Default - 10 x 15 cm / 4 x 6 " *2 #3	Approx. 69 sec per photo (Border) / 92 sec per photo (B		
Printer Language	ESC / P-R		 L4160
Automatic 2-sided printing	No	Yes (up to A4)	Weight: 5.5 kg (12.1 lb)
Copying	::	[
Copy Speed			Numero and a second
ISO 29183, A4, Simplex (Black / Colour)	Up to 7.7 ipm / 3.8 ipm		187 mm (7.4 ")
Copy Quality	Normal / Best quality		(7.4)
Maximum Copies from Standalone	20 copies	99 copies	
Reduction / Enlargement	25 - 400%, Auto Fit Function		
Maximum Copy Resolution	360 x 360 dpi	1440 x 720 dpi	347 mm 375 mm (13.7 ")
		1440 X 720 dpi	(14.8 ")
Maximum Copy Size	A4, Letter		
Scanning Scanner Type	Elathed colour image scapper		
Scanner Type	Flatbed colour image scanner		 *1 Print speed (Pages Per Minute) is calculated when printed on A4 plain paper in the fastest mode, 10 x 15 cm photo print speed when printed on Epson
Sensor Type	CIS 1200 x 2400 dpi		
Optical Resolution	1200 x 2400 dpi		Premium Glossy Photo Paper. Print speed may vary depending on system configuration, print mode,
Maximum Scan Area	216 x 297 mm (8.5 x 11.7 ")		document complexity, software, type of paper used an
Scanner Bit Depth			connectivity. Print speed does not include processing
Colour	48-bit input, 24-bit output		time on host computer.
Grayscale	16-bit input, 8-bit output		
Black & White	16-bit input, 1-bit output		10 ⁻ an-
Scan Speed (Flatbed)			
Monochrome 200 dpi	11 sec		
Colour 200 dpi	28 sec		
Paper Handling			10 ST 1
Paper Feed Method	Friction feed		#1 #2 #3
Number of Paper Trays	1 (Paper Cassette)		Black Text Black Text Photo 4R and graphics (4 x 6 ")
Paper Hold Capacity			
Input Capacity	100 sheets, A4 Plain paper (80 g/m 2)		*2 When printed on Epson Premium Glossy Photo Paper.
	20 sheets, Premium Glossy Photo Paper		*3 Default mode in accordance with ISO7779 for MFPs.
Output Capacity		30 sheets, A4 Plain Paper	
	20 sheets, Premium Glossy Photo Paper		plain paper.
Paper Size	Legal, 8.5 x 13 ", Letter, A4, 195 x 270 mm, B5, A5, A6, 100 x 148 mm, B6, 5 x 7 ", 4 x 6 ", Envelopes #10, DL, C6		*5 In accordance with ISO 24711/24712. Actual yields will vary considerably for reasons including images printed.
Maximum Paper Size	215.9 x 1200 mm (8.5 x 47.24 ")		print settings, temperature and humidity. Yields may
Print Margin	0 mm top, left, right, bottom via custom settings in printer driver		be lower when printing infrequently or predominantly with one ink colour. A variable amount of ink remains
Interface	o mm top, leit, right, bottom via custom settings in printer driver		in the cartridges after the "replace cartridge" signal.
USB			Part of the ink from the first cartridges is used for
	USB 2.0		priming the printer. Ink is used for both printing and pr head maintenance. All inks are used for both black and
Network	Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct		colour printing.
Network Protocol	TCP/IPv4, TCP/IPv6		
Mobile and Cloud Printing			
Epson Connect	Epson iPrint, Epson Email Print, Remote Print Driver		
Other Mobile Solutions	Google Cloud Print, Mopria Print Service	Apple AirPrint, Google Cloud Print, Mopria Print Service	
Control Panel			
LCD Screen	-	1.4 " Colour LCD Panel	
Printer Software			
Operating System Compatibility	Windows XP / XP Professional x 64 Edition / Vista / 7 / 8 / 8.1 / 10 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are supported for Windows Server OS		- Onergy
			ENERGYSTAR
	Mac OS X 10.6.8 or later		© 2017 Epson India Pvt. Ltd. All Rights Reserved.
Electrical Specifications			Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and
Rated Voltage	AC 100 - 240 V	AC 100 - 240 V	
Rated Frequency	50 - 60 Hz		EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other products names and other
Power Consumption			company names used herein are for identification purposes only and are the trademarks or registered trademarks of
	12 W	12 W	only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights
Operating	12 W 3.9 W		in those marks. Print samples shown are simulations only.
	U.U 44	4.5 W 0.7 W	Specifications and product availability are subject to chang without notice and may vary between countries. Please
Standby	0.7.W		
Standby Sleep	0.7 W		check with local Epson offices for more information.
Standby Sleep Power off	0.7 W 0.3 W	0.2 W	
Standby Sleep Power off Noise Level	0.3 W	0.2 W	check with local Epson offices for more information.
Standby Sleep Power off Noise Level PC Printing / Premium Glossy			
Standby Sleep Power off Noise Level PC Printing / Premium Glossy Photo Paper Best Photo	0.3 W 38 dB (A)	0.2 W 37 dB (A)	check with local Epson offices for more information.
Standby Sleep Power off Noise Level PC Printing / Premium Glossy Photo Paper Best Photo PC Printing / Plain Paper Default ^{*4}	0.3 W 38 dB (A) 51 dB (A)	0.2 W	check with local Epson offices for more information.
Standby Sleep Power off Noise Level PC Printing / Premium Glossy Photo Paper Best Photo PC Printing / Plain Paper Default ^{*4}	0.3 W 38 dB (A) 51 dB (A) Page Yield 's Order Code	0.2 W 37 dB (A)	check with local Epson offices for more information.
Standby Sleep	0.3 W 38 dB (A) 51 dB (A)	0.2 W 37 dB (A)	check with local Epson offices for more information.
Standby Sleep Power off Noise Level PC Printing / Premium Glossy Photo Paper Best Photo PC Printing / Plain Paper Default ^{*4} Consumables	0.3 W 38 dB (A) 51 dB (A) Page Yield 's Order Code	0.2 W 37 dB (A)	check with local Epson offices for more information.
Standby Sleep Power off Noise Level PC Printing / Premium Glossy Photo Paper Best Photo PC Printing / Plain Paper Default ^{*4} Consumables Black Ink Bottle	0.3 W 38 dB (A) 51 dB (A) Page Yield 's Order Code 7,500 C13T03Y100	0.2 W 37 dB (A)	check with local Epson offices for more information.

EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A, No.1, Murphy Road, Ulsoor, Bangalore - 560 008. Tel: 080-30515000 Fax: 080-30515005

Regional Offices:

Ahmedabad - 26407176/77, Chennai - 30277500/11, Cochin - 4012315, Coimbatore - 98942 19200, Kolkata - 65009370/77, Mumbai - 28261515/17, New Delhi - 46585444, Pune - 30286000, Secunderabad - 40359898





Epson Helpline: For product info, service or to order a ribbon cartridge - 1800 425 0011 For service - 1860 3000 1600 (9AM - 6PM) (Mon - Sat)