

PowerLite® L200SX Wireless XGA 3LCD Short Throw Laser Display



Bring bright, easy-to-read images up to 112" to the classroom with this XGA display.

Ultra bright — 3,600 lumens of color/white brightness¹

Large, easy-to-read images -4:3 XGA resolution for true-to-life images up to 112" diagonal



Large display size — provides up to 2.5 times larger images than 75" flat panels

Time-saving operation — display in seconds with Instant On laser light source

Convenient short throw design — greatly reduces shadowing

Built-in split screen³ — allows simultaneous display of up to 4 connected devices

Built-in 5GHz wireless — supports Miracast® and wireless displays via Epson iProjection™ software to connect; display and share content simultaneously to/from up to 50 connected devices⁴

Seamlessly update existing projector setups — easily replaces PowerLite 520/530 projectors

Powerful 16 W speaker — fill rooms with rich sound







PowerLite® L200SX Wireless XGA 3LCD Short Throw Laser Display

Specifications

Projection System RGB liquid crystal shutter projection system

Driving Method Poly-silicon TFT Active Matrix Pixel Number 786,432 dots (1024 x 768 x 3) chips Color Brightness¹ Color Light Output: 3,600 lumens

White Brightness¹ White Light Output: 3,600 lumens

Aspect Ratio Supports 4:3, 16:10, 16:9*, 16:6* * With vertical image shift control within letterbox area

Image Size 50" x 112'

Display Resolution XGA (1024 x 768)

Light Source Laser Diode Laser Light Source Life²

Normal Mode: Up to 20,000 hours Extended Mode: Up to 30,000 hours

Throw Ratio Range 0.55 (zoom: wide), 0.74 (zoom: tele)

Size (Projected Distance) 82" (0.91 m) **Keystone Correction Manual**

Vertical: ±15 degrees Horizontal: +15 degrees

Dynamic Contrast Ratio Over 2,500,000:1 Color Reproduction Up to 1.07 billion colors

Projection Lens

Type No Optical Zoom, Focus (Manual)

F-Number 1.6 Focal Length 6.4 mm

Zoom Ratio 1 - 1.35 (digital zoom)

Other

Operating Temperature 32 °F to 104 °F (0 °C to 40 °C) (low altitude), 32 °F to 95 °F (0 °C to 35 °C) (high altitude)

Power Supply Voltage 100 V - 240 V AC ±10%, 50/60 Hz Auto Power On Signal Detection on HDMI®/Plug-In Detection (HDMI, USB, VGA 15-pin, BNC)

Sleep Mode Yes (with timer)

Power Consumption

Normal Mode: 265 W Quiet Mode: 201 W Standby Mode: 2.0 W Energy-Saving Mode: 0.5 W

Fan Noise Normal Mode: 36 dB Quiet Mode: 26 dB

Security Enterprise Level Security Encryption

Country of Origin China

Dimensions (W x D x H)

Projector (Including Feet) 12.8" x 3.6" x 13.3" Weight 99lh

Interfaces

2x HDMI (with CEC Control)

1x Analog D-sub 15-pin (in)

1x Analog D-sub 15-pin (in/out)

1x RCA Composite 2x Stereo Mini In

1x Stereo Mini Out

1x RS232C Control Port

1x USB-A Type for Wireless Adapter and Document Camera (DC-07)

1x USB Connector Type B 1x Wired LAN RJ-45

1x Microphone

802.11b/g/n (2.4GHz) , 802.11a/n/ac (5GHz)



* Maximum speed and range are achievable when used with same enhanced mode technology. Actual features and performance may vary depending on your computer system, the environment and other factors

Remote Control

Features Power, HDMI, LAN, Source Search, USB, Auto, menu, arrow buttons, enter, color mode, aspect, split, home, user volume, default, ID, ESC, freeze, Num, E-Zoom, A/V Mute

Operating Angle

Front to Rear: 0 degrees - 60 degrees Right to Left: 30 degrees - 30 degrees Operating Distance 20 ft (6 m)

Eco Features

RoHS compliant

Epson America, Inc. is a SmartWay® Transport Partner⁵ Recyclable product⁶

Support

Epson ConnectionSM

Pre-sales support: U.S. and Canada (800) 463-7766 Internet website: www.epson.com

Service Programs 3-year projector limited warranty or 20,000 hours, whichever comes first

Epson Road Service program, dedicated toll-free support (Ú.S. and Canada only)

What's in the Box

PowerLite L200SX, User's Guide Kit, Projector Remote Control, 2x AA Batteries, Projector Feet, 6' Power Cord, 6' HDMI Cable

Ordering Information

PowerLite L200SX V11H994020 Short Throw Wall Mount (ELPMB64) V12HA39010 Replacement Air Filter V13H134A60 PowerLite Pilot™ 3 (ELPCB03) V12H927020 Active Speakers (ELPSP02) V12H467020 Wireless 802.11 b/g/n/ac LAN unit (ELPAP11) V12H005A02 Epson DC-07 Document Camera V12H759020 Epson DC-13 Document Camera V12H757020 Epson DC-21 Document Camera V12H758020 Soft Carrying Case ELPKS71 V12H001K71 Ceiling Mount ELPMB60 V12H963010 ES3000 Portable Screen (ELPSC26H) V12H002S3Y Duet™ Screen ELPSC80



1 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. | 2 No required maintenance for the light source for up to 20,000 hours. Approximate time until brightness decreases 50% from first usage Measured by acceleration test assuming use of 0.04 - 0.20 mg/m² of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period. | 3 Split Screen feature requires remote control. Consult your user manual for input combinations. | 4 For wireless functionality, including via the Epson iProjection App, the projector must be configured on a network, either through the Ethernet port on the projector (check model specifications for availability) or via a wireless connection. Check your owner's manual to determine if a wireless LAN module must be purchased separately to enable a wireless connection. Not all Epson projectors are able to be networked. The Epson iProjection App does not support all files and formats. See www.epson.com for details. | 5 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency. | 6 For convenient and reasonable recycling options, visit www.epson.com/recycle

See the latest innovations from Epson Business Solutions at www.epson.com/foreducation

Better Products for a Better Future eco.epson.com

Epson America, Inc. 3131 Katella Ave., Los Alamitos, CA 90270 SmartWay
Transport Partner

Epson Canada Limited . 185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com

Specifications and terms are subject to change without notice. EPSON and PowerLite are registered trademarks, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future and Epson iProjection are trademarks of Seiko Epson Corporation. Duet and Pilot are trademarks and Epson Connection is a service mark of Epson America, Inc. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. Miracast® is a registered trademark of Wi-Fi Alliance®. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2022 Epson America, Inc. CPD-59397R2 11/22

Con	tac	t: