EPSON[®]

Epson[®] GX8C SCARA Robot



Epson GX—taking SCARA performance to the next level.

Ultra high performance and flexibility — high throughput with max-rated payloads and multiple arm configurations to accomplish the most demanding assembly needs

Fast cycle times — high acceleration, smooth motion and fast settling times help maximize throughput with proprietary GYROPLUS[™] vibration reduction system, plus no ringing or overshoot¹

Ultimate ease of use — intuitive and feature-packed Epson RC+[®] development software helps create powerful solutions with a simple user interface, integrated debugger and advanced 3D simulator

Designed for reliability — innovative, compact design handles max-rated workloads at fast speeds and high precision within a small footprint

Low total cost of ownership — includes features that help reduce support and installation costs: batteryless encoders, a built-in Ethernet cable, Epson RC+ software and a rich suite of safety features

Accelerate the development of workcell applications — fully integrated, optional solutions include vision guidance, parts feeding, force guidance, conveyor tracking and fieldbus; Epson RC+ Solutions Platform allows for seamless expansion of third-party solutions, benefiting developers and end users

Increase user interaction without sacrificing productivity — SafeSense[™] technology's standard and advanced safety features, with a proper risk assessment, help allow for increased productivity and worker protection while potentially minimizing machine footprint due to the reduction of physical barriers

Minimize the workcell space requirement with an optimized robot footprint — multiple mount and cable exit options; 450 mm, 550 mm or 650 mm reach available

Built for demanding environments — Standard, Cleanroom (ISO 3)² and ESD, Protected IP65 and standalone ESD models available

EPSON[®]

Epson® GX8C SCARA Robot

Model Name						GX8C SCABA Bobot				
Model Number		GX8-C45x			GX8-C55x			GX8-B65x		
Mounting Type		Tabletop	Ceiling	Wall	Tabletop	Ceiling	Wall	Tabletop	Ceiling	Wall
Arm Length	Joint #1 Plus Joint #2		450 mm			550 mm			650 mm	
	Joints #1 - #2	±0.015 mm								
Repeatability Joint #3 Joint #4		±0.010 mm								
		±0.005 deg								
Payload Rated		4 kg								
Max.						8 kg				
Standard Cycle Times		150 dog	0.28 sec	10E dag	. 150 dag	0.30 Sec	. 10E dog	. 150 dog	0.33 Sec	. 140 dog
Max. Motion Range	Joint #2 Std & ESD	2: 0~-270 mm ± 147.5 deg 2: -270~-330 mm ±145 deg 2: 0~-240 mm ±	±103 deg	±105 deg ±152 deg		±132 deg ±132 deg ±135 deg ±147.5 deg Z: 0~-240 mm ±147.5 deg Z: -240~-300 mm ±137.5 deg ±145 deg		±132 deg ±132 deg ±148 deg		
	Joint #2 Clean/Protected	147.5 deg Z: -240~-300 mm ±137.5 deg			Z: 0~-240 m Z: -240~-300					
	Joint #3 Std & ESD	200 mm/330 mm								
	Joint #3 Clean/Protected	1/U mm/30U mm								
Joint #4		±300 0eg								
Joint #4 Allowable Moment	U.UI KQ:m* 0.16 kn.m2									
Joint #3 Downforce		150 N								
User Electric Lines		15-nin (D-suh) 9-nin (D-suh) 8-nin (R 1/5 Cat5a)								
User Pneumatic Lines		אטאריט ווועד געשירט געשירט געשירט אל איז איז ארא ארא געשירט גע								
Brakes										
Power		AC 200 V – 240 V (sinale nhase)								
Power Consumption		2.2 kVa								
Power Cable Length (Cables Ordered Separately)		3 m/5 m/10 m (straight and angled cable end options)								
Bottom Cable Exit Option (Tabletop Only)		Available	Available		Available	Available -		Available	-	-
Weight (Cables Not Included)		33 kg, 73 lb 35 kg, 77 lb			34 kg	j, 75 lb	36 kg, 79 lb	35 kg	, 77 lb	37 kg, 82 lb
Applicable Controller		RC800A								
Installation Environment		Standard/ESD/Cleanroom ISO Class 3 ² with ESD/Protected IP65								
Safety Standards		TUV Certified to meet ISO 10218-1, UL 1740, CSA Z434, ISO 13849								
What's Included		GX8C robot and RC800A controller, E-Stop unit with cable and connector, cable with flying leads for controller E-stop/Safety connection, connector set (I/O, hand I/O and safety circuit connectors)								
Options										
		Vision Guide				Available				
		IntelliFlex [™] Feeders				Available				
		Force Guide			Available					
		Conveyor Tracking			Available					
		Epson RC+ API 8.0			R19NZ901JK					
		GUI Builder 8.0				R19NZ901JQ				
		Fieldbus Master				Available				
		PROFIBUS. CC-Link)				Available				
		External Control Point (ECP) 8.0				R19NZ901JL				
	Teach Pendant				Available					
	Epson OPC UA for Robotics				R19NZ901JZ					
	Arm Length Calibration				R19NZ901JW					
	Bellows Kit (Standard and Long Z) Available									
Support	Customer ServiceApplications SupportSales Inquiries(562) 290-5920(562) 290-5930(562) 290-5997service@robots.epson.comapplications@robots.epson.cominfo@robots.epson.com									
1 When operated within specifications. 2 Complies with ISO Class 3 (ISO 14644-1) and FED-STD-209D Class 1 cleanroom standards. 3 Cycle time based on round-trip arch motion (300 mm horizontal, 25 mm vertical) with 2 kg payload for tabletop model boost mode (path coordinates optimized for maximum speed). 4 When payload center of gravity is aligned with Joint #4; if not aligned with Joint #4, set parameters using INERTIA command. See the latest innovations from Epson Business Solutions at epson.com/forbusiness										
Epson America, Inc.	Epson Cana	da Limited		www.e	epson.com					

3131 Katella Ave., Los Alamitos, CA 90720

185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.ca

Specifications and terms are subject to change without notice. EPSON and Epson RC+ are registered trademarks and GYROPLUS is a trademark of Seiko Epson Corporation. IntelliFlex and SafeSense are trademarks of Epson America, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2025 Epson America, Inc. CPD-65633R2 3/25