




The capable, affordable POS printer with versatile connectivity



Superior Print Speed

With print speeds up to 250 mm/sec, all while delivering clear and accurate prints.



Flexible Interface Options

Choose from a wide array of connectivity from USB, Ethernet to Serial.



Stylish Design

Stylish design for vertical and horizontal usage. Power and operation switches are covered with one sheet.



Enhanced Auto Cutter Life

The printer's reliability allows it to be used for a longer lifetime.

External Option Buzzer Support (OT-BZ20)

With optional buzzer OT-BZ20, Reduce forgetting to take orders by emitting a sound when the printer completes printing.



SPECIFICATIONS

Print Specifications:

Print method: Thermal line printing

Print resolution: 203 x 203 dpi

Print speed: Max. 250 mm/sec

Cutting method: Partial cut (cutting with one point at center left uncut)

Print Fonts:

Fonts: 9 x 17 and 12 x 24 dots/character (W x H)

Column capacity: 48 (Font A), 42 (Font B)

Character size: 0.88 x 2.13 mm and 1.25 x 3.00mm (W x H)

Character: ANK

Character set: 95 Alphanumeric, 18 International, 128 x 43 Graphic

Paper dimensions: 80 mm: 79.5 ± 0.5

58 mm: 57.5 ± 0.5

Paper thickness: 53 - 75 µm

Connectivity:

Interfaces: USB 2.0 & Serial (25 pin)/

USB 2.0 & Serial (9pin) & Ethernet

Options: External buzzer unit (OT-BZ20),
Wi-Fi dongle (OT-WL06, C31CL47312 only)

General Information:

Data buffer: 4KB or 128KB

NV graphics: 256 KB

Downloaded graphics data: 208KB

Software: Drivers and tool software for PC POS (APD, OPOS, JavaPOS, OPOS NET), TM Virtual port driver, Linux® Cups driver, macOS®, OS X® driver, TM-T20III utility, deployment tool, monitoring tool, Epson Net Config (Windows, Mac®), ePOS SDK



USB+Serial



USB+Ethernet+Serial

Barcode/2D Symbol: UPC-A, UPC-E, JAN 8 (EAN 8), JAN 13 (EAN 13), CODE 39, ITF, CODABAR (NW-7), CODE 93, CODE 128, CODE 128 auto, GS1-128, GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Limited, GS1 DataBar Expanded, GS1 DataBar Expanded Stacked, PDF417, QR CODE, MaxiCode, Composite Symbology, Aztec Code, DataMatrix

Dimensions: 146 mm (W) x 199 mm (D) x 146 mm (H)

Weight: 1.7 kg

LED indicators: Power, Paper, Error

DKD function: Yes (2 drivers)

Power supply: AC100 to 240 V / 50 to 60Hz

Power consumption: Operating: Approx. 27.2 W
Standby: Approx. 0.96 W

MTBF: 360,000 hours

MCBF: 60,000,000 lines

Auto cutter life: 2,000,000 cuts

Noise level: Approx. 55dB

Temperature: Operation 5-45°C/ Storage -10-50°C

Warranty:

Warranty: One-year limited warranty

Eco Features:

Power saving mode

Paper saving function

ENERGY STAR® qualified (select SKUs)

Ordering Information:

Product	Model Number
TM-T82IV, built-in USB & Serial (25pin)	C31CL47311
TM-T82IV, built-in USB & Ethernet & Serial (9pin)	C31CL47312

EPSON

Epson Hong Kong Limited

Unit 715-722A, 7/F, Trade Square, 681 Cheung Sha Wan Road,
Cheung Sha Wan, Kowloon, H.K.

*Please call our sales hotlines for demonstration at our showroom.

Epson Authorized Customer Service Centre

Wah Fung Computer Services Ltd.

Unit 901, 9/F, Westin Centre, 26 Hung To Road,
Kwun Tong, Kowloon, Hong Kong

HK Sales Hotline : (852) 2827 8711

HK Technical Hotline : (852) 2827 8911

Macau Hotline : (853) 6516 4693

URL: www.epson.com.hk

APR25-01-TM-T82IV