SPECIFICATIONS

MODEL NUMBER		EB-L210SF	EB-L210SW	
SKU		V11HA75056	V11HA76056	
Projection Tech	nology	RGB liquid crystal shutter projection system		
Specifications of	of Main Parts			
LCD	Size	0.62" (C2Fine)	0.59" (C2Fine)	
	Resolution	Full HD (1080p)	WXGA (1280 x 800)	
Projection Lens	Туре	No Optical Zoom / Focus (Manual)		
	F-Number	1.60		
	Focal Length	6.40mm		
	Zoom Ratio	1.0 – 1.35 (Digital Zoom)		
	Throw Ratio	0.45 - 0.61	0.48 – 0.65	
Light Source				
Туре		Laser Diode		
	/ Quiet / Extended)	20,000 / 20,000 / 30,000 hrs		
Screen Size (Projected Distance)		Standard: 90" screen @ 91cm	Standard: 87" screen @ 91cm	
		Zoom (Wide): 55" to 125" screen	Zoom (Wide): 53" to 120" screen	
Duightungs"		(54 – 127cm)	(54 – 126cm)	
Brightness*1	ut (Normal / Eac)	4,000lm / 2,800lm		
White Light Output (Normal / Eco) Colour Light Output		4,000lm 4,000lm		
Contrast Ratio		4,000iiii Over 2,500,000 : 1		
Internal Speaker(s)		- OYOI 2,000,000 . I		
Sound Output	1(3)	16W Monaural		
Geometric Corr	rection			
Vertical / Horizontal Keystone		±15°/±15°		
Quick Corner		Yes (Manual)		
Image		(··································		
Noise Reduction		Yes		
Super-Resolution		Yes		
Detail Enhancem		Yes		
Connectivity				
Analog Input	D-Sub 15Pin	2		
	Composite	RCA x 1 (Yellow)		
Digital Input	HDMI	2 (HDCP 2.3)		
Analog Output	D-Sub 15Pin	1 (Black) (in common with Computer 2)		
Audio Input RCA		1 (White, Red)		
	Stereo Mini Jack	2		
Audio Output Stereo Mini Jack		1		
Others	USB Type A	1 (For PC Free, Firmware Update, Copy OSD Settings or 5V/2A Power Supply)		
	USB Type B	1 (for Firmware Update, Copy OSD Settings)		
	Mic I/O	Stereo Mini x 1		
Control I/O RS-232C		D-Sub 9pin x 1		
Network	Wired LAN	RJ45 x 1 (100Mbps)		
	Wireless	Built-in and Optional wireless (using ELPAP11)		
Wireless Specif				
-	and Screen Mirroring)	laforatoriations IEEE 000 11h /0 40l lab 11Mba	"2 IFFE 000 11 - (0 40) I-), F4MI"2 IFFE 000 11- (0 40) I-), 70 0MI"	
Supported Speed	a For Each Mode	Infrastructure: IEEE 802.11b (2.4GHz): 11Mbps ⁻² , IEEE 802.11g (2.4GHz): 54Mbps ⁻² IEEE 802.11n (2.4GHz): 72.2Mbps ⁻¹ IEEE 802.11a (5GHz): 54Mbps ⁻² , IEEE 802.11n (5GHz): 150Mbps ⁻² , IEEE 802.11a (5GHz): 325Mbps ⁻²		
		Access Point (Wi-Fi Direct): IEEE 802.11g (2.4GHz): 54Mbps ⁻² , IEEE 802.11n (2.4GHz): 72.2Mbps ⁻² ,		
		IEEE 802.11a (5GHz): 54Mbps ⁻² , IEEE 802.11n (5GHz): 150Mbps ⁻² , IEEE 802.11ac (5GHz): 325Mbps ⁻²		
Supported Mode				
Supported Mode Wireless LAN Security		Infrastructure, Access Point (Wi-Fi Direct) Infrastructure: OPEN, WPA2 / WPA3-PSK, WPA2 / WPA3-EAP		
Wireless I AN Sec		Infrastructure: OPEN, WPA2 / WPA3-PSK WPA2	/ WPA3-FAP	
Wireless LAN Sec				
Wireless LAN Sec		Supported EAP Type: PEAP, PEAP-TLS, EAP-TLS		
	curity			
(Optional Wirele	ess LAN)	Supported EAP Type: PEAP, PEAP-TLS, EAP-TLS Access Point (Wi-Fi Direct): WPA2-PSK (AES)	S, EAP-Fast;	
(Optional Wirele	ess LAN)	Supported EAP Type: PEAP, PEAP-TLS, EAP-TLS Access Point (Wi-Fi Direct): WPA2-PSK (AES) Access Point (Wi-Fi Direct): IEEE 802.11g (2.44)	S, EAP-Fast; GHz): 54Mbps ⁻² , IEEE 802.11n (2.4GHz): 72.2Mbps ⁻² ,	
(Optional Wirele Supported Speed Supported Mode	ess LAN) d For Each Mode	Supported EAP Type: PEAP, PEAP-TLS, EAP-TLS Access Point (Wi-Fi Direct): WPA2-PSK (AES) Access Point (Wi-Fi Direct): IEEE 802.11g (2.44 IEEE 802.11a (5GHz): 54Mbps², IEEE 802.11t	S, EAP-Fast;	
(Optional Wirele Supported Speed Supported Mode	ess LAN) d For Each Mode	Supported EAP Type: PEAP, PEAP-TLS, EAP-TLS Access Point (Wi-Fi Direct): WPA2-PSK (AES) Access Point (Wi-Fi Direct): IEEE 802.11g (2.44)	S, EAP-Fast; GHz): 54Mbps ⁻² , IEEE 802.11n (2.4GHz): 72.2Mbps ⁻² ,	
(Optional Wirele Supported Speed Supported Mode	ess LAN) d For Each Mode curity	Supported EAP Type: PEAP, PEAP-TLS, EAP-TLS Access Point (Wi-Fi Direct): WPA2-PSK (AES) Access Point (Wi-Fi Direct): IEEE 802.11g (2.44 IEEE 802.11a (5GHz): 54Mbps ⁻² , IEEE 802.11I Access Point (Wi-Fi Direct) WPA2-PSK (AES)	6, EAP-Fast; GHz): 54Mbps ⁻² , IEEE 802.11n (2.4GHz): 72.2Mbps ⁻² , n (5GHz): 150Mbps ⁻² , IEEE 802.11ac (5GHz): 325Mbps ⁻²	
(Optional Wirele Supported Speed Supported Mode Wireless LAN Sed	ess LAN) d For Each Mode curity	Supported EAP Type: PEAP, PEAP-TLS, EAP-TLS Access Point (Wi-Fi Direct): WPA2-PSK (AES) Access Point (Wi-Fi Direct): IEEE 802.11g (2.4t IEEE 802.11a (5GHz): 54Mbps²², IEEE 802.11t Access Point (Wi-Fi Direct) WPA2-PSK (AES) 0 - 2,286 m (0 - 7,500 ft): 0 °C - 40 °C [32 °F	6, EAP-Fast; GHz): 54Mbps ⁻² , IEEE 802.11n (2.4GHz): 72.2Mbps ⁻² , n (5GHz): 150Mbps ⁻² , IEEE 802.11ac (5GHz): 325Mbps ⁻² - 104 °F]; 20% to 80% Humidity, No Condensation	
(Optional Wirele Supported Speed Supported Mode Wireless LAN Sec Operating Temp	ess LAN) d For Each Mode curity perature ³	Supported EAP Type: PEAP, PEAP-TLS, EAP-TLS Access Point (Wi-Fi Direct): WPA2-PSK (AES) Access Point (Wi-Fi Direct): IEEE 802.11g (2.4f IEEE 802.11a (5GHz): 54Mbps*², IEEE 802.11f Access Point (Wi-Fi Direct) WPA2-PSK (AES) 0 - 2,286 m (0 - 7,500 ft): 0 °C - 40 °C [32 °F Over 2,286 m (7,500 ft): 0 - 35 °C [32 °F - 95 °C)	6, EAP-Fast; GHz): 54Mbps ⁻² , IEEE 802.11n (2.4GHz): 72.2Mbps ⁻² , n (5GHz): 150Mbps ⁻² , IEEE 802.11ac (5GHz): 325Mbps ⁻² - 104 °F]; 20% to 80% Humidity, No Condensation F]; 20%-80% Humidity, No Condensation	
(Optional Wirele Supported Speed Supported Mode Wireless LAN Sed	ess LAN) d For Each Mode curity perature's	Supported EAP Type: PEAP, PEAP-TLS, EAP-TLS Access Point (Wi-Fi Direct): WPA2-PSK (AES) Access Point (Wi-Fi Direct): IEEE 802.11g (2.4t IEEE 802.11a (5GHz): 54Mbps²², IEEE 802.11t Access Point (Wi-Fi Direct) WPA2-PSK (AES) 0 - 2,286 m (0 - 7,500 ft): 0 °C - 40 °C [32 °F	6, EAP-Fast; GHz): 54Mbps ⁻² , IEEE 802.11n (2.4GHz): 72.2Mbps ⁻² , n (5GHz): 150Mbps ⁻² , IEEE 802.11ac (5GHz): 325Mbps ⁻² - 104 °F]; 20% to 80% Humidity, No Condensation F]; 20%-80% Humidity, No Condensation	
(Optional Wireles Supported Speed Supported Mode Wireless LAN Sed Operating Temp	ess LAN) d For Each Mode curity cerature ³ dee n / Off	Supported EAP Type: PEAP, PEAP-TLS, EAP-TLS Access Point (Wi-Fi Direct): WPA2-PSK (AES) Access Point (Wi-Fi Direct): IEEE 802.11g (2.44 IEEE 802.11a (5GHz): 54Mbps², IEEE 802.11r Access Point (Wi-Fi Direct) WPA2-PSK (AES) 0 - 2,286 m (0 - 7,500 ft): 0 °C - 40 °C [32 °F - 95 °C) Over 2,286 m (7,500 ft): 0 - 35 °C [32 °F - 95 °C) Over 1,500 m / 4,921 ft, with High Altitude Mo	6, EAP-Fast; GHz): 54Mbps ⁻² , IEEE 802.11n (2.4GHz): 72.2Mbps ⁻² , n (5GHz): 150Mbps ⁻² , IEEE 802.11ac (5GHz): 325Mbps ⁻² - 104 °F]; 20% to 80% Humidity, No Condensation FJ; 20%-80% Humidity, No Condensation de: 0 - 3,048 m (0 - 10,000 ft)	
(Optional Wirele Supported Speed Supported Mode Wireless LAN Sed Operating Temp Operating Altitu Direct Power O	ess LAN) d For Each Mode curity cerature ³ dee n / Off	Supported EAP Type: PEAP, PEAP-TLS, EAP-TLS Access Point (Wi-Fi Direct): WPA2-PSK (AES) Access Point (Wi-Fi Direct): IEEE 802.11g (2.44 IEEE 802.11a (5GHz): 54Mbps², IEEE 802.111 Access Point (Wi-Fi Direct) WPA2-PSK (AES) 0 - 2,286 m (0 - 7,500 ft): 0 °C - 40 °C [32 °F Over 2,286 m (7,500 ft): 0 - 35 °C [32 °F - 95 °C Over 2,286 m (7,500 ft): 0 - 40 °C [32 °F - 95 °C Over 1,500 m / 4,921 ft, with High Altitude Moves	6, EAP-Fast; GHz): 54Mbps ⁻² , IEEE 802.11n (2.4GHz): 72.2Mbps ⁻² , n (5GHz): 150Mbps ⁻² , IEEE 802.11ac (5GHz): 325Mbps ⁻² - 104 °F]; 20% to 80% Humidity, No Condensation FJ; 20%-80% Humidity, No Condensation de: 0 - 3,048 m (0 - 10,000 ft)	
(Optional Wirele Supported Speed Supported Mode Wireless LAN Sed Operating Temp Operating Altitu Direct Power O Start-Up Period	ess LAN) d For Each Mode curity berature's ide n / Off	Supported EAP Type: PEAP, PEAP-TLS, EAP-TLS Access Point (Wi-Fi Direct): WPA2-PSK (AES) Access Point (Wi-Fi Direct): IEEE 802.11g (2.44 IEEE 802.11a (5GHz): 54Mbps², IEEE 802.11t Access Point (Wi-Fi Direct) WPA2-PSK (AES) 0 - 2,286 m (0 - 7,500 ft): 0 °C - 40 °C [32 °F Over 2,286 m (7,500 ft): 0 - 35 °C [32 °F - 95 °C Over 1,500 m / 4,921 ft, with High Altitude Mo Yes Less than 9 seconds (Epson Logo), Warm-up	6, EAP-Fast; GHz): 54Mbps ⁻² , IEEE 802.11n (2.4GHz): 72.2Mbps ⁻² , n (5GHz): 150Mbps ⁻² , IEEE 802.11ac (5GHz): 325Mbps ⁻² - 104 °F]; 20% to 80% Humidity, No Condensation FJ; 20%-80% Humidity, No Condensation de: 0 - 3,048 m (0 - 10,000 ft)	
(Optional Wirele Supported Speed Supported Mode Wireless LAN Sed Operating Temp Operating Altitu Direct Power O Start-Up Period Quick Start-Up	ess LAN) d For Each Mode curity berature's ide n / Off	Supported EAP Type: PEAP, PEAP-TLS, EAP-TLS Access Point (Wi-Fi Direct): WPA2-PSK (AES) Access Point (Wi-Fi Direct): IEEE 802.11g (2.44 IEEE 802.11a (5GHz): 54Mbps², IEEE 802.111 (Access Point (Wi-Fi Direct)) WPA2-PSK (AES) 0 - 2,286 m (0 - 7,500 ft): 0 °C - 40 °C [32 °F - 95 °C Over 2,286 m (7,500 ft): 0 - 35 °C [32 °F - 95 °C Over 1,500 m / 4,921 ft, with High Altitude Mo Yes Less than 9 seconds (Epson Logo), Warm-up Less than 5 seconds (Display)	6, EAP-Fast; GHz): 54Mbps ⁻² , IEEE 802.11n (2.4GHz): 72.2Mbps ⁻² , n (5GHz): 150Mbps ⁻² , IEEE 802.11ac (5GHz): 325Mbps ⁻² - 104 °F]; 20% to 80% Humidity, No Condensation FJ; 20%-80% Humidity, No Condensation de: 0 - 3,048 m (0 - 10,000 ft)	
(Optional Wirele Supported Speed Supported Mode Wireless LAN Set Operating Temp Operating Altitu Direct Power O Start-Up Period Quick Start-Up Cool Down Peri	ess LAN) d For Each Mode curity berature's ide n / Off	Supported EAP Type: PEAP, PEAP-TLS, EAP-TLS Access Point (Wi-Fi Direct): WPA2-PSK (AES) Access Point (Wi-Fi Direct): IEEE 802.11g (2.44 IEEE 802.11a (5GHz): 54Mlpps², IEEE 802.111 Access Point (Wi-Fi Direct) WPA2-PSK (AES) 0 - 2,286 m (0 - 7,500 ft): 0 °C - 40 °C [32 °F Over 2,286 m (7,500 ft): 0 °S C (32 °F - 95 °Over 2,286 m (7,500 ft): 0 ver 1,500 m / 4,921 ft, with High Altitude Mo Yes Less than 9 seconds (Epson Logo), Warm-up Less than 5 seconds (Display) Instant Off Electrostatic Filter	6, EAP-Fast; GHz): 54Mbps ⁻² , IEEE 802.11n (2.4GHz): 72.2Mbps ⁻² , n (5GHz): 150Mbps ⁻² , IEEE 802.11ac (5GHz): 325Mbps ⁻² - 104 °F]; 20% to 80% Humidity, No Condensation FJ; 20%-80% Humidity, No Condensation de: 0 - 3,048 m (0 - 10,000 ft)	
(Optional Wireles Supported Mode Wireless LAN Sec Operating Temp Operating Altitu Direct Power O Start-Up Period Quick Start-Up Cool Down Peri Air Filter Power Supply V	ess LAN) d For Each Mode curity berature* ide n / Off Type Maintenance Cycle* foltage	Supported EAP Type: PEAP, PEAP-TLS, EAP-TLS Access Point (Wi-Fi Direct): WPA2-PSK (AES) Access Point (Wi-Fi Direct): IEEE 802.11g (2.44 IEEE 802.11a (5GHz): 54Mlpps², IEEE 802.111 Access Point (Wi-Fi Direct) WPA2-PSK (AES) 0 - 2,286 m (0 - 7,500 ft): 0 °C - 40 °C [32 °F Over 2,286 m (7,500 ft): 0 °S C (32 °F - 95 °Over 2,286 m (7,500 ft): 0 ver 1,500 m / 4,921 ft, with High Altitude Mo Yes Less than 9 seconds (Epson Logo), Warm-up Less than 5 seconds (Display) Instant Off Electrostatic Filter	6, EAP-Fast; GHz): 54Mbps ⁻² , IEEE 802.11n (2.4GHz): 72.2Mbps ⁻² , n (5GHz): 150Mbps ⁻² , IEEE 802.11ac (5GHz): 325Mbps ⁻² - 104 °F]; 20% to 80% Humidity, No Condensation FJ; 20%-80% Humidity, No Condensation de: 0 - 3,048 m (0 - 10,000 ft)	
(Optional Wirele Supported Speed Supported Mode Wireless LAN Set Operating Temp Operating Altitu Direct Power O Start-Up Period Quick Start-Up Cool Down Peri Air Filter Power Supply V Power Consum	ess LAN) d For Each Mode curity berature 3 ide n / Off I Type Maintenance Cycle foliage ption (220 - 240V)	Supported EAP Type: PEAP, PEAP-TLS, EAP-TLS Access Point (Wi-Fi Direct): WPA2-PSK (AES) Access Point (Wi-Fi Direct): IEEE 802.11g (2.44 IEEE 802.11a (5GHz): 54Mbps², IEEE 802.11t (Access Point (Wi-Fi Direct)) WPA2-PSK (AES) 0 - 2,286 m (0 - 7,500 ft): 0 °C - 40 °C [32 °F Over 2,286 m (7,500 ft): 0 °S °C [32 °F - 95 °C Over 1,500 m / 4,921 ft, with High Altitude Mo Yes Less than 9 seconds (Epson Logo), Warm-up Less than 5 seconds (Display) Instant Off Electrostatic Filter 20,000 hours 100 - 240 V AC ±10%, 50/60 Hz	6, EAP-Fast; GHz): 54Mbps ⁻² , IEEE 802.11n (2.4GHz): 72.2Mbps ⁻² , n (5GHz): 150Mbps ⁻² , IEEE 802.11ac (5GHz): 325Mbps ⁻² - 104 °F]; 20% to 80% Humidity, No Condensation FJ; 20%-80% Humidity, No Condensation de: 0 - 3,048 m (0 - 10,000 ft)	
(Optional Wireles Supported Speed Supported Mode Wireless LAN Sed Operating Temp Operating Altitu Direct Power O Start-Up Period Quick Start-Up Cool Down Peri Air Filter Power Supply V Power Consum Lamp On (Norma	ess LAN) d For Each Mode curity berature 3 de n / Off I Type Maintenance Cycle3 (oltage ption (220 - 240V) al / Extended)	Supported EAP Type: PEAP, PEAP-TLS, EAP-TLS Access Point (Wi-Fi Direct): WPA2-PSK (AES) Access Point (Wi-Fi Direct): IEEE 802.11g (2.44 IEEE 802.11a (5GHz): 54Mbps², IEEE 802.11r Access Point (Wi-Fi Direct) WPA2-PSK (AES) 0 - 2,286 m (0 - 7,500 ft): 0 °C - 40 °C [32 °F Over 2,286 m (7,500 ft): 0 °S - 50 °C [32 °F - 95 °S Over 1,500 m / 4,921 ft, with High Altitude Mo Yes Less than 9 seconds (Epson Logo), Warm-up Less than 5 seconds (Display) Instant Off Electrostatic Filter 20,000 hours 100 - 240 V AC ±10%, 50/60 Hz	6, EAP-Fast; GHz): 54Mbps ⁻² , IEEE 802.11n (2.4GHz): 72.2Mbps ⁻² , n (5GHz): 150Mbps ⁻² , IEEE 802.11ac (5GHz): 325Mbps ⁻² - 104 °F]; 20% to 80% Humidity, No Condensation FJ; 20%-80% Humidity, No Condensation de: 0 - 3,048 m (0 - 10,000 ft)	
(Optional Wireles Supported Speed Supported Mode Wireless LAN Sec Operating Temp Operating Altitu Direct Power O Start-Up Period Quick Start-Up Cool Down Peri Air Filter Power Supply V Power Consum Lamp On (Norma Standby (Network)	curity Pess LAN) d For Each Mode curity Derature'3 Ide Type Maintenance Cycle' foltage ption (220 - 240V) at / Extended) k On / Off)	Supported EAP Type: PEAP, PEAP-TLS, EAP-TLS Access Point (Wi-Fi Direct): WPA2-PSK (AES) Access Point (Wi-Fi Direct): IEEE 802.11g (2.44 IEEE 802.11a (5GHz): 54Mbps², IEEE 802.111 Access Point (Wi-Fi Direct) WPA2-PSK (AES) 0 - 2,286 m (0 - 7,500 ft): 0 °C - 40 °C [32 °F Over 2,286 m (7,500 ft): 0 °S - 35 °C [32 °F - 95 Over 1,500 m / 4,921 ft, with High Altitude Mo Yes Less than 9 seconds (Epson Logo), Warm-up Less than 5 seconds (Display) Instant Off Electrostatic Filter 20,000 hours 100 - 240 V AC ±10%, 50/60 Hz 260W / 191W 2.0W / 0.5W	6, EAP-Fast; GHz): 54Mbps ⁻² , IEEE 802.11n (2.4GHz): 72.2Mbps ⁻² , n (5GHz): 150Mbps ⁻² , IEEE 802.11ac (5GHz): 325Mbps ⁻² - 104 °F]; 20% to 80% Humidity, No Condensation FJ; 20%-80% Humidity, No Condensation de: 0 - 3,048 m (0 - 10,000 ft)	
(Optional Wirele Supported Mode Wireless LAN Sec Operating Temp Operating Altitu Direct Power O Start-Up Period Quick Start-Up Cool Down Peri Air Filter Power Consum Lamp On (Norma Standby (Netword Dimension Excl	curity ess LAN) d For Each Mode curity berature 3 ide n / Off Type Maintenance Cycle 3 foldage ption (220 - 240V) al / Extended) k Con / Off) uding Feet (D x W x H)	Supported EAP Type: PEAP, PEAP-TLS, EAP-TLS Access Point (Wi-Fi Direct): WPA2-PSK (AES) Access Point (Wi-Fi Direct): IEEE 802.11g (2.44 IEEE 802.11a (5GHz): 54Mbps², IEEE 802.111 Access Point (Wi-Fi Direct) WPA2-PSK (AES) 0 - 2,286 m (0 - 7,500 ft): 0 °C - 40 °C (32 °F Over 2,286 m (7,500 ft): 0 °S °C (32 °F - 95 °C	6, EAP-Fast; GHz): 54Mbps ⁻² , IEEE 802.11n (2.4GHz): 72.2Mbps ⁻² , n (5GHz): 150Mbps ⁻² , IEEE 802.11ac (5GHz): 325Mbps ⁻² - 104 °F]; 20% to 80% Humidity, No Condensation FJ; 20%-80% Humidity, No Condensation de: 0 - 3,048 m (0 - 10,000 ft)	
(Optional Wirele Supported Mode Wireless LAN Sec Operating Temp Operating Altitu Direct Power O Start-Up Period Quick Start-Up Cool Down Peri Air Filter Power Supply V Power Consum Lamp On (Norma Standby (Netword Dimension Excl Weight (with ca	curity ass LAN) d For Each Mode curity berature a ide n / Off Type Maintenance Cycle of the companion	Supported EAP Type: PEAP, PEAP-TLS, EAP-TLS Access Point (Wi-Fi Direct): WPA2-PSK (AES) Access Point (Wi-Fi Direct): IEEE 802.11g (2.4/ IEEE 802.11a (5GHz): 54Mbps'², IEEE 802.11r Access Point (Wi-Fi Direct) WPA2-PSK (AES) 0 - 2,286 m (0 - 7,500 ft): 0 °C - 40 °C (32 °F Over 2,286 m (7,500 ft): 0 - 35 °C (32 °F - 95 °C	6, EAP-Fast; GHz): 54Mbps ⁻² , IEEE 802.11n (2.4GHz): 72.2Mbps ⁻² , n (5GHz): 150Mbps ⁻² , IEEE 802.11ac (5GHz): 325Mbps ⁻² - 104 °F]; 20% to 80% Humidity, No Condensation FJ; 20%-80% Humidity, No Condensation de: 0 - 3,048 m (0 - 10,000 ft)	
(Optional Wirele Supported Mode Wireless LAN Sec Operating Temp Operating Altitu Direct Power O Start-Up Period Quick Start-Up Cool Down Peri Air Filter Power Consum Lamp On (Norma Standby (Netword Dimension Excl	curity ass LAN) d For Each Mode curity berature a ide n / Off Type Maintenance Cycle of the companion	Supported EAP Type: PEAP, PEAP-TLS, EAP-TLS Access Point (Wi-Fi Direct): WPA2-PSK (AES) Access Point (Wi-Fi Direct): IEEE 802.11g (2.44 IEEE 802.11a (5GHz): 54Mbps², IEEE 802.111 Access Point (Wi-Fi Direct) WPA2-PSK (AES) 0 - 2,286 m (0 - 7,500 ft): 0 °C - 40 °C (32 °F Over 2,286 m (7,500 ft): 0 °S °C (32 °F - 95 °C	6, EAP-Fast; GHz): 54Mbps ⁻² , IEEE 802.11n (2.4GHz): 72.2Mbps ⁻² , n (5GHz): 150Mbps ⁻² , IEEE 802.11ac (5GHz): 325Mbps ⁻² - 104 °F]; 20% to 80% Humidity, No Condensation FJ; 20%-80% Humidity, No Condensation de: 0 - 3,048 m (0 - 10,000 ft)	

Colour brightness (colour light output) and white brightness (white light output) will vary depending on usage conditions. Colour light output measured in accordance with ISO 21118.

Maximum speed and range is achievable when used with same enhanced mode technology. Actual data rates, features and performance may vary depending on your computer system, the environment and other factors.

when environmental temperature becomes high, the brightness becomes dark automatically.

When environmental temperature becomes high, the brightness becomes dark automatically.

When used in the general office environment (the amount of floating dust: 0.04 - 0.2 mg/m³). Based on the Epson's in-house test results

EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A. No.1. Murphy Road, Ulsoor, Bangalore – 560 008. Tel: 080–4566 5000 Fax: 080–4566 5005

Regional Offices:

Ahmedabad 3314 8500/01, Chennai 3967 7500, Cochin 4012 315, Coimbatore 98942 19200 Hyderabad 4857 0032, Jaipur 78699 11699, Kolkata 4603 4729, Mumbai 3079 8200 New Delhi 3312 0300, Pune 3028 6000/05,





Epson Helpline: For product info or service- 1800 425 0011 For service - 1800 123 001 600 (9AM - 6PM) (Mon - Sat) Email: emp@eid epson co in

www.epson.co.in

Supplied Accessories Power Cable: 4.5m, 3 wires HDMI Cable: 1.8m

Optional Accessories Air Filter: ELPAF60

EB-L210SF/L210SW

User Guide

Remote Control with 2xAA Battery

Wireless Presentation system: ELPWP10 Wireless LAN unit: ELPAP11

©2023 Epson India Pvt. Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON is a registered trademark of Seiko Epson All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their Epson disclaims any and all rights in those marks.

may vary between countries. Please check with local

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Epson offices for more information.


Android is a trademark of Google Inc.

Dealer's Stamp

Information correct at time of printing. Printed October2023

SHORT THROW LASER PROJECTORS EB-L210SF/L210SW





Create a novel experience for your audience with immersive short throw projection.

Capture your audience's imagination with the breathtakingly vibrant and sharp visuals offered by Epson's EB-L210SF/L210SW projectors. Crafted to meet the demands of both educational and corporate environments, these projectors enable you to deliver awe-inspiring presentations in stunning Full HD*1 clarity, even on large screens at a close distance. Whether you are presenting in a cozy boardroom or a vast auditorium, these user-friendly projectors are meticulously designed to convey your message with crystal-clear precision, captivate your audience's undivided attention, and leave an indelible impression that will endure long after your presentation ends.

Full **HD**

1080p













Exceptional Visual Definition

Experience unparalleled visual brilliance in full-HD resolution at 4,000 lumens with a laser light source.

3LCD

Impressive Short-throw Distance

With a throw ratio of 1.264m*2, project vivid and sharp presentations on a 120-inch large screen with ease.

Laser Technology

Our maintenance-free laser light source provides an astounding 20,000 hours*3 of uninterrupted top-notch performance.

^{*1} Only applicable for EB-L210SF. #Source: Futuresource Consulting.

^{*2} EB-L210SW: up to 120 inches for 16:10 at 1.264m throw; EB-L210SF: up to 125 inches for 16:9 at 1.268m throw.

*3 Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m3 of particulate matter. Time varies depending on usage conditions and environments

Captivate your audience


With Short Throw Laser Projector

Elevate the customer's experience with fascinating large-screen projections in various shapes on virtually any surface. Discover a world of endless creative possibilities in even the most compact spaces, thanks to Epson EB-L210SF/L210SW short-throw projectors.



Improved Design

By utilising Epson's original fixed phosphor unit and an optimised design, the projector produces brighter and sharper images while being more compact. Additionally, the new heatsink design enhances heat conductivity and resistance, resulting in improved performance and high-quality, vivid images.




20,000 Maintenance-Free Hours

Epson's unique laser technology allows for 20,000 hours* of maintenance-free laser light source in the projector. Users can enjoy peace of mindand highly reliable performance, thanks to the innovative fixed phosphor unit, providing long-lasting durability to the device.



Maintenance period of laser and lamp




*No required maintenance for the light source for up to 20,000 hours. Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m3 of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period.

Phenomenal Short-throw Functionality



Epson's EB-L210SF/L210SW short throw projectors are capable of producing clear and vibrant large-screen projections of up to 120" diagonal from just 1.264m away*, thanks to throw ratio as low as 0.45**. These projectors can help you deliver sharp and immersive presentations.



- * For EB-L210SW: 120 inch for 16:10 at 1.264m throw; EB-L210SF: 125 inch for 16:9 at 1.268m throw.
- **0.45 for EB-L210SF; 0.48 for EB-L210SW.
 - Only for EB-L210SF. The 21:9 aspect ratio is commonly used for video conferencing in hybrid workspaces.



Wide Aspect Screens

For EB-L210SF

Epson's all-new standard throw Full HD models offer clear wide-screen aspect projection. The EB-L210SF can project up to 125" diagonal in a 16:9 aspect ratio, making these projectors suitable for any education or business need.



Alluring and Captivating For EB-L210SF

Content is projected with exceptional clarity in Full-HD resolution, captivating your audiences.



High Contrast Ratio

The astounding over 2,500,000:1 contrast ratio improves visibility and enhances the contrast of both bright and dark areas, resulting in a more vivid and lifelike image.

Content Playback Function

Maximise the potential of your projector's impressive short-throw capability by displaying distinctive signages in the office, leaving a lasting impression on visitors and employees alike.



Wide Range of Connectivity

Full **HD** 1080p

Experience the convenience and ease of fuss-free projections with EB-L210SF/L210SW's advanced connectivity features. Supporting multiple conventional analogue sources, they are also fully compatible with HDMI input, providing seamless and effortless connectivity for all your presentation needs.













SHORT THROW LASER PROJECTORS

EB-L210SF/L210SW



Better viewing experience for all

Impactful presentations with minimal interference

Deliver flawless presentations with the game-changing EB-L210SF/L210SW projectors. With their short throw distance, bid farewell to glare on the presenter and annoying shadow interference on the screen. Delight in a comfortable and distraction-free viewing experience for all, allowing you to effortlessly educate and captivate your audience.



Perfect Even in Bright Rooms

Even in well-lit environments, Epson projectors are equipped with a powerful 4,000lm light source, ensuring clear and sharp visuals for your presentations.



Multi-PC Projection

The Epson iProjection software allows teachers to display the work of up to four students on the screen for discussion. Additionally, up to 50 students can be connected to the connection list at once.



Wireless Integration

Ease of connection with built-in wireless connectivity through Wi-Fi and screen mirroring support.



Screen Mirroring

Enjoy the freedom to share content wirelessly from multiple devices simultaneously with the built-in screen mirroring function.



With the EB-L210SF/L210SW projectors, you can unleash your team's collaborative potential and

engage your clients like never before with dynamic and impressive presentations. Thanks to the

sharp and vivid projections, your message can be conveyed with uncompromising clarity, whether

Wide Aspect Screen Size

With functions supporting wide-aspect screens, you can easily navigate the controls via a remote controller.



FOR CORPORATE

Cost Effective Upgrades

Simply install your Epson projector on an existing mount* without having to buy a new one.

*Compatible mount: ELPMB23 (White), ELPMB60W (White), ELPMB60B (Black), ELPMB61W (White) and ELPMB61B (Black).

Download and Project



Project Documents, Photos Wirelessly

Enjoy wireless projection via the Epson iProjection app with your PC (Windows, Mac and Chromebook) or mobile devices. This powerful app allows you to share, manage, and annotate on displayed content from an easy-to-use, intuitive menu.







Quick and Easy Connection

The optional ELPWP10* wireless presentation kit provides a quick way to connect wirelessly without installing iProjection software. Simply plug in the dongle and tap the connect button to share your content immediately.



*ELPWP10 is sold separately.

Amplify your messages' outreach


Engage your clients with dynamic and memorable presentations

the projectors are easily mountable on walls, ceiling or set on a desk.



Unveil

EPSON



Up to 3x **Brighter Colours**

BRIGHTNESS



WHITE 3000 LUMENS

COLOUR 3000 LUMENS



WHITE 3000 LUMENS **COLOUR 430 LUMENS**** No Rainbow Effect

COMFORT

















REALISM

3x Wider

Colour Gamut

WIDER COLOUR RANGE









Efforts to mitigate environmental impacts in manufacturing



Toyoshina plant in Japan

Epson becomes the Manufacturing Industry's First to Switch to 100% Renewable Electricity at all sites in Japan.

In November 2021, we achieved 100% renewable electricity at all domestics sites², Shinshu Green Electricity, CO₂-free value-added electric power produced locally in Nagano Perfecture using Nagano Perfecture hydroelectric power. This is both reducing Epson's GHC emissions³ and increasing consumption of locally produced energy.

Assembled using 100% renewable electricity

Epson announced that its worldwide group sites² will all meet their electricity needs from 100% renewable energy sources (renewable electricity) by 2023. We have achieved 100% renewable energy at our projector's manufacturing site in the Philippines by generating power with a rooftop mega-solar power plant and by switching to a mix of geothermal and hydroelectric power in January 2021.




Epson Precision (Philippines), Inc.



recycled cardboard packaging

All carton box packaging of Epson's projectors are made by over 80% recycled cardboard.



³ GHG (Greenhouse Gas), GHG scope 1, 2, 3 emission

4 Products assembled in the Philippines



EPSON 3LCD

PROJECTORS

1 - CHIP

PROJECTORS

