



## Expand your print applications with Epson's minilab printer, featuring both single-sided and double-sided printing.\*

Give your business an edge with Epson's Surelab™ SL-D1030. Carefully engineered to produce sharp colour-accurate photos with the reliable Micro Piezo™ Printhead Technology, the compact yet sturdy minilab printer delivers picture-perfect precision on every print. Enjoy double-sided printing™ along with improved productivity with complete ease. Bring images to life on glossy or luster photo papers flawlessly with Epson's Surelab™ SL-D1030 today.

Find the details at www.epson.co.in



## **SPECIFICATIONS**

**MODEL NUMBER SKU CODE** 

**PRINTING** 

Technology 1 Technology 2 Printhead

Nozzle Configuration Maximum Resolution Maximum Ink Droplet Volume

**INK SYSTEM** 

Ink Type Colours Ink Capacity

**MEDIA HANDLING** 

Maximum Roll Diameter Maximum Roll Weight Paper Width Roll Paper Cut Sheet

Paper Size **ASF** Paper Thickness

Maximum Printable Length

CONNECTIVITY

Interfaces Printer Language Memory

ENVIRONMENT CHARACTERISTICS

Temperature (°C) Humidity

**DIMENSIONS & WEIGHT** 

With Printing ( $W \times D \times H$ )

Stowed (W x D x H)

Weight (Excl. Ink Cartridge)

**ELECTRICAL SPECIFICATION** 

Voltage Power

**NOISE LEVEL** Sound Pressure Level

**UTILITY SOFTWARE** 

Bundled in CD

Window Supported OS Mac Supported OS

SL-D1030

C11CJ33402

Micro Piezo™ Inkjet Technology

Variable-Sized Droplet Technology

Micro Piezo™ Printhead

1080 nozzles (180 nozzles x 6 channels x 1 head)

1,440 x 720 dpi

2.5 pl

Epson UltraChrome™ D6r-S Dye Ink

Cyan, Magenta, Yellow, Light Cyan, Light Magenta, Black

250 mL

Max. 170 mm

Max. 4 kg

89mm to 210 mm

Width: 89 mm - 210 mm; Length: 148 mm - 1,000 mm

Width: 89 mm - 210 mm; Length: 148 mm - 297 mm Roll: 0.22 mm - 0.25 mm / Manual: 0.20 mm - 0.50 mm /

ASF: 0.20 mm - 0.265 mm

Roll: Max. 1,000 mm, Min. 50 mm / Manual Feed: 1,000 mm /

Auto Sheet Feeder (ASF): 297 mm

Hi-Speed USB, 100BASE-TX/10BASE-T, IEEE802.11b/g/n, Wi-Fi

ESC/P-R 1 GB

Operating: 10 °C - 35 °C; Storage: -20 °C - 40 °C

Operating: 20 - 80% (No Condensation); Storage: 5 - 85% (No Condensation)

Roll: 460 x 747 x 441 mm

Manual Feed: 460 x 747 x 476 mm

ASF: 460 x 747 x 441 mm

460 x 374 x 343 mm

23.1 kg

Main unit: 17.6 kg, Duplex Feeder: 5.5 kg

AC 100 to 120 V, 220 to 240 V, 50/60 Hz

Operating: Approx. 80 W / Ready: Approx. 14 W / Sleep: Approx. 1.2 W / Standby: Approx. 0.2 W

< 50 dB(A) or less

Windows®: Printer Driver, Installer Package, Software Updater, EpsonNet Print, EpsonNet setup, EpsonNet Config SE, Manual

Package, System Software, Mac OS X: Installer Package OS: Windows® 10, Windows® 8.1 for each 32bit/64bit

OS: Macintosh Mac OS X (10.9.5 or later), Mac OS 11.X

**DIMENSIONS & WEIGHT** 

SL-D1030 Main Unit SL-D1030 Main Unit with **Duplex Feeder** 



**OPTIONS** 

Duplex Feeder Spindle Unit C12C936001 C12C935981

INK (250mL)

Black C13T46P100 Cyan C13T46P200 Magenta C13T46P300 Yellow C13T46P400 Light Cyan C13T46P500 Light Magenta C13T46P600

**Other Consumables** 

C13S400086 Maintenance Box Roller Assembly Kit C13S210124 Roller Assembly Kit 2 C13S210137

© 2024 Epson India Pvt. Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON is registered trademark of Seiko Epson Corporation. is registered trademark of selko epson corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations. only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.

Dealer's Stamp

Information correct at time of printing. Printed January 2024

**EPSON INDIA PVT. LTD.** 

12th Floor, The Millenia, Tower A, No.1, Murphy Road, Ulsoor, Bangalore - 560 008. Tel: 080-4566 5000 Fax: 080-4566 5005

Scan the QR code to contact an Epson representative close to you.







CONTACT EPSON TODAY! EMAIL: pravin@eid.epson.co.in

Epson Helpline: For product info or service - 1800 425 0011 For service: 1800 123 001 600 or 1860 3000 1600 (9 am - 6 pm) (Mon - Sat) Email: Ifp@epson-india.in www.epson.co.in