INTELLIGENT BUSINESS SOLUTIONS
TM-T88VI

EPSON
EXCEED YOUR VISION

THE FAST AND THE FUTURISTIC POINT OF SALE PRINTER.

Set pace to your business, with extremely fast receipt printing. The TM-T88VI offers state-of-the-art technology that supports the coexistence of traditional PC POS and, web and tablet POS services. Designed to cater to today's urbane POS environments, the TM-T88VI receipt printers are ideal for retail, hospitality and customer-facing businesses of all sizes. All this with the reliability that comes from the World and India's No. 1 POS printers.

| Mobility | Compact | Print | Cost Effective |

World & India's
No.1
Point of Sale

TM-T88VI

ENGINEERED FOR BUSINESS

High Productivity
Class-leading print speed of 300 mm per second that minimises waiting time; coupled with paper saving technology.

Ease of connectivity
Beacon and NFC support along with Server Direct Prints offer the simplest ways to detect and connect with the printer.

Simple Integration
Maintain a traditional set-up, or easily migrate to a tablet or web-based solution without losing access to established systems.

EPSON
EXCEED YOUR VISION

Product Name	TM-T88VI
Print Technology	
Printing Method	Thermal line printing
Print Font	
Font	Font A (default): 12 x 24, Font B: 9 x 17 (including 2-dot horizontal spacing)
Character Size (mm)	Font A: 1.41 x 3.39 (W x H mm), Font B: 0.99 x 2.40 (W x H mm)
Character Set	95 Alphanumeric, 18 set International, 128 x 43 Graphic
	Text (incl. Euro symbol), Graphics, Barcode, South Asia models carry Thai (128 x 3) and
	Vietnamese (128 x 2) characters, Simplified Chinese (GB18030-2000:28,553)
Character Structure	12 x 24 / 9 x 17 / 9 x 24 (including 2-dot spacing horizontally)
Interface	Built-in USB, Built-in Ethernet (10/100Base-T/TX) + UIB (Serial, Parallel, Powered USB)
	Bluetooth 2.1 (Optional) + EDR (dedicated model) Wireless (USB wireless dongle): OT-WL05 (802.11 a/b/g/n)
	or OT-WL02 (802.11 b/g/n), Insert in interface: Beacon (using Bluetooth low energy):
	Beacon dongle (Epson approved dongle:Laird model BT-820)
Dot Density	180 dpi x 180 dpi [dpi: dots per inch (25.4 mm)]
Paper	
Dimensions (mm)	80 mm: 79.50 ± 0.50 (W) mm x dia 83.00 mm, 58 mm: 57.50 ± 0.50 (W) mm x dia 83.00 mm
Power	
Supply Voltage	DC + 24 V ± 7 %
Power Consumption (Operating)	Approx. 1.8 A (mean)
Operating Temperature	5° C - 45°C (41°F - 113°F)
Humidity	Operation 10% - 90%
Power Supply	External power supply (Model: PS-180)
Reliability	
Auto Cutter Life	2 million cuts
MTBF	360,000 hours
MCBF	70 million lines
Colour	Dark Grey / Clear White
Overall Dimensions (W X D X H)	145 mm x 195 mm x 148 mm
Weight (Approx.)	1.6 kg
Options	WH-10 (040) Wall hanging bracket, OT-WL02 (739): Wireless LAN Dongle, 2.4 GHz, Power supply cover
Standard Accessories Rom	Connector cover, main unit, PS-180 and AC cable, paper spacer,
	power switch cover, roll paper, setup guide, warranty document
General Information	
Printer Driver	Windows® Printer Driver (APD), OPOS, Java POS, CUPS, MAC
NV Area	User NV 1 KB, NV Graphics 384 KB
Audible Alert	External Buzzer (Option)
Sensors	Paper End, Cover Open
LED Indicators	Blue LED - On = Power
	Orange LED - Error and/or Paper Out
Software	TM Utility (iOS, Android & Windows)
	TM Bluetooth Connector, Deployment Tool, Monitoring Tool

Information correct at time of printing
Printed May 2018