



**LIFELIKE DETAIL
FOR LARGE AUDIENCES.**

The EB-L1495U is designed to project breathtaking images with WUXGA resolution (1920 x 1200 pixels), 4K enhancement and a brightness of up to 9,000 lumens. Epson's revolutionary 3LCD technology ensures rich, balanced colours. Plus, the projector's light source life of up to 20,000 hours ensures maintenance-free operation.



EB- L1495U



High Brightness



Edge Blending



Arc Correction



Point Correction



iProjection*



THE WORLD NO.1
18 YEARS RUNNING

Crystal-clear Images

WUXGA resolution (1920 x 1200 pixels) and high brightness of up to 9,000 lumens deliver images of impeccable quality.

Cutting-edge Capabilities

Advanced built-in Edge Blending, image warping and curved-surface correction for a host of applications.

Seamless Projection

A light source life of up to 20,000 hours and an electrostatic air filter ensure uninterrupted projection.



*Source: Futuresource Consulting. * Compared against similarly-priced leading 1-chip DLP® business and education projectors based on NPD data from July 2011 through June 2012 (available at www.npd.com). Colour brightness (colour light output) measured in accordance with IDMS 15.4. Actual colour brightness will vary depending on actual usage conditions. 3LCD® is a registered trademark of Seiko Epson Corporation. DLP® is a registered trademark of Texas Instruments, Inc. and its use here does not imply any affiliation with or endorsement by them.

Projection Technology	RGB Liquid Crystal Shutter System
Specifications of Main Parts	
LCD	Size: 1.03-inch (D10)
	Driving Method: Poly-silicon TFT Active Matrix
	Projection Method: Front / rear / ceiling mount
	Aspect Ratio: 16:10
	Native Resolution: WUXGA (1920 x 1200) w/ 4K Enhancement Technology
Lightsource	Type: Laser Diode
	Life (Normal / Extended): 20,000 / 30,000 hours
Projection Lens ⁴	Type ⁵ : Power Zoom / Power Focus / Power Shift
	F-Number: 1.8 - 2.3
	Focal Length: 36.00 - 57.4 mm
	Zoom Ratio ⁶ : 1 - 1.6
	Throw Ratio ⁶ : 1.57 - 2.56:1 (Wide to Tele)
	Lens Change: Optional lens available for purchase
Lens Shift ⁷	Mode: Powered
	Vertical (Up/Down): ±60% (H center) (Powered)
	Horizontal (Left/Right): ±18% (Vertical ±31%) (Powered)
Screen Size (Projected Distance)	
Zoom: Wide	60" - 1000" [1.99 - 34.43 m]
Zoom: Tele	60" - 500" [3.26 - 55.63 m]
Brightness¹	
White Light Output (Normal / Extended)	9,000 lm/ 6,300 lm
Colour Light Output	9,000 lm
Contrast Ratio	2,500,000:1
Geometric Correction	
Vertical / Horizontal Keystone	±45° / ±30° (Zoom: Tele) (with Standard Lens ⁴)
Quick Corner	Yes
Arc	Yes
Curve Surface Correction	Yes
Point Correction	Yes
Corner Wall	Yes
Geometry Correction Memory	Yes
Connectivity	
Analog Input	D-Sub 15Pin: 1
	5-BNC: 1
Digital Input	DVI-D: 1
	HDMI: 1
	SDI: 1
	HDBaseT: 1
Output Terminal	D-Sub 15Pin: 1
Audio Input	Stereo Mini Jack: 3
Audio Output	Stereo Mini Jack: 1
Others	USB Type A: 1 (for Wireless LAN, Firmware Update, Copy OSD Settings)
	USB Type B: 1 (for Firmware Update, Copy OSD Settings)
Control I/O	RS-232C: D-Sub 9Pin x 1
	Remote Control Input: Stereo Mini Jack x 1
Network	Wired LAN: RJ45 x 1
	Wireless: Optional x 1
Wireless Specification	
Supported Speed For Each Mode	IEEE 802.11b: 11Mbps ² IEEE 802.11g: 54Mbps ² IEEE 802.11n: 130Mbps ²
Wireless LAN Security	Quick Mode: OPEN, WPA2-PSK Advanced Mode: OPEN, WPA/WPA2-PSK, WPA/WPA2-EAP Supported EAP Type: PEAP, PEAP-TLS, EAP-TLS, EAP-Fast, LEAP
Operating Temperature	
	0 - 50 °C <32 - 122 °F> (Below 1,500 m / 4,921 ft)
	0 - 45 °C <32 - 113 °F> [Above 1,500 m / 4,921 ft - 3,048 m / 10,000 ft (with high-altitude mode)]
Operating Altitude	
	0 - 3,048 m <0 - 10,000 ft> (over 1,500 m / 4,921 ft (with high-altitude mode))
Direct Power On / Off	
	Yes
Start-up Period	
	Less than 7 seconds, Warm-up Period: 30 seconds
Cool Down Period	
	Instant Off
Air Filter	
Type	High Efficiency Filter
Maintenance Cycle (Normal / Extended)	20,000 / 30,000 hours ³
Power Supply Voltage	
	100 - 240 V AC ±10%, 50/60 Hz
Power Consumption (220V)	
Laser Diode (Normal / Extended)	626 W / 512 W
Standby (Network / Energy Saving)	2.0 W / 0.3 W
Maximum Dimensions (D X W X H)	
	586 x 211 x 492 mm
Weight (Including Standard Lens)	
	Approx. 23.7 kg
Weight (Excluding Standard Lens)	
	Approx. 21.9 kg
Fan Noise (Normal / Quiet)	
	37 dB / 30 dB

Accessories

- Remote Control
- Battery for Remote Control
- Cable Cover
- HDMI Cable Clamp

Optional Lenses

- ELPLX02
- ELPLU03
- ELPLU04
- ELPLW05
- ELPLW06
- ELPLW08
- ELPLM09
- ELPLM15
- ELPLM10
- ELPLM11
- ELPLL08
- ELPLU02
- ELPLR04
- ELPLW04
- ELPLS04
- ELPLM06
- ELPLM07
- ELPLL07

EB-L1495U



¹ Colour brightness (colour light output) and white brightness (white light output) will vary depending on usage conditions. Colour light output measured in accordance with IDMS 15:4; white light output measured in accordance with ISO 21118.

² Maximum speed and range is achievable when used with same enhanced mode technology. Actual data rates, features and performance may vary depending on your computer system, the environment and other factors.

³ When used in the general office environment (the amount of floating dust: 0.04 - 0.2 mg/m³). Based on the Epson's in-house test results.

⁴ Lens are optional and not provided with the projector.
⁵ Indicated values for lens ELPLM15 (informally known as standard throw lens).

©2019 Epson India Pvt. Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited.

EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation.

All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners.

Epson disclaims any and all rights in those marks. Projected images shown herein are simulations. The actual product design and contents may vary. Specifications are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.

Information correct as at October 2019

EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A, No.1,
Murphy Road, Ulsoor, Bangalore - 560 008.
Tel: 080 - 4566 5000 Fax: 080 - 4566 5005

Regional Offices:

Ahmedabad - 3314 8500/01, Chennai - 3967 7500, Cochin - 4012 315, Hyderabad - 4857 0032
Coimbatore - 98942 19200, Kolkata - 4603 4729, Jaipur - 78699 11699
Mumbai - 3079 8200, New Delhi - 3312 0300, Pune - 3028 6000/05



Epson Helpline:

For product info, service or to order a ribbon cartridge - 1800 425 0011
For service - 1800 123 001 600 (9AM - 6PM) (Mon - Sat)

www.epson.co.in

