LightScene EV-115



The EV-115 is an innovative and versatile 2,200 lumens laser projection solution for creating experiential displays and digital signage.

Add movement and life to retail displays, hospitality events, visitor experiences, galleries, museums, corporate environments or exhibitions, with a low visual noise projector that blends into any environment. The EV-115 brings lighting and projection together, and perfectly combines high design, high image quality and installation flexibility.

Minimalist design - maximum impact

The LightScene EV-115 allows users to unlock their creativity and project instantly appealing visuals, with sharp WXGA resolution and 2,200 lumens brightness. Thanks to its discreet design, it can be used where a traditional projector may stand out. A white version is also available.

Simple, flexible implementation

A lightweight, adaptable design means the EV-115 can be installed in a variety of ways, from a traditional ceiling mount to a freestanding floor mount, or attached to a lighting track, including recessed lighting tracks.

Signage-ready

Featuring a built-in media player with wireless content upload, allowing playlists to be loaded onto an SD card and played directly from the projector1. The EV-115 also features HDMI connectivity for simple integration into content management systems without specialist installation.


Advanced installations made easy

The GPI function supports direct sensor connectivity for creating dynamic experiences that can adapt to situational changes without the need for costly external hardware. The EV-115 also uses advanced techniques such as edge blending to achieve stunning results in larger spaces that require multiple unit installations.

Fit and forget reliability

A five-year warranty, combined with Epson's reliable laser light source technology and sealed optical engine, means that the EV-115 does not require regular maintenance.

DATASHEET / BROCHURE



KEY FEATURES

- Experiential projection Create borderless content, lighting effects and blended displays with ease
- Sensor-based content GPI function for simple sensor-based experiences
- Flexible installation Can be ceiling-mounted, freestanding or attached to a lighting track
- **Signage-ready** Built-in media player and simple CMS integration
- Fit and forget reliability Durable Epson laser technology supported by a five-year warranty



PRODUCT SPECIFICATIONS

TECHNOLOGY	
Projection System	3LCD Technology
LCD Panel	0.59 inch with C2 Fine
IMAGE	
Color Light Output	2,200 Lumen- 1,100 Lumen (economy) In accordance with IDMS15.4
White Light Output	2,200 Lumen - 1,100 Lumen (economy) In accordance with ISO 21118:2020
Resolution	WXGA 2
Aspect Ratio	
Contrast Ratio	Over 5,000,000:1
Native Contrast	2,000 : 1
Light source	Laser
Laser Light source	20,000 hours Durability High, 30,000 hours Durability Eco
Keystone Correction	Manual vertical: ± 45 °, Manual horizontal ± 40 °
Colour Reproduction	16.77 million colours
OPTICAL	
Throw Ratio	1.38 - 2.19:1
Zoom	Motorized, Factor: 1 - 1.58
Lens	Optical
Screen Size	30 inches - 150 inches
Projection Distance Wide	0.9 m - 4.5 m
Projection Lens F Number	1.51 - 1.92
Projection Lens Focal Length	
Projection Lens Focus	Motorized
CONNECTIVITY	
Interfaces	USB 2.0-A, USB 2.0 Type B (Service Only), Ethernet interface (100 Base-TX / 10 Base-T),
	Wireless LAN b/g/g 25GHz, HDMI in, Jack plug out, SD Card Slot, SD Card playback, Wireless
	LAN a/n (5GHz)
Natwork Protocol	HTTPS IDVE SNMD ESCARD act Billink
Network Protocol	HTTPS, IPv6, SNMP, ESC/VP.net, PJLink
Network Protocol ADVANCED FEATURES	HTTPS, IPv6, SNMP, ESC/VP.net, PJLink
	HTTPS, IPv6, SNMP, ESC/VP.net, PJLink Wireless LAN security, Password protection
ADVANCED FEATURES	
ADVANCED FEATURES Security	Wireless LAN security, Password protection
ADVANCED FEATURES Security	Wireless LAN security, Password protection A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone
ADVANCED FEATURES Security Other features	Wireless LAN security, Password protection A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote
ADVANCED FEATURES Security Other features Video Color Modes	Wireless LAN security, Password protection A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal
ADVANCED FEATURES Security Other features Video Color Modes Projector control	Wireless LAN security, Password protection A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal
ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL	Wireless LAN security, Password protection A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView
ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL	Wireless LAN security, Password protection A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4
ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption	Wireless LAN security, Password protection A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby)
ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage	Wireless LAN security, Password protection A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz
ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default position)	Wireless LAN security, Password protection A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 530 x 470 x 250 mm (Width x Depth x Height)
ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default position) Dimensions: Projection Unit	Wireless LAN security, Password protection A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 530 x 470 x 250 mm (Width x Depth x Height) Ø175 x 260 mm (Depth)
ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default position)	Wireless LAN security, Password protection A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 530 x 470 x 250 mm (Width x Depth x Height)
ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default position) Dimensions: Projection Unit Dimensions: Power Supply	Wireless LAN security, Password protection A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 530 x 470 x 250 mm (Width x Depth x Height) Ø175 x 260 mm (Depth) 361 x 110 x 65 mm (Width x Depth x Height) 5 kg
ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default position) Dimensions: Projection Unit Dimensions: Power Supply Product weight Noise Level	Wireless LAN security, Password protection A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 530 x 470 x 250 mm (Width x Depth x Height) Ø175 x 260 mm (Depth) 361 x 110 x 65 mm (Width x Depth x Height) 5 kg Normal: 34 dB (A) - Economy: 22 dB (A)
ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default position) Dimensions: Projection Unit Dimensions: Power Supply Product weight Noise Level Supported Temperature	Wireless LAN security, Password protection A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 530 x 470 x 250 mm (Width x Depth x Height) Ø175 x 260 mm (Depth) 361 x 110 x 65 mm (Width x Depth x Height) 5 kg Normal: 34 dB (A) - Economy: 22 dB (A) Operation 5° C - 40° C, Storage -10° C - 60° C
ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default position) Dimensions: Projection Unit Dimensions: Power Supply Product weight Noise Level Supported Temperature Supported Humidity	Wireless LAN security, Password protection A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 530 x 470 x 250 mm (Width x Depth x Height) Ø175 x 260 mm (Depth) 361 x 110 x 65 mm (Width x Depth x Height) 5 kg Normal: 34 dB (A) - Economy: 22 dB (A) Operation 5° C - 40° C, Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90%
ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default position) Dimensions: Projection Unit Dimensions: Power Supply Product weight Noise Level Supported Temperature Supported Humidity Included Software	Wireless LAN security, Password protection A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 530 x 470 x 250 mm (Width x Depth x Height) 0175 x 260 mm (Depth) 361 x 110 x 65 mm (Width x Depth x Height) 5 kg Normal: 34 dB (A) - Economy: 22 dB (A) Operation 5° C - 40° C, Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Epson Creative Projection, Epson Projector Content Manager
ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default position) Dimensions: Projection Unit Dimensions: Projection Unit Dimensions: Power Supply Product weight Noise Level Supported Temperature Supported Humidity Included Software Options	Wireless LAN security, Password protection A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 530 x 470 x 250 mm (Width x Depth x Height) Ø175 x 260 mm (Depth) 361 x 110 x 65 mm (Width x Depth x Height) 5 kg Normal: 34 dB (A) - Economy: 22 dB (A) Operation 5° C - 40° C, Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Epson Creative Projection, Epson Projector Content Manager Floor stand, Lighting track mount
ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default position) Dimensions: Projection Unit Dimensions: Projection Unit Dimensions: Projection Unit Dimensions: Power Supply Product weight Noise Level Supported Temperature Supported Humidity Included Software Options Room Type / Application	 Wireless LAN security, Password protection A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 530 x 470 x 250 mm (Width x Depth x Height) Ø175 x 260 mm (Depth) 361 x 110 x 65 mm (Width x Depth x Height) 5 kg Normal: 34 dB (A) - Economy: 22 dB (A) Operation 5° C - 40° C, Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Epson Creative Projection, Epson Projector Content Manager Floor stand, Lighting track mount Projection Mapping, Signage / Retail, Visitor Attraction
ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default position) Dimensions: Projection Unit Dimensions: Projection Unit Dimensions: Power Supply Product weight Noise Level Supported Temperature Supported Humidity Included Software Options	Wireless LAN security, Password protection A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 530 x 470 x 250 mm (Width x Depth x Height) Ø175 x 260 mm (Depth) 361 x 110 x 65 mm (Width x Depth x Height) 5 kg Normal: 34 dB (A) - Economy: 22 dB (A) Operation 5° C - 40° C, Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Epson Creative Projection, Epson Projector Content Manager Floor stand, Lighting track mount
ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default position) Dimensions: Projection Unit Dimensions: Power Supply Product weight Noise Level Supported Temperature Supported Temperature Supported Humidity Included Software Options Room Type / Application Positioning Colour	 Wireless LAN security, Password protection A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 530 x 470 x 250 mm (Width x Depth x Height) Ø175 x 260 mm (Depth) 361 x 110 x 65 mm (Width x Depth x Height) 5 kg Normal: 34 dB (A) - Economy: 22 dB (A) Operation 5° C - 40° C, Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Epson Creative Projection, Epson Projector Content Manager Floor stand, Lighting track mount Projection Mapping, Signage / Retail, Visitor Attraction Ceiling Mounted, Floor, Lighting Track, Wall Mounted
ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions (default position) Dimensions: Projection Unit Dimensions: Projection Unit Dimensions: Projection Unit Dimensions: Power Supply Product weight Noise Level Supported Temperature Supported Humidity Included Software Options Room Type / Application Positioning	 Wireless LAN security, Password protection A/V mute, Auto Power On, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Image Shift, Long light source life, Quick Corner, Web Control, Web Remote Dynamic, Normal via: Crestron, Crestron Integrated Partner, Crestron RoomView 124 Watt (Normal On-Mode), 149 Watt (Normal Peak-mode), 112 Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 530 x 470 x 250 mm (Width x Depth x Height) Ø175 x 260 mm (Depth) 361 x 110 x 65 mm (Width x Depth x Height) 5 kg Normal: 34 dB (A) - Economy: 22 dB (A) Operation 5° C - 40° C, Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Epson Creative Projection, Epson Projector Content Manager Floor stand, Lighting track mount Projection Mapping, Signage / Retail, Visitor Attraction Ceiling Mounted, Floor, Lighting Track, Wall Mounted

*

LightScene EV-115

WHAT'S IN THE BOX

- Cable cover
- Direct mount unit
- HDMI Cable Clamp
- Power cable
- Remote control incl. batteries

EPSON

- User's Manual Set
- Hexagon wrench
- Safety wire set

OPTIONAL ACCESSORIES

- Floor Stand ELPMB55B EV-105 V12H888B10
- Lighting Track Mount ELPMB66B EV-115 V12HA32140

LOGISTICS INFORMATION

SKU	V11HA22156
Country of Origin	China

* Warranty offers are not available for all countries. Please contact your local Epson representative.

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.

1. Requires free Epson Projector Content Manager software or Epson Creative Projection app.

EPSON

LightScene EV-115

EPSON INDIA PVT. LTD. 12th Floor, The Millenia, Tower A, No.1, Murphy Road, Ulsoor, angalore – 560 008. Tel: 080–4566 5000 Fax: 080–4566 5005

Regional Offices:

Ahmedabad 4037 0075, Chennai 3967 7500, Ernakulam 4012 315, Coimbatore 99620 00969 Hyderabad 4857 0032, Jaipur 0141 4923119, Kolkata 4603 4714/15/29/30, Mumbai 3079 8200 New Delhi 4107 3101, 4752 2414, 4226 3483, 4215 1033, Pune 3028 6000.





Epson Helpline: Epson Helpline: For product info or service - 1800 425 0011 For service: 1800 123 001 600 or 1860 3000 1600 (9 am - 6 pm) (Mon - Sat) Email: emp@eid.epson.co.in www.epson.co.in