ECOTANK PRINTERS ECOTANK M2140/M2170





The monochrome EcoTank M2140 and M2170 multi-function printers are designed to ensure the finest office printing experience. With each print, you save big on energy and printing costs as it costs just 12 paise* per print while consuming up to $30X^4$ less power than mono laser printers which, in turn, ensures minimal impact on the environment. A speed of 20 ipm ensures that every job is done well within time. The flexibility to print, scan, copy and fax ensures productivity like never before. A high print yield of $6,000^1$ prints ensures printing without the inconvenience of frequent refills.





















3 years o 100,000



Etherne







Designed to support the Sustainable Development Goals (SDGs) set by the UN



Each printer comes bundled with a starter kit of 1 high-capacity bottle of Epson genuine ink.

Cutting-edge Printhead Technology

Meet every deadline with swift printing as these printers enable high-quality printing at the speed of 20 ipm.

Multi-functional Edge

Enhance your productivity to a whole new level as these printers enable you to print, scan, copy and fax effortlessly.

Better For The Environment

Low power consumption and less replacement parts compared to laser printers mean less e-waste for a positive impact on the environment.

SPECIFICATIONS

ECOTANK M2140/M2170



MODEL NUMBER	M2140 M2170			Dimensions & Weight
Printer Type	Print, Scan, Copy			· ·
Printing				M2140/M2170
Printing Technology	Epson's Heat-Free Technology	ıy		Weight: 6.2 kg (3.7 lbs)
Nozzle Configuration Print Direction	400 x 2 nozzles Black Bi-directional printing			
Maximum Resolution	1200 x 2400 dpi (with Variable	e-sized Droplet Technology)		ATT WHY
Minimum Ink Droplet Volume	2.8 pl			
Print Speed ¹¹	<u>.</u>			A comment designed
Draft Text - Memo, A4 (Black#1)	Up to 39 ppm			
ISO 24734, A4 (Black) First Page Out Time (Black)	Simplex: Up to 20 ipm, Duplex: 9.0 ipm			
Printer Language	Approx. 6 sec ESC / P Raster (Factory Use), ESC / P-R			
Automatic 2-sided printing	Yes			
Copying				
Copy Speed				375 mm (14.8")
ISO 29183, A4, Simplex (Black)	Up to 17 ipm			
Copy Quality	Standard / Best			
Maximum Copies from Standalone Reduction/Enlargement	99 copies 25-400% Auto Fit Function			
Maximum Copy Resolution	600 x 600 dpi			
Maximum Copy Size	A4, Letter			*1 Print speed (Pages Per Minute)
Scanning				printed on A4 plain paper in the
Scanner Type	Flatbed colour image scanner	ſ		speed may vary depending on
Sensor Type	CIS			print mode, document complex paper used and connectivity. P
Optical Resolution	1200 x 2400 dpi			include processing time on hos
Maximum Scan Area	216 x 297 mm (8.5 x 11.7")			·
Scanner Bit Depth Colour	48-bit input, 24-bit output			
Grayscale	48-bit input, 24-bit output 16-bit input, 8-bit output			-
Black & White	16-bit input, 1-bit output			harmen and
Scan Speed (Flatbed)				
Monochrome 200 dpi Colour 200 dpi	12 sec			Princers.
Colour 200 dpi	27 sec			
Paper Handling				#1
Paper Feed Method Number of Paper Trays	Friction feed			Black Text
Paper Hold Capacity	2			and graphics
Input Capacity	Front Tray 1: 250 Sheets-A4 / Letter Plain Paper (80 g/m²); 10-sheets-Envelope;			*2 Default mode in accordance wi
	Rear slot: 1 sheet-A4 paper			*3 Quoted yields are based on the
Output Capacity	Up to 100 sheets Legal, Indian-Legal (215 x 345 mm), 8.5 x 13", Letter, A4, 16K (195 x 270 mm), B5, A5, B6, A6, Hagaki (100 x 148 mm),			patterns of mixed text and blac
Paper Size	Envelopes: #10, DL, C6	5 mm), 8.5 x 13", Letter, A4, 16K (19	95 x 270 mm), B5, A5, B6, A6, Hagaki (100 x 148 mm),	with Epson methodology. Quote
Maximum Paper Size	215.9 x 1200 mm (8.5 x 47.24")			on the replacement ink bottles quality, part of the ink from the
Print Margin	Top / Bottom / Left / Right: 3			used for printer startup so yield
Interface	 -			those of replacement ink bottle
USB	Hi-speed USB			vary due to reasons including ir settings, temperature and humi
Network	-		Ethernet, WiFi IEEE 802.11b/g/n, WiFi Direct	lower when printing infrequently
Network Protocol	-		TCP/IPv4, TCP/IPv6	printing and printhead maintena
Network Management Protocols	-		SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD	© 2020 Epson India Pvt. Ltd. All Rig
				Reproduction in part or in whole, w
Mobile and Cloud Printing			Engan iBrint Email Brint Barreta Brint Brint	permission from Epson, is strictly p
Epson Connect			Epson iPrint, Email Print, Remote Print Driver, Scan to Cloud	and EXCEED YOUR VISION are reg
Other Mobile Solutions	-		Apple AirPrint™, Google Cloud Print™,	Seiko Epson Corporation. All other other company names used herein
			, , , , , , , , , , , , , , , , , , ,	purposes only and are the trademai
Control Panel				trademarks of their respective owners any and all rights
LCD Screen	1.44" LCD Touchscreen			in those marks. Print samples show
Printer Software				only. Specifications and product av
Operating System Compatibility				to change without notice and may v countries. Please check with local E
	Windows Server 2003 / 2008 / 2012 / 2016			information.
	Only printing and scanning functions are supported for Windows Server OS			
	Mac OS X 10.6.8 or later			Apple, iPad and iPhone are tradema
Electrical Specifications		-		registered in the U.S. and other cou a service mark of Apple Inc. Android
Rated Voltage	AC 220 – 240 V			Google Inc.
Rated Frequency Power Consumption	50 – 60 Hz			. <u> </u>
Power Consumption Operating	14 W		12 W	Dealer's Stamp
Standby	3.4 W		4.9 W	Dealer's Starrip
Sleep	0.6 W		0.7 W	
Power off	0.2 W		0.8 W	
Noise Level (PC Printing)				
Plain Paper Default*2	6.9 B(A), 56 dB (A)			
	Page Yield*3	Order Code		
Consumables Standard Black Ink Bottles	Page Yield*3 2,000	005S		
Consumables				



te) is calculated when the fastest mode. Print on system configuration, elexity, software, type of . Print speed does not lost computer.

- with ISO7779 for MFPs.
- the ISO 24711/24712 the ISO 24711/24712 ollack-and-white graphics uoted yields are based es purchased. For print he included bottles is ields could be lower than ttles. Actual yields will g images printed, print umidity. Yields may be nttly. Ink is used for both tenance.

Rights Reserved. , without the written y prohibited. EPSON registered trademarks of ler products names and ein are for identification narks or registered vners. Epson disclaims

own are simulations availability are subject by vary between al Epson offices for more

emarks of Apple Inc., countries. App Store is roid is a trademark of

Information correct at time of printing Printed January 2020

EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A, No.1, Murphy Road, Ulsoor, Bangalore - 560 008. Tel: 080-3051 5000 Fax: 080-3051 5005

Regional Offices:

Epson Helpline: For product info or service- 1800 425 0011

For service - 1800 123 001 600 (9AM - 6PM) (Mon - Sat)

Ahmedabad - 3314 8500/01, Chennai - 3967 7500, Cochin - 4012 315, Coimbatore - 98942 19200, Kolkata - 4603 4729, Mumbai - 3079 8200, New Delhi - 3312 0300, Pune - 3028 6000/05, Hyderabad - 4857 0032, Jaipur - 78699 11699



