



The multi-function Epson EcoTank L6270 delivers borderless prints in sizes up to A4 at a high speed. Equipped with an integrated ink tank, this printer has a small footprint for space savings in any office. It prints at just 12 Paise (black) and 20 Paise (colour) for true cost savings. The affordable ink bottles, complete with designated nozzles, ensure spill-free refilling. A high print yield of up to 7,500 pages (black) and 6,000 pages (colour) ensures uninterrupted printing. The auto-duplex function helps print on both sides of the paper, further reducing the printing expenses. WiFi Direct and Epson Connect features enable effortless wireless printing. You can also download the Epson Smart Panel app to your mobile devices, making it an intuitive control centre to easily set up, monitor and operate the printer functions.









Print Speed (Black)

Ultra-High Page Yield (Black)

Duplex Printing

WiFi Direct









Epson 1-Year Smart Panel Warranty\*









# **Superior Savings with Auto-Duplex**

Enjoy greater savings and higher page yields with auto-duplex function, saving up to 50% on paper cost.

# Speed, Quality and Reliability

Epson PrecisionCore printhead produces faster print speed, quality and reliability. Pigment black ink delivers water and smudge-resistant printouts.

The total Colour CPP including black ink is 32 paise.

# **Epson Smart Panel**

Download the Epson Smart Panel app to mobile devices for direct access to functions such as print, scan and copy while monitoring the printer's operation.

#### **SPECIFICATIONS**

#### **ECOTANK L6270**



	L6270
Printer Type	Print, Scan, Copy with ADF
Printing	thing county copy materials
•	
Printing Technology	PrecisonCore Printhead
lozzle Configuration	400 x 1 nozzles Black, 128 x 1 per Colour (Cyan, Magenta, Yellow)
/laximum Resolution	4800 x 1200 dpi (with Variable-Sized Droplet Technology)
rint Speed"	
Draft Text - Memo, A4 (Black#1 / Colour#2)	Up to 33.0 ppm / 20.0 ppm
- 1	
ISO 24734, A4 (Black/Colour)	Simplex: Up to 15.5 ipm / 8.5 ipm
	Duplex: Up to 6.5 ipm / 4.5 ipm
First Page Out Time (Black / Colour)	Approx. 9 sec / 15 sec
Photo Default - 10 x 15 cm / 4 x 6"*2 #3	Approx. 69 sec per photo / 92 sec per photo
(Border / Borderless)	, pp. 3.4 co coo po. p. stor com coo po. p. stor
rinter Language	ESC/P-R, ESC/P Raster
utomatic 2-sided printing	Yes
opying	
opy Speed	
ISO 29183, A4 (Black / Colour), Flatbed	Simplex: Up to 11.0 ipm / 5.5 ipm
ISO 24734, aFSOT, A4 (Black / Colour), ADF	60 sec / 82 sec
laximum Copies from Standalone	99 copies
Maximum Copy Resolution	600 x 600 dpi
1aximum Copy Size	Legal
	5
canning	
canner Type	Flatbed colour image scanner
ensor Type	CIS
optical Resolution	1200 x 2400 dpi
Maximum Scan Area	216 x 297 mm (8.5 x 11.7")
	210 / 201 1111 (0.0 / 11.1 )
canner Bit Depth	
Colour	48-bit input, 24-bit output
Grayscale	16-bit input, 8-bit output
Black & White	16-bit input, 1-bit output
can Speed (Flatbed / ADF (Simplex))	to memping the object
Monochrome 200dpi	Flatbed: 12 sec ADF: 5.0 ipm
Co <b>l</b> our 200dpi	Flatbed: 27 sec ADF: 5.0 ipm
DF Function	
upport Paper Thickness	64-95 g/m²
	30 sheets
aper Capacity	30 sneets
aper Handling	
lumber of Paper Trays	1
aper Hold Capacity	
Input Capacity	Up to 250 sheets of Plain Paper (80 g/m²), Up to 20 sheets of Premium Glossy Photo Paper
Output Capacity	Up to 30 sheets of Plain Paper (80 g/m²), Up to 20 sheets of Premium Glossy Photo Paper
Paper Size	Legal (8.5 x 14"), 8.5 x 13", Letter, A4, B5, A5, A6, Hagaki (100 x 148 mm), 16K (195 x 270 mm),
	Indian-Legal (215 x 345 mm), B6, 5 x 7", 4 x 6", Envelopes #10, DL, C6
Maximum Paper Size	215.9 x 1200 mm (8.5 x 47.24")
rint Margin	Omm top, left, right, bottom via custom settings in printer driver'3
	onlin top, tett, right, bottom via custom settings in printer univer
nterface	
ISB	USB 2.0
letwork	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct
letwork Protocol	TCP/IPv4, TCP/IPv6
letwork Management Protocols	SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD
Mobile/Software and Cloud Printing	
pson Connect	Epson iPrint, Email Print, Remote Print Driver, Scan to Cloud
Other Mobile Solutions	Apple AirPrint, Mopria Print Service, Epson Smart Panel
Software	Epson ScanSmart
	mpoor, oom, of the C
Control Panel	0.4 (0.4%) 0.1 (0.4%)
CD Screen	6.1 cm (2.4") Colour LCD Screen
Printer Software	
Operating System Compatibility	Windows XP SP3 / XP Professional x64 SP2 / Vista / 7 / 8 / 8.1 / 10
-ps.ag Gyotorn Compatibility	Windows Server 2003 /2008 / 2012 / 2016 / 2019
	Only printing and scanning functions are supported for Windows Server OS
	Mac OS X 10.6.8 or later
landa locales e	MIRCOO A TOLOLO UL IRITEL
lectrical Specifications	
ated Voltage	AC 220-240 V
ated Frequency	50 - 60 Hz
ower Consumption	
	12.0W
Operating	12.0 W
Standby	<u>5.3 W</u>
Sleep	0.9 W
Power Off	0.2 W
oise Level	
	Occord Proves (Physic / Octoor & 5 / 5 PM)
C Printing / Premium Glossy	Sound Power (Black / Colour) 5 / 5 B(A)
hoto Paper Best Photo	Sound Pressure (Black / Colour) 37 / 38 dB(A)
•	
C Printing / Plain Paper Default <sup>4</sup>	Sound Power (Black / Colour) 6.9 / 6.4 B(A)
O Frinding / Flair Flaper Delault	Sound Pressure (Black / Colour) 5.5 / 52 dB(A)
onsumables	Page Yield' <sup>5</sup> Order Code
Black Ink Bottle	7,500 C13T03Y198
yan Ink Bottle	C13T03Y298
Magenta Ink Bottle	
/allow lnk Bottle	
OHOW HIS DOUG	C13T03Y498
Part Code of Maintenance Boy	

**Dimensions & Weight** EcoTank L6270 Weight: 6.7 kg



\*1 Print speed (Pages Per Minute) is calculated when Print speed (Pages Per Minute) is calculated when printed on A4 plain paper in the fastest mode, 10 x 15 cm photo print speed when printed on Epson Premium Glossy Photo Paper. Print speed may vary depending on system configuration, print mode, document complexity, software, type of paper used and connectivity. Print speed does not include processing time on host computer.





#1 Black Text

- \*2 When printed on Epson Premium Glossy Photo Paper.
- \*3 Otherwise 3mm top, left, right, bottom.
- \*4 Default mode in accordance with ISO7779 for MFPs.
- \*4 Default mode in accordance with ISO7779 for MFPs.
  \*5 Quoted yields are based on the ISO 24711/24712 patterns of mixed text and colour graphics with Epson methodology. Quoted yields are based on the replacement ink bottles purchased. For print quality, part of the ink from the included bottles is used for printer startup so yields could be lower than those of replacement ink bottles. Actual yields will vary due to reasons including images printed, print settings, temperature and humidity. Yields may be lower when printing infrequently or predominantly with one ink colour. Ink is used for both printing and printhead maintenance. All inks are used for both black and colour printing.

© 2021 Epson India Pvt. Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. or registered traderinarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.

Dealer's Stamp

Information correct at time of printing Printed January 2022

### EPSON INDIA PVT. LTD.

Part Code of Maintenance Box

12th Floor, The Millenia, Tower A, No.1, Murphy Road, Ulsoor, Bangalore - 560 008. Tel: 080-4566 5000 Fax: 080-4566 5005

### Regional Offices:

C13T04D198

Ahmedabad - 3314 8500/01, Chennai - 3967 7500, Ernakulam - 4012 315, Coimbatore - 98942 19200, Kolkata - 4603 4729, Mumbai - 3079 8200, New Delhi - 3312 0300, Pune - 3028 6000/05, Hyderabad - 4857 0032, Jaipur - 0141 4923119



