# ECOTANK PRINTERS ECOTANK M2140/M2170





The monochrome EcoTank M2140 and M2170 multi-function printers are designed to ensure the finest office printing experience. With each print, you save big on energy and printing costs as it costs just 12 paise\* per print while consuming up to 20X<sup>4</sup> less power than mono laser printers which, in turn, ensures minimal impact on the environment. A speed of 20 ipm ensures that every job is done well within time. The flexibility to print, scan, copy and fax ensures productivity like never before. A high print yield of 6,000¹ prints ensures printing without the inconvenience of frequent refills.



















3 years or 50,000



Etherne











Designed to support the Sustainable Development Goals (SDGs) set by the UN



Each printer comes bundled with a starter kit of 1 high capacity bottle of Epson genuine ink.

# **Cutting-edge Printhead Technology**

Meet every deadline with swift printing as these printers enable high-quality printing at the speed of 20 ipm.

### **Multi-functional Edge**

Enhance your productivity to a whole new level as these printers enable you to print, scan, copy and fax effortlessly.

### **Better For The Environment**

Low power consumption and less replacement parts compared to laser printers mean less e-waste for a positive impact on the environment.

# **SPECIFICATIONS**

## **ECOTANK M2140/M2170**



MODEL NUMBER	M2140		M2170	Dimensions & \
Printer Type	Print, Scan, Copy			
Printing				M2140/M2170
Printing Technology	PrecisionCore Heat-Free Technology			Weight: 6.2 kg
Nozzle Configuration	400 x 2 nozzles Black			
Print Direction	Bi-directional printing			
Maximum Resolution	1200 x 2400 dpi (with Variable-sized Droplet Technology)			ALC: NO
Minimum Ink Droplet Volume	2.8 pl			
Print Speed*1				
Draft Text - Memo, A4 (Black#1)	Up to 39 ppm			
ISO 24734, A4 (Black)	Simplex: Up to 20 ipm, Duplex: 9.0 ipm			
First Page Out Time (Black)	Approx. 6 sec ESC / P Raster (Factory Use), ESC / P-R			-
Printer Language Automatic 2-sided printing	Yes			
Copying Copy Speed				375 mm (1-
ISO 29183, A4, Simplex (Black)	Up to 17 ipm			
Copy Quality	Standard / Best			=
Maximum Copies from Standalone	99 copies			-
Reduction/Enlargement	25-400% Auto Fit Function			
Maximum Copy Resolution	600 x 600 dpi			_
Maximum Copy Size	Copy Size A4, Letter			
Scanning				
Scanner Type	Flatbed colour image scanner			
Sensor Type	CIS			
Optical Resolution	1200 x 2400 dpi			*1 Print speed (Pa
Maximum Scan Area	216 x 297 mm (8.5 x 11.7")			printed on A4 p
Scanner Bit Depth	48-bit input 24-bit output			speed may vary print mode, doo
Colour Gravscale	48-bit input, 24-bit output  16-bit input, 8-bit output			print mode, doc paper used and
Black & White	16-bit input, 8-bit output 16-bit input, 1-bit output			include process
Scan Speed (Flatbed)	10-bit input, 1-bit output			-
Monochrome 200 dpi	12 sec			
Colour 200 dpi	27 sec			100
Danes Handlins				
Paper Handling Paper Feed Method	Friction feed			1111111111111
Number of Paper Trays	2			- 1
Paper Hold Capacity				200
Input Capacity	Front Tray 1: 250 Sheets-A4 / Letter Plain Paper (80 g/m²); 10-sheets-Envelope;			
	Rear slot: 1 sheet-A4 paper			
Output Capacity	Up to 100 sheets			- #1 Black Text
Paper Size	Legal, Indian-Legal (215 x 345 mm), 8.5 x 13", Letter, A4, 16K (195 x 270 mm), B5, A5, B6, A6, Hagaki (100 x 148 mm),			and graphics
	Envelopes: #10, DL, C6			
Maximum Paper Size	215.9 x 1200 mm (8.5 x 47.24")	215.9 x 1200 mm (8.5 x 47.24") Top / Bottom / Left / Right: 3		*2 Default mode in
Print Margin	iop / Bottom / Lett / Right: 3			*3 Quoted yields a
Interface				patterns of mixe with Epson met
USB	Hi-speed USB			on the replacer
Network	<del>-</del>		Ethernet, WiFi IEEE 802.11b/g/n, WiFi Direct	- quality, part of t
Network Protocol	- TCP/IPv4, TCP/IPv6			used for printer
Network Management Protocols	-		SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD	those of replace
				vary due to reas settings, tempe
Mobile and Cloud Printing			E 1811 E 1181 E 1 E 1 E 1	lower when prin
Epson Connect			Epson iPrint, Email Print, Remote Print Driver,	printing and prin
Other Mobile Solutions			Scan to Cloud  Apple AirPrint™ Google Cloud Print™	-
Other Mobile Solutions	-		Apple AirPrint™, Google Cloud Print™,	© 2019 Epson India Reproduction in par
			_	permission from Ep
Control Panel	4 44II I OD Tovohovica			and EXCEED YOUR
LCD Screen	1.44" LCD Touchscreen			Seiko Epson Corpo
Printer Software				other company nam
Operating System Compatibility	Windows XP / Vista / 7 / 8 / 8.1 / 10			purposes only and trademarks of their
		Windows Server 2003 / 2008 / 2012 / 2016		
	Only printing and scanning functions are supported for Windows Server OS			any and all rights in those marks. Prin only. Specifications
	Mac OS X 10.6.8 or later	Mac OS X 10.6.8 or later		
Electrical Specifications		·		to change without n
Rated Voltage	AC 220 - 240 V			countries. Please ch information.
Rated Frequency	50 – 60 Hz			-
Power Consumption				Apple, iPad and iPh
Operating	14 W		12 W	registered in the U.S
Standby	3.4 W		4.9 W	a service mark of A
Sleep	0.6 W		0.7 W	Google Inc.
Power off	0.2 W		0.8 W	
Noise Level (PC Printing)				Dealer's Stamp
Plain Paper Default*2	6.9 B(A), 56 dB (A)			
Consumables	Page Yield <sup>13</sup> Order Code			-
Standard Black Ink Bottles	2,000 005S			-
High Capacity Black Ink Bottles	6,000	005		-
Maintenance Box	=	=		=

Weight

(3.7 lbs)



ages Per Minute) is calculated when rages Per Minute) is calculated when plain paper in the fastest mode. Print ary depending on system configuration, ocument complexity, software, type of nd connectivity. Print speed does not issing time on host computer.



- in accordance with ISO7779 for MFPs
- are based on the ISO 24711/24712 s are based on the ISO 24711/24712 ixixed text and black-and-white graphics nethodology. Quoted yields are based ement ink bottles purchased. For print of the ink from the included bottles is ter startup so yields could be lower than acement ink bottles. Actual yields will be assons including images printed, print perature and humidity. Yields may be viriting infrequently. Ink is used for both printhead maintenance.

dia Pvt. Ltd. All Rights Reserved.
part or in whole, without the written
Epson, is strictly prohibited. EPSON
URI VISION are registered trademarks of
poration. All other products names and
armes used herein are for identification
d are the trademarks or registered
eir respective owners. Epson disclaims
.

rint samples shown are simulations ns and product availability are subject t notice and may vary between check with local Epson offices for more

Phone are trademarks of Apple Inc., J.S. and other countries. App Store is Apple Inc. Android is a trademark of

Information correct at time of printing Printed September 2019

## EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A, No.1, Murphy Road, Ulsoor, Bangalore - 560 008. Tel: 080-4566 5000 Fax: 080-4566 5005

### **Regional Offices:**

Ahmedabad - 3314 8500/01, Chennai - 3967 7500, Cochin - 4012 315, Coimbatore - 98942 19200, Kolkata - 4603 4714/15/29/30, Mumbai - 3079 8200, New Delhi - 3312 0300, Pune - 3028 6000/05, Hyderabad - 4857 0032, Jaipur - 78699 11699



