

DOT MATRIX PRINTER
24-PIN NARROW CARRIAGE
LQ-310



YOUR FAST AND AFFORDABLE PRINTING SOLUTION.



Designed to do more with less, Epson LQ-310 offers fast-printing at a low cost. Compact and capable, Epson LQ-310 24-pin dot matrix printer features extraordinary speed, output quality and reliability. Epson's constant innovations in printing solutions, together with the use of our genuine ribbons, give you the most reliable and best performing printer in today's fast paced and demanding working environments.



		
Print	Cost Effective	Power Savings

Epson genuine ribbons ensure greater yield, better quality and longer lifespan.



ENGINEERED FOR BUSINESS

High Processing Speed

You can now enjoy high-speed processing time, with 128KB data buffer that will reduce waiting time.

Fast Print Speed

Maximize productivity with a fast print speed of up to 416 characters per second (12 cpi).

Long-life Reliability

With a Mean Time Between Failure (MTBF) rating of 10,000 POH (power on hours), it saves cost on electricity without compromising good quality printing.

MODEL NUMBER	LQ-310		
Printing Technology	Impact dot matrix		
Print Method	Impact dot matrix		
Number of Pins in Head	24 pins		
Print Direction	Bi-direction with logic seeking		
Control Code	ESC/P2 and IBM PPDS emulation		
Print Speed			
High Speed Draft	10 / 12 cpi	347 / 416 cps	
Draft	10 / 12 / 15 cpi	260 / 312 / 390 cps	
Draft Condensed	17 / 20 cpi	222 / 260 cps	
LQ	10 / 12 / 15 cpi	86 / 103 / 129 cps	
LQ Condensed	17 / 20 cpi	147 / 172 cps	
Print Characteristics			
Character Sets	Italic table, PC437 (US Standard Europe), PC850 (Multilingual), PC860 (Portuguese), PC861 (Icelandic), PC863 (Canadian-French), PC865 (Nordic), Abicom, BRASCI, Roman 8, ISO Latin 1, PC 858, ISO 8859-15		
Bitmap Fonts	Epson Draft: 10, 12, 15 cpi; Epson Roman & San Serif: 10, 12, 15 cpi, Proportional; Epson Courier: 10, 12, 15 cpi; Epson Prestige: 10, 12 cpi; Epson Script, OCR-B, Orator & Orator-S: 10cpi; Epson Script C: Proportional		
Scalable Fonts	Epson Roman, Epson San Serif, Epson Roman T & Epson San Serif H: 10.5pt., 8pt. - 32pt. (every 2pt.)		
Barcode Fonts	EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, Postnet		
Printable Columns			
Pitch	10 / 12 / 15 / 17 / 20 cpi	80 / 96 / 120 / 137 / 160 cpl	
Paper Handling			
Paper Path	Tractor	Rear in, Top out	
	Manual Insertion	Rear in, Top out	
Paper Size		Length	Width
Cut Sheet (Single Sheet)		100 ~ 364 mm (3.9 ~ 14.3")	100 ~ 257 mm (3.9 ~ 10.1")
Cut Sheet (Multi Part)		100 ~ 364 mm (3.9 ~ 14.3")	100 ~ 257 mm (3.9 ~ 10.1")
Envelope (No.6)		92 mm (3.6")	165 mm (6.5")
Envelope (No.10)		105 mm (4.1")	241 mm (9.5")
Continuous Paper (Single Sheet and Multi part)		101.6 ~ 558.8 mm (4.0 ~ 22.0")	101.6 ~ 254.0 mm (4.0 ~ 10.0")
Roll Paper		NA	216 mm (8.5")
Paper Feeding			Thickness
Standard			0.065 ~ 0.14 mm (0.0025 ~ 0.0055")
Optional			0.12 ~ 0.32 mm (0.0047 ~ 0.0126") (Total)
Copies			0.16 ~ 0.52 mm (0.0063 ~ 0.0205") (Total)
Line Spacing			0.065 ~ 0.32 mm (0.0025 ~ 0.0126") (Total)
Input Data Buffer			0.07 ~ 0.09 mm (0.0028 ~ 0.0035")
Interface			
Standard		Bi-directional parallel interface (IEEE-1284 nibble mode supported) USB 2.0 Full-Speed Serial	
Ribbon Cartridge			
Standard		Fabric Ribbon Cartridge (Black)	
Ribbon Life		Approx. 2.5 million characters (Draft 10 cpi, 48 dots/character)	
Acoustic Noise		Approx. 53 dB(A) (ISO 7779 pattern)	
Reliability			
Mean Print Volume Between Failure (MVPF)		Approx. 20 million lines (Except print head)	
Mean Time Between Failure (MTBF)		Approx. 10,000 POH (25% Duty)	
Print Head Life		Approx. 400 million strokes/wire	
Control Panel		4 switches and 5 LEDs	
Environmental Conditions (Operating)			
Temperature		5 ~ 35°C	
Humidity		10 ~ 80 % RH	
Electrical Specification			
Rated Voltage		AC 220 - 240V	
Rated Frequency		50Hz ~ 60Hz	
Power Consumption			
Operating		Approx. 22W (ISO/IEC 10561 Letter pattern)	
Sleep Mode		Approx. 1.3 W	
Auto Off Mode		Approx. 0.5W	
Power Off		0W	
Printer Driver / Utility			
Operating System		Microsoft® Windows® 2000 / XP / 7 / 8	
Utility			
Epson Status Monitor 3		Microsoft® Windows® 2000 / XP / 7 / 8	
Epson Printer Setting		Microsoft® Windows® 2000 / XP / 7 / 8	

Dimensions & Weight

Weight: Approx. 4.1kg (9.0lb)



Options

Fabric Ribbon Cartridge (Black) S015634

Legend

- cpi Characters per inch (Characters per 25.4mm)
- cps Characters per second
- cpl Characters per line
- POH Power On Hours

© 2019 Epson India Pvt. Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Information correct as at June 2019

EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A, No.1,
Murphy Road, Ulsoor, Bangalore - 560 008.
Tel: 080-45665000 Fax: 080-45665005

Regional Offices:

Ahmedabad - 3314 8500/01, Chennai - 3967 7500, Cochin - 4012 315,
Coimbatore - 98942 19200, Hyderabad - 4857 0032, Jipur - 78699 11699, Kolkata - 4603 4714/15/29/30,
Mumbai - 3079 8200, New Delhi - 3312 0300, Pune - 3028 6000/05



Epson Helpline: For product info or service - 1800 425 0011
For service - 1800 123 001 600 (9AM - 6PM) (Mon - Sat)
Email: ifp@epsonindia.in

www.epson.co.in

Dealer's Stamp