

Technical Specifications for EcoTank® L4260

PRINT	
Print Technology	Heat-Free™ PrecisionCore® 4-Color Inkjet (CMYK)
Maximum print resolution	up to 5,760 dpi x 1,440 dpi on various types of paper
Maximum print speed ¹	Simplex: 33 ppm black, 15 ppm color (scratch, A4/Letter)
ISO print speed ²	Simplex: 10.5 ppm black, 5 ppm color (A4/Letter)
First page out time (FPOT) ³	10 seconds black and white, 16 seconds color automatic duplex printing (A4/Letter)
Printing functions	
10 seconds black and white, 16 seconds color automatic duplex printing (A4/Letter)	
COPIES	
ISO copy speed ⁴	7.7 cpm black, 3.8 cpm color (A4/Letter)
Maximum copy resolution	300 dpi x 600 dpi
Maximum copy size	A4/Letter
SCAN	
Scan type	flatbed with color CIS line sensor
Maximum scan area	216 mm x 297 mm
Maximum resolution	1,200 dpi x 2,400 dpi
Color depth	color: 48 bits input, 24 bits output. Grayscale: 16 bits input, 8 bits output. Black and white: 16 bits input, 1 bit output.
WIRELESS PRINTING FROM SMART DEVICES	
Epson Connect™	Epson Smart Panel App (iOS, Android), Epson Email Print, Remote Print Driver
Others	Apple AirPrint®, Chromebook Native Print, Mopria Print Service™
INTERFACE AND CONNECTIVITY	
Standard connectivity	Hi-speed USB (compatible with USB 2.0), Wi-Fi 4 (IEEE 802.11 b/g/n), Wi-Fi Direct®
Network printing protocols	
Network management protocols	LPD, PORT9100, WSD
Network security	SNMP, HTTP, DHCP, APPA, Ping, DNS, MDNS, SLP, WSD, LLTD
Compatibility with operating systems	WEP, 64-bit/128-bit, WPA-PSK (TKIP), WPA2-PSK (AES), WPA3-SAE (AES), Windows Vista® / 7 / 8 / 8.1 / 10 or later (32 bits, 64 bits), Windows Server 2003 (SP2) or later, Mac OS X 10.7.5 or later, Mac OS 11 or later
MEDIA AND PAPER HANDLING	
Maximum printing size	215.9 mm x 1,200 mm
Supported paper	Plain paper, special Epson paper (Photo Glossy/Semi-gloss, Presentation Paper Matte, High Quality Ink Jet Paper and envelopes)
Supported paper sizes	A4, Letter, Legal (21.59 cm x 33.02 cm), Mexico-Legal (21.59 cm x 34.04 cm), Folio (21.59 cm x 33.02 cm), Executive, Half letter, A6, Photo: 4" x 6" (10 cm x 15 cm), 5" x 7" (12.5 cm x 8 cm), 8" x 10". Envelopes: #10. Defined by user: 54 mm x 86 mm - 215.9 mm x 1,200 mm Back tray: up to 100 pages (A4/LTR/Legal)
Load capacity	
GENERAL	
Included software	CD and web download: Printer driver, Epson Scan 2, Epson ScanSmart. Web download: Epson Photo+LCD screen - 1.44" color 1.44" a color
LCD Screen	Opened: 37.5 cm x 56.7 cm x 25.9 cm. Closed: 37.5 cm x 34.7 cm x 18.7 cm
Dimensions (W x D x H)	5.5 kg
Weight	Epson EcoTank L4260 multifunctional printer, installation guide, CD with drivers, power cable, USB cable.
What's in the box?	Philippines
Country of origin	2 years with product registration
Limited extended warranty ⁵	12 W (in operation mode)
Energy Consumption (approximate)	EcoTank L4260 (110V) C11CJ63301; AC 100 - 240 V / 50 - 60 Hz
Tension and nominal frequency	EcoTank L4260 (220V) C11CJ63303; AC 220 - 240 V / 50 - 60 Hz
INK YIELDS	
Genuine Epson replacement bottles	1 bottle of black ink prints up to 7,500 pages ⁶ 3 bottles of color ink (cyan, magenta, yellow) print up to 6,000 pages EcoTank® 4260 was designed to use exclusively Epson original inks. Epson recommends the use of original inks to ensure the best printing performance without warranty loss.
PRODUCT CODES	
Multifunctional Printer Epson EcoTank L4260 (110V) C11CJ63301	
Multifunctional Printer Epson EcoTank L4260 (220V) C11CJ63303	
Black ink bottle T504120-AL	
Cyan ink bottle T504220-AL	
Magenta ink bottle T504320-AL	
Yellow ink bottle T504420-AL	



EcoTank® is a registered trademark of Seiko Epson Corporation. Epson ink tank units sold worldwide through July 2021. 1-The maximum number of pages/copies per minute (PPM/CPM) is measured after the first page with test patterns in draft mode (or economy mode, depending on printer/MP) on plain paper. Actual printout times will vary based on system configuration, software and page complexity. 2-Black and color copy speeds are determined in accordance with the ISO/IEC 24734 standard. Actual printout time may vary based on system configuration, software and page complexity. For more information, visit latin.epson.com. 3- FPOT printing speed is determined in accordance with the ISO/IEC 17202 standard. 4- Black and color copy speeds are determined in accordance with the ISO/IEC 20155 standard. Actual copy time may vary based on system configuration, software and page complexity. For more information, visit latin.epson.com. 5- The standard warranty is 0-3 months with no page limit and 4-12 months, or up to 15,000 pages, whichever comes first. For an additional 12 months (24 month total warranty) or up to 30,000 pages (whichever comes first), register your product within 30 days of purchase and use genuine Epson ink bottles. For more information about the extended warranty program, visit latin.epson.com/warranty. 6- Part of the ink from the bottles included and used for the initial configuration; yields are lower than those of refill ink bottles. The yields of included ink bottles and refill ink bottles based on ISO/IEC 24712 test pages, using Epson methodology. Actual performance may vary considerably. For some reasons including printed images, print settings, temperature and humidity. Performance may be lower when not frequently impressed or when performing impressed with just a certain amount of ink. All ink cores are used for printing and printer maintenance, and all colors must be available for printing. For more information, go to latin.epson.com. 7- Wi-Fi CERTIFIED™: the performance level depends on the range of the router used. Wi-Fi Direct™ may require printer software.

Better Products for a Better Future®
For more information about Epson's environmental programs, visit eco.epson.com

www.latin.epson.com

In Latin America, call your local office or your authorized dealer. Epson Subsidiaries:

Epson Argentina, S.R.L. (5411) 5167 0300	Epson Centroamérica (506) 2588 7800	Epson Ecuador 1-800-000-044
Epson Bolivia (800) 100 116	Epson México, S.A. de C.V. (5255) 1323 2000	Epson Venezuela, S.R.L. (58212) 240 1111
Epson Chile, S.A. (562) 2484 3400	Epson Perú, S.A. (511) 418 0210	RF: J-00192669-0
Epson Colombia, Ltda. (571) 523 5000		

Epson EcoTank® and PrecisionCore are registered trademarks. EPSON Exceed Your Vision is a registered logo and Better Products for a Better Future, Epson Connect and Epson Print are registered trademarks of Seiko Epson Corporation. Mac, Mac OS y OS X are registered trademarks of Apple Inc., registered in the United States and other countries. Wi-Fi CERTIFIED is a registered trademark of Wi-Fi Alliance®. Every other products and brands are registered trademarks of their respective companies. Epson denies any and all rights to these brands. CPD: LS101432, 02/2022

EcoTank® FOR ENTREPRENEURS
Performance and efficiency at your fingertips



EcoTank® L4260
PRINT | COPY | SCAN | WIRELESS

100%
CARTRIDGE-FREE



Intuitive Smart Panel app
Easy printer configuration



High reliability and performance



Advanced connectivity
Wi-Fi®, Wi-Fi Direct®



Automatic duplex printing
(A4/Letter) Saves up to 50% of paper

EcoTank® L4260

PRINT | COPY | SCAN | WIRELESS



PRODUCTIVITY



Intuitive Smart Panel app
Easy printer configuration



Advanced connectivity
Wi-Fi®, Wi-Fi Direct®⁵⁷



Automatic duplex printing
(A4/Letter) Saves up to 50% of paper



Larger paper capacity
Backtray paper of 100 pages (A4/Letter/legal)



Pigmented black ink
Resistant to water, discoloration and spots on text documents



High-speed
Black up to 33 ppm¹ - color up to 15 ppm¹
Black up to 10,5 ppm² (ISO) - color up to 5 ppm² (ISO)



CONVENIENCE



EcoFit™ System
Easy and error-free ink loading



Easy computerless copying and scanning
with 1.44" color LCD screen



Compact and lightweight
Designed to take up little space

ECONOMY

100% No cartridges or heads to replace
CARTRIDGE-FREE



— PRINTS UP TO —
7.500 PAGES IN BLACK³
6.000 PAGES IN COLOR³

Always use genuine Epson inks. Protect your printer. Protect your investment.

60 PREFERRED BY
MILLION*



Peace of mind with Epson support.
Limited warranty extended to 2 years with product registration⁴