

# Full detailed report

(ISO/IEC 29183)

Model Stylus NX530

## Machine setting

Test Start Date and Time	2011/3/24 , 10:20 am
Tester	H.Nakata
Color or B/W	Color MFD
Configuration (Option)	Option wasn't used
Temperature	23 °C
Humidity	23 %
Test End Date and Time	2011/3/24 , 2:05 pm

	Pre-set item	Pre-set value
Mode	Output resolution	Default
	Output Quality	Default
	Copying mode	Default
	Auto density adjustment	N/A
	Collating function	N/A
Paper	Paper sending direction	Default
	Paper type setting	Default
Paper path	Paper feeding	Default Paper Feeder
	Paper exit	Standard exit tray
	Output orientation	Default (face up)
Temporary stop	N/A	N/A

Paper	Manufacturer	Fuji Xerox
	Weight	64g/m2
	Size	Letter
	Paper type/Name	PPC/V604

## Summary Report

	sFCOT [seconds]	sESAT [ipm]
Color	24	5.5
B&W	9	13

## Full Report

	Target	sFCOT [seconds]	sEFTP [ipm]			sESAT [ipm]
			1Copy test	1Copy+30 seconds (# copies)	1Copy+4 minutes (# copies)	
Color	A	24	2.5	4.3	6.1	5.7
				4 copies	28 copies	
	B	22	2.8	6.3		8.5
				6 copies		
	C	24	2.5	3.7		4.4
4 copies						
D	24	2.5	3.2		3.6	
Average		24	2.5	4.3		5.5
B&W	A	9	6.9	11	13	13
				8 copies	58 copies	
	B	9	7.4	13		15
				9 copies		
	C	9	6.8	12		13
8 copies						
D	9	6.7	11		12	
Average		9	6.9	11		13