

Kitchen and Receipt Impact Printer

TM-U220II



Durable kitchen and receipt printer supports mPOS and PC-POS systems.

Main Features

- **Engineered for reliability:** proven robust enclosure and long component lives; backed by a 2-year limited warranty.
- mPOS and PC-POS support: compatible with mobile devices and traditional POS systems.
- Two-color printing: highlight order exceptions with black and red for clear identification.
- Online order ready¹ with Server Direct Print: retrieve orders from a Web server and print receipts without requiring integration with POS software.
- **Resilient prints:** impact printer paper stands up to heat and moisture to remain legible.

- Flexible installation: wall-mount options with right-side up printing for easy reading in all orientations.
- **Comprehensive performance:** crisp printing up to 6 lps with auto cutter and take-up journal options to cover virtually any need.
- Easy network configuration: DHCP-enabled model for seamless configuration over networks.

TM-U220II

EPSON®

Specification Sheet

Carbon Paper Copy Capacity

Ribbon Life

Easy Setting Tool

Print

Fillit			
Printing Method Print Speed	9-pin, serial impact dot matrix Up to 8.8 lps (16 columns per line, 16 cpi) Up to 6.0 lps (30 columns per line, 16 cpi) Up to 4.7 lps (40 columns per line, 16 cpi)		
Print Fonts			
(Name, Structure [W x H dots], Size [mm], Horizontal Dot Spacing, Max. Columns Per Line [cpl])	ANK Font A, 9 x 9 dots, 1.6 mm x 3.1 mm, 3 half dots, 33 cp ANK Font A, 9 x 9 dots, 1.6 mm x 3.1 mm, 2 half dots, 35 cp ANK Font B, 7 x 9 dots, 1.2 mm x 3.1 mm, 3 half dots, 40 cp ANK Font B, 7 x 9 dots, 1.2 mm x 3.1 mm, 2 half dots, 42 cp Kanji, 16 x 16 dots, 2.7 mm x 2.7 mm, 1 or 2 dots, 22 cp		
Character Sets	95 alphanumeric characters, 16 internationa sets, 128 x 12 graphic, Japanese (JIS X0208-1990), Simplified Chinese (GB18030-2000), Traditional Chinese (Big5) Thai (128 x 7 page), Korean (KSC5601)		
Media Handling			
Media Dimensions	76.0 ± 0.5 mm/69.5 ±0.5 mm/57.5 ±0.5 mm (width) x 83 mm (rol diameter)		
Paper Thickness	60 µm – 85 µm		

Connectivity	
Interfaces (Choice of Connect-It™ Interface)	Connect-It Interfaces (UIB): USB, Ethernet, Serial, Parallel, Powered USB, Wireless
Protocolos de comunicación	Communication Protocols ESC/POS®, ePOS-Print Service (Ethernet/Wireless), Server Direct Print (Ethernet/Wireless) ¹

General				
Data Buffer	Receive: 40 bytes or 20KB, selectable			
	NV Graphics: 128KB (maximum)			
	NV User: 8KB (maximum)			
Development Kit	ePOS SDK (Android®, iOS®), OPOS ADK			
	(Windows), JavaPOS ADK (Windows, Linux®),			
	OPOS ADK for .NET (Windows)			
Drivers	Epson Advanced Printer Driver (APD), Mac®			
	Printer Driver, GNU/Linux Printer Driver			
Software	TM-U220II Utility (Windows), Deployment Tool,			
	Monitoring Tool, TM-U220II Firmware Updater			
LED Indicators	Power, Paper, Error			
Sensors	Paper-End, Near-End (factory			
	option), Cover Open			
DKD Function	Yes			
Mean Power Consumption	n Operating: 24.7 W; Standby: 1.2 W			
Power Supply	Adapter PS-190 (included on select SKUs); Adapter			
	PS-180; Adapter C1 Power Source 24 VDC \pm 7%			
Dimensions	Type A: 6.3"" x 11.3"" x 6.2"" (160 mm x 286			
(W x D x H)	mm x 157.5 mm)			
	Type B: 6.3"" x 9.8"" x 5.5"" (160 mm x 248			
	mm x 138.5 mm)			
	Type D: 6.3"" x 9.8"" x 5.5"" (160 mm x 248			
	mm x 138.5 mm)"			
Weight	Type A: Approx. 5.9 lb (2.7 kg)			
	Type B: Approx. 5.5 lb (2.5 kg)			
	Type D: Approx. 5.1 lb (2.3 kg)			

Eco Features	
Power-Saving Mode	
ENERGY STAR® qualified (select SKUs)	
RoHS compliant	

Dark Gray (EDG), Cool White (ECW)

FMI FCC Class A. ICFS-3

What's Included

Case Color

Approvals

Standards and

One (1) original and one (1) copy

TM-U220II Utility (Windows®)

ERC-38B; up to 3,000,000 characters

ERC-38BR; up to 1,500,000 characters (black), up to 750,000 characters (red)

TM-U220II, roll paper (starter roll for testing), User Manual, ERC-38BR ribbon cassette, AC adapter and AC cord (Contents vary by individual SKU, including AC adapter and cord)

Warranty				
2-year limited				

Ordering I	nformation			
Printer Model	Interface	Power Supply	Color	Part Number
TM-U220IIA TM-U220IIA TM-U220IIA TM-U220IIB TM-U220IIB TM-U220IIB TM-U220IIB	Parallel USB Ethernet Serial Serial Ethernet Ethernet (DHCP) Parallel	Included Included Included Included Included Included Included	EDG EDG EDG EDG EDG EDG EDG	C31CL26042AA C31CL26042AE C31CL26042AE C31CL27002 C31CL27032 C31CL27032A2 C31CL27032A2
TM-U220IIB TM-U220IIB TM-U220IIB TM-U220IID TM-U220IID TM-U220IID TM-U220IID TM-U220IID	Wireless USB Serial USB Parallel Serial Ethernet	Included Included Included Included Included Included Included	EDG EDG EDG EDG EDG ECW EDG	C31CL27042A4 C31CL27042A3 C31CL28002 C31CL28002 C31CL28052AE C31CL28052AA

Accessories

Power Supply Cover (OT-BX220) C32C814612 Wall-Hanging Bracket (WH-10) C32C845040 Wireless USB Adapter (OT-WL06) C32C891321

(A)/NMB-3 (A), cTUVus For additional options, please contact your Epson representative.







1 Requires an Internet network connection. 2 For convenient and reasonable recycling options, visit www.epson.com/recycle. 3 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency. 4 Product comes with 2-year limited warranty with the option to purchase extended service. See individual service plan for details. See the latest innovations from Epson Business Solutions at www.epson.com/forbusiness

Authorized Distributors:

www.latin.epson.com/pos

In Latin America and the caribbean, contact your authorized distributor or local office.

Epson Argentina S.R.L. (0800) 288 37766

Epson Bolivia (800) 100 116 Epson Chile S.A. (562) 2484 3400

Epson Colombia Ltda. (571) 602 4750 Epson Centroamérica (506) 2588 7800 Epson México S.A. de C.V. (5255) 1323 2000

Epson Perú S.A. (511) 418 0210