





SureColor SC-F6430

Epson new powerhouses, SureColor F6430/F6430H, are setting fresh benchmarks in textile printers with their reliable and superior print quality. Offering a high-performance solution for small to mid-sized textile production companies, these 44" digital dye sublimation printers are equipped with an integrated ink system and the all-new PrecisionCore MicroTFP Printhead. With the addition of orange and violet inks, the SC-F6430H raises the bar with its 6-colour printing, delivering fluorescent brightness and unique colours for specific printing needs.



ST Ink







Reliable & High Productivity

Equipped with the all-new 1.33-inch PrecisionCore MicroTFP printhead, printing speeds are improved by approximately 20%'.

Integrated Ink System

Minimise downtime with the improved 1.6L ink capacity along with easy and user-friendly machine operation and maintenance. Ink life after installation has been improved up to one year from just 25 days.

Improved Colour Options

SureColor SC-F6430H

Expand business opportunities with SC-F6430H's improved colour set options which are fluorescent yellow and fluorescent pink, light cyan and light magenta, and orange and violet.

MODEL NUMBER	SC-F6430	SC-F6430H	PRINTER DIMENSION
PRINT			SC-F6430/F6430H
Technology 1	PrecisionCore Inkjet Technology		Without Take Up Reel
Technology 2 Printhead	Variable-Sized Droplet Technology PrecisionCore MicroTFP Printhead		Without take op neet
Nozzle Configuration	The number of nozzles:	lead The number of nozzles:	NAME OF THE PARTY
Nozzie Comigaration	3,200 nozzles	2.400 nozzles	- B
	CMYHDK:	CMYHDKLcLm: 2,400 nozzles (400 x 6 colours)	1,128 m
	3,200 nozzles	CMYHDKFpFy: 2,400 nozzles (400 x 6 colours)	
	(800 x 4 colours)	CMYHDKOrV: 2,400 nozzles (400 x 6 colours)	
Maximum Resolution	600 x 1,200 dpi		745 mm
Minimum Ink Droplet Volume Maximum Print Speed	3.6pl 78.3 m²/h	38.8 m²/h	1,608 mm
Margin (Roll Paper)	3~25 mm (Right/Left) / 5~35 n		
INK	10 20 mm (mg/m 200) / 0 00 mm (10p) / 0 100 mm (2000m)		With Take Up Reel
Ink Types	Dye Sublimation Transfer Ink		
Ink Brand Name	UltraChrome DS Ink	UltraChrome DS 6 Ink	
Colours	Cyan, Magenta, Yellow, High D		1,128 mi
	N/A	Light Cyan, Light Magenta,	1,12011
		Fluorescent Yellow, Fluorescent Pink,	70)
Ink Capacity	1.6L	Orange, Violet	
Ink Capacity Ink Case	Ink Supply Unit		1.608 mm
MEDIA HANDLING	THE CORPLY OF THE		1,000 11111
Paper Path	Roll (Single Roll)		
Paper Feed Method	Friction Feed		UltraChrome DS Inks
Paper Width (Roll)	254 mm to 1,118 mm (10" to 4	14")	Cyan C13T53Q200 Magenta C13T53Q300
Paper Thickness (Roll)	Up to 0.5 mm		Yellow C13T53Q400
CONTROL PANEL	4.3" Colour LCD Touch Panel		High Density Black C13T53Q900
Colour/Size CONNECTIVITY	4.5 Colour Lod Touch Pariel		I litera Olamana - DO C larlas
Interfaces	Super Speed USB, 100BASE-TX/1000BASE-T		UltraChrome DS 6 Inks Light Cyan C13T53Q500
Printer Language	ESC/P raster		Light Magenta C13T53Q600
Memory	1 GB		Fluorescent Pink C13T53Q800
ENVIRONMENT			Fluorescent Yellow C13T53Q700
CHARACTERISTICS			Orange C13T53QA00 Violet C13T53QD00
Temperature (°C)	Operating: 10 °C – 35 °C		1,5,5
Humidity	Storage: -20 °C - 40 °C Operating: 20 - 80% (No Condensation)		Options & Consumables
DIMENSIONS	Operating, 20 - 80% (NO Condensation)		Auto Take-up Reel Unit C12C934671 Roll Adapter C12C934701
Printer (W x D x H)	With Take Up Reel: 1,608 x 916 mm x 1,128 mm		Maintenance Kit C13S210063
	Without Take Up Reel: 1,608 x		Head Maintenance Kit C13S400145
WEIGHT			Waste Ink Bottle C13T724000
With Take Up Reel:	Approx. 133 kg	_ Approx. 140 kg	Auto Cutter Spare Blade C13S902006
Without Take Up Reel:	Approx. 120 kg	_ Approx. 127 kg	*Bundled for SC-F6430H.
ELECTRICAL SPECIFICATIO		40 400\4	
Voltage Frequency	AC 220 - 240V (withstand volt 50/60 Hz	age AC 400V)	
Power Consumption	Operating: Approx. 80W		©2023 Epson India Pvt. Ltd. All Rights Reserved.
Tower Concampacin	Ready: Approx. 36W		Reproduction in part or in whole, without the writter
	Sleep: Approx. 19W		permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered
	Power Off (Standby): Approx. (0.3W	trademarks of Seiko Epson Corporation.
ACOUSTIC NOISE LEVEL			All other product names and other company names
Sound Pressure Level - db(A)	53.5 db		used herein are for identification purposes only and are the trademarks or registered trademarks of their
Sound Power Level - B(A)	<u>7.0 B</u>		respective owners.
UTILITY SOFTWARE	Encon Software Undator Engage Not Driet Engage Not Coofig CF		Epson disclaims any and all rights in those marks. Projected images shown herein are simulations.
Bundled in CD Web Delivery	Epson Software Updater, Epson Net Print, Epson Net Config SE Epson Edge Print Pro, Epson Edge Colour, Epson Device Admin		The actual product design and contents may vary.
Web Delivery CERTIFICATIONS	Lpson Lage Finit Pro, Epson Lage Colour, Epson Device Admin		Specifications are subject to change without notice may vary between countries. Please check with loc
Safety	USA and Canada (NRTL Certified), EU (Low Voltage Directive),		Epson offices for more information.
	Custom Union (Russia, Belarus, Kazakhstan) (EAC),		
	Morocco, Ukraine, India, Argentina (S-mark), Mexico (NOM), UK (UKCA),		Dealer's Stamp
	Germany (GS), Singapore, Car	nbodia	
WHAT'S IN THE BOX	Main unit, Stand, Waste ink bottle, Roll adapter, Epson Edge Print Pro DVD,		
		nd instructions, Warranty sheet, AC cable,	
	Maintenance tools, Auto take-	up reel unit (standard bundle only for F6430H)	

EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A, No.1
Murphy Road, Ulsoor, Bangalore 560 008
Tel: 080-4566 5000, Fax: 080-4566 5005

Scan the QR code or Click here to contact an Epson representative close to you.

Information correct at time of printing. Printed September 2023



nm





Epson Helpline: For product info or service - 1800 425 0011 For service: 1800 123 001 600 (9AM - 6PM) (Mon-Sat)

Email: Ifp@epsonindia.in