

Mobilink[™] TM-P80II

3" Wireless Portable Receipt Printer



Ultra fast, compact and rugged 3" wireless portable receipt printer.

Portable and lightweight — ultra compact, easy for users to wear (belt clip included); helps prevent carry fatigue

Robust design — IP54-rated enclosure is water- and dust-resistant; holds up to rigorous use, with a drop rating of 6.2 feet

Long-lasting battery life — up to 47 hours on a full charge¹ (battery and USB-C cable included)

Fast battery charging capability — fully charges as fast as 2.5 hours² (charger sold separately)

Versatile connectivity — wireless connectivity options (Wi-Fi® 5 or Bluetooth® 5.0) to provide connections to a wide variety of devices and networks

Exceptional print quality and ultra fast print speed — quickly produce sharp and crisp text, barcodes and logos at up to 100 mm/sec

High-capacity media basket to help maximize uptime — 51 mm outer diameter allows for large paper capacity; replace rolls less often

Modern design — sleek design suited to complement your business

Enhance your printing with accessories — choose from a wide range of optional accessories, such as single or quad battery charger, spare battery, belt strap, shoulder strap and soft carrying case (each sold separately)

World-class service and support — 1-year limited warranty; Epson Preferred[™] Plus Extended Service Plans available for up to a total of 5 years of continuous coverage



Mobilink™ TM-P80II 3" Wireless Portable Receipt Printer

Print

Print Method Thermal line printing

Print Speed Receipt version: 100 mm/sec (maximum)

Print Resolution Dots/inch: 203 dpi

Print Fonts

Fonts/Column Capacity 48 cpl mode: Font A: 12 x 24, 48 cpl (default); Font B: 9 x 17, 64 cpl; 42 cpl mode: Font A: 13 x 24, 42 cpl: Font B: 9 x 17, 60 cpl

Character Size (W x H) 48 cpl mode: Font A: 1.50 mm x 3.00 mm, Font B: 1.125 mm x 2.13 mm; 42 cpl mode: Font A: 1.63 mm x 3.00 mm, Font B: 1.125 mm x 2.13 mm

Barcode UPC-A, UPC-E, JAN13/EAN13, JAN8/EAN8, Code 39, ITF, CODEBAR (NW-7), Code 93, Code 128, GS1-128, GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded

2D Symbol Printing QR Code, Maxi Code, PDF417, Composite Symbology, GS-1, Aztec, Datamatrix

Media Handling

Type Thermal roll paper **Paper Feed Method** Friction feed

Width 3.13"/79.5 mm Paper Loading Drop-in

Roll Diameter (maximum) 2.0"/51.0 mm Core Diameter (minimum) 0.71"/18.0 mm

Auto Cutter No

Connectivity

Interfaces USB-C (built-in), Wi-Fi 802.11 a/b/g/n/ac (2.4 GHz or 5 GHz band) or Bluetooth 5.0 (Classic + LE)

Wireless Security Mode WPA/WPA2-PSK (TKIP/AES)

WPA3-SAE (AES) WPA2/WPA3-Enterprise

Supported Mobile Operating Systems iOS®, Android® and Windows®

Easy Setting SimpleAP, TM Utility, NFC and QR Code

General

Printer Reliability³ 10 million printing lines

IP Rating IP54

Drop Rating 6.2 feet

Charging Available Epson options: Single-Battery Charging Cradle (OT-SB80II) and Quad-Battery Charging Cradle (OT-CH80II); fully charges as fast as 2.5 hours²

Third-party options: USB-C charging devices,

wireless charging devices4

Battery Life 25 hours for Wi-Fi and 47 hours for Bluetooth¹ NV Bit Image Memory NV User: 192KB (maximum),

NV Graphics: 384KB (maximum)

Data Buffer Wi-Fi: 4KB, Bluetooth: 64KB

Printer Driver ePOS-Print SDK, Windows driver (APD), OPOS, OPOS.NET, JavaPOS (Win), JavaPOS (Linux®), TM Virtual Port

Software TM Utility (for iOS and Android), Integrated Utility, TM Bluetooth Connector, Epson WebConfig, Monitoring Tool, Deployment Tool, Firmware Updater

Audible Alert Programmable Buzzer

LED Indicators Power LED, Battery LED (x3), Charging LED, Bluetooth Connection LED or Wi-Fi Connection LED, Error LED Sensors Paper End, Cover Open

Power Source Lithium-ion battery pack, USB-C port

Power Saving Yes

Temperature -15°C to 50°C (5°F to 122°F)

Relative Humidity 10% – 90% Acoustic Noise Level 53 dB

Standards and Approvals EMI FCC Class B, ICES-003 Class B, Safety Standard UL62368-1/CAN/CSA C22.2 No.62368-1

Dimensions (W x D x H) 4.1" x 5.4" x 2.2"

Weight 0.8 lb
Color Epson Black

Eco Features

Paper Saving Mode
Power Saving Mode
RoHS compliant
End-of-life options available

Epson America, Inc. is a SmartWay® Transport Partner⁶

Warranty

Standard 1-year limited warranty, with optional extended service plans available

Epson Preferred Plus Extended Service Plans7

| 1-Year Return for Repair | EPPSDEXTB1 |
|--|--------------|
| 2-Year Return for Repair | EPPSDEXTB2 |
| 3-Year Return for Repair | EPPSDEXTB3 |
| 4-Year Return for Repair | EPPSDEXTB4 |
| 1-Year Renewal, Return for Repair | EPPSDEXTB1S |
| 1-Year Spare-in-the-Air™ (SITA) Coverage | EPPSDSITAB1 |
| 2-Year SITA Coverage | EPPSDSITAB2 |
| 3-Year SITA Coverage | EPPSDSITAB3 |
| 4-Year SITA Coverage | EPPSDSITAB4 |
| 5-Year SITA Coverage | EPPSDSITAB5 |
| 1-Year Renewal, SITA Coverage Extension | EPPSDSITAB1S |

What's Included

Mobilink TM-P80II, Battery (OT-BY80II), Belt Clip (attached to printer), Starter Roll Paper, USB-C Cable, Documentation

Ordering Information

rinters

| FIIIIGIS | |
|--|--------------|
| TM-P80II Wi-Fi | C31CK00011 |
| TM-P80II Wi-Fi with Battery Cradle | C31CK00A9981 |
| TM-P80II Bluetooth | C31CK00001 |
| TM-P80II Bluetooth with Battery Cradle | C31CK00A9991 |
| | |

Optional Accessories

| Battery (OT-BY80II) | C32C882301 |
|--|--------------|
| Single-Battery Charging Cradle (OT-SB80II) | C32C882A8541 |
| Quad-Battery Charging Cradle (OT-CH80II) | C32C882A8521 |
| Belt Strap (OT-BE01) | C32C882321 |
| Shoulder Strap (OT-SH01) | C32C882331 |
| Soft Case (OT-PC80II) | C32C882351 |

▲ WARNING: The paper roll shipped together with this product can expose you to chemicals, including Bisphenol A and Bisphenol S, which are known to the State of California to cause birth defects or other reproductive harm. Wash hands after handling.

For more information, go to www.P65Warnings.ca.gov

1 Battery life will vary considerably depending on connectivity (Wi-Fi or Bluetooth), usage and environment. | 2 Speed based on charging with Epson genuine battery chargers (OT-SB20II, OT-SB80II, OT-CH20II, OT-CH80II). | 3 Epson's statements about reliability levels are only estimates, based on normal use of the printer using tested media only. See www.epson.com/testedmedia for more information on Tested Media. These reliability statements are not warranties of the media or Epson's printers, and the only warranties for printers are the limited warranty statements for each printer. | 4 Epson cannot guarantee the performance or quality of third-party power adapters. | 5 For convenient and reasonable recycling options, visit www.epson.com/recycle | 6 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency. | 7 Product comes with 2-year limited warranty with the option to purchase extended service plans up to a total of 5 years of continuous coverage. Spare-in-the-Air extended service plans can be purchased anytime that you are covered under an Epson limited warranty or Epson extended service plan. Return for Repair extended service plan must be purchased within 90 days of product purchase. See individual service plan for details.

See the latest innovations from Epson Business Solutions at www.epson.com/forbusiness



Epson America, Inc. 3131 Katella Ave., Los Alamitos, CA 90720

Epson Canada Limited 185 Renfrew Drive, Markham, Ontario L3R 6G3 www.epson.com www.epson.ca

Specifications and terms are subject to change without notice. EPSON is a registered trademark of Seiko Epson Corporation. Epson Preferred, Mobilink and Spare-in-the-Air are trademarks of Epson America, Inc. Android is a registered trademark of Google LLC. Windows is a trademark of the Microsoft group of companies. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. Wi-Fi® is a registered trademark of Wi-Fi Alliance®. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2024 Epson America, Inc. CPD-62216R3 10/24

| \nearrow |
|------------|
| 1 |
| |
| |
| |
| |
| |
| |
| |