



Epson's TM-C3510 deliver high quality colour labels on-demand to improve efficiencies and reduce labeling costs. With a high printing speed of up to 103mm per second, excellent resolution and reliability, they are the perfect choice for industrial, chemical, warehousing, medical and other labeling applications. Now you can do away with expensive preprinted labels and simply print them whenever you need.









igh Speed High Capacity Us

USB 2.0

Ethernet



TM-C3510

# **ENGINEERED FOR BUSINESS**

## **Colour Labels On-Demand**

Designed to meet the needs of high mix, low-volume applications that require multiple label variations.

## **Better Inventory Management**

Save up to 50% on labeling costs by reducing the need to stock up on different types of preprinted labels.

## **BS5609 Certified**

Printers used together with pigment inks and approved media, are BS5609 certified to print GHS compliant labels.



MODEL NUM	BER	TM-C3510					
Print Technology Technology		MicroPiezo® inkjet technology, serial inkjet dot matrix					
	Colour		dividual ink cartridge (DURABri		gment ink: C, M, Y, K)		
Ink Cartridge							
J	Model	SJIC23P(C), SJIC23P(M), SJIC23P(Y), SJIC23P(K)					
Print Resolution		Up to 720 × 360 dpi					
Printing Width		Max. 104mm (Max. 1,474 dot positions / 360dpi)					
Print Speed Interfaces		Max. 103mm/sec.					
		(Printing Width: 56mm, 360 x 360 dpi, Bi-directional Printing)					
		Hi-Speed USB 2.0 and Ethernet (100BASE-TX /10BASE-T)					
Print Font  Barcode Font (Printer Driver Built-in)  Media Source		Not equipped with print fonts; prints all data as the graphic data					
		Barcode: UPC-A, UPC-E, JAN13(EAN), JAN8(EAN), Code39, ITF, Codabar, Code93, Code128, GS1-128, GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded Two-dimensional symbols: PDF417, QR Code, Maxi Code, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Expanded Stacked, DataMatrix, Aztec Code Roll-fed, Fanfold					
							Media Types
Paper Specifications		Width			Thickness		
Media Form							
Roll	Continuous Paper Black Mark Continuous Paper	30 - 108 mm		0.084 - 0.124 mm			
	Full-page Label	Label Width: 25.4 - 108 mm		Plain Label, Matte Label,			
	Transparent Full-page Label	Backing Paper Width:		Synthetic Label:			
	Die-cut Label (gap) Transparent Die-cut Label	30 - 112 mm Glossy Label: 0.184mm		0.128 - 0.195 mm			
	Black Mark Die-cut Label			D			
	o	0 "			Label, Matte Label, netic Label: 0.129 - 0.143 mm		
		Backing paper Width: 30 - 112 mm Synthetic Label: 0.129 - 0.143 mm Glossy Label: 0.184mm					
	Wristband	30mm 0.190 - 0.225 mm					
Fanfold	,						
	Black Mark Die-cut Label	Label Width: 46 - 108 mm, 0.161 - 0.164 mm					
External Roll Diameter		Backing Paper Width: 50 - 112 mm					
		Max. 101.6mm	O milestic Lede Lette 44.5				
Paper Core External Diameter		Plain Label, Matte Label, Synthetic Label: min. 44.1mm Glossy Label, Wristband: min. 56.8mm					
Number Of Folds		Fanfold Paper: 500 or Less					
Winding Direction		Face Out					
Autocutter Life		Paper	Die-cut Label		Full Page Label	Wristband	
		Plain: 1,500,000 cuts Matte: 750,000 cuts		n, Matte, Glossy: 1,500,000 cuts		200,000 cuts	
Temperature / Humidity Printing Storage Overall Dimensions (D x W x H) *		Plain: 750,000 cuts  Printing: 10 - 35°C / 20 - 80% RH; Barcode Printing: 15 - 35°C / 20 - 80% RH					
		-20 - 60°C / 5 - 85% RH (Without lnk.)					
		283 x 310 x 261 mm					
Mass		Approx. 12.0kg					
Power Supply		Dedicated AC Adapter					
Power Consumption Printing		Approx. 30W (mean)					
	Standby	Approx. 2.5W (mean)					
Rated Voltage		100 - 240 V					
Rated Freque		50 - 60 Hz					
Reliability MTBF		88,000 hours					
,	MCBF	9,800,000 passes					
EMC Standards		VCCI Class B, FCC / ICES-003 Class B, CE Marking, C-Tick Class B, CCC, BSMI, MIC, Ukraine EMC					
Safety Standards		UL, CSA, TÜV (EN60950-1), GOST, CCC, BSMI					
Operating System		Windows® XP SP2 (64bit) / SP3 (32bit), Windows Vista® SP2 (32bit / 64bit), Windows® 7 SP1 (32bit / 64bit), Windows Server® 2003 RZ SP2 (32bit / 64bit), Windows Server® 2008 RZ SP2 (32bit / 64bit), Windows Server® 2012, Windows® 8 (32bit / 64bit), Windows Server® 2012, Windows® 8 (32bit / 64bit), Windows Server® 2008 R2 SP1					

#### Dimensions & Weight

#### TM-C3510

Weight: Approx. 12kg (26.45lbs)



#### Option

C32C811281 OT-WA34 Wristband Attachment

#### Consumables for TM-C3510

 C33S020580
 SJMB3500
 Maintenance Box

 C33S020584
 SJIC23P(C)
 Ink Cartridge Cyan

 C33S020585
 SJIC23P(M)
 Ink Cartridge Magenta

 C33S020586
 SJIC23P(Y)
 Ink Cartridge Yellow

 C33S020578
 SJIC23P(K)
 Ink Cartridge Black

© 2016 Epson India Pvt. Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited.

EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation.

All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners.

Epson disclaims any and all rights in those marks. Print samples shown herein are simulations. The actual product design and contents may vary. Specifications are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Information correct at time of printing Printed December 2017

### Usage Restrictions:

When this product is used for applications requiring high reliability/safety such as transportation devises related to aviation, rail, marine, automotive etc.; disaster prevention devices; various safety devices etc.; or functional/precision device etc., you should use this product only after giving consideration by inclusion of fail-safes and redundancies into your design to maintain safety and total system reliability. Because this product was not intended for use in applications requiring extremely high reliability/safety such as aerospace equipment, main communication equipment, nuclear power control equipment, or medical equipment related to direct medical care etc., please make your own judgement on this product's suitability after full evaluation.

# EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A, No.1, Murphy Road, Ulsoor, Bangalore - 560 008. Tel: 080-30515000 Fax: 080-30515005

### **Regional Offices:**

Ahmedabad - 33148500/01, Chennai - 3967 7500, Cochin - 4012 315, Coimbatore - 98942 19200, Kolkata - 6500 9370/77, Mumbai - 3079 8200, New Delhi - 3312 0300/01, Pune - 3028 6000/05, Hyderabad - 6463 9640/41





Dealer's Stamp

