

# PowerLite® 770F

1080p 3LCD Ultra Short Throw Lamp-Free Laser Display



The large, easy-to-read HD display for dynamic classroom environments.





Best-in-Class Color Brightness<sup>1</sup> with 3-chip 3LCD technology — 4,100 lumens of color and white brightness<sup>2</sup>

**Incredible image quality** — Full HD 1080p resolution for amazing clarity and readability

**No lamps to replace ever** — solid-state, 30,000-hour (ECO mode), virtually maintenance-free laser light source<sup>3</sup>

**Convenient ultra short throw design** — displays large true-to-life images up to 150" from less than two feet away

**Flexible display** — 16:9 display with additional support for ultra wide 16:6 and 21:9 format is ideal for large, multi-device, split screen images<sup>4</sup>

Connect and cast from up to 50 devices<sup>5</sup> — free downloadable Epson iProjection™ software<sup>6</sup> makes it easy to cast wirelessly from Chromebooks, iOS® and Android™ devices, Mac® computers and PCs<sup>5</sup>; with moderator feature<sup>7</sup>, teachers never lose control of the displayed content

**Easily project wall-sized images** — built-in edge blending features for easy, scalable projection

**Simple, flexible installation** — 360-degree placement capabilities; mount or place the projector in any position, from landscape to portrait

**Easily programmable with the built-in media player** — which includes templates, effects, color filters and customizable options; playlist and playback functions allow for seamless content management for single or multiple PowerLite projectors

**Easy access and maintenance** — with remote management and control tools



#### **Specifications**

Projection System RGB liquid crystal shutter projection system

**Driving Method** Poly-Silicon TFT Active Matrix Pixel Number 2,073,600 dots (1920 x 1080) x 3 Color Brightness<sup>2</sup> Color Light Output: 4,100 lumens

White Brightness<sup>2</sup> White Light Output: 4,100 lumens Aspect Ratio 16:9 (native); 16:6, 4:3, 16:10, 21:9

Image Size (Projected Distance)

Without Mount:

49" - 123" (12.8" - 35.2") 4:3 60" - 150" (12.8" - 35.2") 16:9

55" - 139" (12.8" - 35.2") 16:10

56" - 140" (12.8" - 35.2") 16:6

57" - 142.5" (12.8" - 35.2") 21:9

With ELPMB62 Mount:

58" – 117" (15.5" – 33.6") 4:3 71" – 143" (15.5" – 33.6") 16:9

65" - 132" (15.5" - 33.6") 16:10

66" - 133" (15.5" - 33.6") 16:6

67" - 135" (15.5" - 33.6") 21:9

**Display Resolution** 1080p (1920 x 1080)

**Light Source** Laser Diode

Laser Light Source Life<sup>3</sup>

Normal Mode: Up to 20,000 hours Extended Mode: Up to 30,000 hours

Throw Ratio Range 0.25 (Zoom: Wide), 0.35 (Zoom: Tele)

Size (Projected Distance)

Without Mount:

60" - 150" 16:9 55" - 139" 16:10

56" - 140" 16:6

57" - 142.5" 21:9

With ELPMB62 Mount:

71" - 143" 16:9

65" - 132" 16:10 66" - 133" 16:6

67" - 135" 21:9

**Keystone Correction (Manual)** 

Vertical: ± 3 degrees Horizontal: ± 3 degrees

Dynamic Contrast Ratio Over 2,500,000:1

Color Reproduction Up to 1.07 billion colors

Foot Adjuster

Vertical: -0.8 to +0.8 degrees

Horizontal: -0.8 to +0.8 degrees

Modes

Dynamic, Presentation, Cinema, sRGB, DICOM SIM,

Multi-Projection

# **Projection Lens**

Type Digital zoom, Focus (manual) F-Number 1.6

Focal Length 3.7 mm

**Zoom Ratio** 1.00 – 1.35 (digital zoom)

#### Interfaces

3x HDMI

1x Analog VGA 15-Pin (in)

1x RCA Composite

1x Analog VGA 15-Pin (input/monitor out)

3x Stereo Mini In

1x Stereo Mini Out

1x RS-232C Control Port

1x USB Type-A (powered 5 V, 2 A)

2x USB Type-B (USB display with audio)

1x Wired LAN RJ-45

Wireless Support for Built-In WLAN Adapter: Wireless

802.11 b/g/n/ac

IEEE 802.11b: 11 Mbps\* (2.4 GHz)

IEEE 802.11g: 54 Mbps\* (2.4 GHz)

IEEE 802.11n: 72.2 Mbps\* (2.4 GHz)

IEEE 802.11a: 54 Mbps\* (5 GHz)

IEEE 802.11n: 150 Mbps\* (5 GHz)

IEEE 802.11ac: 325 Mbps\* (5 GHz)

#### Software

In addition to compatibility with Epson's standard suite of software, this product has a direct playback function via USB. Works with:

- Epson® Projector Content Manager Software (visit our support pages for the latest version)
- Epson Creative Projection App

#### Speaker

16 W monaural

Operating Temperature 41 °F to 104 °F (0 °C to 40 °C)

(20% - 80% humidity, no condensation)

**Power Supply Voltage** 100 V - 240 V AC ±10%, 50/60 Hz Auto Power On Signal Detection on HDMI/Plug-In Detection (HDMI, USB, VGA 15-Pin, BNC)

Sleep Mode Yes (with timer)

#### **Power Consumption**

Normal Mode: 277 W Quiet Mode: 214 W, Quiet Mode Extended: 208 W

Standby Mode: 2.0 W Energy-Saving Mode: 0.5 W

#### Fan Noise

Normal Mode: 37 dB Quiet Mode: 27 dB

Security Enterprise-Level Security Encryption

**Country of Origin** China

# Dimensions (W x D x H)

Projector (Including Feet) 14.1" x 6.5" x 15.6"

Weight 13 lb

#### **Remote Control**

Features Source Search, HDMI, Computer, USB, LAN, ID, Default, User, E-Zoom, Color Mode, Aspect, A/V Mute, Split, Freeze, Home, Auto, ESC, Menu, Volume, User, Right, Left, Up, Down Arrows



\* These modes and actual data throughputs depend on supported wireless mode of source devices and/or environmental conditions

#### **Remote Control (Continued)**

Operating Angle Front: Right/Left: -30 to +30 degrees Upper/Lower: 0 to +60 degrees Rear: Right/Left: -55 to +55 degrees Upper/Lower: +75 to +15 degrees Operating Distance 20 ft (6 m)

## **Eco Features**

RoHS compliant

End-of-life options available<sup>8</sup>

Epson America, Inc. is a SmartWay® Transport Partner9

# **Limited Warranty and Service**

Warranty Three-year limited or 20,000 hours, whichever comes first, in the U.S. and Canada

Service Whole unit exchange, usually Next-Business-Day10 Toll-free telephone support, Monday through Friday

**Epson Connection**<sup>SM</sup>

Pre-Sales Support (U.S. and Canada): 800-463-7766 Website: www.enson.com

# Epson Preferred<sup>SM</sup> Plus Extended Service Plan<sup>11</sup>

1-Year Next-Business-Day Whole Unit Exchange 2-Year Next-Business-Day Whole Unit Exchange<sup>10</sup> EPPEXPF2 (available for up to a total of 5 years of continuous coverage)

## What's Included

PowerLite 770F, Quick Setup Guide, projector remote control, 2x AA batteries, 6' power cord, projector feet

# Ordering Information

PowerLite 770F V11HA79020 Ultra Short Throw Wall Mount (ELPMB62) V12HA06A05 Wireless LAN Adapter (ELPAP11) V12H005A02 Air Filter V13H134A60 PowerLite Pilot™ 3 (ELPCB03) V12H927020 Active Speakers (ELPSP02) V12H467020 DC-07 Document Camera V12H759020 DC-13 Document Camera V12H757020 DC-21 Document Camera V12H758020 DC-30 Document Camera V12HB09020

1 Color brightness measured per IDMS 15.4. Additional colors and picture modes tested. Top-selling Epson 3LCD projectors vs. comparable top-selling 1-chip DLP projectors based on NPD sales data for October 2019 — September 2020. COLOR BRIGHTNESS WILL VARY BASED ON USAGE CONDITIONS. 2 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. I 3 No required maintenance for the light source for up to 30,000 hours (Extended Mode) or 20,000 hours (Normal Mode). Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.44 - 0.20 mg/m³ of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period. I 4 Consult your user manual for Split Screen input combinations. I 5 For wireless functionality, including via the Epson iProjection App, the projector must be configured on a network, either through the Ethernet port on the projector (check model specifications for availability) or via a wireless connection. Check your owner's manual to determine if a wireless LAN module must be purchased separately to enable a wireless connection. Not all Epson projectors are able to be networked. The Epson iProjection App does not support all files and formats. See www.epson.com for details. | 6 Internet connection required for download. Data usage fee may apply. I 7 Moderator control, connecting via QR code and projector remote are not available on Epson iProjection for Chromebooks. I 8 For convenient and reasonable recycling options, visit www.epson.com/recycle I 9 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency. I 10 Subject to limited warranty terms and conditions. Expedited shipping not available in all areas. Orders must be placed and processed by 1 p.m. Pacific Time, Monday through Friday, excluding holidays. I 11 Product comes with a 3-year limited warranty with the option to purchase Extended Service Plans up to a total of 5 years of continuous coverage. Extended Service Plan can be purchased at any time that you are covered under an Epson limited warranty or Epson Extended Service Plan. See individual service plan for details.

Learn more about how our products can empower your institution. Visit us at www.epson.com/foreducation



Epson America, Inc.

3131 Katella Ave., Los Alamitos, CA 90720

**Epson Canada Limited** 185 Renfrew Drive, Markham, Ontario L3R 6G3 www.epson.com www.epson.ca

Specifications and terms are subject to change without notice. EPSON and PowerLite are registered trademarks and Epson iProjection is a trademark of Seiko Epson Corporation. Pilot is a trademark and Epson Connection and Epson Preferred are service marks of Epson America, Inc. Mac is a trademark of Apple Inc., registered in the U.S. and other countries. Android and Chromebook are trademarks of Google LLC. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2023 Epson America, Inc. CPD-62993R2 10/23