SPECIFICATIONS

| MODEL NUMBER | | TM-P20II | | TM-P80II | TM-P80II | |
|--------------------------------|---------------|-----------------------------------------------------------------------------------------------------------------------------------------|----------------------------|-------------------------|--------------------------------------------------------------------------|--|
| | | Bluetooth Wi-Fi | | | Bluetooth Wi-Fi | |
| Print Technology | | | | | | |
| Printing Method | | Thermal Line Prir | ntina | | | |
| Print Font | | | 9 | | | |
| Font | | ANK: 12 x 24 / 9 x 24 (default) / 9 x 17 / | | I ANK(48 cl): 12 x 2 | ANK(48 cl): 12 x 24 / 9 x 17 (default) / 8 x 16; | |
| Tonk | | 10 x 24 / 8 x 16; Kanji Font: 24 x 24 / 20 x 24 / 16 x 16; | | , , | Jap Font: 12 x 24 / 10 x 24; Kanji Font: 24 x 24 / 20 x 24 / 16 x 16; | |
| | | | | | | |
| | | Special Font: 12 x 24 / 9 x 24; | | | Special Font: 12 x 24 / 9 x 24; | |
| | | India Font: Width x 32 / Width x 24 | | | x 32 / Width x 24 | |
| | | | | | ANK(42 cl): 13 x 24 / 9 x 17 / 8 x 16; | |
| | | | | , , | Jap Font: 13 x 24 / 10 x 17 / 8 x 16; | |
| | | | | | Kanji Font: 26 x 24 / 20 x 24 / 16 x 16; | |
| | | | | 1 ' | Special Font: 12 x 24 / 9 x 24; | |
| | | | | | India Font: Width x 32 / Width x 24 | |
| Character Set | | 05 Alphanumoria | , 18 set International, 1 | | X 32 / WIUII X 24 | |
| Barcode Standards | | | | | dabar/NIW 7) Codo20 | |
| Darcoue Stariuarus | | Bar code: UPC-A, UPC-E, JAN8, EAN8, JAN13, EAN13, ITF, Codabar(NW-7), Code39, Code93, Code128, GS1-128, GS1 DataBar | | | | |
| | | 2D Symbol: PDF417, QR code, Maxi Code, Data Matrix, Aztec, Two-dimensional GS1 | | | | |
| | | DataBar, Composite Symbology | | | | |
| lulus form | | Databar, Compo | Site Symbology | | | |
| Interface | | LIOD O 4 BI | | | | |
| Bluetooth Model | | USB-C x1, Bluet | | | | |
| Wi-Fi Model | | USB-C x1, Wi-Fi | | 1011/0 | | |
| Receive Data Buffe | er | 64 KB | <u>4 KB</u> | <u>64 KB</u> | <u>4 KB</u> | |
| Print Speed | | 100 mm/s | | 1 | | |
| Dot / Line | | 384 dots | | 576 dots (48 colu | mn), 546 dots (42 column | |
| Dot / Inch | | 203 x 203 dpi | | | | |
| Paper | | | | | | |
| Roll Paper | | | 5 mm) × Dia. 18 - 40 m | m 79.5 ± 0.5 mm (W | /) × Dia. 18 - 51 mm | |
| Media Thickness | | Max 75µm, Min 8 | 50µm | | | |
| Power | | | | | | |
| Battery Type | | Lithium Ion Batte | ery | | | |
| Charging Port | | USB-C | | | | |
| Charging Rating | | | | | | |
| 5 | V - 3A | 3 Hrs (10 - 30°C) |), | 2.5 Hrs (10 - 30°C | C), | |
| | | 6 Hrs (0 - 10°C) | | 5 Hrs (0 - 10°C) | | |
| 5 | V - 1.5A | 4 Hrs (10 - 30°C) |), | 3 Hrs (10 - 30°C), | | |
| | | 8 Hrs (0 - 10°C) | | 6 Hrs (0 - 10°C) | | |
| 5 | V - 900/500mA | 7 Hrs (10 - 30°C) |), | 14 Hrs (10 - 30°C | 5), | |
| | | 14 Hrs (0 - 10°C) | | 28 Hrs (0 - 10°C) | | |
| Battery Life *2 | | 27 Hrs | <u>15 Hrs</u> | 47 Hrs | <u>25 Hrs</u> | |
| Operating Temperatu | ire | -15 - 50°C (Norn | nal), 0 - 40°C (While Ch | narging) | | |
| Humidity | | 10 - 90% RH | | | | |
| Reliability | | | | | | |
| Printer Mechanism L | ife | 10 million lines | | | | |
| Thermal Printhead Li | fe | 50 Km | | | | |
| MTBF | | 120,000 hours | | | | |
| MCBF | | 16 million lines | | | | |
| IP Protection Rating | | IP54 | | | | |
| Drop Rating | | 2.1m | | 1.9m | | |
| Colour | | Epson Black (EB | CK) | | | |
| Overall Dimensions | s (W x D x H) | 79 x 120 x 46 mi | m | 105 x 138 x 57.6 | mm | |
| Weight | <u> </u> | Approx. 216g | | Approx. 379g | | |
| General Informatio | n | | | | | |
| LED Indicators | | Blue LED - Powe | er, Battery Level, Interfa | ces (Bluetooth, Wi-Fi) | | |
| EES maidatoro | | Orange LED - Error, Battery Charging | | | | |
| Built-in Features | | Paper Reduction, Status Notification, Server Direct Print | | | | |
| Printer Driver | | | | | inux). TM Virtual Port Drive | |
| | | Windows Driver (APD), OPOS, OPOS.NET, JavaPOS(Windows, Linux), TM Virtual Port Driver, ePOS SDK (iOS, Android, Javascript) | | | | |
| Utility Tools | | TM Utility (Android, iOS), TM-P20II/TM-P80II Utility (Windows PC), TM-Print Assistant | | | | |
| | | (Android, iOS), Deployment Tool, Monitoring Tool, Epson WebConfig, TM Bluetooth | | | | |
| | | (Android, iOS), Deployment 100i, Monitoring 100i, Epson WebConfig, 1M Bluetooth Connector, Firmware Updater, BmpToRaster, ePOS-Print *3 | | | | |
| Facy Catting | | | ware Updater, Bmp IoR | aster, ePOS-Print | | |
| Easy Setting What's in the Box | | NFC | 1100 0 11 7 | F 0) D #B | 0 : 1 | |
| | | Beit Clip. Battery | , USB Cable (Type-C to | TIVNE CI BOILPaner Seti | | |

- Battery life result may ultier from usage. Testing Conditions:

 1) Battery: New 2) Start of Charging state: Full Charge 3) Print Patter: ANK 42 digits, 20 lines + paper feed for 6 lines
 4) Interval of print: Each 5 minutes 5) Environment: normal temperature (25 degree) 6) Print density: 100%
 7) Access point: CISCO AIR-LAP1142N-P-K9 8) Wi-Fi condition: beacon interval: 200ms, DTIM: interval 1, disable Broadcast
- 9) Battery state: from full charge to until 0% (E level)*3 ePOS-Print applicable for Wi-Fi version only

EPSON INDIA PVT. LTD.

Regional Offices:

12th Floor, The Millenia, Tower A, No.1, Ahmedabad 4037 0075, Chennai 3967 7500, Ernakulam 4012 315, Coimbatore 99620 00969 Murphy Road, Ulsoor, Bangalore - 560 008. Hyderabad 4857 0032, Jaipur 0141 4923119, Kolkata 4603 4714/15/29/30, Mumbai 3079 8200

Tel: 080-4566 5000 Fax: 080-4566 5005 New Delhi 4107 3101, 4752 2414, 4226 3483, 4215 1033, Pune 3028 6000.

Epson Helpline: For product info or service - 1800 425 0011 For service: 1800 123 001 600 or 1860 300 016 00 (9AM - 6pm) (Mon - Sat)

DIMENSIONS & WEIGHT

TM-P20II

Weight: Approx. 216g



TM-P80II Weight: Approx. 379g



©2023 Epson India Pvt. Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON is registered trademark of Seiko Epson

All other product names and other company names

used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. epson disclaims any arto all rights in those thanks. Projected images shown herein are simulations. The actual product design and contents may vary. Specifications are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.


Dealer's Stamp

www.epson.co.in

Information correct at time of printing. Printed November 2023

MOBILE POINT-OF-SALE PRINTER TM-P20II/P80II

EPSON



Durable and reliable POS printers for outdoor printing with user-friendly functions.

Designed with wearability in mind, the compact Epson TM-P20II/P80II portable receipt printer is the ideal solution for on-the-go printing with its long battery life and multiple connectivity options. With high impact protection, conforming to Ingress Protection 54 (IP54) standard for dust and liquid resistance, the portable printer is built to withstand harsh environments, ideal for outdoor work in adverse conditions.













Built For Outdoors

With high impact protection, conforming to IP54 standard for dust and liquid resistance, the TM-P20II/P80II is built to withstand outdoor use.

Outstanding Performance

Enjoy peace of mind during business operation with its long battery life of up to 47 hours*

Compact Ergonomic Design

Designed for convenience and wearability in mind, the portable printer is compact and lightweight, with handy optional accessories.

*Battery life result may differ from usage.

Note: for battery life testing condition, please refer to disclaimer (superscript *2) under specifications page.

ERGONOMICALLY DESIGNED FOR RELIABILITY



ROBUST & DURABLE DESIGN



High Impact Resistance*

With a drop rating of 2.1m for TM-P20II and 1.9m for TM-P80II, the portable receipt printer is a trusty component for businesses that require mobility and outdoor use.




*Unit drop test JIS C60068-2-31:2013 (IEC 60068-2-31: 2008).



Dust Particles Resistance

Conforming to the IP54 dust resistance standard, you can conveniently use this portable printer for outdoor work or in adverse conditions.







Liquid Resistance

Enjoy peace of mind when using your



CATERED FOR OUTDOOR WORK

Long-lasting Battery Life

The all-new TM-P20II/P80II receipt printer comes with a long-lasting battery life that enables continuous use on both Wi-Fi and Bluetooth. Using the bundled USB Type C cable, the TM-P20II can be fully charged within 3 hours and P80II in 2.5 hours.

TM-P20II

Wi-Fi model: up to 15 hours*

Bluetooth model: up to 27 hours

**Enabled Power Saving Mode.

Note: for battery life testing condition, please refer to disclaimer (superscript *2) under specifications page

Convenient Paper Roll Replacement

The paper roll compartment is easily accessible even when you are wearing the TM-P20II/P80II receipt printer, allowing convenient and quick paper roll replacement in between use.



Handy Optional Accessories



The optional shoulder and belt strap allows users to access the printer easily,

TM-P80II

Wi-Fi model: up to 25 hours**

Bluetooth model: up to 47 hours

An optional carrying case further protect your printer against adverse conditions.





INTUITIVE FEATURES FOR EASY OPERATION

The TM-P20II/P80II is designed for seamless operation.

Clear Indicator

An easy-to-see indicator that shows the printer status at a glance.

Safety Design

With a hidden cutter design, users can operate the printer without worrying about getting injured.

Easy-to-clean Surface

A smooth printer surface allows quick and easy cleaning while on the go.

Compact & Wearable Compact and lightweight, the

TM-P20II/P80II receipt printer is suitable for direct-to-door, proof of delivery, marketplace receipt, and on-the-go receipt printing.

Multiple Language Support

The versatile TM-P20II/P80II is compatible with multiple languages including Chinese, Japanese, and Korean, with UTF-8 font support.

*Unicode support is only for languages listed in the specifications sheet

57.6mm (P80II)

VERSATILE CONNECTIVITY

Multiple Interface Options

