

BrightLink® Interactive Series

575Wi Widescreen

585WiWidescreen
Ultra bright



The bright choice in interactive projectors for today's BYOD classroom.

3x Higher Color Brightness¹, and reliable performance - 3LCD, 3-chip technology

One measurement of brightness is not enough — look for both high color brightness and high white brightness. The BrightLink 575Wi and 585Wi have:

Color/Interactive Brightness: 2,700 lumens (575Wi) and 3,300 lumens (585Wi)²

White/Interactive Brightness: 2,700 lumens (575Wi) and 3,300 lumens (585Wi)²

PC-free interactivity — display and write on content from an iPad®/iPod®/iPhone®, Android™ device, document camera, DVD player, or no source at all

Convenient collaboration for BYOD classrooms — wirelessly share³ and compare students' work from multiple devices, simultaneously, with Moderator software⁴

Wireless interactivity³ — use EasyMP[®] software with a networked BrightLink projector to share and interact with content from your laptop as you move freely about the classroom

Dual pen support — allows two users to annotate simultaneously anywhere on the surface on which the image is projected

Includes SMART Notebook® collaborative learning software — plus a 1-year subscription to the SMART Notebook Advantage software maintenance program









The bright choice in interactive projectors for today's BYOD classroom.

The BrightLink 575Wi and 585Wi bring cutting-edge kinesthetic learning to the BYOD classroom. Offering 3x Higher Color Brightness¹ than competitive models, Epson® 3LCD projectors ensure bright, vivid lessons. The 575Wi and 585Wi ultra short-throw projectors deliver dynamic images, whatever the task at hand. And, they display images up to 100" from just 12" away. Best of all, with PC-free interactivity, these projectors make it easy to walk in and start an interactive session on any wall or whiteboard. Instructors can use the Moderator software⁴ to share students' work over the network from multiple devices, simultaneously. Or, they can wirelessly project content³ from iOS® or Android devices or utilize popular learning applications.

Projectors at a glance

Model	575Wi	585Wi
Resolution	WXGA resolution (1280 x 800)	WXGA resolution (1280 x 800)
Color Brightness	2,700 lumens ²	3,300 lumens ²
White Brightness	2,700 lumens ²	3,300 lumens ²
Interactive Brightness	2,700 lumens ²	3,300 lumens²

Specification Sheet | Page 2 of 6

Advanced connectivity



Wireless interactivity³.

When using Epson's EasyMP software with a networked BrightLink projector, teachers are no longer tied down by restrictive and confining cables. Educators can wirelessly display and interact with content as they move about the classroom with their laptop, experiencing a whole new level of interactive freedom.

Advanced network connectivity and management capabilities.

Present A/V content over the LAN or annotate on network content using BrightLink's instant annotation tools. With Epson's EasyMP Monitor software, IT administrators can configure and monitor the status of their Epson networked projectors, including the remote viewing of power status, lamp hours and temperature/filter conditions.

Amazing image quality







BrightLink 575Wi





BrightLink 585Wi

3x Higher Color Brightness with Epson¹.

Brilliant image quality requires high color brightness (color light output), and Epson 3LCD projectors have 3x Higher Color Brightness than leading competitive projectors¹.

One brightness measurement (lumens) is not enough. A projector's specification needs to show both high color brightness and high white brightness. If color brightness is lower than white brightness, images may be dark, dull and lose detail. If not provided, be sure to ask for a projector's color brightness specification.















COMPETITORColor brightness significantly lower than white brightness

Actual photographs of projected images from an identical signal source. Price, resolution and white brightness are similar for both projectors (Epson 3LCD and 1-chip DLP competitor). Both projectors are set to their brightest mode.







3LCD, the #1 projection technology in the world, has:


- Both high color brightness and high white brightness
- 3 chips for up to 3x Higher Color Brightness⁶ than DLP projectors
- 25% lower power consumption for lower energy costs⁷
- 25 years of road-tested reliability
- A nationwide study reveals that 9 out of 10 people prefer images from 3LCD projectors⁵


Classroom collaboration

Teaching tools.

Support BYOD classroom collaboration and wirelessly share and control content from personal devices to the projector with Epson's Moderator device management software⁴.

- Wirelessly connect up to 50 Windows® and Mac® devices, plus iOS or Android mobile devices running the Epson iProjection™ App®
- The teacher can share content from up to four device screens simultaneously to the projector and control which device screens to display





Easy Interactive Tools 3.0.

This new annotation software from Epson allows users to control projector settings over the network; record and save video from Epson document cameras; save, re-open and edit annotation files; access archived curriculum; and program the interactive pen button to provide instant access to the most used tools. Best of all, Easy Interactive Tools is free and ships with each BrightLink projector.



SMART Notebook software for BrightLink.

SMART Notebook collaborative learning software helps teachers create engaging and interactive learning experiences. Make learning fun with SMART Notebook's subject-specific functionality, easy integration with mobile devices, and thousands of pieces of pre-created content. Each BrightLink includes a 4-seat user license (available for Windows and Macintosh®) for SMART Notebook, as well as a 1-year subscription to the SMART Notebook Advantage software maintenance program.

Energy saving

Save energy and reduce operating costs.

- ECO Mode operates the projector at a lower brightness setting
- Light Optimizer Mode adjusts the lamp brightness, based on the projected image
- Auto Mode sensor automatically adjusts the lamp brightness, based on the room environment
- Lamp dimming after a certain period of inactivity, the projector lamp dims, thereby extending the lamp life
- Sleep Mode (A/V Mute) control your presentation; it's right at your fingertips
- Direct Power Off/On power the projector on/off with the flip of a wall switch
- Standby audio out use the projector's internal speakers or continue to pass audio out to an external speaker and play your audio even when the projector is "off" (in Standby Mode)

Easy to use





Simple Setup Suite from Epson.

Epson projectors offer a suite of innovative features that ensure flexible placement and fast, easy setup.

- Flexible wall mount (included) the telescopic arm makes it easy to mount the projector and then adjust the image on any surface, including plain walls and existing boards, as well as thicker boards
- Auto calibration get up and running in no time
- 2x HDMI® use with multiple high-definition A/V devices (compatible with the latest laptops, Blu-Ray Disc® and media players)
- MHL® the latest in connectivity9
- Display content with MHL-enabled smartphones, tablets and Roku® devices¹⁰
- Use the projector remote to control MHL-enabled devices
- Charge your MHL-enabled device when it's plugged into the projector
- · Get instant access to movies, games and more
- Quick Corner® this innovative feature allows you to move any of the four corners of an image independently, to adjust each corner for a perfectly rectangular picture
- Quick, convenient control Instant Off® means no cool-down time required;
 it's ready to shut down when you are
- Copy menu settings for multiple projector installations save on installation time; copy settings via a USB flash drive, USB cable or LAN



1 Color brightness (color light output) measured in accordance with IDMS 15.4. Color brightness will vary depending on usage conditions. The projectors used by a third-party lab for measuring color brightness were leading Epson 3LCD business and education projectors and leading 1-chip DLP projectors, based on NPD sales data for June 2013 through May 2014 and PMA Research sales data for C1 through G3 2013. | 2 Color brightness (color light output) and white brightness (color light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. | 3 Check your owner's manual to determine if a wireless LAN module must be purchased separately to enable wireless connection on your Epson projector. Epson projectors can be networked either through the Ethernet port on the projector (check model specifications for availability) or via a wireless connection. Not all Epson projectors are able to be networked. Availability varies depending on model. | 4 Moderator feature is part of EasyMP Multi-PC Projection software. | 5 Leading 3LCD business and education projectors vs. leading 1-chip DLP projectors, selected according to NPD data as of July 2015. Based on U.S. research conducted by Radius Research. | 6 Color brightness (color light output) measured in accordance with IDMS 15.4. Color brightness were leading Epson 3LCD projectors and leading 1-chip DLP projectors, based on NPD sales data for June 2013 through May 2014 and PMA Research sales data for Q1 through Q3 2013. | 7 Data source: ProjectorCentral.com, Feb. 2015. Average of 1420 shipping models for which the manufacturers provided lumens and total power data, all resolutions and brightness levels. Energy efficiency was measured as wattage per lumen. It was measured for both 3LCD and 1-chip projectors in each of six brightness segments. 3LCD projectors averaged less required electricity per lumen in each of the six segments. | 8 To use Epson iProjection, the projector

Specifications and terms are subject to change without notice. EPSON, EasyMP, Instant Off, Quick Corner and PowerLite are registered trademarks, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future and Epson iProjection are trademarks of Seiko Epson Corporation. BrightLink and PrivateLine are registered trademarks, Pilot is a trademark and Epson Connection is a service mark of Epson America, Inc. iPad, iPhone, iPod, Mac, Mac OS and Macintosh are trademarks of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google Inc. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2016 Epson America, Inc. Com-SS-Oct-13 CPD-52680 8/16

Epson



BrightLink® Interactive Series 575Wi | 585Wi

Specifications

Projection System Epson 3LCD, 3-chip technology Projection Method Front/rear/wall mount/table **Driving Method** Epson Poly-silicon TFT Active Matrix Pixel Number 1,024,000 dots (1280 x 800) x 3

Color Brightness²

(Color Light Output) 575Wi: 2,700 lumens, 585Wi: 3,300 lumens

White Brightness²

(White Light Output) 575Wi: 2,700 lumens, 585Wi: 3,300 lumens

Interactive Color Brightness²

(Color Light Output) 575Wi: 2,700 lumens, 585Wi: 3,300 lumens

Interactive White Brightness²

(White Light Output) 575Wi: 2,700 lumens 585Wi: 3,300 lumens

Aspect Ratio 16:10

Native Resolution 1280 x 800 (WXGA)

Lamp Type¹¹ 575Wi: 215 W UHE, 585Wi: 245 W UHE Lamp Life¹¹ 575Wi: Up to10,000 hours (ECO Mode) Up to 5,000 hours (Normal Mode)

Lamp Life¹¹ 585Wi: Up to 6,000 hours (ECO Mode)

Up to 4,000 hours (Normal Mode)

Size (projected) Area: 4:3 53" - 88' 16:10 60" - 100" 16:9 59" – 97'

Keystone Correction (manual)

Horizontal: ± 3 degrees; Vertical: ± 3 degrees

USB Plug 'n Play

Mac 0S® 10.5/10.6/10.7/10.8/10.9

USB Plug 'n Play for Windows 2000 XP/Windows Vista®/Windows 7/Windows 8

Contrast Ratio Up to 10,000:1

Color Reproduction Up to 1 billion colors

Projection Lens

Type Manual focus F-number 1.80 Focal Length 3.71 mm

Throw Ratio Range (16:10) 0.27 – 0.37, (4:3) 0.33 – 0.44, (16:9) 0.27 – 0.37

Zoom Ratio Digital zoom 1.0 - 1.35x

Display Performance NTSC: 480 lines, PAL: 576 lines (Depends on observation of the multi-burst pattern) Color Modes Input Signal NTSC/NTSC4.43/PAL/M-PAL/N-PAL/PAL60/SECAM

Speaker 16 W monaural

Operating Temperature 41 ° to 95 °F (5 ° to 35 °C) Power Supply Voltage $100 - 240 \text{ V} \pm 10\%$, 50/60 HzPower Consumption 575Wi: 333 W, 585Wi: 376 W

4.3 W standby (Communication On) 0.33 W standby (Communication Off)

Fan Noise 35 dB (Normal Mode), 28 dB (ECO Mode) Security Kensington lock provision, security anchor bar, password protection function

Interactivity

Interactive Technology Infrared, 940 nm

Interactive Area (image size)

575Wi/585Wi: 60" - 100" diagonal (16:10, WXGA) Interactive Modes Computer interactivity/input, Interactive and Whiteboard Modes annotation, Dual user

PC-free Annotation Dual user

Annotation Tools Epson Easy Interactive Tools, dual user PC Annotation Sources USB, HDMI, Computer 1, Computer 2, LAN

PC-free Annotation Devices Document Cameras, DVD/Blu-Ray Disc player, iPod/iPad devices

Calibration Method Automatic or Manual


Interactive Connectivity USB cable for non-networked and LAN

Interactive Software Requirements

Epson Easy Interactive Driver (Mac only) Windows and Linux: no driver required Macintosh®: Mac OS X 10.5/10.6/10.7/10.8/10.9 Epson Easy Interactive Tools for Windows and Macintosh

Interfaces

Wireless LAN Port 802.11 b/g/n



Interactivity (continued)

System Compatibility
Microsoft Windows XP SP2, Windows XP SP3 (Home Edition/ Professional), Windows Vista, Windows Vista SP1, Windows Vista SP2 (All editions except for Starter), Windows 8.x, Windows 7 SP1 (All editions except for Starter), Mac OS X 10.5/10.6/10.7/10.8/10.9

SMART Notebook

Windows: Pentium® 4 processor or better, 2GB of RAM, 2.5GB of free hard disk space for SMART® education software installation (an additional 600MB is required for complete Gallery installation), Windows XP SP3, Windows 7 SP1 or Windows 8 operating system

Macintosh: Intel® Core™ 2 Duo processor or better, 2GB of RAM, 2GB of free hard disk space for SMART education software installation (an additional 600MB is required for complete Gallery installation), Mac OS X 10.7 or 10.8 operating system software

Interactive Input Device

Type of Interactive Input Device Digital pen Interactive Pen Functions Mouse functions (left and right click), Electronic pen, LED battery status indicator Interactive Pen Power AA battery, rechargeable

Compatible Pen Battery Types SANYO Eneloop® HR-3UTG/ HR-UTGA (Eneloop batteries included, Eneloop is registered trademark of Sanyo Electronic Co. Ltd.), Manganese dry cell, alkaline dry cell

Interactive Pen Dimensions 6.4" x 0.94" Interactive Pen Weight 1.1 oz (without battery)

Dimensions (W x D x H)

Excluding feet: 14.5" x 14.8" x 6.1" Weight: 12.1 lb

Remote Control

Features computer, video, USB, LAN, source search, power, aspect, color mode, volume, e-zoom, AV mute, freeze, menu, help, auto, enter, esc, pointer, user

Operating Angle

Rear: Right/left: -55 to +55 degrees, Upper/lower: +75 to +15 degrees Front: Right/left: -30 to +30 degrees, Upper/lower: 0 to +60 degrees **Operating Distance** 19.7 ft (6 m)

Support

The Epson ConnectionSM

Pre-sales support U.S. and Canada 800-463-7766 www.epson.com, www.epson.com/brightlink

Service Programs

2-year projector limited warranty, Epson Road Service program, PrivateLine® dedicated toll-free support and 90-day limited lamp warranty

What's In the Box

A BrightLink 575Wi or 585Wi ultra short-throw interactive projector, projector wall mount, projector template sheet, installation guide, quick user's guide, power cable, USB A/B cable, computer/VGA cable, electronic user manual, interactive driver for Mac, Epson Easy Interactive Tools, Network Management software, projector remote control, two (2) interactive pens, pen tray, two (2) AA batteries (for interactive pens) + battery charger, two (2) AA batteries (for remote), SMART Notebook redemption code

HDMI 2 HDMI 1/MHI

Eco Features

96" whiteboard

Contact:

Energy-efficient 3LCD light engine, RoHS compliant, recyclable product¹², Epson America, Inc. is a SmartWay® Transport Partner¹³

Ordering Information

BrightLink 575Wi	V11H601022
BrightLink 585Wi	V11H600022
Accessories	
Genuine Epson lamp 575Wi:	V13H010L79
585Wi:	V13H010L80
Replacement air filter	V13H134A40
Component video cable HD15/3RCA (male), 3.0 m	ELPKC19
Wall mount	V12H675020
Table projection mount	V12H516020
Wireless microphone	V12H4430M2
External speakers (ELPSP02)	V12H467020
Wireless 802.11b/g/n LAN unit	V12H418P12
Quick wireless USB key	V12H005M09
DC-06 USB document camera	V12H321005
DC-11 document camera	V12H377020
DC-12 document camera	V12H594020
DC-20 document camera	V12H500020
Easy interactive pen A (orange)	V12H666010
Easy interactive pen B (blue)	V12H667010
Replacement pen tips	V12H668010
Interactive pen extension	V12H590001
USB extension cable	V12H525001
PowerLite® Pilot [™] connection and control box	V12H614020
16:10 height adjustable cart for Epson	V12H457008
90" whiteboard	V12H468002

V12H468001

Better Products for a Better Future eco.epson.com



Epson America, Inc. 3840 Kilroy Airport Way, Long Beach, CA 90806 **Epson Canada Limited**

www.epson.com www.epson.ca

185 Renfrew Drive, Markham, Ontario L3R 6G3