

LARGE FORMAT PRINTER SURECOLOR™ SC-F6270/F7270

EPSON
EXCEED YOUR VISION



TWO NEW STANDARDS FOR PERFORMANCE & AFFORDABILITY

The Epson SureColor F-series is the next generation of high-performance dye-sublimation transfer printers. Incorporating advanced printing technology, including Epson's exclusive PrecisionCore™ TFP® printhead and the all-new high-density black ink, the SureColor F-series delivers amazing performance at affordable running costs. The F6270 is designed for sheet production, and is ideal for short-volume dye-sublimation transfer printing of custom clothing, soft signage, merchandise and hard surface work. While the F7270 is designed for roll-based production, and is ideal for short to medium-volume roll-to-roll custom fabric, textile and soft signage.



Up to
64" Wide*



1.5L Ink
Tanks



1 Year
Warranty



Environmentally
Friendly

4 COLOURS		DS EPSON ULTRACHROME DYE SUB INK	MAXIMUM MEDIA WIDTH	MAX. INK CAPACITY PER COLOUR	PRINT SPEEDS** SQM/HR		
					MAX SPEED	PRODUCTION	HIGH QUALITY
	SC-F6270		44"	1.5 L	63.4	22.7	8.3
	SC-F7270		64"		58.9	22.2	8.2



SC-F6270
44" Wide Dye-Sub



SC-F7270
64" Wide Roll-to-Roll Dye-Sub



High capacity
1L ink packs.

ENGINEERED FOR BUSINESS

Remarkable Productivity

Epson's advanced PrecisionCore™ printhead delivers superior print quality, speed and reliability in continuous operations, with minimal downtime.

Affordable Prints with Peace of Mind

Cost-effective 1L ink packs and the new high-density black ink ensure lower ink usage and reduced overall printing costs.

Consistent Vibrant Quality

Epson UltraChrome™ DS ink is specially formulated to produce vibrant colours, intense blacks, sharp contours and smooth gradations.




EPSON ULTRACHROME
DS INK

*Up to 64" wide for F7270, 44" for F6270, **All speed is dependent on RIP used

Model Number	SC-F6270	SC-F7270
Printer Width	44"	64"
Printing Technology		
Print Method	PrecisionCore™ TFP® Printhead	
Nozzle Configuration	360 x 2 nozzles each colour (x4)	
Maximum Resolution	720 x 1440 dpi	
Print Modes	Resolution	Pass
Draft	360 x 720	1
High Speed	720 x 720	2
Production	720 x 720	3
Production	720 x 720	4
High Quality	720 x 720	6
High Quality	720 x 1440	8
Print Speed (m²/h)		
	63.4	58.9
	30.4	30.3
	22.7	22.2
	15.8	16.2
	11.2	11.1
	8.3	8.2
Ink System		
Ink Type	Epson UltraChrome™ DS dye-sublimation ink	
Colours	4 colours - Cyan, Magenta, Yellow, High-Density Black	
Ink Tank Capacity	1500ml	
Ink Pack Capacity	1000ml	
Paper Handling		
Paper Feed Method	Rear roll feed (2" / 3" core with max 150mm diameter)	Rear roll feed (2" / 3" core with max 250mm diameter); Auto take-up reel unit
Media Width	254 to 1118mm	300 to 1625.6mm
Printing Width (Margin)	Max. 1112mm Side Margin: 3mm both sides	Max. 1615.6mm Side Margin: 5mm both sides (10mm when using Media Holding Plates)
Media Thickness	0.08 - 0.50mm (over 75gsm)	0.08 - 1mm (over 75gsm)
Control Panel		
Colour & Size	2.5" Colour LCD	
Connectivity		
Standard	Hi-Speed USB 2.0	
Ethernet	10BASE-T / 100BASE-TX / 1000BASE-T	
Memory		
Main	512MB	
Network	128MB	
Printer Software	Communication Driver, User's Guide, EPSON LFP Remote Panel 2, EpsonNet Setup, EpsonNet Config, EpsonNet Pprint, Wasatch SoftRIP	
Electrical Specifications		
Rated Voltage	AC 100 – 240V	
Rated Frequency	50 – 60Hz	
Power Supply	1.0 - 0.5A	10 - 5A
Power Consumption		
Operating	Approx. 65W	Approx. 460W
Standby	Approx. 20W	Approx. 30W w/ heater OFF
Sleep	Approx. 3W	Approx. 10W
Power Off	Less than 0.4W	Less than 0.6W
Recommended Operating Temperature & Humidity		
	15 - 35°C; 20 - 80% RH (non-condensing)	
Bundled Items		
Ink Supply System and Waste Ink Bottle Kit	C12C932491	-
Substrate Support System and Ink Supply System	-	C12C932471
Initial Ink Pack Set	C12C932111	C12C932111
Optional		
Auto Cutter Blade	C13S902006	-
Media Holding Plate	-	C12C932121
Maintenance Kit	C13S210042	C13S210038
Waste Ink Bottle	C13T724000	C13T724000
Roll Media Adapter	C12C811391	-

Dimensions & Weight
SC-F6270
Weight: 94kg (without ink)



SC-F7270
Weight: 274kg (without ink)



Ink Pack Compatibility

1L Ink Packs

● High Density Black	C13T741X00
● Cyan	C13T741200
● Magenta	C13T741300
● Yellow	C13T741400



Tested for harmful substances
according to Oeko-Tex® Standard 100
N-KEN 12143 Nissenken

©2017 Epson India Pvt. Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited.

EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation.

All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners.

Epson disclaims any and all rights in those marks. Print samples shown herein are simulations. The actual product design and contents may vary. Specifications are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Information correct at time of printing.
Printed in January 2018

EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A, No.1,
Murphy Road, Ulsoor, Bangalore - 560 008.
Tel: 080-30515000 Fax: 080-30515005

Regional Offices:

Ahmedabad - 3314 8500, Chennai - 3967 7500, Cochin - 4012 315,
Coimbatore - 98942 19200, Hyderabad - 6463 9640/41, Kolkata - 6500 9370/77, Mumbai - 3079 8200,
New Delhi - 3312 0300/01, Pune - 3028 6000/05

CONTACT EPSON TODAY! EMAIL: vasu@eid.epson.co.in

SOUTH Alok Singh 098405 03210, Harishankar 098802 85075 **NORTH** Akhtar Imam 099101 08780, Ashutosh Kumar 098153 94550,
Sudhir Kumar 093898 35156 **EAST** Sourov Kumar 098746 72616 **WEST** Milind 098209 74733, Devendra 098509 49453.



Epson Helpline: For product info or service - 1800 425 0011
For service - 1860 3000 1600 (9AM - 6PM) (Mon - Sat)
Email: lfp@epsonindia.in

www.epson.co.in

Dealer's Stamp

