

PROJECTORS &
DOCUMENT CAMERAS
2018 LINE GUIDE



	Budget-friendly Classroom Projectors			Basic Projectors for Small and Medium Rooms	
Note: Highlighted boxes indicate step-ups between models within a series.					
Epson® Model	PowerLite® S39	PowerLite X39	PowerLite W39	PowerLite 1266	PowerLite 1286
Product Code	V11H854020	V11H855020	V11H856020	V11H845120	V11H846120
Replacement Lamp Code	V13H010L96	V13H010L96	V13H010L96	V13H010L96	V13H010L96
Previous Epson Model	PowerLite S27	PowerLite X27	PowerLite W29	PowerLite 1264	PowerLite 1284
Road Service Warranty	2-Year	2-Year	2-Year	2-Year	2-Year
Basics					
Color Brightness (Color Lumens)*	3,300	3,500	3,500	3,600	3,600
White Brightness (White Lumens)*	3,300	3,500	3,500	3,600	3,600
Native Resolution**	SVGA	XGA	WXGA	WXGA	Full HD WUXGA
Weight	6.0 lb	6.0 lb	6.0 lb	6.2 lb	6.2 lb
Dimensions (Inches)†	11.8 x 9.8 x 3.6	11.8 x 9.8 x 3.6	11.8 x 9.8 x 3.6	11.9 x 9.9 x 3.6	11.9 x 9.9 x 3.6
Contrast Ratio (up to)	15,000:1	15,000:1	15,000:1	15,000:1	15,000:1
Throw Ratio	1.45 Wide 1.96 Tele	1.48 Wide 1.77 Tele	1.30 Wide 1.56 Tele	1.38 Wide 1.68 Tele	1.38 Wide 1.68 Tele
Zoom Lens (Ratio)	1.35x Digital	1.2x Optical	1.2x Optical	1.2x Optical	1.2x Optical
Light Source	Lamp	Lamp	Lamp	Lamp	Lamp
Light Source Life Cycle (Normal/ECO [Hours])††	6,000/10,000	6,000/12,000	6,000/12,000	6,000/10,000	6,000/10,000
Power Consumption	326 W	326 W	326 W	315 W	315 W
Value-added Features					
Built-in Speaker	5 W	5 W	5 W	2 W	2 W
Closed Captioning	YES	YES	YES	YES	YES
A/V Mute	Slide Door	Slide Door	Slide Door	Slide Door	Slide Door
Split Screen	YES	YES	YES	YES	YES
Edge Blending	—	—	—	—	—
Curved Surface and Corner Wall	—	—	—	—	—
Scheduling Function	—	—	—	—	—
Easy Connectivity and Setup					
Epson iProjection™ Suite (Moderator, Multi-PC, Device Management)	—	YES	YES	YES	YES
Miracast®	—	—	—	—	YES
USB Plug 'n Play Image/Video	YES	YES	YES	YES	YES
PC-free Presentations via USB-A	Images	Images	Images	Photo, Motion JPEG	Photo, Motion JPEG
Quick Corner® Adjustments	YES	YES	YES	YES	YES
Screen Fit	—	—	—	—	—
Keystone (Horizontal/Vertical)	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto
Easy-Slide Horizontal Keystone Adjustment	YES	YES	YES	YES	YES
Lens Shift (Vertical and Horizontal)	—	—	—	—	—
LAN Networking and Control					
Wired	—	RJ-45 (Content over IP)	RJ-45 (Content over IP)	—	—
Wireless	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Included (802.11 b/g/n) QR Code Quick Connect	Included (802.11 b/g/n) QR Code Quick Connect
Compatible Control Systems	Crestron®, AMX®, Extron®, Control4®	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	—	—
Connections					
HDMI®	HDMI x 1		HDMI x 2	HDMI x 2 (Includes MHL® x 1)	
Analog Connections	VGA x 2, S-video			VGA x 1, S-video Composite Video	
Audio In	RCA (L & R) x 1 Mini Stereo x 2			RCA x 1	
Variable Audio Out	Mini Stereo x 1			Mini Stereo x 1	
USB 2.0 Connectors	Type B x 1, Type A x 1			Type B x 1, Type A x 1	
DisplayPort/DVI-D	—			—	
HDBaseT™	—			—	
SDI	—			—	
Monitor Out	D-sub 15 pin x 1			—	
Serial Control	RS-232c x 1			—	
Recommended Accessory 1	Wireless LAN Module			ES3000 Screen	
Recommended Accessory 1 SKU	V12H731P02			V12H002S3Y	
Recommended Accessory 2	DC-13 Document Camera			Carrying Case	
Recommended Accessory 2 SKU	V12H757020			V12H001K69	

*Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 2118.

**WUXGA (1920 x 1200), WXGA (1280 x 800), XGA (1024 x 768), SVGA (800 x 600).

	Advanced Networking Classroom Projectors				
	Standard Throw				
Note: Highlighted boxes indicate step-ups between models within a series.					
Epson® Model	PowerLite 107	PowerLite 108	PowerLite 109W	PowerLite 970	PowerLite 975W
Product Code	V11H859020	V11H860020	V11H861020	V11H865020	V11H835020
Replacement Lamp Code	V13H010L96	V13H010L96	V13H010L96	V13H010L96	V13H010L95
Previous Epson Model	PowerLite 97H	PowerLite 98H	PowerLite 99WH	PowerLite 965H	PowerLite 935W
Road Service Warranty	2-Year	2-Year	2-Year	2-Year	2-Year
Basics					
Color Brightness (Color Lumens)*	3,500	3,700	4,000	4,000	3,600
White Brightness (White Lumens)*	3,500	3,700	4,000	4,000	3,600
Native Resolution**	XGA	XGA	WXGA	XGA	WXGA
Weight	6.2 lb	6.2 lb	6.2 lb	6.7 lb	9.7 lb
Dimensions (Inches)†	11.6 x 9.7 x 3.5	11.6 x 9.7 x 3.5	11.6 x 9.7 x 3.5	12.1 x 11.5 x 4.1	14.8 x 11.4 x 4.5
Contrast Ratio (up to)	15,000:1	15,000:1	15,000:1	15,000:1	15,000:1
Throw Ratio	1.48 Wide 1.77 Tele	1.48 Wide 1.77 Tele	1.30 Wide 1.56 Tele	1.38 Wide 2.24 Tele	1.38 Wide 2.24 Tele
Zoom Lens (Ratio)	1.2x Optical	1.2x Optical	1.2x Optical	1.6x Optical	1.6x Optical
Light Source	Lamp	Lamp	Lamp	Lamp	Lamp
Light Source Life Cycle (Normal/ECO [Hours])††	6,000/12,000	6,000/12,000	6,000/12,000	6,000/12,000	10,000 (Bright Mode)
Power Consumption	326 W	326 W	326 W	326 W	334 W
Value-added Features					
Built-in Speaker	16 W	16 W	16 W	16 W	16 W
Closed Captioning	YES	YES	YES	YES	YES
A/V Mute	Slide Door	Slide Door	Slide Door	Slide Door	Slide Door
Split Screen	YES	YES	YES	YES	YES
Edge Blending	—	—	—	—	—
Curved Surface and Corner Wall	—	—	—	—	—
Scheduling Function	—	—	—	—	YES
Easy Connectivity and Setup					
Epson iProjection™ Suite (Moderator, Multi-PC, Device Management)	YES	YES	YES	YES	YES
Miracast®	—	—	—	—	YES
USB Plug 'n Play Image/Video	YES	YES	YES	YES	YES
PC-free Presentations via USB-A	Images, PDFs	Images, PDFs	Images, PDFs	Images, PDFs	Images, PDFs
Quick Corner® Adjustments	YES	YES	YES	YES	YES
Screen Fit	—	—	—	—	YES
Keystone (Horizontal/Vertical)	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto
Easy-Slide Horizontal Keystone Adjustment	YES	YES	YES	YES	—
Lens Shift (Vertical and Horizontal)	—	—	—	—	—
LAN Networking and Control					
Wired	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Wireless	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Included (802.11 b/g/n)
Compatible Control Systems	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4
Connections					
HDMI®	HDMI x 2 (Includes MHL x 1)				HDMI x 2 (Includes MHL x 1)
Analog Connections	VGA x 2, S-video				VGA x 2, Composite Video
Audio In	RCA (L & R) x 1 Mini Stereo x 2				RCA (L & R) x 1 Mini Stereo x 2
Variable Audio Out	Mini Stereo x 1				Mini Stereo x 1
USB 2.0 Connectors	Type B x 1, Type A x 1				Type B x 1, Type A x 1
DisplayPort/DVI-D	—				—
HDBaseT™	—				—
SDI	—				—
Monitor Out	D-sub 15 pin x 1				Mini D-sub 15 pin x 1
Serial Control	RS-232c x 1				RS-232c x 1
Recommended Accessory 1	Wireless LAN Module				Universal Projector Mount (ELPMBPJG)
Recommended Accessory 1 SKU	V12H731P02				V12H808001
Recommended Accessory 2	DC-21 Document Camera				DC-21 Document Camera
Recommended Accessory 2 SKU	V12H758020				V12H758020

†Dimensions including feet and standard lens.

††Maximum lamp life will vary depending upon mode selected, environmental conditions, and usage. Brightness decreases over time. Lamps are warranted for 90 days. The PowerLite has a single lamp mode, rated to last up to 10,000 hours.

	Advanced Networking Classroom Projectors Standard Throw (continued)		Advanced Networking Classroom Projectors			
	Short Throw					
Note: Highlighted boxes indicate step-ups between models within a series.						
Epson® Model	PowerLite 980W	PowerLite 990U	PowerLite 520	PowerLite 525W	PowerLite 530	PowerLite 535W
Product Code	V11H866020	V11H867020	V11H674020	V11H672020	V11H673020	V11H671020
Replacement Lamp Code	V13H010L96	V13H010L96	V13H010L87	V13H010L87	V13H010L87	V13H010L87
Previous Epson Model	PowerLite 955WH	—	PowerLite 420	PowerLite 425W	PowerLite 430	PowerLite 435W
Road Service Warranty	2-Year	2-Year	2-Year	2-Year	2-Year	2-Year
Basics						
Color Brightness (Color Lumens)*	3,800	3,800	2,700	2,800	3,200	3,400
White Brightness (White Lumens)*	3,800	3,800	2,700	2,800	3,200	3,400
Native Resolution**	WXGA	Full HD WUXGA	XGA	WXGA	XGA	WXGA
Weight	6.9 lb	7.1 lb	8.2 lb	8.2 lb	8.2 lb	8.2 lb
Dimensions (Inches)†	12.1 x 11.5 x 4.1	12.1 x 11.5 x 4.1	13.5 x 12.5 x 5.2	13.5 x 12.5 x 5.2	13.5 x 12.5 x 5.2	13.5 x 12.5 x 5.2
Contrast Ratio (up to)	15,000:1	15,000:1	16,000:1	16,000:1	16,000:1	16,000:1
Throw Ratio	1.38 Wide 2.24 Tele	1.39 Wide 2.23 Tele	0.55 Wide 0.74 Tele	0.48 Wide 0.65 Tele	0.55 Wide 0.74 Tele	0.48 Wide 0.65 Tele
Zoom Lens (Ratio)	1.6x Optical	1.6x Optical	1.35x Digital	1.35x Digital	1.35x Digital	1.35x Digital
Light Source	Lamp	Lamp	Lamp	Lamp	Lamp	Lamp
Light Source Life Cycle (Normal/ECO [Hours])††	6,000/12,000	6,000/12,000	5,000/10,000	5,000/10,000	5,000/10,000	5,000/10,000
Power Consumption	326 W	326 W	293 W	293 W	315 W	315 W
Value-added Features						
Built-in Speaker	16 W	16 W	16 W	16 W	16 W	16 W
Closed Captioning	YES	YES	YES	YES	YES	YES
A/V Mute	Slide Door	Slide Door	Digital	Digital	Digital	Digital
Split Screen	YES	YES	—	—	—	—
Edge Blending	—	—	—	—	—	—
Curved Surface and Corner Wall	—	—	—	—	—	—
Scheduling Function	—	—	—	—	—	—
Easy Connectivity and Setup						
Epson iProjection™ Suite (Moderator, Multi-PC, Device Management)	YES	YES	YES	YES	YES	YES
Miracast®	—	—	—	—	—	—
USB Plug 'n Play Image/Video	YES	YES	YES	YES	YES	YES
PC-free Presentations via USB-A	Images, PDFs	Images, PDFs	YES	YES	YES	YES
Quick Corner® Adjustments	YES	YES	YES	YES	YES	YES
Screen Fit	—	—	—	—	—	—
Keystone (Horizontal/Vertical)	Manual/Auto	Manual/Auto	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual
Easy-Slide Horizontal Keystone Adjustment	YES	YES	—	—	—	—
Lens Shift (Vertical and Horizontal)	—	—	—	—	—	—
LAN Networking and Control						
Wired	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Wireless	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)
Compatible Control Systems	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron	Crestron, AMX, Extron	Crestron, AMX, Extron	Crestron, AMX, Extron
Connections						
HDMI®	HDMI x 2 (Includes MHL x 1)		HDMI x 1			
Analog Connections	VGA x 2, S-video		VGA x 2, S-video, Composite Video			
Audio In	RCA (L & R) x 1 Mini Stereo x 2		RCA (L & R) x 1 Mini Stereo x 2			
Variable Audio Out	Mini Stereo x 1		Mini Stereo x 1			
USB 2.0 Connectors	Type B x 1, Type A x 1		Type B x 1, Type A x 1			
DisplayPort/DVI-D	—		—			
HDBaseT™	—		—			
SDI	—		—			
Monitor Out	D-sub 15 pin x 1		Mini D-sub 15 pin x 1			
Serial Control	RS-232c x 1		RS-232c x 1			
Recommended Accessory 1	Wireless LAN Module		Short-throw Wall Mount (ELPMB45)			
Recommended Accessory 1 SKU	V12H731P02		V12H706020			
Recommended Accessory 2	DC-21 Document Camera		PowerLite® Pilot™ 3 Connection and Control Box (ELPCB03)			
Recommended Accessory 2 SKU	V12H758020		V12H927020			

	Advanced Networking Classroom Projectors				Short- and Ultra Short-throw Projectors for SMART®		
	Ultra Short Throw						
Note: Highlighted boxes indicate step-ups between models within a series.							
Epson® Model	PowerLite 675W	PowerLite 680	PowerLite 685W	PowerLite 700U for Signage	PowerLite 530 for SMART	PowerLite 680 for SMART	PowerLite 685W for SMART
Product Code	V11H745520	V11H746520	V11H744520	V11H878520	V11H673320	V11H746620	V11H744620
Replacement Lamp Code	V13H010L90	V13H010L91	V13H010L91	Laser	V13H010L87	V13H010L91	V13H010L91
Previous Epson Model	PowerLite 575W	PowerLite 580	PowerLite 585W	—	—	PowerLite 580 for SMART	PowerLite 585W for SMART
Road Service Warranty	2-Year	2-Year	2-Year	3-year	2-Year	2-Year	2-Year
Basics							
Color Brightness (Color Lumens)*	3,200	3,500	3,500	4,000	3,200	3,500	3,500
White Brightness (White Lumens)*	3,200	3,500	3,500	4,000	3,200	3,500	3,500
Native Resolution**	WXGA	XGA	WXGA	Full HD WUXGA	XGA	XGA	WXGA
Weight	12.6 lb	12.6 lb	12.6 lb	24.3 lb	8.2 lb	12.6 lb	12.6 lb
Dimensions (Inches)†	14.5 x 15.8 x 7.4	14.5 x 15.8 x 7.4	14.5 x 15.8 x 7.4	19.5 x 17.2 x 7.4	13.5 x 12.5 x 5.2	14.5 x 15.8 x 7.4	14.5 x 15.8 x 7.4
Contrast Ratio (up to)	14,000:1	14,000:1	14,000:1	2,500,000:1	16,000:1	14,000:1	14,000:1
Throw Ratio	0.28 Wide 0.37 Tele	0.32 Wide 0.43 Tele	0.28 Wide 0.37 Tele	0.27 Wide 0.37 Tele	0.55 Wide 0.74 Tele	0.32 Wide 0.43 Tele	0.28 Wide 0.37 Tele
Zoom Lens (Ratio)	1.35x Digital	1.35x Digital	1.35x Digital	1.35x Digital	1.35x Digital	1.35x Digital	1.35x Digital
Light Source	Lamp	Lamp	Lamp	Laser	Lamp	Lamp	Lamp
Light Source Life Cycle (Normal/ECO [Hours])††	5,000/10,000	5,000/10,000	5,000/10,000	20,000‡	5,000/10,000	5,000/10,000	5,000/10,000
Power Consumption	333 W	373 W	373 W	448 W	315 W	373 W	373 W
Value-added Features							
Built-in Speaker	16 W	16 W	16 W	16 W	16 W	16 W	16 W
Closed Captioning	YES	YES	YES	YES	YES	YES	YES
A/V Mute	Digital	Digital	Digital	Digital	Digital	Digital	Digital
Split Screen	YES	YES	YES	YES	—	YES	YES
Edge Blending	—	—	—	—	—	—	—
Curved Surface and Corner Wall	—	—	—	—	—	—	—
Scheduling Function	—	—	—	Yes	—	—	—
Easy Connectivity and Setup							
Epson iProjection™ Suite (Moderator, Multi-PC, Device Management)	YES	YES	YES	YES	YES	YES	YES
Miracast®	—	—	—	—	—	—	—
USB Plug 'n Play Image/Video	YES	YES	YES	YES	YES	YES	YES
PC-free Presentations via USB-A	YES	YES	YES	YES	YES	YES	YES
Quick Corner® Adjustments	YES	YES	YES	YES	YES	YES	YES
Screen Fit	—	—	—	—	—	—	—
Keystone (Horizontal/Vertical)	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Auto	Manual/Manual	Manual/Manual	Manual/Manual
Easy-Slide Horizontal Keystone Adjustment	—	—	—	—	—	—	—
Lens Shift (Vertical and Horizontal)	—	—	—	—	—	—	—
LAN Networking and Control							
Wired	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Wireless	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)
Compatible Control Systems	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink
Connections							
HDMI®	HDMI x 3 (Includes MHL x 1)			HDMI x 3 (Includes MHL x 1)	HDMI x 1	HDMI x 3 (Includes MHL x 1)	
Analog Connections	VGA x 2, Composite Video			VGA x 1, Composite Video	VGA x 2, S-video, Composite Video	VGA x 2, Composite Video	
Audio In	Mini Stereo x 3			Mini Stereo x 2	RCA (L & R) x 1 Mini Stereo x 2	Mini Stereo x 3	
Variable Audio Out	Mini Stereo x 1			Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	
USB 2.0 Connectors	Type B x 1, Type A x 1			Type B x 1, Type A x 2	Type B x 1, Type A x 1	Type B x 1, Type A x 1	
DisplayPort/DVI-D	—			—	—	—	
HDBaseT™	—			—	—	—	
SDI	—			—	—	—	
Monitor Out	Mini D-sub 15 pin x 1			Mini D-sub 15 pin x 1	Mini D-sub 15 pin x 1	Mini D-sub 15 pin x 1	
Serial Control	RS-232c x 1			RS-232c x 1	RS-232c x 1	RS-232c x 1	
Recommended Accessory 1	Ultra Short-throw Wall Mount (ELPMB46)			Ultra Short-throw Wall Mount (ELPMB53)	Short-throw Wall Mount (ELPMB45)	Ultra Short-throw Wall Mount (ELPMB46)	
Recommended Accessory 1 SKU	V12H777020			V12H902020	V12H706020	V12H777020	
Recommended Accessory 2	PowerLite Pilot 3 Connection and Control Box (ELPCB03)			Replacement Air Filter	DC-21 Document Camera		
Recommended Accessory 2 SKU	V12H927020			V13H134A43	V12H758020		

‡20,000 hours is the estimated projector life when used in Normal Mode. Actual hours may vary depending on mode and usage environment. The projector comes with a 3-year limited warranty.

	Ultra Mobile Projectors – 1700 Series Extra Thin and Light			
Note: Highlighted boxes indicate step-ups between models within a series.				
Epson® Model	PowerLite 1780W	PowerLite 1781W	PowerLite 1785W	PowerLite 1795F
Product Code	V11H795020	V11H794120	V11H793020	V11H796020
Replacement Lamp Code	V13H010L94	V13H010L94	V13H010L94	V13H010L94
Previous Epson Model	PowerLite 1761W	PowerLite 1771W	PowerLite 1776W	–
Road Service Warranty	2-Year	2-Year	2-Year	2-Year
Basics				
Color Brightness (Color Lumens)*	3,000	3,200	3,200	3,200
White Brightness (White Lumens)*	3,000	3,200	3,200	3,200
Native Resolution**	WXGA	WXGA	WXGA	1080p
Weight	4.0 lb	4.0 lb	4.0 lb	4.0 lb
Dimensions (Inches)†	11.5 x 8.4 x 2.1	11.5 x 8.4 x 2.1	11.5 x 8.4 x 2.1	11.5 x 8.4 x 2.1
Contrast Ratio (up to)	10,000:1	10,000:1	10,000:1	10,000:1
Throw Ratio	1.04 Wide 1.26 Tele	1.04 Wide 1.26 Tele	1.04 Wide 1.26 Tele	1.02 Wide 1.23 Tele
Zoom Lens (Ratio)	1.2x Optical	1.2x Optical	1.2x Optical	1.2x Optical
Light Source	Lamp	Lamp	Lamp	Lamp
Light Source Life Cycle (Normal/ECO [Hours])††	4,000/7,000	4,000/7,000	4,000/7,000	4,000/7,000
Power Consumption	290 W	290 W	309 W	309 W
Value-added Features				
Built-in Speaker	1 W	1 W	1 W	1 W
Closed Captioning	YES	YES	YES	YES
A/V Mute	Slide Door	Slide Door	Slide Door	Slide Door
Split Screen	YES	YES	YES	YES
Edge Blending	–	–	–	–
Curved Surface and Corner Wall	–	–	–	–
Scheduling Function	–	–	–	–
Easy Connectivity and Setup				
Epson iProjection™ Suite (Moderator, Multi-PC, Device Management)	YES	YES	YES	YES
Miracast®	–	–	YES	YES
USB Plug 'n Play Image/Video	YES	YES	YES	YES
PC-free Presentations via USB-A	Video, Images	Video, Images	Video, Images, PDF	Video, Images, PDF
Quick Corner® Adjustments	YES	YES	YES	YES
Screen Fit	–	–	YES	YES
Keystone (Horizontal/Vertical)	Manual/Auto	Manual/Auto	Auto/Auto	Auto/Auto
Easy-Slide Horizontal Keystone Adjustment	–	–	–	–
Lens Shift (Vertical and Horizontal)	–	–	–	–
LAN Networking and Control				
Wired	–	–	–	–
Wireless	Included (802.11 b/g/n)	Included (802.11 b/g/n)	Included (802.11 b/g/n)	Included (802.11 b/g/n)
Compatible Control Systems	–	–	–	–
Connections				
HDMI®	HDMI x 1			
Analog Connections	VGA x 1, Composite Video			
Audio In	Mini Stereo x 1			
Variable Audio Out	–			
USB 2.0 Connectors	Type B x 1, Type A x 1			
DisplayPort/DVI-D	–			
HDBaseT™	–			
SDI	–			
Monitor Out	–			
Serial Control	–			
Recommended Accessory 1	ES3000 Screen			
Recommended Accessory 1 SKU	V12H002S3Y			
Recommended Accessory 2	DC-21 Document Camera			
Recommended Accessory 2 SKU	V12H758020			

	Meeting Room and Large Room Projectors – 2000 Series				
Note: Highlighted boxes indicate step-ups between models within a series.					
Epson® Model	PowerLite 2065	PowerLite 2142W	PowerLite 2247U	PowerLite 2250U	PowerLite 2255U
Product Code	V11H820020	V11H875020	V11H881020	V11H871020	V11H815020
Replacement Lamp Code	V13H010L95	V13H010L96	V13H010L96	V13H010L95	V13H010L95
Previous Epson Model	PowerLite 1960/1965	PowerLite 2140W	PowerLite 2245U	PowerLite 1980WU	PowerLite 1985WU
Road Service Warranty	2-Year	2-Year	2-Year	2-Year	2-Year
Basics					
Color Brightness (Color Lumens)*	5,500	4,200	4,200	5,000	5,000
White Brightness (White Lumens)*	5,500	4,200	4,200	5,000	5,000
Native Resolution**	XGA	WXGA	WUXGA	WUXGA	WUXGA
Weight	9.7 lb	6.8 lb	7.1 lb	10.2 lb	10.1 lb
Dimensions (Inches)†	14.9 x 11.5 x 4.6	12.2 x 11.5 x 4.2	14.9 x 11.5 x 5.0	14.9 x 11.5 x 5.0	14.9 x 11.5 x 5.0
Contrast Ratio (up to)	15,000:1	15,000:1	15,000:1	15,000:1	15,000:1
Throw Ratio	1.38 Wide 2.24 Tele	1.38 Wide 2.24 Tele	1.39 Wide 2.23 Tele	1.38 Wide 2.28 Tele	1.57 Wide 2.58 Tele
Zoom Lens (Ratio)	1.0 – 1.6x Optical	1.0 – 1.6x Optical	1.0 – 1.6x Optical	1.0 – 1.6x Optical	1.0 – 1.6x Optical
Light Source	Lamp	Lamp	Lamp	Lamp	Lamp
Light Source Life Cycle (Normal/ECO [Hours])††	5,000/10,000	5,500/12,000	5,500/12,000	5,000/10,000	5,000/10,000
Power Consumption	333 W	350 W	350 W	429 W	429 W
Value-added Features					
Built-in Speaker	16 W	16 W	16 W	16 W	16 W
Closed Captioning	YES	YES	YES	YES	YES
A/V Mute	YES	YES	YES	YES	YES
Split Screen	YES	YES	YES	YES	YES
Edge Blending	–	–	–	–	–
Curved Surface and Corner Wall	–	–	–	–	–
Scheduling Function	YES	YES	YES	YES	YES
Easy Connectivity and Setup					
Epson iProjection™ Suite (Moderator, Multi-PC, Device Management)	YES	YES	YES	YES	YES
Miracast®	–	YES	YES	–	YES
USB Plug 'n Play Image/Video	YES	YES	YES	YES	YES
PC-free Presentations via USB-A	YES	YES	YES	YES	YES
Quick Corner® Adjustments	YES	YES	YES	YES	YES
Screen Fit	–	–	–	–	–
Keystone (Horizontal/Vertical)	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto
Easy-Slide Horizontal Keystone Adjustment	–	Yes	Yes	–	–
Lens Shift (Vertical and Horizontal)	–	–	–	–	–
LAN Networking and Control					
Wired	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Wireless	Included (802.11 b/g/n) QR Code Quick Connect	Included (802.11 b/g/n) QR Code Quick Connect	Included (802.11 b/g/n) QR Code Quick Connect	Optional (802.11 b/g/n)	Included (802.11 b/g/n) QR Code Quick Connect
Compatible Control Systems	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4
Connections					
HDMI®	HDMI x 2 (Includes MHL x 1)				
Analog Connections	VGA x 2, Composite Video				
Audio In	RCA (L & R) x 1, Mini Stereo x 2				
Variable Audio Out	Mini Stereo x 1				
USB 2.0 Connectors	Type B x 1, Type A x 1				
DisplayPort/DVI-D	–				
HDBaseT™	–				
SDI	–				
Monitor Out	Mini D-sub 15 pin x 1				
Serial Control	RS-232c x 1				
Recommended Accessory 1	Universal Projector Mount (ELPMBPJG)				
Recommended Accessory 1 SKU	V12H808001				
Recommended Accessory 2	Replacement Air Filter (ELPAF41)	Replacement Air Filter (ELPAF55)	Replacement Air Filter (ELPAF55)	Wireless LAN Module	Replacement Air Filter (ELPAF41)
Recommended Accessory 2 SKU	V13H134A41	V13H134A55	V13H134A55	V12H731P02	V13H134A41

	PowerLite L Series Laser Projectors for Meeting Rooms and Large Rooms						
Note: Highlighted boxes indicate step-ups between models within a series.							
Epson® Model	PowerLite L400U	PowerLite L500W	PowerLite L510U	PowerLite L610	PowerLite L610W	PowerLite L610U	PowerLite L615U
Product Code	V11H907020	V11H908020	V11H903020	V11H905020	V11H904020	V11H901020	V11H901120
Replacement Lamp Code	Laser	Laser	Laser	Laser	Laser	Laser	Laser
Previous Epson Model	—	—	—	—	—	—	—
Road Service Warranty	3-Year	3-Year	3-Year	3-Year	3-Year	3-Year	3-Year
Basics							
Color Brightness (Color Lumens)*	4,500	5,000	5,000	6,000	6,000	6,000	6,000
White Brightness (White Lumens)*	4,500	5,000	5,000	6,000	6,000	6,000	6,000
Native Resolution**	WUXGA	WXGA	WUXGA	XGA	WXGA	WUXGA	WUXGA
Weight	17.1 lb	16.3 lb	18.7 lb	18.7 lb	18.7 lb	18.7 lb	18.7 lb
Dimensions (Inches)†	17.4 x 12.0 x 5.4	17.4 x 12.0 x 5.4	17.4 x 12.0 x 5.4	17.4 x 12.0 x 5.4	17.4 x 12.0 x 5.4	17.4 x 12.0 x 5.4	17.4 x 12.0 x 5.4
Contrast Ratio (up to)	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1
Throw Ratio	1.35–2.20	1.38–2.24	1.35–2.20	1.52–2.47	1.35–2.20	1.35–2.20	1.35–2.20
Zoom Lens (Ratio)	1.0–1.6x Optical	1.0–1.6x Optical	1.0–1.6x Optical	1.0–1.6x Optical	1.0–1.6x Optical	1.0–1.6x Optical	1.0–1.6x Optical
Light Source	Laser	Laser	Laser	Laser	Laser	Laser	Laser
Light Source Life Cycle (Normal/ECO [Hours])††	20,000 hours‡	20,000 hours‡	20,000 hours‡	20,000 hours‡	20,000 hours‡	20,000 hours‡	20,000 hours‡
Power Consumption	324 W	337 W	337 W	370 W	370 W	370 W	370 W
Value-added Features							
Built-in Speaker	10 W	10 W	10 W	10 W	10 W	10 W	10 W
Closed Captioning	—	—	—	—	—	—	—
A/V Mute	YES	YES	YES	YES	YES	YES	YES
Split Screen	YES	YES	YES	YES	YES	YES	YES
Edge Blending	—	—	—	—	—	—	—
Curved Surface and Corner Wall	—	—	—	—	—	—	—
Scheduling Function	YES	YES	YES	YES	YES	YES	YES
Easy Connectivity and Setup							
Epson iProjection™ Suite (Moderator, Multi-PC, Device Management)	YES	YES	YES	YES	YES	YES	YES
Miracast®	—	—	—	—	—	YES	YES
USB Plug 'n Play Image/Video	YES	YES	YES	YES	YES	YES	YES
PC-free Presentations via USB-A	YES	YES	YES	YES	YES	YES	YES
Quick Corner® Adjustments	YES	YES	YES	YES	YES	YES	YES
Screen Fit	—	—	—	—	—	—	—
Keystone (Horizontal/Vertical)	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto
Easy-Slide Horizontal Keystone Adjustment	—	—	—	—	—	—	—
Lens Shift (Vertical and Horizontal)	—	—	V ±50%, H ±20%	V ±50%, H ±30%	V ±50%, H ±20%	V ±50%, H ±20%	V ±50%, H ±20%
LAN Networking and Control							
Wired	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Wireless	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Included (802.11 b/g/n/a/ac) 2.4 GHz and 5 GHz	Included (802.11 b/g/n/a/ac) 2.4 GHz and 5 GHz
Compatible Control Systems	Crestron, AMX, PJLink, Control4	Crestron, AMX, PJLink, Control4	Crestron, AMX, PJLink, Control4	Crestron, AMX, PJLink, Control4	Crestron, AMX, PJLink, Control4	Crestron, AMX, PJLink, Control4	Crestron, AMX, PJLink, Control4
Connections							
HDMI®	HDMI x 2 (Includes MHL x 1)	HDMI x 2					
Analog Connections	VGA x 2, Composite Video	VGA x 2					
Audio In	RCA (L & R) x 1, Mini Stereo x 2	Mini Stereo x 2					
Variable Audio Out	Mini Stereo x 1						
USB 2.0 Connectors	Type B x 1, Type A x 1						
DisplayPort/DVI-D	—						
HDBaseT™	—	HDBaseT x 1		—	HDBaseT x 1		
SDI	—						
Monitor Out	Mini D-sub 15 pin x 1						
Serial Control	RS-232c x 1						
Recommended Accessory 1	Universal Projector Mount (ELPMBPJG/ELPM3PRH)						
Recommended Accessory 1 SKU	V12H808001/V12H809001						
Recommended Accessory 2	Replacement Air Filter (ELPAF56)	Replacement Air Filter (ELPAF56)	HDBaseT Transmitter	Replacement Air Filter (ELPAF56)	HDBaseT Transmitter	HDBaseT Transmitter	HDBaseT Transmitter
Recommended Accessory 2 SKU	V13H134A56	V13H134A56	V12H547020	V13H134A56	V12H547020	V12H547020	V12H547020

‡20,000 hours is the estimated laser light source life when used in Normal Mode. Actual hours may vary depending on mode and usage environment. The projector has a standard limited warranty of 3 years.

	Large Meeting Room – 5000 Series Basic Installation Projectors		Large Venue Installation – Pro G Series Lamp-based Projectors with Optional Lenses			
Note: Highlighted boxes indicate step-ups between models within a series.						
Epson® Model	PowerLite 5520W	PowerLite 5535U	Pro G7100	Pro G7805	Pro G7000W	Pro G7200W
Product Code	V11H826020	V11H824120	V11H754020	V11H753120	V11H752020	V11H751020
Replacement Lamp Code	V13H010L95	V13H010L95	V13H010L93	V13H010L93	V13H010L93	V13H010L93
Previous Epson Model	PowerLite 4770W	PowerLite 4855WU	Pro G6170	Pro G6870	Pro G6270W	–
Road Service Warranty	2-Year	2-Year	3-Year or 20,000 hours	3-Year or 20,000 hours	3-Year or 20,000 hours	3-Year or 20,000 hours
Basics						
Color Brightness (Color Lumens)*	5,500	5,500	6,500	8,000	6,500	7,500
White Brightness (White Lumens)*	5,500	5,500	6,500	8,000	6,500	7,500
Native Resolution**	WXGA	WUXGA	XGA	XGA	WXGA	WXGA
Weight	15.2 lb	15.2 lb	28.4 lb	28.4 lb	28.4 lb	28.4 lb
Dimensions (Inches)†	18.6 x 13.4 x 6.3	18.5 x 13.9 x 6.2	20.7 x 16.7 x 7.5	20.7 x 16.7 x 7.5	20.7 x 16.7 x 7.5	20.7 x 16.7 x 7.5
Contrast Ratio (up to)	15,000:1	15,000:1	50,000:1	50,000:1	50,000:1	50,000:1
Throw Ratio	1.26 Wide 2.30 Tele	1.26 Wide 2.30 Tele	See Chart for Lens Options			
Zoom Lens (Ratio)	1.0 – 2.0x Optical	1.0–1.8x Optical				
Light Source	Lamp	Lamp	Lamp	Lamp	Lamp	Lamp
Light Source Life Cycle (Normal/ECO [Hours])††	5,000/10,000	5,000/10,000	3,000/4,000 2,000 in Portrait Mode	3,000/4,000 2,000 in Portrait Mode	3,000/4,000 2,000 in Portrait Mode	3,000/4,000 2,000 in Portrait Mode
Power Consumption	462 W	462 W	540 W	601 W	540 W	601 W
Value-added Features						
Built-in Speaker	10 W	10 W	10 W	10 W	10 W	10 W
Closed Captioning	–	–	–	–	–	–
A/V Mute	YES	YES	YES	YES	YES	YES
Split Screen	YES	YES	YES	YES	YES	YES
Edge Blending	–	–	YES	YES	YES	YES
Curved Surface and Corner Wall	–	–	YES	YES	YES	YES
Scheduling Function	YES	YES	YES	YES	YES	YES
Easy Connectivity and Setup						
Epson iProjection™ Suite (Moderator, Multi-PC, Device Management)	YES	YES	YES	YES	YES	YES
Miracast®	YES	YES	–	–	–	–
USB Plug 'n Play Image/Video	YES	YES	–	–	–	–
PC-free Presentations via USB-A	–	–	–	–	–	–
Quick Corner® Adjustments	YES	YES	YES	YES	YES	YES
Screen Fit	–	–	–	–	–	–
Keystone (Horizontal/Vertical)	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Manual	Manual/Manual	Manual/Manual
Easy-Slide Horizontal Keystone Adjustment	–	–	–	–	–	–
Lens Shift (Vertical and Horizontal)	V ±50%, H ±10%	V ±50%, H ±10%	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory
LAN Networking and Control						
Wired	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Wireless	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)
Compatible Control Systems	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4
Connections						
HDMI®	HDMI x 2 (Includes MHL x 1)		HDMI x 1 (HDCP 2.2)			
Analog Connections	VGA x 2, Composite Video		VGA x 1, 5-BNC x 1			
Audio In	RCA (L & R) x 1, Mini Stereo x 2		Mini Stereo x 3			
Variable Audio Out	Mini Stereo x 1		Mini Stereo x 1			
USB 2.0 Connectors	Type B x 1, Type A x 1		Type B x 1 (For Service, Clone), Type A x 1 (For Wireless, FW Update, Clone)			
DisplayPort/DVI-D	–		DVI-D x 1			
HDBaseT™	HDBaseT x 1 (HDCP 2.2)		HDBaseT x 1 (HDCP 2.2)			
SDI	–		–			
Monitor Out	Mini D-sub 15 pin x 1		Mini D-sub 15 pin x 1			
Serial Control	RS-232c x 1		RS-232c x 1			
Recommended Accessory 1	Universal Projector Mount (ELPMBPJG/ELPM3PRH)		HDBaseT Transmitter (ELPHD01)			
Recommended Accessory 1 SKU	V12H808001/V12H809001		V12H547020			
Recommended Accessory 2	HDBaseT Transmitter		Epson Mount for Low Ceiling/High Ceiling			
Recommended Accessory 2 SKU	V12H547020		Low - V12H802010/High - V12H803010			

	Large Venue Installation – Pro G Series Lamp-based Projectors with Optional Lenses (continued)			Large Venue Installation – Pro L Series Laser Projectors with Optional Lenses		
Note: Highlighted boxes indicate step-ups between models within a series.						
Epson® Model	Pro G7400U	Pro G7500U	Pro G7905U	Pro L1100U	Pro L1200U	Pro L1300U
Product Code	V11H762020	V11H750020	V11H749120	V11H735020	V11H734020	V11H733020
Replacement Lamp Code	V13H010L93	V13H010L93	V13H010L93	Laser	Laser	Laser
Previous Epson Model	Pro G6570WU	Pro G6770WU	–	–	–	–
Road Service Warranty	3-Year or 20,000 hours	3-Year or 20,000 hours	3-Year or 20,000 hours	3-Year or 20,000 hours	3-Year or 20,000 hours	3-Year or 20,000 hours
Basics						
Color Brightness (Color Lumens)*	5,500	6,500	7,000	6,000	7,000	8,000
White Brightness (White Lumens)*	5,500	6,500	7,000	6,000	7,000	8,000
Native Resolution**	WUXGA with 4K Enhancement††	WUXGA with 4K Enhancement††	WUXGA with 4K Enhancement††	WUXGA with 4K Enhancement††	WUXGA with 4K Enhancement††	WUXGA with 4K Enhancement††
Weight	28.4 lb	28.4 lb	28.4 lb	44.4 lb	45.4 lb	45.5 lb
Dimensions (Inches)†	20.7 x 16.7 x 7.5	20.7 x 16.7 x 7.5	20.7 x 16.7 x 7.5	23.1 x 19.4 x 8.3	23.1 x 19.4 x 8.3	23.1 x 19.4 x 8.3
Contrast Ratio (up to)	50,000:1	50,000:1	50,000:1	2,500,000:1	2,500,000:1	2,500,000:1
Throw Ratio	See Chart for Lens Options			See Chart for Lens Options		
Zoom Lens (Ratio)						
Light Source	Lamp	Lamp	Lamp	Laser Phosphor	Laser Phosphor	Laser Phosphor
Light Source Life Cycle (Normal/ECO [Hours])††	3,000/4,000 2,000 in Portrait Mode	3,000/4,000 2,000 in Portrait Mode	3,000/4,000 2,000 in Portrait Mode	20,000†††	20,000†††	20,000†††
Power Consumption	498 W	601 W	601 W	479 W	594 W	658 W
Value-added Features						
Built-in Speaker	10 W	10 W	10 W	10 W Mono	10 W Mono	10 W Mono
Closed Captioning	–	–	–	–	–	–
A/V Mute	YES	YES	YES	Digital	Digital	Digital
Split Screen	YES	YES	YES	YES	YES	YES
Edge Blending	YES	YES	YES	YES	YES	YES
Curved Surface and Corner Wall	YES	YES	YES	YES	YES	YES
Scheduling Function	YES	YES	YES	YES	YES	YES
Easy Connectivity and Setup						
Epson iProjection™ Suite (Moderator, Multi-PC, Device Management)	YES	YES	YES	YES	YES	YES
Miracast®	–	–	–	–	–	–
USB Plug 'n Play Image/Video	–	–	–	–	–	–
PC-free Presentations via USB-A	–	–	–	–	–	–
Quick Corner® Adjustments	YES	YES	YES	YES	YES	YES
Screen Fit	–	–	–	–	–	–
Keystone (Horizontal/Vertical)	Manual/Manual	Manual/Manual	Manual/Manual	Auto/Auto	Auto/Auto	Auto/Auto
Easy-Slide Horizontal Keystone Adjustment	–	–	–	–	–	–
Lens Shift (Vertical and Horizontal)	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory
LAN Networking and Control						
Wired	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Wireless	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)
Compatible Control Systems	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4
Connections						
HDMI®	HDMI x 1 (HDCP 2.2)			HDMI x 1 (HDCP 2.2)		
Analog Connections	VGA x 1, 5-BNC x 1			VGA x 1, 5-BNC x 1		
Audio In	Mini Stereo x 3			Mini Stereo x 3		
Variable Audio Out	Mini Stereo x 1			Mini Stereo x 1		
USB 2.0 Connectors	Type B x 1 (For Service, Clone), Type A x 1 (For Wireless, FW Update, Clone)			Type B x 1 (For Service, Clone), Type A x 1 (For Wireless, FW Update, Clone)		
DisplayPort/DVI-D	DVI-D x 1			DVI-D x 1		
HDBaseT™	HDBaseT x 1 (HDCP 2.2)			HDBaseT x 1 (HDCP 2.2)		
SDI	–			–		
Monitor Out	Mini D-sub 15 pin x 1			Mini D-sub 15 pin x 1		
Serial Control	RS-232c x 1			RS-232c x 1		
Recommended Accessory 1	HDBaseT Transmitter (ELPHD01)			HDBaseT Transmitter (ELPHD01)		
Recommended Accessory 1 SKU	V12H547020			V12H547020		
Recommended Accessory 2	Epson Mount for Low Ceiling/High Ceiling			Epson Mount for Low Ceiling/High Ceiling		
Recommended Accessory 2 SKU	Low - V12H802010/High - V12H803010			Low - V12H802010/High - V12H803010		

††4K Enhancement Technology shifts each pixel diagonally by 0.5 pixels to double the resolution and surpass Full HD image quality.

†††20,000 hours is the estimated projector life when used in Normal Mode. Actual hours may vary depending on mode and usage environment. The projector has a limited warranty of 3 years or 20,000 hours, whichever comes first.

	Large Venue Installation – Pro L Series Laser Projectors with Optional Lenses (continued)						
Note: Highlighted boxes indicate step-ups between models within a series.							
Epson® Model	Pro L1405U	Pro L1500UH	Pro L1505UH	Pro L1715SNL	Pro L1750UNL	Pro L1755UNL	Pro L25000U
Product Code	V11H739120	V11H910020	V11H910120	V11H890820	V11H892920	V11H892820	V11H679820
Replacement Lamp Code	Laser	Laser	Laser	Laser	Laser	Laser	Laser
Previous Epson Model	–	Pro L1500U	Pro L1505U	–	–	–	–
Road Service Warranty	3-Year or 20,000 hours	3-Year or 20,000 hours	3-Year or 20,000 hours	3-Year or 20,000 hours	3-Year or 20,000 hours	3-Year or 20,000 hours	3-Year or 20,000 hours
Basics							
Color Brightness (Color Lumens)*	8,000	12,000	12,000	15,000	15,000	15,000	25,000
White Brightness (White Lumens)*	8,000	12,000	12,000	15,000	15,000	15,000	25,000
Native Resolution**	WUXGA with 4K Enhancement††	WUXGA with 4K Enhancement††	WUXGA with 4K Enhancement††	SXGA+	WUXGA with 4K Enhancement††	WUXGA with 4K Enhancement††	WUXGA with 4K Enhancement††
Weight	45.5 lb	52.3 lb	52.3 lb	49.0 lb	49.2 lb	49.2 lb	144.6 lb
Dimensions (Inches)†	23.1 x 19.4 x 8.3	23.1 x 19.4 x 8.3	23.1 x 19.4 x 8.3	23.1 x 19.4 x 8.3	23.1 x 19.4 x 8.3	23.1 x 19.4 x 8.3	36.9 x 14.9 x 33.9
Contrast Ratio (up to)	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1
Throw Ratio	See Chart for Lens Options						
Zoom Lens (Ratio)							
Light Source	Laser Phosphor	Laser Phosphor	Laser Phosphor	Laser Phosphor	Laser Phosphor	Laser Phosphor	Laser Phosphor
Light Source Life Cycle (Normal/ECO [Hours])††	20,000††	20,000††	20,000††	20,000††	20,000††	20,000††	20,000††
Power Consumption	658 W	955 W	955 W	1,082 W	1,082 W	1,082 W	2,390 W
Value-added Features							
Built-in Speaker	–	–	–	–	–	–	–
Closed Captioning	–	–	–	–	–	–	–
A/V Mute	Digital	Digital	Digital	Digital	Digital	Digital	Digital
Split Screen	YES	YES	YES	YES	YES	YES	YES
Edge Blending	YES	YES	YES	YES	YES	YES	YES
Curved Surface and Corner Wall	YES	YES	YES	YES	YES	YES	YES
Scheduling Function	YES	YES	YES	YES	YES	YES	YES
Easy Connectivity and Setup							
Epson iProjection™ Suite (Moderator, Multi-PC, Device Management)	YES	YES	YES	YES	YES	YES	YES
Miracast®	–	–	–	–	–	–	–
USB Plug 'n Play Image/Video	–	–	–	–	–	–	–
PC-free Presentations via USB-A	–	–	–	–	–	–	–
Quick Corner® Adjustments	YES	YES	YES	YES	YES	YES	YES
Screen Fit	–	–	–	–	–	–	–
Keystone (Horizontal/Vertical)	Auto/Auto	Auto/Auto	Auto/Auto	Auto/Auto	Auto/Auto	Auto/Auto	Auto/Auto
Easy-Slide Horizontal Keystone Adjustment	–	–	–	–	–	–	–
Lens Shift (Vertical and Horizontal)	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory
LAN Networking and Control							
Wired	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Wireless	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)
Compatible Control Systems	Creston, AMX, Extron, Control4, Art-Net	Creston, AMX, Extron, Control4, Art-Net	Creston, AMX, Extron, Control4, Art-Net	Creston, AMX, Extron, Control4, Art-Net	Creston, AMX, Extron, Control4, Art-Net	Creston, AMX, Extron, Control4, Art-Net	Creston, AMX, Extron, Control4, Art-Net
Connections							
HDMI®	HDMI x 1 (HDCP 2.2)						
Analog Connections	VGA x 1, 5-BNC x 1						
Audio In	Mini Stereo x 3						–
Variable Audio Out	Mini Stereo x 1						–
USB 2.0 Connectors	Type B x 1 (For Service, Clone), Type A x 1 (For Wireless, FW Update, Clone)						
DisplayPort/DVI-D	DVI-D x 1						
HDBaseT™	HDBaseT x 1 (HDCP 2.2)						
SDI	3G-SDI			–	3G-SDI		
Monitor Out	Mini D-sub 15 pin x 1						
Serial Control	RS-232c x 1						
Recommended Accessory 1	HDBaseT Transmitter (ELPHD01)						
Recommended Accessory 1 SKU	V12H547020						
Recommended Accessory 2	Epson Mount for Low Ceiling/High Ceiling						–
Recommended Accessory 2 SKU	Low - V12H802010/High - V12H803010						–

††4K Enhancement Technology shifts each pixel diagonally by 0.5 pixels to double the resolution and surpass Full HD image quality.

†††20,000 hours is the estimated projector life when used in Normal Mode. Actual hours may vary depending on mode and usage environment. The projector has a limited warranty of 3 years or 20,000 hours, whichever comes first.

	Interactive Projectors – BrightLink Series Projector Specs Only					
Note: Highlighted boxes indicate step-ups between models within a series.						
Epson® Model	BrightLink® 536Wi	BrightLink 685Wi	BrightLink 695Wi	BrightLink 696Ui	BrightLink 697Ui	BrightLink 710Ui
Product Code	V11H670022	V11H741522	V11H740522	V11H728022	V11H823022	V11H877022
Replacement Lamp Code	V13H010L87	V13H010L91	V13H010L91	V13H010L92	V13H010L92	Laser
Previous Epson Model	BrightLink 436Wi	BrightLink 585Wi	BrightLink 595Wi	–	–	–
Road Service Warranty	2-Year	2-Year	2-Year	2-Year	2-Year	3-year
Basics						
Color Brightness (Color Lumens)*	3,400	3,500	3,500	3,800	4,400	4,000
White Brightness (White Lumens)*	3,400	3,500	3,500	3,800	4,400	4,000
Native Resolution**	WXGA	WXGA	WXGA	Full HD WUXGA	Full HD WUXGA	Full HD WUXGA
Weight	8.5 lb	12.8 lb	12.8 lb	18.3 lb	18.7 lb	24.7 lb
Dimensions (Inches)†	13.5 x 12.5 x 5.2	14.5 x 15.8 x 5.9	14.5 x 15.8 x 5.9	18.7 x 17.6 x 5.1	18.7 x 17.6 x 5.1	19.5 x 17.2 x 6.8
Contrast Ratio (up to)	16,000:1	14,000:1	14,000:1	16,000:1	16,000:1	2,500,000:1
Throw Ratio	0.48 Wide 0.65 Tele	0.28 Wide 0.37 Tele	0.28 Wide 0.37 Tele	0.27 Wide 0.37 Tele	0.27 Wide 0.37 Tele	0.27 Wide 0.37 Tele
Zoom Lens (Ratio)	1.35x Digital	1.35x Digital	1.35x Digital	1.35x Digital	1.35x Digital	1.35x Digital
Light Source	Lamp	Lamp	Lamp	Lamp	Lamp	Laser
Light Source Life Cycle (Normal/ECO [Hours])††	5,000/10,000	5,000/10,000	5,000/10,000	5,000/10,000	5,000/10,000	20,000+
Power Consumption	315 W	373 W	373 W	425 W	477 W	448 W
Value-added Features						
Built-in Speaker	16 W	16 W	16 W	16 W	16 W	16 W
Closed Captioning	YES	YES	YES	YES	YES	YES
A/V Mute	Digital	Digital	Digital	Digital	Digital	Digital
Split Screen	–	YES	YES	YES	YES	YES
Edge Blending	–	–	–	–	–	–
Curved Surface and Corner Wall	–	–	–	–	–	–
Scheduling Function	–	–	–	–	YES	–
Easy Connectivity and Setup						
Epson iProjection™ Suite (Moderator, Multi-PC, Device Management)	YES	YES	YES	YES	YES	YES
Miracast®	–	–	–	–	YES	–
USB Plug 'n Play Image/Video	YES	YES	YES	YES	YES	YES
PC-free Presentations via USB-A	YES	YES	YES	YES	YES	YES
Quick Corner® Adjustments	YES	YES	YES	YES	YES	YES
Screen Fit	–	–	–	–	–	–
Keystone (Horizontal/Vertical)	Manual/Auto	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual
Easy-Slide Horizontal Keystone Adjustment	–	–	–	–	–	–
Lens Shift (Vertical and Horizontal)	–	–	–	–	–	–
LAN Networking and Control						
Wired	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Wireless	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Included (802.11 b/g/n) QR Code Quick Connect	Optional (802.11 b/g/n)
Compatible Control Systems	Crestron, AMX, Extron	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink
Connections						
HDMI®	HDMI x 1	HDMI x 3 (Includes MHL x 1)			HDMI x 2 (Includes MHL x 1)	HDMI x 3 (Includes MHL x 1)
Analog Connections	VGA x 2, S-video, Composite Video	VGA x 2, Composite Video		VGA x 1, Composite Video		
Audio In	RCA (L & R) x 1 Mini Stereo x 2	Mini Stereo x 3		Mini Stereo x 2		
Variable Audio Out	Mini Stereo x 1					
USB 2.0 Connectors	Type B x 1, Type A x 1			Type B x 1, Type A x 1 (Memory Stick & Document Camera)		
DisplayPort/DVI-D	–				DVI-D x 1	–
HDBaseT™	–					
SDI	–					
Monitor Out	Mini D-sub 15 pin x 1					
Serial Control	RS-232c x 1					
Recommended Accessory 1	Short-throw Wall Mount (ELPMB27)	Ultra Short-throw Wall Mount (ELPMB46)		Wireless LAN Module	DC-21 Document Camera	Wireless LAN Module
Recommended Accessory 1 SKU	V12H706020	V12H777020		V12H731P02	V12H758020	V12H731P02
Recommended Accessory 2	Wireless LAN Module	100" Whiteboard or Da-Lite® IDEA Screen®				
Recommended Accessory 2 SKU	V12H418P12	V12H831000 or V12H831001				

‡20,000 hours is the estimated projector life when used in Normal Mode. Actual hours may vary depending on mode and usage environment. The projector comes with a 3-year limited warranty.

Interactive Projectors – BrightLink Series Projector Specs Only (continued)			
Note: Highlighted boxes indicate step-ups between models within a series.			
Epson® Model	BrightLink Pro 1450Ui	BrightLink Pro 1460Ui	BrightLink Pro 1470Ui
Product Code	V11H727520	V11H726520	V11H876520
Replacement Lamp Code	V13H010L92	V13H010L92	Laser
Previous Epson Model	BrightLink Pro 1430Wi	—	—
Road Service Warranty	2-Year	2-Year	3-year
Basics			
Color Brightness (Color Lumens)*	3,800	4,400	4,000
White Brightness (White Lumens)*	3,800	4,400	4,000
Native Resolution**	Full HD WUXGA	Full HD WUXGA	Full HD WUXGA
Weight	18.5 lb	18.7 lb	25.1 lb
Dimensions (Inches)†	18.7 x 17.6 x 5.1	18.7 x 17.6 x 5.1	19.5 x 17.2 x 6.8
Contrast Ratio (up to)	16,000:1	16,000:1	2,500,000:1
Throw Ratio	0.27 Wide 0.37 Tele	0.27 Wide 0.37 Tele	0.27 Wide 0.37 Tele
Zoom Lens (Ratio)	1.35x Digital	1.35x Digital	1.35x Digital
Light Source	Lamp	Lamp	Laser
Light Source Life Cycle (Normal/ECO [Hours])††	5,000/10,000	5,000/10,000	20,000†
Power Consumption	425 W	477 W	448 W
Value-added Features			
Built-in Speaker	16 W	16 W	16 W
Closed Captioning	YES	YES	YES
A/V Mute	Digital	Digital	Digital
Split Screen	YES	YES	YES
Edge Blending	—	—	—
Curved Surface and Corner Wall	—	—	—
Scheduling Function	YES	YES	YES
Easy Connectivity and Setup			
Epson iProjection™ Suite (Moderator, Multi-PC, Device Management)	YES	YES	YES
Miracast®	—	YES	YES
USB Plug 'n Play Image/Video	YES	YES	YES
PC-free Presentations via USB-A	YES	YES	YES
Quick Corner® Adjustments	YES	YES	YES
Screen Fit	—	—	—
Keystone (Horizontal/Vertical)	Manual/Manual	Manual/Manual	Manual/Manual
Easy-Slide Horizontal Keystone Adjustment	—	—	—
Lens Shift (Vertical and Horizontal)	—	—	—
LAN Networking and Control			
Wired	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Wireless	Included (802.11 b/g/n) QR Code Quick Connect	Included (802.11 b/g/n) QR Code Quick Connect	Included (802.11 b/g/n)
Compatible Control Systems	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink
Connections			
HDMI®	HDMI x 2 (Includes MHL x 1)		
Analog Connections	VGA x 1, Composite Video		
Audio In	Mini Stereo x 2		
Variable Audio Out	Mini Stereo x 1		
USB 2.0 Connectors	Type B x 1, Type A x 1 (Memory Stick & Document Camera)		
DisplayPort/DVI-D	DVI-D x 1		
HDBaseT™	—		
SDI	—		
Monitor Out	Mini D-sub 15 pin x 1		
Serial Control	RS-232c x 1		
Recommended Accessory 1	All-in-One Whiteboard/Mount System		
Recommended Accessory 1 SKU	V12H8949001		
Recommended Accessory 2	Ultra Short-throw Wall Mount (ELPMB46)		Ultra Short-throw Wall Mount (ELPMB53)
Recommended Accessory 2 SKU	V12H777020		V12H902020



LightScene™ Accent Lighting Laser Projectors

A convergence of lighting and display technology, LightScene laser projectors captivate audiences by simultaneously illuminating and projecting on virtually any surface or material. This groundbreaking solution elevates ordinary spaces into stunning visual environments, unleashing dynamic, experiential content for digital art, spatial design, signage and wayfinding applications.

LightScene Projectors		
Product Code	V11H868020	V11H868120
Product Color	White	Black
Road Service Warranty	3 years or 20,000 hours, whichever comes first	
Color Brightness (Color Lumens)*	2,000	
White Brightness (White Lumens)*	2,000	
Native Resolution	WXGA (1280 x 800)	
Contrast Ratio (Dynamic)	Up to 2,500,000:1	
Light Source Life	20,000 hours**	
Left/Right Up/Down Movement	180 degrees	
Ball-joint Axis Rotation	360 degrees	
Zoom (Powered)	1.58x	
HDMI® SD Card Slot	1x HDMI 1x SD Card Slot	
Variable Audio Out	1x Stereo Mini Out	

*Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118.

**20,000 hours is the estimated projector life when used in Normal Mode. Actual hours may vary depending on mode and usage environment. The projector comes with a 3-year limited warranty.

Note: Highlighted boxes indicate step-ups between models within a series.	Interactive Projectors – BrightLink Series								
	Interactive Specs								
	BrightLink 536Wi	BrightLink 685Wi	BrightLink 695Wi	BrightLink 696Ui	BrightLink 697Ui	BrightLink 710Ui	BrightLink Pro 1450Ui	BrightLink Pro 1460Ui	BrightLink Pro 1470Ui
Interactive Features									
Pens	1 Pen Included, Dual-user Support	2 Pens Included, Dual-user Support	2 Pens Included, Dual-user Support	2 Pens Included, Dual-user Support	2 Pens Included, Dual-user Support	2 Pens Included, Dual-user Support	2 Pens Included, Dual-user Support	2 Pens Included, Dual-user Support	2 Pens Included, Dual-user Support
Pen Technology	IR, 850nm								
Finger Touch	–	–	Yes, up to 6 fingers	Yes, up to 6 fingers	Yes, up to 6 fingers	Yes, up to 6 fingers	Yes, up to 6 fingers	Yes, up to 6 fingers	Yes, up to 6 fingers
Interactive Pen Functions	Mouse Function (Left/Right Click), Digital Pen, LED Battery Status Indicator								
PC-free Whiteboard Sharing	–	–	–	–	YES	–	YES	YES	YES
DuoLink Extended Whiteboard ^o	–	YES	YES	YES	YES	YES	YES	YES	YES
Calibration	Automatic or Manual								
Interactive Image Size (Inches)	53 – 116	60 – 100	60 – 100	70 – 100	70 – 100	70 – 100	70 – 100	70 – 100	70 – 100
Interactive Connectivity	USB or LAN								
PC-free Annotation	YES								
PC-free Digital Whiteboard	1 page	1 page	1 page	1 page	Up to 50 pages	1 page	Up to 50 pages	Up to 50 pages	Up to 50 pages
Wall-mounted Control Panel	–	–	–	–	YES	–	YES	YES	YES
PC-free Save, Email, Print	–	Save, Print	Save, Print	Save, Print	YES	Save, Print	YES	YES	YES
Gestures Support	–	–	Yes, computers require Windows® 7/8/10 or Mac® OS 10.x						
Included Software	Easy Interactive Tools for PC/Mac, Built-in Annotation Toolbar, SMART Learning Suite						Easy Interactive Tools, Built-in Annotation Toolbar		

^oRequires Easy Interactive Driver. Certain functionality is only available through Epson Interactive Tools (EIT) software. For a list of supported operating systems, visit www.epson.com

Lenses Compatible with Pro G7000 Series Projectors and the Pro L1100U, L1200U, L1300U and L1405U										
Model	Ultra Short Lens	Short Lens #1	Short Lens #2	Wide Lens #1	Wide Lens #2	Middle Lens #1	Middle Lens #2	Middle Lens #3	Middle Lens #4	Long Lens
Product Code	V12H004X01	V12H004U03	V12H004U04	V12H004W05	V12H004W06	V12H004M08	V12H004M0F	V12H004M0A	V12H004M0B	V12H004L08
Zoom Ratio	1.0	1.0 – 1.2x	1.0 – 1.2x	1.0 – 1.4x	1.0 – 1.4x	1.0 – 1.6x	1.0 – 1.6x	1.0 – 1.5x	1.0 – 1.5x	1.0 – 1.4x
Throw Ratio (16:10)	0.35	0.65 – 0.78	0.87 – 1.06	1.04 – 1.46	1.63 – 2.22	1.44 – 2.32	2.16 – 3.49	3.33 – 5.06	4.86 – 7.38	7.22 – 10.12

Lenses Compatible with Pro L1500 Series and Pro L1700 Series										
Model	Ultra Short Lens	Short Lens #1	Short Lens #2	Wide Lens #1	Wide Lens #2	Wide Lens #3	Middle Lens #2	Middle Lens #3	Middle Lens #4	Long Lens
Product Code	V12H004X02	V12H004U03	V12H004U04	V12H004W05	V12H004W06	V12H004W08	V12H004M0F	V12H004M0A	V12H004M0B	V12H004L08
Zoom Ratio	1.0	1.0 – 1.2x	1.0 – 1.2x	1.0 – 1.4x	1.0 – 1.37x	1.0 – 1.4x	1.0 – 1.6x	1.0 – 1.5x	1.0 – 1.5x	1.0 – 1.39x
Throw Ratio (16:10)	0.35	0.48 – 0.57	0.64 – 0.77	0.77 – 1.07	1.19 – 1.62	.86 – 1.21	1.57 – 2.56	2.43 – 3.71	3.54 – 5.41	5.27 – 7.41

An essential teaching tool for the modern classroom

Share books, 3D objects, and detailed demonstrations or experiments with your entire class using Epson's easy-to-use document cameras. Record lessons for viewing at a later time, and give your students a more interactive learning experience.

Document Cameras			
			
Model	DC-07	DC-13	DC-21
Product Code	V12H759020	V12H757020	V12H758020
Zoom	8x digital	16x digital	12x optical, 10x digital
Pixel Count	2MP	2MP	2MP
Output Resolution (Max.)	1080p	1080p	1080p
Frame Rate	15 fps	30 fps	30 fps
Connectivity (Output)	USB	USB, VGA, HDMI	USB, VGA, HDMI
Capture Area (Inches)	10.7 x 14.3	11.7 x 20.7	11.7 x 20.7
A/V Recording	YES	YES	YES
Built-in Microphone	YES	YES	YES
Microscope Adapter	–	YES	YES
SD Card Slot ^o	–	YES	YES
Software Included	YES	YES	YES

^oSD card sold separately.

Comprehensive Warranty with Convenient Road Service

Epson projector customers receive first-class service with Epson's standard 2-year limited warranty, including Road Service and a dedicated toll-free support line. Epson laser projectors receive a standard 3-year limited warranty.^o

^oReplacement projectors typically shipped within 24 hours. Actual delivery time may vary. Lamps have a 90-day limited warranty. Pro G and Pro L Series projectors are warranted for 3 years or 20,000 hours, whichever comes first.

Epson Laser Projection Technology

As a world leader in digital 3LCD projection solutions, Epson continues to drive the future of projection technology with its full suite of laser projectors and displays. Featuring lamp-free, long-life, laser light engines, Epson laser solutions achieve new levels of performance and reliability.

Why Choose Laser?

Breakthrough laser technology—long-life laser light engine provides up to 20,000 hours of light source life¹

Outstanding color performance and contrast—get exceptional, true-to-life color reproduction and deep, dark blacks for stunning visuals you can count on for an array of applications

Instant Off®/On—displays and projectors reach maximum brightness and turn off almost immediately, without waiting for the projectors to warm up or cool down

Reliable operation—ideal for applications requiring continuous projection

Explore Epson's Suite of Laser Projectors and Displays				
				
Laser Large-venue Projectors	Laser Interactive Displays	Corporate Laser Projectors	Laser Digital Signage Displays	Accent Lighting Laser Projectors
High-lumen laser projectors designed for exceptional performance in large venues	Full HD, ultra short-throw interactive laser displays for collaborative meetings and learning	High-performance laser projectors offering a variety of brightness, connectivity and resolution	Bold, rich, Full HD laser displays for virtually any signage or presentation need	Project dynamic, experiential content for digital art, commercial signage and décor applications



Epson Business Solutions

Epson is a leading provider of innovative technology solutions that help businesses succeed. We partner with you to best meet your specific needs, focusing on:

- Improved productivity
- World-class customer service and support
- Cost-effective, high-quality solutions
- A commitment to the environment

Discover how Epson can help you work toward the future www.epson.com/forbusiness

Epson America, Inc.
3840 Kilroy Airport Way, Long Beach, CA 90806

www.epson.com
www.epson.com/projectors

¹ Large-venue series: 20,000 hours is the estimated life when the projector is used in Normal Mode in an ordinary environment. Actual hours may vary depending on mode and usage environment. The projector has a limited warranty of 3 years or 20,000 hours, whichever comes first; Interactive, Digital Signage and Accent Lighting projectors: 20,000 hours is the estimated projector life when used in Normal Mode. Actual hours may vary depending on mode and usage environment. The projector comes with a 3-year limited warranty; Corporate series: 20,000 hours is the estimated laser light source life when used in Normal Mode. Actual hours may vary depending on mode and usage environment. The projector has a standard limited warranty of 3 years.

Specifications and terms are subject to change without notice. EPSON, PowerLite, Instant Off and Quick Corner are registered trademarks, EPSON Exceed Your Vision is a registered logomark and Epson iProjection and LightScene are trademarks of Seiko Epson Corporation. BrightLink is a registered trademark and Pilot is a trademark of Epson America, Inc. Mac is a trademark of Apple Inc., registered in the U.S. and other countries. Windows is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries. Miracast® is a registered trademark of Wi-Fi Alliance®. Da-Lite and IDEA Screen are registered trademarks of Milestone AV Technologies. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2018 Epson America, Inc. Com-LG-Oct-13 CPD-56524 8/18