

SPECIFICATION SHEET

 $(\blacklozenge$

EB-PQ2010B

10,000-Lumen 4K 3LCD Laser Projector



The world's smallest and lightest 10,000-lumen 4K projector¹.





The world's smallest and lightest 10,000-lumen 4K projector¹: produces incredibly bright images with a light, compact and energy efficient design

Incredible color: Epson 3-chip 3LCD technology produces 10,000 lumens of equal white and color brightness²

4K resolution on-screen: leverages Epson's 4K Crystal Motion technology, thermo-controlled panel and double micro-lens array for crystal clear image quality that fully realizes 4K resolution (3840 x 2160)

Low-maintenance design: virtually maintenance-free 20,000-hour laser light source and air filter³; optional external air filter is available for high-dust environments

Stunning image quality: high native contrast ratio for deep blacks; 50% improvement over the already high contrast ratio found with the current Epson EB-PU Series; frame interpolation for fast moving objects; HDR support⁴ and scene adaptive gamma correction

Simplified installation: 10 optional powered lenses (sold separately) including ultra short throw 0,35 throw lens with a unique zero offset design for installation flexibility; projector compatible with existing Epson lens family

Enhanced connectivity: HDMI[®] two in and one out; 12G-SDI in/out for daisy chaining and signal monitoring; features automatic input switching when input signal is disrupted

Low latency performance and high frame rate support: high-speed graphics chip and panel drive technology enable high frame rate 4K playback

Optional attachable PixAlign™ external camera: access powerful automated tools including edge blending assist⁵, stacking assist function⁵, auto color calibration⁶ and screen matching⁶ with or without a connected PC and router

Efficient setup and management: control multiple projectors in a single, large space with Epson Projector Professional Tool (EPPT app)⁷; easily manage your installed inventory using Epson Projector Management – Connected (EPM-C)⁸ from any device with a Web browser



۲

EPSON

Specifications

Projection System High-aperture Epson 3-chip 3LCD technology Projection Method Front/rear/ceiling mount Driving Method Poly-Silicon TFT Active Matrix Pixel Number 2,073,600 pixels (1920 x 1080) x 3 chips Signal Input Maximum Display Resolution: 4096 x 2160 pixels (resizing display) Native Resolution 1080p with 4K Crystal Motion (1920 x 1080 x 4) Resolution on Screen 4K UHD (3840 x 2160) Aspect Ratio Supports 4:3, 16:10, 16:9*, 21:9* *With vertical image shift control within letterbox area. Pixel Arrangement Cross stripe Color Brightness² Color Light Output: 10,000 lumens White Brightness² White Light Output: 10,000 lumens Contrast Ratio Up to 5,000,000:1 (Dynamic Contrast: On) Brightness Uniformity (Typical) 85% Color Reproduction Up to 1.07 billion colors **Keystone Correction** Vertical: +45 degrees: Horizontal: ±30 degrees Illumination Technology Laser Phosphor

Light Source Life³ 20,000 hours (Normal Mode) 30,000 hours (Extended Mode)

Projection Lens (Standard)

Visit www.epson.com for information on optional lenses. Standard Lens ELPLM15 (sold separately) Tvne Powered shift/focus/zoom F-Number 1.8 - 2.3 Focal Length 36.0 mm - 57.3 mm Zoom Ratio Optical Zoom: 1.0 - 1.6 Throw Ratio Range 1.52 - 2.47 Lens Shift Vertical: ±64%; Horizontal: ±16%

Other Features

Operating Temperature 32 °F to 122 °F (0 °C to 50 °C) Power Supply Voltage 100 V - 240 V ±10%, 50/60 Hz AC Power Consumption 640 W (Normal/Custom) 501 W (Quiet/Extended) 2.0 W Standby (Network Standby) 0.5 W Standby (Energy Saving) Fan Noise 39 dB (Normal Mode), 29 dB (Eco Mode) Security Security cable hole, lens lock, Kensington® lock provision, wireless LAN unit lock

Interfaces

12G-SDI In/Out HDMI (HDCP 2.3) x 2/HDMI Out x 1 HDBaseT x 1 Variable Audio Out: Mini Stereo x 1 USB Type-A for Wireless LAN (optional) USB Connector Type-B x 1 Serial: RS-232c x 1 Remote Stereo Mini Network: RJ-45



 $(\mathbf{\bullet})$

SPECIFICATION SHEET

EB-PQ2010B

V11HB02820

 (\blacklozenge)

Video I/O

Input Signal Input Video Signal (HDMI and HDBaseT[®] ports) 480i/480p/576i/576p/720p/1080i/1080p/3840 x 2160/ 4096 x 2160 Max PC Graphics: 2560 x 1600/3440 x 1440"

Auto Power On Signal Detection on HDMI/Plug-In Detection

(HDMI) Sleep Mode Yes (with timer) HDMI CEC Control Yes

Dimensions (W x D x H)

Excluding Feet 21.5" x 17.2" x 6.5" (545 mm x 436 mm x 164 mm) Weight 41.4 lb (18.8 kg)

Remote Control

Features Power, Source Search Selection, Lens Shift, Zoom, Focus, Test Pattern Selection. Shutter, Freeze, ID, Color Mode, Number E-Zoom, Volume, Menu, Enter, ESC, Pointer Functions, Blend Guides, Multi-Projection, Color Tone Adjust and Memory **Operating Angle**

Angle Front: Right/Left: 60 to +60; Upper/Lower: +30 to 20 degrees Angle Rear: Right/Left: 30 to +30; Upper/Lower: +50 to +10 degrees **Operating Distance** 98 ft

Eco Features

RoHS compliant

Limited Warranty and Service

Warranty The projector has a 2-year limited warranty and an additional year by registering the product9. Service Toll-free telephone support, Monday through Friday Epson Connection^{sn} Website: latin.epson.com Other extended service plans may be available.

What's Included

EB-PQ2010B projector, power cable, remote control with 2 batteries, cable cover, lens connector cap, quick reference guide and warranty sheet

Ordering Information EB-PQ2010B

Air Filter (ELPAF46)	V13H134A46
External Air Filter (ELPAF63)	V13H134AD0
Ultra Short Throw Lens (ELPLX02S)	V12H004X0B
Short Throw #1 Zoom Lens (ELPLU03S)	V12H004UA3
Short Throw #2 Zoom Lens (ELPLU04)	V12H004U04
Wide Throw #1 Zoom Lens (ELPLW05)	V12H004W05
Wide Throw #3 Zoom Lens (ELPLW08)	V12H004W08
Wide Throw #2 Zoom Lens (ELPLW06)	V12H004W06
Middle Throw #2 Zoom Lens (ELPLM15)	V12H004M0F
Middle Throw #3 Zoom Lens (ELPLM10)	V12H004M0A
Middle Throw #4 Zoom Lens (ELPLM11)	V12H004M0B
Long Throw Zoom Lens (ELPLL08)	V12H004L08
Wireless LAN Module (ELPAP11)	V12H005A02
PixAlign Camera (ELPEC01)	V12HA46010

1 Comparison based on 4K projectors rated at 10,000 lumens. Lumens, resolution, size and weight based on the manufacturers' online specifications and industry-available data as of October 2023. | 2 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. | 3 No required maintenance for the light source and filter for up to 20,000 hours (Normal Mode), 30,000 hours (Extended Mode). Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m³ of particulate matter. Time varies depending on usage, 14 HDR performance available with select third-party devices. For more information, see www.epson.com/hdrcompatibility | 5 Requires Epson external camera for each projector and may require Epson Projector Professional Tool app. | 6 Using separate camera for each projector.] 7 Mac[®] and PC only.] 8 Requires one on-site PC with Epson Projector Connected Agent installed. | 9 This Epson product is covered by a limited warranty of 2 years from the date of purchase, that is, from the date of issuance of the purchase invoice to the original purchase. To be eligible for Epson's 3-year Extended Limited Warranty (1 additional year), you must register your product at latin.epson.com/garantia within 30 days of your purchase date, i.e. from the date of the original purchase invoice.

See the latest innovations from Epson Business Solutions at latin.epson.com

www.latin.epson.com Contact: En Latinoamérica llamar a la oficina local o a tu distribuidor autorizado. Subsidiarias Epson: Epson Argentina S.R.L. Epson Bolivia Epson Centroamérica Epson Chile S.A. Epson Colombia Ltda. Epson México S.A. de C.V. Epson Perú S.A. (0800) 288 37766 (800) 100 116 (506) 2588 7800 (552) 2484 3400 (571) 602 4750 (525) 1323 2000 (511) 418 0210

Specifications and terms are subject to change without notice. EPSON is a registered trademark of Seiko Epson Corporation. PixAlign, Epson Connection and Epson Preferred are trademarks of Epson America, Inc. Mac is a trademark of Apple Inc., registered in the U.S. and other countries. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2024 Epson America, Inc. CPD-64127R1 2/24