

EPSON[®]
EXCEED YOUR VISION

PROJECTORS &
DOCUMENT CAMERAS
2018 LINE GUIDE



Meeting Room and Large Room Projectors – 2000 Series

Note: Highlighted boxes indicate step-ups between models within a series.						
Epson® Model	PowerLite® 2042	PowerLite 2065	PowerLite 2142W	PowerLite 2155W	PowerLite 2165W	PowerLite 2247U
Product Code	V11H874020	V11H820020	V11H875020	V11H818020	V11H817020	V11H881020
Replacement Lamp Code	V13H010L96	V13H010L95	V13H010L96	V13H010L95	V13H010L95	V13H010L96
Previous Epson Model	PowerLite 2040	PowerLite 1960/1965	PowerLite 2140W	PowerLite 1945W	PowerLite 1975W	PowerLite 2245U
Road Service Warranty	2-Year	2-Year	2-Year	2-Year	2-Year	2-Year
Basics						
Color Brightness (Color Lumens)*	4,400	5,500	4,200	5,000	5,500	4,200
White Brightness (White Lumens)*	4,400	5,500	4,200	5,000	5,500	4,200
Native Resolution**	XGA	XGA	WXGA	WXGA	WXGA	Full HD WUXGA
Weight	6.7 lb	9.7 lb	6.8 lb	9.5 lb	10.2 lb	7.1 lb
Dimensions (Inches)†	12.2 x 11.5 x 4.2	14.9 x 11.5 x 4.6	12.2 x 11.5 x 4.2	14.9 x 11.5 x 4.6	14.9 x 11.5 x 5.0	14.9 x 11.5 x 5.0
Contrast Ratio (up to)	15,000:1	15,000:1	15,000:1	15,000:1	15,000:1	15,000:1
Throw Ratio	1.38 Wide 2.24 Tele	1.38 Wide 2.24 Tele	1.38 Wide 2.24 Tele	1.38 Wide 2.24 Tele	1.38 Wide 2.24 Tele	1.39 Wide 2.23 Tele
Zoom Lens (Ratio)	1.0 – 1.2x Optical	1.0 – 1.6x Optical	1.0 – 1.6x Optical	1.0 – 1.6x Optical	1.0 – 1.6x Optical	1.0 – 1.6x Optical
Light Source	Lamp	Lamp	Lamp	Lamp	Lamp	Lamp
Light Source Life Cycle (Normal/ECO [Hours])††	5,500/12,000	5,000/10,000	5,500/12,000	5,000/10,000	5,000/10,000	5,500/12,000
Power Consumption	331 W	333 W	350 W	429 W	450 W	350 W
Value-added Features						
Built-in Speaker	16 W	16 W	16 W	16 W	16 W	16 W
Closed Captioning	YES	YES	YES	YES	YES	YES
A/V Mute	YES	YES	YES	YES	YES	YES
Split Screen	YES	YES	YES	YES	YES	YES
Edge Blending	–	–	–	–	–	–
Curved Surface and Corner Wall	–	–	–	–	–	–
Scheduling Function	–	YES	YES	YES	YES	YES
Easy Connectivity & Setup						
Epson iProjection™ Suite (Moderator, Multi-PC, Device Management)	YES	YES	YES	YES	YES	YES
Miracast®	–	YES	YES	–	YES	–
USB Plug 'n Play Image/Video	YES	YES	YES	YES	YES	YES
PC-free Presentations via USB-A	YES	YES	YES	YES	YES	YES
Quick Corner® Adjustments	YES	YES	YES	YES	YES	YES
Screen Fit	–	–	–	–	–	–
Keystone (Horizontal/Vertical)	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto
Easy-Slide Horizontal Keystone Adjustment	Yes	–	Yes	–	–	Yes
Lens Shift (Vertical & Horizontal)	–	–	–	–	–	–
LAN Networking & Control						
Wired	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Wireless	Optional (802.11 b/g/n)	Included (802.11 b/g/n) QR Code Quick Connect	Included (802.11 b/g/n) QR Code Quick Connect	Included (802.11 b/g/n) QR Code Quick Connect	Included (802.11 b/g/n) QR Code Quick Connect	Included (802.11 b/g/n) QR Code Quick Connect
Compatible Control Systems	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4
Connections						
HDMI®						HDMI x 2 (Includes MHL x 1)
Analog Connections						VGA x 2, Composite Video
Audio In						RCA (L & R) x 1, Mini Stereo x 2
Variable Audio Out						Mini Stereo x 1
USB 2.0 Connectors						Type B x 1, Type A x 1
DisplayPort/DVI-D						–
HDBaseT™						HDBaseT x 1 (HDCP 2.2)
SDI						–
Monitor Out						Mini D-sub 15 pin x 1
Serial Control						RS-232c x 1
Recommended Accessory 1						Universal Projector Mount (ELPMBPJG)
Recommended Accessory 1 SKU						V12H808001
Recommended Accessory 2	Replacement Air Filter (ELPAF55)	Replacement Air Filter (ELPAF41)	Replacement Air Filter (ELPAF55)	Replacement Air Filter (ELPAF41)	HDBaseT Transmitter (ELPAF55)	Replacement Air Filter (ELPAF55)
Recommended Accessory 2 SKU	V13H134A55	V13H134A41	V13H134A55	V13H134A41	V12H547020	V13H134A55



*Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118.

**WUXGA (1920 x 1200), WXGA (1280 x 800), XGA (1024 x 768), SVGA (800 x 600).

			Large Meeting Room – 5000 Series Basic Installation Projectors					
								
PowerLite 2250U	PowerLite 2255U	PowerLite 2265U	PowerLite 5510	PowerLite 5520W	PowerLite 5530U	PowerLite 5535U	Pro G7100	Pro G7805
V11H871020	V11H815020	V11H814020	V11H828020	V11H826020	V11H824020	V11H824120	V11H754020	V11H753120
V13H010L95	V13H010L95	V13H010L95	V13H010L95	V13H010L95	V13H010L95	V13H010L95	V13H010L93	V13H010L93
PowerLite 1980WU	PowerLite 1985WU	–	PowerLite 4650	PowerLite 4770W	–	PowerLite 4855WU	Pro G6170	Pro G6870
2-Year	2-Year	2-Year	2-Year	2-Year	2-Year	2-Year	3-Year or 20,000 hours	3-Year or 20,000 hours
5,000	5,000	5,500	5,500	5,500	5,500	5,500	6,500	8,000
5,000	5,000	5,500	5,500	5,500	5,500	5,500	6,500	8,000
Full HD WUXGA	Full HD WUXGA	Full HD WUXGA	XGA	WXGA	Full HD WUXGA	Full HD WUXGA	XGA	XGA
10.2 lb	10.1 lb	10.4 lb	15.2 lb	15.2 lb	15.2 lb	15.2 lb	28.4 lb	28.4 lb
14.9 x 11.5 x 5.0	14.9 x 11.5 x 5.0	14.9 x 11.5 x 5.0	18.5 x 13.9 x 6.2	18.6 x 13.4 x 6.3	18.5 x 13.9 x 6.2	18.5 x 13.9 x 6.2	19.9 x 16.0 x 6.8	19.9 x 16.0 x 6.8
15,000:1	15,000:1	15,000:1	15,000:1	15,000:1	15,000:1	15,000:1	50,000:1	50,000:1
1.38 Wide 2.28 Tele	1.57 Wide 2.58 Tele	1.38 Wide 2.28 Tele	1.27 Wide 2.59 Tele	1.26 Wide 2.30 Tele	1.26 Wide 2.30 Tele	1.26 Wide 2.30 Tele		
1.0 – 1.6x Optical	1.0 – 1.6x Optical	1.0 – 1.6x Optical	1.0 – 1.6x Optical	1.0 – 2.0x Optical	1.0 – 1.8x Optical	1.0 – 1.8x Optical		
Lamp	Lamp	Lamp	Lamp	Lamp	Lamp	Lamp	Lamp	Lamp
5,000/10,000	5,000/10,000	5,000/10,000	5,000/10,000	5,000/10,000	5,000/10,000	5,000/10,000	3,000/4,000 2,000 in Portrait Mode	3,000/4,000 2,000 in Portrait Mode
429 W	429 W	450 W	462 W	462 W	462 W	462 W	540 W	601 W
16 W	16 W	16 W	10 W	10 W	10 W	10 W	10 W	10 W
YES	YES	YES	–	–	–	–	–	–
YES	YES	YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES	YES	YES
–	–	–	–	–	–	–	YES	YES
–	–	–	–	–	–	–	YES	YES
YES	YES	YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES	YES	YES
–	–	–	–	–	–	–	–	–
–	–	–	–	–	–	–	–	–
Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Manual
–	–	–	–	–	–	–	–	–
–	–	–	V ±58%, H ±38%	V ±50%, H ±10%	V ±50%, H ±10%	V ±50%, H ±10%	V ±50%, H ±10%	Powered with Lens Memory
RJ-45 (Content over IP)	RJ-45 (Content over IP)	–	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Optional (802.11 b/g/n)	Included (802.11 b/g/n) QR Code Quick Connect	Included (802.11 b/g/n) QR Code Quick Connect	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)
Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4
			HDMI x 2 (Includes MHL x 1)					
			VGA x 2, Composite Video					
			RCA (L & R) x 1, Mini Stereo x 2					
			Mini Stereo x 1					
			Type B x 1, Type A x 1					
			–					
			HDBaseT x 1 (HDCP 2.2)					
			–					
			Mini D-sub 15 pin x 1					
			RS-232c x 1					
			Universal Projector Mount (ELPMBPJG)					
			V12H808001					
Wireless LAN Module	Replacement Air Filter (ELPAF41)	HDBaseT Transmitter	Wireless LAN Module	HDBaseT Transmitter				
V12H731P02	V13H134A41	V12H547020	V12H731P02	V12H547020				




†Dimensions including feet and standard lens.

††Maximum lamp life will vary depending upon mode selected, environmental conditions, and usage. Brightness decreases over time.

Large Venue Installation – Pro G Series Lamp-based Projectors with Optional Lenses							
							
Pro G7000W	Pro G7200W	Pro G7400U	Pro G7500U	Pro G7905U	Pro L1100U	Pro L1200U	Pro L1300U
V11H752020	V11H751020	V11H762020	V11H750020	V11H749120	V11H735020	V11H734020	V11H733020
V13H010L93	V13H010L93	V13H010L93	V13H010L93	V13H010L93	–	–	–
Pro G6270W	–	Pro G6570WU	Pro G6770WU	–	–	–	–
3-Year or 20,000 hours	3-Year or 20,000 hours	3-Year or 20,000 hours	3-Year or 20,000 hours	3-Year or 20,000 hours	3-Year or 20,000 hours	3-Year or 20,000 hours	3-Year or 20,000 hours
6,500	7,500	5,500	6,500	7,000	6,000	7,000	8,000
6,500	7,500	5,500	6,500	7,000	6,000	7,000	8,000
WXGA	WXGA	WUXGA with 4K Enhancement ^{††}	WUXGA with 4K Enhancement ^{††}	WUXGA with 4K Enhancement ^{††}	WUXGA with 4K Enhancement ^{††}	WUXGA with 4K Enhancement ^{††}	WUXGA with 4K Enhancement ^{††}
28.4 lb	28.4 lb	28.4 lb	28.4 lb	28.4 lb	44.4 lb	45.4 lb	45.5 lb
19.9 x 16.0 x 6.8	19.9 x 16.0 x 6.8	19.9 x 16.0 x 6.8	19.9 x 16.0 x 6.8	19.9 x 16.0 x 6.8	23.1 x 19.4 x 8.3	23.1 x 19.4 x 8.3	23.1 x 19.4 x 8.3
50,000:1	50,000:1	50,000:1	50,000:1	50,000:1	2,500,000:1	2,500,000:1	2,500,000:1
See Pro G Chart for Lens Options							
Lamp	Lamp	Lamp	Lamp	Lamp	Laser Phosphor	Laser Phosphor	Laser Phosphor
3,000/4,000 2,000 in Portrait Mode	3,000/4,000 2,000 in Portrait Mode	3,000/4,000 2,000 in Portrait Mode	3,000/4,000 2,000 in Portrait Mode	3,000/4,000 2,000 in Portrait Mode	20,000 ^{†††}	20,000 ^{†††}	20,000 ^{†††}
540 W	601 W	498 W	601 W	601 W	479 W	594 W	658 W
10 W	10 W	10 W	10 W	10 W	10 W Mono	10 W Mono	10 W Mono
–	–	–	–	–	–	–	–
YES	YES	YES	YES	YES	Digital	Digital	Digital
YES	YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES	YES
–	–	–	–	–	–	–	–
Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Auto/Auto	Auto/Auto	Auto/Auto
–	–	–	–	–	–	–	–
Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)
Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4
HDMI x 1 (HDCP 2.2)							
VGA x 1, 5-BNC x 1							
Mini Stereo x 3							
Mini Stereo x 1							
Type B x 1 (For Service, Clone), Type A x 1 (For Wireless, FW Update, Clone)							
DVI-D x 1							
HDBaseT x 1 (HDCP 2.2)							
–							
Mini D-sub 15 pin x 1							
RS-232c x 1							
HDBaseT Transmitter							
V12H547020							
Epson Mount for Low Ceiling/High Ceiling							
Low - V12H802010/High - V12H803010							






†† 4K Enhancement Technology shifts each pixel diagonally by 0.5 pixels to double the resolution and surpass Full HD image quality.

**Large Venue Installation – Pro L Series
Laser Projectors with Optional Lenses**

								
Pro L1405U	Pro L1500UH	Pro L1505UH	Pro L1715SNL	Pro L1750UNL	Pro L1755UNL	Pro L25000U	BrightLink® 536Wi	
V11H739120	V11H7910020	V11H7910120	V11H890820	V11H892920	V11H892820	V11H679820	V11H670022	
–	–	–	–	–	–	–	V13H010L87	
–	Pro L1500U	Pro L1505U	–	–	–	–	BrightLink 436Wi	
3-Year or 20,000 hours	3-Year or 20,000 hours	3-Year or 20,000 hours	3-Year or 20,000 hours	3-Year or 20,000 hours	3-Year or 20,000 hours	3-Year or 20,000 hours	2-Year	
8,000	12,000	12,000	15,000	15,000	15,000	25,000	3,400	
8,000	12,000	12,000	15,000	15,000	15,000	25,000	3,400	
WUXGA with 4K Enhancement**	WUXGA with 4K Enhancement**	WUXGA with 4K Enhancement**	SXGA+	WUXGA with 4K Enhancement**	WUXGA with 4K Enhancement**	WUXGA with 4K Enhancement**	WXGA	
45.5 lb	52.3 lb	52.3 lb	49.0 lb	49.2 lb	49.2 lb	144.6 lb	8.5 lb	
23.1 x 19.4 x 8.3	23.1 x 19.4 x 8.3	23.1 x 19.4 x 8.3	23.1 x 19.4 x 8.3	23.1 x 19.4 x 8.3	23.1 x 19.4 x 8.3	36.9 x 14.9 x 33.9	13.5 x 12.5 x 5.2	
2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	16,000:1	
See Pro L Chart for Lens Options							8 Lens Options	0.48 Wide 0.65 Tele 1.35x Digital Lamp
Laser Phosphor	Laser Phosphor	Laser Phosphor	Laser Phosphor	Laser Phosphor	Laser Phosphor	Laser Phosphor	Laser Phosphor	
20,000**	20,000**	20,000**	20,000**	20,000**	20,000**	20,000**	20,000**	
658 W	955 W	955 W	1,082 W	1,082 W	1,082 W	2,390 W	5,000/10,000	
–	–	–	–	–	–	–	315 W	
–	–	–	–	–	–	–	16 W	
–	–	–	–	–	–	–	YES	
Digital	Digital	Digital	Digital	Digital	Digital	Digital	Digital	
YES	YES	YES	YES	YES	YES	YES	YES	
YES	YES	YES	YES	YES	YES	YES	–	
YES	YES	YES	YES	YES	YES	YES	–	
YES	YES	YES	YES	YES	YES	YES	–	
YES	YES	YES	YES	YES	YES	YES	–	
YES	YES	YES	YES	YES	YES	YES	YES	
–	–	–	–	–	–	–	–	
Auto/Auto	Auto/Auto	Auto/Auto	Auto/Auto	Auto/Auto	Auto/Auto	Auto/Auto	Auto/Auto	
–	–	–	–	–	–	–	Manual/Auto	
–	–	–	–	–	–	–	–	
Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	
–	–	–	–	–	–	–	–	
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	
Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	
Crestron, AMX, Extron, Control4, Art-Net	Crestron, AMX, Extron, Control4, Art-Net	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4, Art-Net	Crestron, AMX, Extron, Control4, Art-Net	Crestron, AMX, Extron, Control4, Art-Net	Crestron, AMX, Extron, Control4, Art-Net	Crestron, AMX, Extron	
HDMI x 1 (HDCP 2.2)							HDMI x 1	
VGA x 1, 5-BNC x 1							VGA x 2, S-video, Composite Video	
Mini Stereo x 3						–	RCA (L & R) x 1	
Mini Stereo x 1						–	Mini Stereo x 2	
Type B x 1 (For Service, Clone), Type A x 1 (For Wireless, FW Update, Clone)								
DVI-D x 1								
HDBaseT x 1 (HDCP 2.2)								
3G-SDI			–	3G-SDI				
Mini D-sub 15 pin x 1								
RS-232c x 1								
HDBaseT Transmitter							Short-throw Wall Mount (ELPMB27)	
V12H547020							V12H706020	
Epson Mount for Low Ceiling/High Ceiling						–	Wireless LAN Module	
Low - V12H802010/High - V12H803010						–	V12H418P12	

** 20,000 hours is the estimated projector life when used in Normal Mode. Actual hours may vary depending on mode and usage environment. The projector has a limited warranty of 3 years or 20,000 hours, whichever comes first.

Interactive Projectors – BrightLink Series
Projector Specs Only

								
BrightLink 685Wi	BrightLink 695Wi	BrightLink 696Ui	BrightLink 697Ui	BrightLink 710Ui	BrightLink Pro 1450Ui	BrightLink Pro 1460Ui	BrightLink Pro 1470Ui	
V11H741522	V11H740522	V11H728022	V11H823022	V11H877022	V11H727520	V11H726520	V11H876520	
V13H010L91	V13H010L91	V13H010L92	V13H010L92	–	V13H010L92	V13H010L92	–	
BrightLink 585Wi	BrightLink 595Wi	–	–	–	BrightLink Pro 1430Wi	–	–	
2-Year	2-Year	2-Year	2-Year	3-year	2-Year	2-Year	3-year	
3,500	3,500	3,800	4,400	4,000	3,800	4,400	4,000	
3,500	3,500	3,800	4,400	4,000	3,800	4,400	4,000	
WXGA	WXGA	Full HD WUXGA	Full HD WUXGA	Full HD WUXGA	Full HD WUXGA	Full HD WUXGA	Full HD WUXGA	
12.8 lb	12.8 lb	18.3 lb	18.7 lb	24.7 lb	18.5 lb	18.7 lb	25.1 lb	
14.5 x 15.8 x 5.9	14.5 x 15.8 x 5.9	18.7 x 17.6 x 5.1	18.7 x 17.6 x 5.1	19.5 x 17.2 x 6.8	18.7 x 17.6 x 5.1	18.7 x 17.6 x 5.1	19.5 x 17.2 x 6.8	
14,000:1	14,000:1	16,000:1	16,000:1	2,500,000:1	16,000:1	16,000:1	2,500,000:1	
0.28 Wide 0.37 Tele	0.28 Wide 0.37 Tele	0.27 Wide 0.37 Tele	0.27 Wide 0.37 Tele	0.27 Wide 0.37 Tele	0.27 Wide 0.37 Tele	0.27 Wide 0.37 Tele	0.27 Wide 0.37 Tele	
1.35x Digital	1.35x Digital	1.35x Digital	1.35x Digital	1.35x Digital	1.35x Digital	1.35x Digital	1.35x Digital	
Lamp	Lamp	Lamp	Lamp	Laser	Lamp	Lamp	Laser	
5,000/10,000	5,000/10,000	5,000/10,000	5,000/10,000	20,000 [†]	5,000/10,000	5,000/10,000	20,000 [†]	
373 W	373 W	425 W	477 W	448 W	425 W	477 W	448 W	
16 W	16 W	16 W	16 W	16 W	16 W	16 W	16 W	
YES	YES	YES	YES	YES	YES	YES	YES	
Digital	Digital	Digital	Digital	Digital	Digital	Digital	Digital	
YES	YES	YES	YES	YES	YES	YES	YES	
–	–	–	–	–	–	–	–	
–	–	–	–	–	–	–	–	
–	–	–	YES	–	YES	YES	YES	
YES	YES	YES	YES	YES	YES	YES	YES	
–	–	–	YES	–	–	YES	YES	
–	–	–	–	–	–	–	–	
Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	
–	–	–	–	–	–	–	–	
–	–	–	–	–	–	–	–	
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	
Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Included (802.11 b/g/n) QR Code Quick Connect	Optional (802.11 b/g/n)	Included (802.11 b/g/n) QR Code Quick Connect	Included (802.11 b/g/n) QR Code Quick Connect	Included (802.11 b/g/n)	
Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink	
HDMI x 3 (Includes MHL x 1)			HDMI x 2 (Includes MHL x 1)	HDMI x 3 (Includes MHL x 1)	HDMI x 2 (Includes MHL x 1)			
VGA x 2, Composite Video		VGA x 1, Composite Video						
Mini Stereo x 3		Mini Stereo x 2						
Mini Stereo x 1								
Type B x 1, Type A x 1		Type B x 1, Type A x 2 (Memory Stick and Document Camera)						
–			DVI-D x 1 Output	–		DVI-D x 1 Output		
–								
–								
Mini D-sub 15 pin x 1								
RS-232c x 1								
Ultra Short-throw Wall Mount (ELPMB46)	Ultra Short-throw Wall Mount (ELPMB46)	Wireless LAN Module	DC-21 Document Camera	Wireless LAN Module	Motorized Interactive Table	Motorized Interactive Table	Motorized Interactive Table	
V12H777020	V12H777020	V12H731P02	V12H758020	V12H731P02	V12H893020	V12H893020	V12H893020	
100" Whiteboard	100" Whiteboard	100" Whiteboard	100" Whiteboard	100" Whiteboard	Ultra Short-throw Wall Mount (ELPMB46)	Ultra Short-throw Wall Mount (ELPMB46)	Ultra Short-throw Wall Mount (ELPMB53)	
V12H831000	V12H831000	V12H831000	V12H831000	V12H831000	V12H777020	V12H777020	V12H902020	

Note: Highlighted boxes indicate step-ups between models within a series.	Interactive Projectors – BrightLink Series								
	Interactive Specs								
	BrightLink 536Wi	BrightLink 685Wi	BrightLink 695Wi	BrightLink 696Ui	BrightLink 697Ui	BrightLink 710Ui	BrightLink Pro 1450Ui	BrightLink Pro 1460Ui	BrightLink Pro 1470Ui
Interactive Features									
Pens	1 Pen Included, Dual-user Support	2 Pens Included, Dual-user Support	2 Pens Included, Dual-user Support	2 Pens Included, Dual-user Support	2 Pens Included, Dual-user Support	2 Pens Included, Dual-user Support	2 Pens Included, Dual-user Support	2 Pens Included, Dual-user Support	2 Pens Included, Dual-user Support
Pen Technology	IR, 850nm								
Finger Touch	–	–	Yes, up to 6 fingers	Yes, up to 6 fingers	Yes, up to 6 fingers	Yes, up to 6 fingers	Yes, up to 6 fingers	Yes, up to 6 fingers	Yes, up to 6 fingers
Interactive Pen Functions	Mouse Function (Left/Right Click), Digital Pen, LED Battery Status Indicator								
PC-free Whiteboard Sharing	–	–	–	–	YES	–	YES	YES	YES
DuoLink Extended Whiteboard [◊]	–	YES	YES	YES	YES	YES	YES	YES	YES
Calibration	Automatic or Manual								
Interactive Image Size (Inches)	60 – 113	60 – 100	60 – 100	60 – 100	70 – 100	70 – 100	70 – 100	70 – 100	70 – 100
Interactive Connectivity	USB or LAN								
PC-free Annotation	YES								
PC-free Digital Whiteboard	1 page	1 page	1 page	1 page	Up to 50 pages	1 page	Up to 50 pages	Up to 50 pages	Up to 50 pages
Wall-mounted Control Panel	–	–	–	–	YES	–	YES	YES	YES
PC-free Save, Email, Print	–	Save, Print	Save, Print	Save, Print	YES	Save, Print	YES	YES	YES
Gestures Support	–	–	Yes, computers require Windows® 7/8/10 or Mac OS® 10.x						
Included Software	Easy Interactive Tools for PC/Mac®, Built-in Annotation Toolbar, SMART Notebook®						Easy Interactive Tools, Built-in Annotation Toolbar		




[◊]Certain functionality is only available through Epson Interactive Tools (EIT) software. For a list of supported operating systems, visit www.epson.com

Lenses Compatible with Pro G7000 Series Projectors and the Pro L1100U, L1200U, L1300U and L1405U										
Model	Ultra Short Lens	Short Lens #1	Short Lens #2	Wide Lens #1	Wide Lens #2	Middle Lens #1	Middle Lens #2	Middle Lens #3	Middle Lens #4	Long Lens
Product Code	V12H004X01	V12H004U03	V12H004U04	V12H004W05	V12H004W06	V12H004M08	V12H004M0F	V12H004M0A	V12H004M0B	V12H004L08
Zoom Ratio	0	1.0 – 1.2x	1.0 – 1.2x	1.0 – 1.4x	1.0 – 1.4x	1.0 – 1.6x	1.0 – 1.6x	1.0 – 1.5x	1.0 – 1.5x	1.0 – 1.4x
Throw Ratio (4:3)	0.36	0.66 – 0.80	0.89 – 1.08	1.07 – 1.49	1.66 – 2.27	1.47 – 2.38	2.20 – 3.56	3.39 – 5.17	4.95 – 7.54	7.36 – 10.33
Throw Ratio (16:10)	0.35	0.65 – 0.78	0.87 – 1.06	1.04 – 1.46	1.63 – 2.22	1.44 – 2.32	2.16 – 3.49	3.33 – 5.06	4.86 – 7.38	7.22 – 10.12

Lenses Compatible with Pro L1500 Series and Pro L1700 Series									
Model	Ultra Short Lens	Short Lens #1	Short Lens #2	Wide Lens #1	Wide Lens #2	Middle Lens #2	Middle Lens #3	Middle Lens #4	Long Lens
Product Code	V12H004X02	V12H004U03	V12H004U04	V12H004W05	V12H004W06	V12H004M0F	V12H004M0A	V12H004M0B	V12H004L08
Zoom Ratio	0	1.0 – 1.2x	1.0 – 1.2x	1.0 – 1.4x	1.0 – 1.37x	1.0 – 1.6x	1.0 – 1.5x	1.0 – 1.5x	1.0 – 1.39x
Throw Ratio (4:3)	0.36	0.49 – 0.59	0.66 – 0.80	0.79 – 1.11	1.23 – 1.67	1.62 – 2.65	2.50 – 3.84	3.64 – 5.58	5.43 – 7.65
Throw Ratio (16:10)	0.35	0.48 – 0.57	0.64 – 0.77	0.77 – 1.07	1.19 – 1.62	1.57 – 2.56	2.43 – 3.71	3.54 – 5.41	5.27 – 7.41

An essential teaching tool for the modern classroom

Share books, 3D objects, and detailed demonstrations or experiments with your entire class using Epson's easy-to-use document cameras. Record lessons for viewing at a later time, and give your students a more interactive learning experience.

Document Cameras			
			
Model	DC-07	DC-13	DC-21
Product Code	V12H759020	V12H757020	V12H758020
Zoom	8x digital	16x digital	12x optical, 10x digital
Pixel Count	2MP	2MP	2MP
Output Resolution (Max.)	1080p	1080p	1080p
Frame Rate	15 fps	30 fps	30 fps
Connectivity (Output)	USB	USB, VGA, HDMI	USB, VGA, HDMI
Capture Area (Inches)	10.7 x 14.3	11.7 x 20.7	11.7 x 20.7
AV Recording	YES	YES	YES
Built-in Microphone	YES	YES	YES
Microscope Adapter	–	YES	YES
SD Card Slot ^{◊◊}	–	YES	YES
Software Included	YES	YES	YES

^{◊◊}SD card sold separately.

Comprehensive Warranty with Convenient Road Service

Epson projector customers receive first-class service with Epson's standard 2-year limited warranty, including Road Service and a dedicated toll-free support line. Epson laser projectors receive a standard 3-year limited warranty.^{◊◊◊}

^{◊◊◊}Replacement projectors typically shipped within 24 hours. Actual delivery time may vary. Lamps have a 90-day limited warranty. Pro G and Pro L Series projectors are warranted for 3 years or 20,000 hours, whichever comes first.

	Budget-friendly Classroom Projectors			Basic Projectors for Small and Medium Rooms	
Note: Highlighted boxes indicate step-ups between models within a series.					
Epson® Model	PowerLite® S39	PowerLite X39	PowerLite W39	PowerLite 1266	PowerLite 1286
Product Code	V11H854020	V11H855020	V11H856020	V11H845120	V11H846120
Replacement Lamp Code	V13H010L96	V13H010L96	V13H010L96	V13H010L96	V13H010L96
Previous Epson Model	PowerLite S27	PowerLite X27	PowerLite W29	PowerLite 1264	PowerLite 1284
Road Service Warranty	2-Year	2-Year	2-Year	2-Year	2-Year
Basics					
Color Brightness (Color Lumens)*	3,300	3,500	3,500	3,600	3,600
White Brightness (White Lumens)*	3,300	3,500	3,500	3,600	3,600
Native Resolution**	SVGA	XGA	WXGA	WXGA	Full HD WUXGA
Weight	6.0 lb	6.0 lb	6.0 lb	6.2 lb	6.2 lb
Dimensions (Inches)†	11.8 x 9.8 x 3.6	11.8 x 9.8 x 3.6	11.8 x 9.8 x 3.6	11.9 x 9.9 x 3.6	11.9 x 9.9 x 3.6
Contrast Ratio (up to)	15,000:1	15,000:1	15,000:1	15,000:1	15,000:1
Throw Ratio	1.45 Wide 1.96 Tele	1.48 Wide 1.77 Tele	1.30 Wide 1.56 Tele	1.38 Wide 1.68 Tele	1.38 Wide 1.68 Tele
Zoom Lens (Ratio)	1.35x Digital	1.2x Optical	1.2x Optical	1.2x Optical	1.2x Optical
Light Source	Lamp	Lamp	Lamp	Lamp	Lamp
Light Source Life Cycle (Normal/ECO [Hours])††	6,000/10,000	6,000/12,000	6,000/12,000	6,000/10,000	6,000/10,000
Power Consumption	326 W	326 W	326 W	315 W	315 W
Value-added Features					
Built-in Speaker	5 W	5 W	5 W	2 W	2 W
Closed Captioning	YES	YES	YES	YES	YES
A/V Mute	Slide Door	Slide Door	Slide Door	Slide Door	Slide Door
Split Screen	YES	YES	YES	YES	YES
Edge Blending	–	–	–	–	–
Curved Surface and Corner Wall	–	–	–	–	–
Scheduling Function	–	–	–	–	–
Easy Connectivity & Setup					
Epson iProjection™ Suite (Moderator, Multi-PC, Device Management)	–	YES	YES	YES	YES
Miracast®	–	–	–	–	–
USB Plug 'n Play Image/Video	YES	YES	YES	YES	YES
PC-free Presentations via USB-A	Images	Images	Images	Photo, Motion JPEG	Photo, Motion JPEG
Quick Corner® Adjustments	YES	YES	YES	YES	YES
Screen Fit	–	–	–	–	–
Keystone (Horizontal/Vertical)	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto
Easy-Slide Horizontal Keystone Adjustment	YES	YES	YES	YES	YES
Lens Shift (Vertical & Horizontal)	–	–	–	–	–
LAN Networking & Control					
Wired	–	RJ-45 (Content over IP)	RJ-45 (Content over IP)	–	–
Wireless	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Included (802.11 b/g/n) QR Code Quick Connect	Included (802.11 b/g/n) QR Code Quick Connect
Compatible Control Systems	Crestron®, AMX®, Extron®, Control4®	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	–	–
Connections					
HDMI®	HDMI x 1		HDMI x 2	HDMI x 2 (Includes MHL® x 1)	
Analog Connections	VGA x 2, S-video			VGA x 1, S-video Composite Video	
Audio In	RCA (L & R) x 1 Mini Stereo x 2			RCA x 1	
Variable Audio Out	Mini Stereo x 1			Mini Stereo x 1	
USB 2.0 Connectors	Type B x 1, Type A x 1			Type B x 1, Type A x 1	
DisplayPort/DVI-D	–			–	
HDBaseT™	–			–	
SDI	–			–	
Monitor Out	D-sub 15 pin x 1			–	
Serial Control	RS-232c x 1			–	
Recommended Accessory 1	Wireless LAN Module			ES3000 Screen	
Recommended Accessory 1 SKU	V12H731P02			V12H002S3Y	
Recommended Accessory 2	DC-13 Document Camera			Carrying Case	
Recommended Accessory 2 SKU	V12H757020			V12H001K69	

*Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118.

**WUXGA (1920 x 1200), WXGA (1280 x 800), XGA (1024 x 768), SVGA (800 x 600).

Advanced Networking Classroom Projectors

Standard Throw

							
PowerLite 107	PowerLite 108	PowerLite 109W	PowerLite 970	PowerLite 975W	PowerLite 980W	PowerLite 990U	
V11H859020	V11H860020	V11H861020	V11H865020	V11H835020	V11H866020	V11H867020	
V13H010L96	V13H010L96	V13H010L96	V13H010L96	V13H010L95	V13H010L96	V13H010L96	
PowerLite 97H	PowerLite 98H	PowerLite 99WH	PowerLite 965H	PowerLite 935W	PowerLite 955WH	–	
2-Year	2-Year	2-Year	2-Year	2-Year	2-Year	2-Year	
3,500	3,700	4,000	4,000	3,600	3,800	3,800	
3,500	3,700	4,000	4,000	3,600	3,800	3,800	
XGA	XGA	WXGA	XGA	WXGA	WXGA	Full HD WUXGA	
6.2 lb	6.2 lb	6.2 lb	6.7 lb	9.7 lb	6.9 lb	7.1 lb	
11.6 x 9.7 x 3.5	11.6 x 9.7 x 3.5	11.6 x 9.7 x 3.5	12.1 x 11.5 x 4.1	14.8 x 11.4 x 4.5	12.1 x 11.5 x 4.1	12.1 x 11.5 x 4.1	
15,000:1	15,000:1	15,000:1	15,000:1	15,000:1	15,000:1	15,000:1	
1.48 Wide 1.77 Tele	1.48 Wide 1.77 Tele	1.30 Wide 1.56 Tele	1.38 Wide 2.24 Tele	1.38 Wide 2.24 Tele	1.38 Wide 2.24 Tele	1.39 Wide 2.23 Tele	
1.2x Optical	1.2x Optical	1.2x Optical	1.6x Optical	1.6x Optical	1.6x Optical	1.6x Optical	
Lamp	Lamp	Lamp	Lamp	Lamp	Lamp	Lamp	
6,000/12,000	6,000/12,000	6,000/12,000	6,000/12,000	10,000 (Bright Mode)	6,000/12,000	6,000/12,000	
326 W	326 W	326 W	326 W	334 W	326 W	326 W	
16 W	16 W	16 W	16 W	16 W	16 W	16 W	
YES	YES	YES	YES	YES	YES	YES	
Slide Door	Slide Door	Slide Door	Slide Door	Slide Door	Slide Door	Slide Door	
YES	YES	YES	YES	YES	YES	YES	
–	–	–	–	–	–	–	
–	–	–	–	–	–	–	
–	–	–	–	YES	–	–	
YES	YES	YES	YES	YES	YES	YES	
–	–	–	–	YES	–	–	
YES	YES	YES	YES	YES	YES	YES	
Images, PDFs	Images, PDFs	Images, PDFs	Images, PDFs	Images, PDFs	Images, PDFs	Images, PDFs	
YES	YES	YES	YES	YES	YES	YES	
–	–	–	–	YES	–	–	
Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	
YES	YES	YES	YES	–	YES	YES	
–	–	–	–	–	–	–	
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	
Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Included (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	
Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	
HDMI x 2 (Includes MHL x 1)				HDMI x 2 (Includes MHL x 1)		HDMI x 2 (Includes MHL x 1)	
VGA x 2, S-video				VGA x 2, Composite Video		VGA x 2, S-video	
RCA (L & R) x 1 Mini Stereo x 2				RCA (L & R) x 1 Mini Stereo x 2		RCA (L & R) x 1 Mini Stereo x 2	
Mini Stereo x 1				Mini Stereo x 1		Mini Stereo x 1	
Type B x 1, Type A x 1				Type B x 1, Type A x 1		Type B x 1, Type A x 1	
–				–		–	
–				–		–	
–				–		–	
D-sub 15 pin x 1				Mini D-sub 15 pin x 1		D-sub 15 pin x 1	
RS-232c x 1				RS-232c x 1		RS-232c x 1	
Wireless LAN Module				Universal Projector Mount (ELPMBPJG)		Wireless LAN Module	
V12H731P02				V12H808001		V12H731P02	
DC-21 Document Camera				DC-21 Document Camera		DC-21 Document Camera	
V12H758020				V12H758020		V12H758020	

†Dimensions including feet and standard lens.

††Maximum lamp life will vary depending upon mode selected, environmental conditions, and usage. Brightness decreases over time. The PowerLite 975W has a single lamp mode, rated to last up to 10,000 hours. Lamps are warranted for 90 days.

Advanced Networking Classroom Projectors

Short Throw				Ultra Short Throw		
						
PowerLite 520	PowerLite 525W	PowerLite 530	PowerLite 535W	PowerLite 675W	PowerLite 680	PowerLite 685W
V11H674020	V11H672020	V11H673020	V11H671020	V11H745520	V11H746520	V11H744520
V13H010L87	V13H010L87	V13H010L87	V13H010L87	V13H010L90	V13H010L91	V13H010L91
PowerLite 420	PowerLite 425W	PowerLite 430	PowerLite 435W	PowerLite 575W	PowerLite 580	PowerLite 585W
2-Year	2-Year	2-Year	2-Year	2-Year	2-Year	2-Year
2,700	2,800	3,200	3,400	3,200	3,500	3,500
2,700	2,800	3,200	3,400	3,200	3,500	3,500
XGA	WXGA	XGA	WXGA	WXGA	XGA	WXGA
8.2 lb	8.2 lb	8.2 lb	8.2 lb	12.6 lb	12.6 lb	12.6 lb
13.5 x 12.5 x 5.2	13.5 x 12.5 x 5.2	13.5 x 12.5 x 5.2	13.5 x 12.5 x 5.2	14.5 x 15.8 x 7.4	14.5 x 15.8 x 7.4	14.5 x 15.8 x 7.4
16,000:1	16,000:1	16,000:1	16,000:1	14,000:1	14,000:1	14,000:1
0.55 Wide 0.74 Tele	0.48 Wide 0.65 Tele	0.55 Wide 0.74 Tele	0.48 Wide 0.65 Tele	0.28 Wide 0.37 Tele	0.32 Wide 0.43 Tele	0.28 Wide 0.37 Tele
1.35x Digital Lamp	1.35x Digital Lamp	1.35x Digital Lamp	1.35x Digital Lamp	1.35x Digital Lamp	1.35x Digital Lamp	1.35x Digital Lamp
5,000/10,000	5,000/10,000	5,000/10,000	5,000/10,000	5,000/10,000	5,000/10,000	5,000/10,000
293 W	293 W	315 W	315 W	333 W	373 W	373 W
16 W	16 W	16 W	16 W	16 W	16 W	16 W
YES	YES	YES	YES	YES	YES	YES
Digital	Digital	Digital	Digital	Digital	Digital	Digital
-	-	-	-	YES	YES	YES
-	-	-	-	-	-	-
-	-	-	-	-	-	-
-	-	-	-	-	-	-
YES	YES	YES	YES	YES	YES	YES
-	-	-	-	-	-	-
YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES
-	-	-	-	-	-	-
Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual
-	-	-	-	-	-	-
-	-	-	-	-	-	-
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)
Crestron, AMX, Extron	Crestron, AMX, Extron	Crestron, AMX, Extron	Crestron, AMX, Extron	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink
HDMI x 1				HDMI x 3 (Includes MHL x 1)		
VGA x 2, S-video, Composite Video				VGA x 2, Composite Video		
RCA (L & R) x 1 Mini Stereo x 2				Mini Stereo x 3		
Mini Stereo x 1				Mini Stereo x 1		
Type B x 1, Type A x 1				Type B x 1, Type A x 1		
-				-		
-				-		
-				-		
Mini D-sub 15 pin x 1				Mini D-sub 15 pin x 1		
RS-232c x 1				RS-232c x 1		
Short-throw Wall Mount (ELPMB45)				Ultra Short-throw Wall Mount (ELPMB46)		
V12H706020				V12H777020		
PowerLite Pilot™ 2 Connection & Control Box (ELPCB02)				PowerLite Pilot 2 Connection & Control Box (ELPCB02)		
V12H614020				V12H614020		

‡ 20,000 hours is the estimated projector life when used in Normal Mode. Actual hours may vary depending on mode and usage environment. The projector comes with a 3-year limited warranty.

	Short- and Ultra Short-throw Projectors for SMART®			Ultra Mobile Projectors – 1700 Series Extra Thin and Light			
							
PowerLite 700U for Signage	PowerLite 530 for SMART	PowerLite 680 for SMART	PowerLite 685W for SMART	PowerLite 1780W	PowerLite 1781W	PowerLite 1785W	PowerLite 1795F
V11H878520	V11H673320	V11H746620	V11H744620	V11H795020	V11H794120	V11H793020	V11H796020
–	V13H010L87	V13H010L91	V13H010L91	V13H010L94	V13H010L94	V13H010L94	V13H010L94
–	–	PowerLite 580 for SMART	PowerLite 585W for SMART	PowerLite 1761W	PowerLite 1771W	PowerLite 1776W	–
3-year	2-Year	2-Year	2-Year	2-Year	2-Year	2-Year	2-Year
4,000	3,200	3,500	3,500	3,000	3,200	3,200	3,200
4,000	3,200	3,500	3,500	3,000	3,200	3,200	3,200
Full HD WUXGA	XGA	XGA	WXGA	WXGA	WXGA	WXGA	1080p
24.3 lb	8.2 lb	12.6 lb	12.6 lb	4.0 lb	4.0 lb	4.0 lb	4.0 lb
19.5 x 17.2 x 7.4	13.5 x 12.5 x 5.2	14.5 x 15.8 x 7.4	14.5 x 15.8 x 7.4	11.5 x 8.4 x 2.1	11.5 x 8.4 x 2.1	11.5 x 8.4 x 2.1	11.5 x 8.4 x 2.1
2,500,000:1	16,000:1	14,000:1	14,000:1	10,000:1	10,000:1	10,000:1	10,000:1
0.27 Wide 0.37 Tele	0.55 Wide 0.74 Tele	0.32 Wide 0.43 Tele	0.28 Wide 0.37 Tele	1.04 Wide 1.26 Tele	1.04 Wide 1.26 Tele	1.04 Wide 1.26 Tele	1.02 Wide 1.23 Tele
1.35x Digital	1.35x Digital	1.35x Digital	1.35x Digital	1.2x Optical	1.2x Optical	1.2x Optical	1.2x Optical
Laser	Lamp	Lamp	Lamp	Lamp	Lamp	Lamp	Lamp
20,000*	5,000/10,000	5,000/10,000	5,000/10,000	4,000/7,000	4,000/7,000	4,000/7,000	4,000/7,000
448 W	315 W	373 W	373 W	290 W	290 W	309 W	309 W
16 W	16 W	16 W	16 W	1 W	1 W	1 W	1 W
YES	YES	YES	YES	YES	YES	YES	YES
Digital	Digital	Digital	Digital	Slide Door	Slide Door	Slide Door	Slide Door
YES	–	YES	YES	YES	YES	YES	YES
–	–	–	–	–	–	–	–
–	–	–	–	–	–	–	–
Yes	–	–	–	–	–	–	–
YES	YES	YES	YES	YES	YES	YES	YES
–	–	–	–	–	–	YES	YES
YES	YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	Video, Images	Video, Images	Video, Images, PDF	Video, Images, PDF
YES	YES	YES	YES	YES	YES	YES	YES
–	–	–	–	–	–	YES	YES
Manual/Auto	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Auto	Manual/Auto	Auto/Auto	Auto/Auto
–	–	–	–	–	–	–	–
–	–	–	–	–	–	–	–
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	–	–	–	–
Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Included (802.11 b/g/n)	Included (802.11 b/g/n)	Included (802.11 b/g/n)	Included (802.11 b/g/n)
Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink	–	–	–	–
HDMI x 3 (Includes MHL x 1)	HDMI x 1	HDMI x 3 (Includes MHL x 1)		HDMI x 1			
VGA x 2, Composite Video	VGA x 2, S-video, Composite Video	VGA x 2, Composite Video		VGA x 1, Composite Video			
Mini Stereo x 2	RCA (L & R) x 1 Mini Stereo x 2	Mini Stereo x 3		Mini Stereo x 1			
Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1		–			
Type B x 1, Type A x 1	Type B x 1, Type A x 1	Type B x 1, Type A x 1		Type B x 1, Type A x 1			
–	–	–		–			
–	–	–		–			
–	–	–		–			
Mini D-sub 15 pin x 1	Mini D-sub 15 pin x 1	Mini D-sub 15 pin x 1		–			
RS-232c x 1	RS-232c x 1	RS-232c x 1		–			
Ultra Short-throw Wall Mount (ELPMB53)	Short-throw Wall Mount (ELPMB45)	Ultra Short-throw Wall Mount (ELPMB46)		ES3000 Screen			
V12H902020	V12H706020	V12H777020		V12H002S3Y			
Replacement Air Filter	DC-21 Document Camera			DC-21 Document Camera			
V13H134A43	V12H758020			V12H758020			

Epson 3LCD Projectors have:

- Up to 3x Higher Color Brightness¹
- Up to 3x Wider Color Gamut²
- Vastly Superior Color Accuracy



**Epson.com —
Your one-stop resource.**

Epson projectors have up to 3x Higher Color Brightness¹ over top-selling 1-chip DLP projectors.

Traditional lumens specifications only measure white brightness. If you don't see a separate color brightness specification, it may be as low as 1/3 of the listed specification. Learn more about the color brightness specification and look up the color brightness for hundreds of projectors at www.colorlightoutput.com

Collaborative Whiteboarding Solutions

www.epson.com/blpro

For remote collaboration, conference rooms and huddle spaces

Projectors

For more information, visit www.epson.com/projectors

www.epson.com/2000series

For well-lit rooms (network-ready options available)

www.epson.com/largevenue

For large rooms and large venues

www.epson.com/interactive

For interactive and touch-enabled applications

www.epson.com/HOW

For worship spaces

www.epson.com/education

For higher education/K-12 educators

Document Cameras

www.epson.com/documentcameras

Over 100 ways to enhance lessons and presentations

Epson Business Solutions

Epson is a leading provider of innovative technology solutions that help businesses succeed. We partner with you to best meet your specific needs, focusing on:

- Improved productivity
- World-class customer service and support
- Cost-effective, high-quality solutions
- A commitment to the environment

Discover how Epson can help you work toward the future

www.epson.com/forbusiness

Epson 3LCD Projector (WXGA):

WHITE BRIGHTNESS
3,000*

COLOR BRIGHTNESS
3,000*



Competitor 1-chip DLP Projector (WXGA):

WHITE BRIGHTNESS
3,200³

COLOR BRIGHTNESS
650³



Actual photographs of projected images from an identical signal source. Both projectors are set to their brightest mode.

* Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118.

¹ Color brightness (color light output) in brightest mode, measured by a third-party lab in accordance with IDMS 15.4. Color brightness will vary depending on usage conditions. Top-selling Epson 3LCD projectors versus top-selling 1-chip DLP projectors based on PMA Research sales data for Dec. 2015 through Nov. 2016.

² Gamut volume in brightest mode, measured by a third-party lab in 3D in the CIE L*a*b* coordinate space. Top-selling Epson 3LCD projectors versus top-selling 1-chip DLP projectors based on PMA Research sales data for Dec. 2015 through Nov. 2016.

³ White brightness is according to the manufacturer's specifications. The manufacturer does not provide a color brightness specification for this model. This data was obtained from third-party laboratory testing of a unit according to the international standard for measuring color brightness, IDMS 15.4.

Epson America, Inc.
3840 Kilroy Airport Way, Long Beach, CA 90806
www.epson.com

Epson Canada Limited
185 Renfrew Drive, Markham, Ontario L3R 6G3
www.epson.ca

Note: Highlighted boxes indicate step-ups between models within a series.

Epson® Model

Product Code

Replacement Lamp Code

Previous Epson Model

Road Service Warranty

Basics

Color Brightness (Color Lumens)*

White Brightness (White Lumens)*

Native Resolution**

Weight

Dimensions (Inches)†

Contrast Ratio (up to)

Throw Ratio

Zoom Lens (Ratio)

Light Source

Light Source Life Cycle (Normal/ECO [Hours])††

Power Consumption

Value-added Features

Built-in Speaker

Closed Captioning

A/V Mute

Split Screen

Edge Blending

Curved Surface and Corner Wall

Scheduling Function

Easy Connectivity & Setup

Epson iProjection™ Suite
(Moderator, Multi-PC, Device Management)

Miracast®

USB Plug 'n Play Image/Video

PC-free Presentations via USB-A

Quick Corner® Adjustments

Screen Fit

Keystone (Horizontal/Vertical)

Easy-Slide Horizontal Keystone Adjustment

Lens Shift (Vertical & Horizontal)

LAN Networking & Control

Wired

Wireless

Compatible Control Systems

Connections

HDMI®

Analog Connections

Audio In

Variable Audio Out

USB 2.0 Connectors

DisplayPort/DVI-D

HDBaseT™

SDI

Monitor Out

Serial Control

Recommended Accessory 1

Recommended Accessory 1 SKU

Recommended Accessory 2

Recommended Accessory 2 SKU