

EPSON

DESIGNED FOR PROFESSIONAL REPRODUCTION OF PHOTOS

SURECOLOR™ SC-P703 & SC-P903



The Epson SureColor™ SC-P703 and SC-P903 printers will be a treat for professional photographers and creatives who have a keen eye for detail and an appreciation for high-performance hardware that is aesthetically pleasing. The accuracy and quality of the printers' output is further enhanced by the deepest blacks and an expanded blue colour gamut.



Versatile Media
Handling



Up to
1.5 mm Thick



Ethernet



Wi-Fi



Epson
Connect

ULTRACHROME
PRO₁₀ INK



SPECIFICATIONS

SureColor™ SC-P703 & SC-P903

MODEL NUMBER	SC-P703		SC-P903
Maximum Print Size	33.02 cm (13")		43.18 cm (17")
Printing Technology	On-demand ink jet (piezo electric), Variable-Sized Droplet Technology		
Printing Method	Black/Gray : 180 nozzles for each 4 black ink, Colour : 180 nozzles for each 6 colour ink		
Nozzle Configuration	Black Enhance Overcoat		
Overcoat Print	Bi-directional printing, uni-directional printing		
Print Direction	LUT		
LUT	(LCCS Technology, The promotion depends on each ESC)		
Print Quality	5760x1440 dpi		
Maximum Resolution	1.5 pl		
Minimum Ink Droplet Volume			
Ink System	UltraChrome™ PRO10 ink		
Name	Cyan, Vivid Magenta, Photo Black, Matte Black, Gray, Light Gray, Yellow, Vivid Light Magenta, Light Cyan, Violet		
Colours	25 mL		
Ink Capacity	25 mL		50 mL
Control Panel	4.3 inch colour LCD & Electrostatic touch screen		
Colour & Size			
Paper Handling	Friction Feed		
Paper Feed Method	Cut Sheet : 89 mm (3.5") - 330.2 mm (13")		Cut Sheet : 89 mm (3.5") - 431.8 mm (17")
Printing Area (width)	Roll paper (Built in unit), Width: 210 mm (A4) - 330.2 mm (13"), Max roll diameter : 84 mm		Roll paper (Option roll paper unit), Width: 210 mm (A4) - 431.8 mm(17"), Max roll diameter : 132 mm
Thickness	ASF: PlainPaper: 0.08-0.11 mm, Genuine Media : 0.08-0.50 mm, Front Thick Paper Path : 0.3 - 0.7 mm, Front Straight Path : 0.7 - 1.5 mm, Roll Path : 0.12-0.70 mm		
ASF Capacity:Max. sheets	ASF: Plain paper 120 sheets (73g/m²)		
Required Minimum Margin			
Without Border	3.5" x 5, 4" x 6", 4" x 7.11"(16:9 wide), 5" x 7", 5" x 8, 8" x 10", 10" x 12", 11" x 14", 13" x 19"; all directions 0 mm "Max quality" [Level4, 5] mode doesn't have borderless print.		3.5" x 5, 4" x 6", 4" x 7.11"(16:9 wide), 5" x 7", 5" x 8, 8" x 10", 10" x 12", 11" x 14", 16" x 20", 17" x 22" : all directions 0 mm "Max quality" [Level4, 5] mode doesn't have borderless print.
Required Minimum Margin	Board paper (Front) : Top and bottom 20 mm, right and left 3 mm, Roll paper : Top 50 mm , Botto m 14 mm, The others : all directions 3 mm		
Support Operation System	Windows 7/ 8/ 8.1/ 10, MacOS 10.9 or later		
Interface	Wired Connection: Super-Speed USB, 10BASE-T/100BASE-TX, Wireless Connection: Wi-Fi 4		
Control Code	ESC/P-R		
Environmental Characteristics			
Temperature	Operating: 10°C - 35°C, Storage: -20°C - 40°C		
Humidity	Operating: 20 - 80% (no condensation), Storage: 5 - 85% (no condensation)		
Dimensions / Weight			
Dimension (WxDxH)	Close: 515x368x185 mm, Open: 515x769x420 mm		Close: 615x368x199 mm, Open: 615x905x520 mm
Weight	Main Unit: Approx. 12.6 kg (without ink cartridge)		Main Unit: Approx. 14.8 kg (without ink cartridge), Option roll unit: 3.1 kg
Electrical Characteristics			
Rated power supply Voltage	AC 100-120V / 100-240V / 220-240V *Rated Voltage will vary depending on area		
Rated Frequency	50-60Hz		
Power Consumption	Printing: Approx.22 W		Printing: Approx.24 W
	Sleep : Approx. 1.1 W		
	Power off : Approx. 0.14 W(100-240V), Power off : Approx. 0.08 W(100-120V), Power off : Approx. 0.18 W(220-240V)		
Rated power supply Current	1.3-0.7A (100-240V), 1.2A (100-120V), 0.7A (220-240V)		
Acoustic Noise Level	Colour printing: Approx. 39 dB(A) according to ISO 7779		Colour printing: Approx. 41 dB(A) according to ISO 7779
Bundled Item	Setup I/C, Software disc, Disc tray, Setup guide, Power cable, USB cable, Warranty		

EPSON

SC-P703

Dimension & Weight

Weight: Approx. 12.6kg (without ink cartridge)



SC-P903

Dimension & Weight

Weight: Approx. 14.8kg (without ink cartridge)



© 2024 Epson India Pvt. Ltd. All Rights Reserved.
Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON is registered trademark of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners.
Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.

Partner's Stamp

Information correct at time of printing
Printed January 2024

EPSON INDIA PVT. LTD.

11th Floor, Godrej Centre, Hebbal, Survey No.26, Bellary Road, Sahakar Nagar, Byatarayanapura, Bangalore 560 092, Karnataka.

Tel: 080-6939 5000 Fax: 080-6939 5005

Scan the QR code to contact an Epson representative close to you.

CONTACT EPSON TODAY! EMAIL: pravin@eid.epson.co.in



Epson Helpline: For product info or service - 1800 425 0011

For service: 1800 123 001 600 or 1860 3000 1600 (9 am - 6 pm) (Mon - Sat)

Email: lfp@eid.epson.co.in

www.epson.co.in