

BrightLink® 710Ui WUXGA 3LCD Interactive Laser Display



The world's first 3LCD ultra short-throw interactive laser display.

More accurate, vivid color, even in well-lit rooms -4,000 lumens of equal color and white brightness¹

Breakthrough laser technology — provides up to 20,000 hours of virtually maintenance-free operation²; plus, get higher image contrast and Instant ON/OFF

Full HD WUXGA display up to 100" diagonal — optimal readability from anywhere in the room; 2x the interactive space of a 70" flat panel

Pen- and touch-based interactivity — allows up to eight users to draw, share and collaborate at once, with six points of touch plus two pens

Enhanced wireless display technology — connect up to 50 Chromebook[™], Mac[®], PC, iOS[®] and Android[™] devices, and simultaneously display up to four screens, with Epson iProjection^{™3} (wireless module sold separately)

Two-way content sharing — teachers can push content from the projector to wirelessly connected devices and control which device screens to display; students can make notes and send their work back to the projector³

Includes 1-year subscription and support for SMART Learning Suite — SMART Notebook®, SMART amp $^{\text{\tiny{TM}}}$, SMART lab $^{\text{\tiny{TM}}}$, SMART Learning Suite Online and more

DuoLink — install two BrightLink displays side-by-side to create one seamless interactive surface up to 177" diagonal⁴

Remarkable color accuracy — up to 3x Higher Color Brightness⁵ and up to 3x Wider Color Gamut⁶ with Epson[®] over 1-chip DLP projectors









BrightLink® 710Ui WUXGA 3LCD Interactive Laser Display

Specifications

Display System Epson 3LCD, 3-chip technology Display Method Ceiling/wall mount/table mount Driving Method Epson Poly-silicon TFT Active Matrix **Pixel Number** 2,304,000 dots (1920 x 1200) x 3 Color Brightness¹ Color Light Output: 4,000 lumens White Brightness¹ White Light Output: 4,000 lumens Interactive Color Brightness¹ Color Light Output: 4,000 lumens

Interactive White Brightness¹ White Light Output: 4,000 lumens

Aspect Ratio 16:10

Native Resolution 1920 x 1200 (WUXGA) Size (Projected) Area (16:10) 70.4" - 100"

Keystone Correction (Manual)

Horizontal: ±3 degrees Vertical: ±3 degrees

USB Plug 'n Play Mac OS X® 10.7/10.8/10.9/10.10/10.11/ macOS® 10.12.x

USB Plug 'n Play for Windows® Windows Vista®/Windows 7/Windows 8/Windows 10

Contrast Ratio Up to 2.500.000:1 Color Reproduction Up to 1 billion colors **Illumination Technology** Laser Phosphor

Light Source Life² 20,000 hours (Normal) 30,000 hours (Extended)

Projection Lens

Type Manual focus F-number 1.6 Focal Length 4.2 mm

Throw Ratio Range (16:10) 0.22 - 0.37, (4:3) 0.33 - 0.44, (16:9)

Zoom Ratio Digital zoom: 1.0 – 1.35x

Display Performance NTSC: 480 lines PAL: 576 lines (Depends on observation of the multi-burst pattern)

Input Signal NTSC/NTSC4.43/PAL/M-PAL/N-PAL/PAL60/SECAM

Speaker 16 W monaural

Operating Temperature 32 ° to 113 °F (0 ° to 45 °C) **Power Supply Voltage** 100 – 240 V ±10%, 50/60 Hz

Power Consumption ECO Mode: 348 W Normal Mode: 448 W

Standby (Communication On): 2.0 W Standby (Communication Off): 0.3 W

Fan Noise

Quiet Mode: 27 dB Normal Mode: 38 dB

Security Kensington lock provision, security anchor bar, password-protect function

Interactivity

Interactive Technology Infrared, 850 nm Interactive Area (Image Size) 70" - 100" diagonal (16:10,

Interfaces

2x HDMI

1x HDMI/MHL®

Computer/Component video: 1x D-sub 15 pin

Composite video: 1x RCA (Yellow)

Audio in: 2x Mini stereo USB connector: 1x Type B (USB display, audio and mouse control interactivity)

USB connector: 2x Type A (USB memory/document camera) 1x RJ-45

Serial: 1x RS-232c Monitor Out: 1x D-sub 15 pin

Audio Out: 1x Mini stereo Wireless LAN port: 802.11 b/g/n (not included) Interactive Synchronization

Mini stereo In Interactive Synchronization

Mini stereo Out Touch Unit Connection Port



Interactivity (continued)

Interactive Modes Computer Interactivity/Input, PC-free and Whiteboard Annotation Mode, Pen: Dual User, Finger Touch: Up to 6 points of touch PC-free Annotation Two pens and two fingers Annotation Tools Epson Easy Interactive Tools, dual user

PC Annotation Sources USB, HDMI, Computer 1, Computer 2, LAN PC-free Annotation Devices Document cameras, DVD/Blu-ray Disc® player, iPod®/iPad® devices, Chromebooks

Calibration Method Automatic or Manual

Interactive Connectivity USB cable for non-networked Interactive Software Requirements Epson Easy Interactive Driver (Mac and PC — required for DuoLink); Windows and Linux: driver not required Mac: Mac OS X 10.7/10.8/10.9/10.10/10.11/ macOS 10.12.x Epson Easy Interactive Tools for Windows and Mac

System Compatibility Microsoft® Windows Vista SP2 (All editions except for Starter), Windows 8/8.1, Windows 10, Windows 7 SP1 (All editions except for Starter)
mac OS™ 10.7/10.8/10.9/10.10/10.11/macOS 10.12.x, UBUNTU

15.10, 16.04 LTX, 16.10, 17.04

Gestures Requires Windows 7 or later, or or Mac OS 10.7 or later

SMART Notebook Requirements

Supported Operating Systems Windows 7 SP1, Windows 8/8.1, Windows 10, Mac OS X 10.9, 10.10, 10.11 Minimum Processor Intel® Core 2 Duo

Minimum RAM 2GB (4GB for UHD displays)

Minimum Hard Disk Space 3GB (Windows); 3GB (Mac)

Interactive Input Device

Dimensions (W x D x H)

Type of Interactive Input Device Digital pen Interactive Pen Functions Mouse Functions (left and right click), Electronic pen, LED battery status indicator

Interactive Pen Power AA battery, rechargeable Compatible Pen Battery Types Eneloop® batteries (included), Manganese dry cell, alkaline dry cell

Interactive Pen Dimensions 6.3" x 0.94" (diameter) Interactive Pen Weight 1.1 oz (without battery)

19.5" x 17.3" x 6.8' **Weight** 24.7 lb

Remote Control

Features Computer, Video/HDMI, USB, LAN, Source Search, Power, Aspect, Color Mode, Volume, E-Zoom, AV Mute, Freeze, Menu, Auto, Enter, ESC, Pointer, User, Home, Split, Pen Mode, Link Menu, ID, Page up, Page down

Operating Angle

Rear: Right/left: -55 to +55 degrees, Upper/lower: +75 to +15 degrees Front: Right/left: -30 to +30 degrees, Upper/lower: 0 to +60 degrees Operating Distance 19.7 ft (6 m)

Eco Features

Energy-efficient 3LCD light engine Recyclable product⁷ Epson America, Inc. is a SmartWay® Transport Partner⁸

Service Programs 3-year projector limited warranty, Epson Road Service program, PrivateLine® dedicated toll-free support

What's in the Box

BrightLink 710Ui ultra short-throw interactive laser display, wall mount, mount template sheet, installation manual, finger-touch module, touch module mounting bracket, touch module cable, Quick Start Guide, power cable, USB A/B cable, electronic user manual, projector remote control, two (2) interactive pens, two (2) AA batteries (for interactive pens) plus battery charger, two (2) AA batteries (for remote), SMART Learning Suite redemption code

Ordering Information

BrightLink 710Ui V11H877022 Air Filter V13H134A43 PowerLite® Pilot™ 2 (ELPCB02) V12H614020 Active Speakers (ELPSP02) V12H467020 Wireless 802.11b/g/n LAN Unit (ELPAP10) V12H731P02 100" Whiteboard V12H831000 Interactive Pen A (orange) V12H773010 Interactive Pen B (blue)
Replacement Pen Tips (hard/Teflon®) V12H774010 V12H775010 Replacement Pen Tips (soft/felt)
Ultra Short-throw Wall Mount (ELPMB53) V12H776010 V12H902020

1 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. | 2 20,000 hours is the estimated projector life when used in Normal Mode. Actual hours may vary depending on mode and usage environment The projector comes with a 3-year limited warranty. | 3 For wireless functionality, including via the Epson iProjection App, the projector must be configured on a network, either through the Ethernet port on the projector (check model specifications for availability) or via a wireless connection. Check your owner's manual to determine if a wireless LAN module must be purchased separately to enable a wireless connection. Not all Epson projectors are able to be networked. The Epson iProjection App does not support all files and formats. See www.epson.com for separately to relate a wineses connection. Not an epsori projectors are able to be networked. The post in rejection application and continuous and formats, see www.epson.com details, | 4 Requires Easy Interactive Driver. Certain functionality is only available through Epson Interactive Tools (EIT) software. For a list of supported operating systems, visit www.epson.com | 5 Color brightness (color light output) in brightest mode, measured by a third-party lab in accordance with IDMS 15.4. Color brightness will vary depending on usage conditions. Top-selling Epson 3LCD projectors versus top-selling 1-chip DLP projectors based on PMA Research sales data for Dec. 2015 through Nov. 2016. | 6 Gamut volume in brightest mode, measured by a third-party lab in 3D in the CIE L'arb* coordinate space. Top-selling Epson 3LCD projectors versus top-selling 1-chip DLP projectors based on PMA Research sales data for Dec. 2015 through Nov. 2016. | 7 For convenient and reasonable recycling options, visit www.epson.com/recycle | 8 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.

Learn more about how our products can empower your institution. Visit us at www.epson.com/foreducation

Better Products for a Better Future eco.epson.com

Epson America, Inc. 3840 Kilroy Airport Way, Long Beach, CA 90806 SmartWay Transport Partner

Epson Canada Limited 185 Renfrew Drive, Markham, Ontario L3R 6G3 www.epson.com www.epson.ca

Specifications and terms are subject to change without notice. EPSON and PowerLite are registered trademarks, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future and Epson iProjection are trademarks of Seiko Epson Corporation. BrightLink and PrivateLine are registered trademarks, Pilot is a trademark and Epson Connection is a service mark of Epson America, Inc. iPad, iPod, Mac, macOS and OS X are trademarks of Apple, Inc., registered in the U.S. and other countries. Android and Chromebook are trademarks of Google Inc. Microsoft, Windows and Windows Vista are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks.

Copyright 2018 Epson America, Inc. Com-SS-Oct-13 CPD-54463R1 3/18

Contact: