

SPECIFICATION SHEET

BrightLink[®] 695Wi WXGA 3LCD Ultra Short-throw Interactive Display

Collaborate Pen- and touch-based interactivity



Touch-based WXGA ultra short-throw interactive display for classrooms.

Bright display - 3,500 lumens color/white brightness¹

Pen- and touch-based interactivity — touch interactivity allows up to six users to draw, share and collaborate at once using familiar gestures

Wirelessly connect up to 50 devices — simultaneously share and control content from up to four screens at once using Moderator software, including Chromebook[™], PC, Mac[®], iOS[®] and Android[™] devices

Easy content sharing — share images between the big screen and wirelessly connected mobile devices, for individualized learning²

Includes 1-year subscription and support for SMART Learning Suite — SMART Notebook[®], SMART amp[™], SMART lab[™], SMART Learning Suite Online and more

Ultra short-throw interactive display — get a large, easy-to-read 100" image from as little as 11" away with virtually no shadow interference

Long-life, low-cost lamps - lasts up to 10,000 hours in ECO Mode³

 $\mbox{DuoLink}$ — install two BrightLink displays side-by-side to create one seamless interactive surface^4







BrightLink[®] 695Wi WXGA 3LCD Ultra Short-throw Interactive Display

Specifications

Projection System Epson® 3LCD, 3-chip technology Projection Method Front/rear/wall mount/table mount Driving Method Epson Poly-silicon TFT Active Matrix Pixel Number 1,024,000 dots (1280 x 800) x 3 Color Brightness¹ Color Light Output: 3,500 lumens White Brightness¹ White Light Output: 3,500 lumens Interactive Color Brightness¹ Color Light Output: 3,500 lumens Interactive White Brightness¹ White Light Output: 3,500 lumens Aspect Ratio 16:10 Native Resolution 1280 x 800 (WXGA) Lamp Type 250 W UHE Lamp Life⁴ ECO Mode: Up to10,000 hours Normal Mode: Up to 5,000 hours **Size (Projected)** (4:3) 53" - 88"; (16:10) 60" - 100"; (16:9) Keystone Correction (Manual) Horizontal: ±3 degrees; Vertical: ±3 degrees USB Plug 'n Play Mac OS 10.7/10.8/10.9/10.10/10.11/ macOS® 10.12.x USB Plug 'n Play for Windows® Windows Vista®/Windows 7/ Windows 8/Windows 10 Contrast Ratio Up to 14,000:1 Color Reproduction Up to 1 billion colors

Projection Lens

Type Manual focus F-number 1.6 Focal Length 3.7 mm Throw Ratio Range (16:10) 0.28 - 0.37, (4:3) 0.33 - 0.45, (16:9) 0.28 - 0.37Zoom Ratio Digital zoom: 1.0 – 1.35x

Other

Display Performance

NTSC: 480 lines PAL: 576 lines (Depends on observation of the multi-burst pattern) Input Signal NTSC/NTSC4.43/PAL/M-PAL/N-PAL/PAL60/SECAM Speaker 16 W monaural **Operating Temperature** 41 $^\circ$ to 104 $^\circ$ F (5 $^\circ$ to 40 $^\circ$ C) **Power Supply Voltage** 100 – 240 V ±10%, 50/60 Hz Power Consumption 373 W

2.2 W Standby (Communication On) 0.23 W Standby (Communication Off)

Fan Noise ECO Mode: 29 dB

Normal Mode: 35 dB Security Kensington lock provision, security anchor bar, Password Protection function

Interactivity

Interactive Technology Infrared, 850 nm Interactive Area (Image Size) 60" - 100" diagonal (16:10, WXGA) Interactive Modes Computer Interactivity/Input, PC-free with Whiteboard Annotation, Pen: Dual User, Finger Touch: Up to 6 points of touch

PC-free Annotation Two pens and two fingers Interactive Tools Epson Easy Interactive Tools, Dual User PC Interactive Sources USB, HDMI, Computer 1, Computer 2, LAN PC-free Annotation Devices Document Cameras, DVD/Blu-ray Disc[®] player, iPod[®]/iPad[®] devices, Chromebooks

Interfaces

2x HDMI® 1x HDMI/MHL® Computer/Component video: 1x D-sub 15 pin Composite video: 1x RCA (Yellow) Audio in: 3x Mini stereo USB connector: 1x Type B (USB display, audio and mouse control interactivity) USB connector: 1x Type A (USB memory/document camera) 1x RJ-45 Serial: 1x RS-232c Monitor Out/Computer 2: 1x D-sub 15 pin Audio Out: 1x Mini stereo Microphone: 1 x Mini stereo Wireless LAN port: 802.11 b/g/n (optional – module sold separately) Interactive Synchronization Mini stereo In Interactive Synchronization Mini stereo Out Touch Unit Connection Port

Interactivity (continued)

Calibration Method Automatic or Manual Interactive Connectivity USB cable for non-networked Interactive Software Requirements Epson Easy Interactive Driver (Mac and PC – required for DucLink): Windows and Linux: driver required Mac: Mac OS X® 10.7/10.8/10.9/10.10/10.11/macOS 10.12.x Epson Easy Interactive Tools for Windows and Mac System Compatibility

Microsoft[®] Windows Vista, Windows Vista SP1, Windows Vista SP2 (All editions except for Starter), Windows 8/8.1, Windows 10, Windows 7 SP1 (All editions except for Starter), Mac OS 10.7/10.8/10.9/10.10/10.11/macOS 10.12.x Gestures Requires Windows 7 or later, or Mac OS 10.7 or later

SMART Notebook Requirements

Supported Operating Systems Windows 7 SP1, Windows 8/8.1, Windows 10, Mac OS X 10.9, 10.10, 10.11, macOS 10.12

Minimum Processor Intel Core 2 Duo Minimum RAM 2GB (4GB for UHD displays)

Minimum Hard Disk Space 3GB (Windows); 3GB (Mac)

Interactive Input Device

Type of Interactive Input Device Digital pen Interactive Pen Functions Mouse Functions (left and right click), Electronic Pen, LED Battery Status Indicator Interactive Pen Power AA battery, rechargeable Compatible Pen Battery Types Eneloop® batteries (included), Manganese dry cell, alkaline dry cell Interactive Pen Dimensions 6.3" x 0.94" (diameter)

Interactive Pen Weight 1.1 oz (without battery)

Dimensions (W x D x H)

14.5" x 15.8" x 5.9'

Weight 12.8 lb **Remote Control**

Features Computer Video/HDMLUSB LAN Source Search Power, Aspect, Color Mode, Volume, E-Zoom, AV Mute, Freeze, Menu, Auto, Enter, ESC, Pointer, Home, Split, Pen Mode, Link Menu **Operating Angle**

Rear: Right/left: -55 to +55 degrees, Upper/lower: +75 to +15 degrees Front: Right/left: -30 to +30 degrees, Upper/lower: 0 to +60 degrees Operating Distance 19.7 ft (6 m)



Eco Features

RoHS compliant Recyclable product5

Epson America, Inc. is a SmartWay® Transport Partner⁶

Support

Epson ConnectionSM

Pre-sales support U.S. and Canada: 800-463-7766 www.epson.com

Service Programs 2-year projector limited warranty, Epson Road Service program, PrivateLine® dedicated toll-free support and 90-day limited lamp warranty

What's in the Box

BrightLink 695Wi ultra short-throw interactive projector, fingertouch module, touch module mounting bracket, touch module cable, Quick Start Guide, power cable, USB A/B cable, USB extender cable, electronic user manual, interactive driver for Mac and PC, Epson Easy Interactive Tools, Network Management software, projector remote control, two (2) interactive pens, pen tray, two (2) AA batteries (for interactive pens) plus battery charger, two (2) AA batteries (for remote), SMART Learning Suite redemption code

Ordering Information

0	
BrightLink 695Wi	V11H740522
Genuine Epson Lamp	V13H010L91
Air Filter	V13H134A49
PowerLite [®] Pilot [™] 2 (ELPCB02)	V12H614020
Active Speakers (ELPSP02)	V12H467020
Wireless 802.11b/g/n LAN Unit (ELPAP10)	V12H731P02
100" Whiteboard	V12H831000
100" Da-Lite [®] IDEA Screen [®]	V12H831001
Interactive Pen A (orange)	V12H773010
Interactive Pen B (blue)	V12H774010
Replacement Pen Tips (hard/Teflon®)	V12H775010
Replacement Pen Tips (soft/felt)	V12H776010
Ultra Short-throw Wall Mount (ELPMB46)	V12H777020

Learn more about how our products can empower your institution. Visit us at www.epson.com/foreducation

1 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with ISO 21118.] **2** For wireless functionality, including via the Epson IProjection[™] App, the projector must be configured on a network, either through the Ethernet port on the projector (check model specifications for availability) or via a wireless connection. App dees not support all files and formats. See www.epson.com for details, | **3** Lamp life will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time. | **4** Requires Easy Interactive Driver. Certain functionality is only available through Ethernet port on for letting to be preventing upon the coles (EIT) software. For a list of supported operating systems, visit www.epson.com | **5** For convenient and reasonable recycling options, visit www.epson.com/recycle | **6** SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.

Better Products for a Better Future eco.epson.com

Epson America, Inc.

Epson Canada Limited 3840 Kilroy Airport Way, Long Beach, CA 90806

185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com www.epson.ca

Specifications and terms are subject to change without notice. EPSON and PowerLite are registered trademarks, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future and Epson iProjection are trademarks of Seiko Epson Corporation. BrightLink and PrivateLine are registered trademarks, Pilot is a trademark and Epson Connection is a service mark of Epson America, Inc. iPad, iPod, Mac, macOS and OS X are trademarks of Apple, Inc., registered in the U.S. and other countries. Android and Chromebook are trademarks of Google Inc. Microsoft, Windows and Windows Vista are either registered trademarks of trademarks of Microsoft Corporation in the United States and/or other countries. Da-Lite and IDEA Screen are registered trademarks of Milestone AV Technologies. SmartWay is a registered trademark of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2018 Epson America, Inc. Com-SS-Oct-13 CPD-53494R2 6/18

nteractive Displays

Contact:

