

WorkForce® Pro EP-C800

Workgroup Color Printer

Wireless | Print | Ethernet | PCL1/PS



The compact network printer with fast speeds and low printing costs.



PrecisionCore technology — simple, smart and clean solution that delivers outstanding quality with low waste

Powerful business productivity — fast print speeds up to 25 ISO ppm† (black/color) with zero warmup time, plus fast first page out and auto 2-sided printing

Engineered for reliable performance — recommended monthly print volume: 2,500 – 10,000 pages

Energy efficient — low power consumption

Minimal user intervention — Replaceable Ink Pack System with Extra High-capacity packs lets you print up to 50,000 ISO pages black/20,000 ISO pages color² without changing the ink packs; paper capacity up to 1,830 pages with optional trays

Compact design — for a streamlined, efficient workstation

Remarkable image quality — DURABrite® Ultra fast-drying, water-resistant pigment ink delivers vivid color and crisp black text

Robust security — full suite of advanced security features

Compatible with Epson Solutions Suite and industry-leading third-party solutions — Epson Open Platform for seamless workflow integration

Designed for use exclusively with Epson ink packs*.



WorkForce Pro EP-C800 Workgroup Color Printer

Printing Technology PrecisionCore 4S printhead 4-color inkjet Printer Language Epson ESC/P-R, PCL 5 emulation¹, PCL 6 emulation1, PostScript 3 emulation

Maximum Print Resolution 4800 x 1200 optimized dpi ISO Print Speed† 25 ISO ppm (black), 25 ISO ppm (color) 2-Sided ISO Print Speed† 14 ISO ppm (black), 14 ISO ppm (color) Maximum Draft Print Speed^{††} 34 ppm (black), 34 ppm (color) Minimum Ink Droplet Size As small as 3.8 picoliters Recommended Monthly Print Volume³ 2,500 to 10,000 pages

Mobile Printing

Epson Connect™ Solutions⁴ Epson Email Print, Epson Smart Panel™, Mobile App, Epson Remote Print, Other Apple® AirPrint®, Mopria™, Microsoft® Universal Print,

Security

Security Features PIN number certification for job release, user control access, printer and network settings via Web Config using printer's IP address, SSL/TLS security, IPsec

Connectivity

Standard Connectivity

Hi-Speed USB (compatible with USB 2.0 specification) Wireless LAN IEEE Standard Connectivity: Wireless (802.11 b/g/n/a/ac/k/v/r)5

Wi-Fi Wired Ethernet (1000 Base-T/100 Base-TX/10 Base-T) Wi-Fi Direct[©]

Network Protocols TCP/IP v4/v6

Network Printing Protocols IPP, LDP, Port 9100, WSD Network Management Protocols SNMP, HTTP, DHCP, BOOTP. APIPA, DDNS, mDNS, SNTP, Ping, SLP, WSD, LLTD

WLAN Security WEP 64 Bit, WEP 128 Bit, WPA PSK (AES), WPA2-Enterprise, WPA2-PSK (TKIP/AES), WPA3-Enterprise, WPA3-SAE (AES)

Operating Systems

Windows® 10 (32-bit, 64-bit), Windows 8 (32-bit, 64-bit), Windows 7 (32-bit, 64-bit), Windows Server® 2012 R26, Windows Server 2012⁶, Windows Server 2008 R2⁶, Windows Server 2008⁶, macOS[®] 11 – 14⁷, Mac OS X 10.9.5 - macOS 14.x

Solutions Suite Support

Epson Device Admin, Epson Print Admin, Epson Remote Services (support ES Agent)

Epson Open Platform Capability for 3rd party solution support

Paper Handling

PC-free Paper Support Plain (Letter, A4), Photo (Letter, A4, 8" x 10", 5" x 7", 4" x 6"

Maximum Paper Size 8.5" x 47.2"

Paper Sizes 3.5" x 5", 4" x 6", 5" x 7", 8" x 10", 8.5" x 11", 8.5" x 14", A4, A6, half letter, executive, user definable (3" x 5" - 8.5" x 47")

Paper Types Plain paper, Epson Bright White Paper, Epson Presentation Paper Matte, Epson Premium Presentation Paper Matte, Epson Premium Presentation Paper Matte Double-sided, Epson Photo Glossy, Epson Premium Photo Paper Glossy, Epson Ultra Premium Photo Paper Glossy, Epson Premium Photo Paper Semi-gloss

Envelope Types No. 10

Input Paper Capacity 250 sheets plain paper (250 sheets plain paper x 1 tray); Rear Feed: 80 sheets (1,830 sheets total with three optional 500-sheet paper trays); 10 envelopes

Display 2.4" color

Temperature

Operating: 50 ° to 95 °F (10 ° to 35 °C) Storage: -4 ° to 104 °F (-20 ° to 40 °C)

Relative Humidity

Operating: 20 - 80%

Storage: 5 - 85% (no condensation)

Sound Level

Power: 6.9 dB(A) Pressure: 54 dB(A)

Rated Voltage AC 100 - 240 V Universal (Automatic)

Rated Frequency 50 - 60 Hz Rated Current 0.7 A - 0.4 A

Power Consumption

Standalone: Approx. 24 W ISO 24712 Standby: Approx. 8 W Sleep: Approx. 1.2 W Power Off: Approx. 0.2 W ENERGY STAR® qualified

Typical Energy Consumption(TEC)8 0.16 kWh

Safety Approvals Safety standards UL60950, CSA C22.2 No. 60950 EMI FCC Part 15 subpart B class B, CAN/CSA-CEI/IEC,

Telecom Regulations FCC Part 68 (U.S.A.), IC/CS03 (Canada)

Country of Origin Indonesia

Weight and Dimensions (W x D x H)

Printing: 16.7" x 22.8" x 23.8' Storage: 16.7" x 21.1" x 20.2'

Weight: 48 7 lb

Warranty

1-year limited warranty in the U.S. and Canada

Epson PreferredSM Plus Extended Service Plans⁹

Next-Business-Day Whole Unit Exchange¹⁰ FPPWFC800F1 (available for up to a total of 5 years of continuous coverage)

What's Included

WorkForce Pro EP-C800 color printer, power cord, DURABrite® Ultra Ink packs² – 4 initial ink packs: Black, Cyan, Magenta, Yellow

Software Available¹¹

Epson printer driver, PCL 5 driver emulation1, PCL 6 driver emulation¹, PostScript 3, Epson Document Capture Pro

Ink Type DURABrite Ultra pigment ink Ink Palette Cyan, Magenta, Yellow and Black Ink Pack Configuration 4 individual ink packs

Replacement Ink Packs²

T12N Black, Cyan, Magenta, Yellow (Yield, ISO pages -Black: 10,000, Color: 5,000) T12P Black, Cyan, Magenta, Yellow

(Yield, ISO pages - Black: 50,000, Color: 20,000)

Printer is designed for use with Epson ink packs only, not thirdparty ink systems*

Save up to 50% of your paper supply with auto 2-sided printing **ENERGY STAR qualified** RoHS compliant

Epson America, Inc. is a SmartWay® Transport Partner12

Ordering Information

Oracining initialitation	
WorkForce Pro EP-C800	C11CK21201
Ink Maintenance Box	C12C938211
Optional Input Tray	C12C937901
Authentication Device Table	C12C939531
Low Optional Cabinet	C12CFM7066
Medium Optional Cabinet	C12CFM7067
Tall Optional Cabinet	C12CFM7068

- * This product uses only genuine Epson-brand ink packs. Other brands of ink supplies are not compatible and, even if described as compatible, may not function properly or at all.
- † Black and color print speeds are measured in accordance with ISO/IEC 24734. Actual print times will vary based on factors including system configuration, software and page complexity. For more
- †† Maximum print speeds are measured with text patterns in Draft Mode on plain paper. Actual print times will vary based on factors including system configuration, software, and page complexity.
- 1 Not all media types are supported for PCL printing. | 2 Replacement ink pack yields are estimated based on ISO/IEC 24711 test in Default Mode printing continuously. Ink pack yields vary considerably for reasons including images printed, print settings, temperature and humidity. Yields may be lower when printing infrequently or predominantly with one ink color. All ink colors are used for printing and printer maintenance, and all colors have to be installed for printing. For print quality, part of the ink from the included ink packs is used for printer startup and a variable amount of ink remains in the ink pack after the "replace ink pack" signal. For details, see www.epson.com/inkinfo | 3 Monthly duty cycle up to 45,000 is the highest duty a user could expect in a month, based on near constant operation of a device of this kind. It is not recommended that the device be run at this duty. For best device performance, run the device at the recommended duty of 2,500 pages per month. | 4 Most features require an Internet connection to the printer, as well as an Internet- and/or email-enabled device. | 5 Wi-Fi CERTIFIEDTM; level of performance subject to the range of the router being used. Wi-Fi Direct may require printer software. | 6 Only printing is supported under Windows Server OS. | 7 Some applications and/or functions may not be supported under Mac OS X. | 8 Based on ENERGY STAR TEC measurement methodology; 288 prints/day, actual electricity consumption may vary depending on printer use. For more information, see www.energystar.gov | 9 Product comes with a 1-year limited warranty with the option to purchase extended service plans up to a total of 5 years of continuous coverage. Extended service plan can be purchased at any time that you are covered under an Epson limited warranty or Epson Extended Service Plan. See individual service plan for details. | 10 Expedited shipping not available in all areas. Orders must be placed and processed by 1 p.m. Pacific Time for Next-Business-Day delivery. See limited warranty or service plan for details. | 11 Internet access is required to install all OS drivers and software. | 12 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.

See the latest innovations from Epson Business Solutions at www.epson.com/forbusiness





Epson America, Inc.

3131 Katella Ave., Los Alamitos, CA 90720

Epson Canada Limited

185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com www.epson.ca

Specifications and terms are subject to change without notice. EPSON, DURABrite, PrecisionCore and WorkForce are registered trademarks, Epson Connect, Epson iPrint and Precision Core Heat-Free Technology are trademarks of Seiko Epson Corporation.

AirPrint, Apple, Mac and OS X are trademarks of Apple Inc., registered in the U.S. and other countries. Google Cloud Print is a trademark of Google LLC. Windows, Windows Server and Windows Vista are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Wi-Fi Direct® is a registered trademark and Wi-Fi CERTIFIED™ is a trademark of Wi-Fi Alliance®. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks Copyright 2024 Epson America, Inc. CPD-64377R2 10/24

C	OI	π	a	C	ι:

(