

LARGE FORMAT PHOTO PRINTERS
SURECOLOR SC-P6530E/P6530D/
P8530D/P8530DL/P8530DM

EPSON

AMPLIFY YOUR IDEAS WITH TOP CLASS PRINT QUALITY.



Transform your ideas into striking true-to-life prints with Epson's P-series printers.

Nothing beats seeing life injected into your ideas, turning them into picturesque prints in vivid and vibrant colours with top-class accuracy. Equipped with the Epson's proprietary PrecisionCore™ MicroTFP printheads, the Epson SureColor P-Series photographic printers take pride in their precise and reliable print productivity, along with the colour-accurate reproduction with Epson genuine UltraChrome PRO 6 inks. With high installation flexibility and seamless printing workflow, increase your print efficiency today!


LFP New Architecture Run


ULTRACHROME
PRO 6 INK


PRECISIONCORE
PRINTHEAD

SPECIFICATIONS

MODEL NUMBER		SC-P6530E	SC-P6530D
SKU Number		C11CJ48403	C11CJ49403
Printing Technology		PrecisionCore Inkjet Technology, Variable-Sized Droplet Technology	
Printing Method		PrecisionCore™ MicroTFP® Printhead	
Print Head		9,600 Nozzles	
Nozzle Configuration		Pk:1,600, Mk:1,600	
Black		C:1,600, M:1,600, Y:1,600, Gray:1,600	
Colour		2,400 x 1,200 dpi	
Maximum Resolution		3.5pl	
Minimum Ink Droplet Volume		A1 Size Premium Glossy Photo Paper 170gsm, 1200dpi x 1200dpi	
Printing Specifications		EPSON Standard (sRGB) / Quality: 111 sec	
Print Speed		Right: Min. 3mm ¹ / Left : Min. 0mm ¹	
Margin	Roll Paper	Top: Min. 3mm ¹ / Bottom: Min. 1mm ¹	
	Cut Sheet	0.08 mm ² (0.02 mm ³)	
Minimum Line Width			
Ink System		Pigment Ink	
Ink Type		UltraChrome Pro 6 Ink	
Ink Brand Name		Cyan, Magenta, Yellow, Grey, Photo Black, Matte Black	
Colour		350 mL, 700 mL	
Ink Capacity		Ink Cartridge	
Ink Case			
Paper Handling			
Paper Path		Roll (Single Roll), Cut Sheet (Manual Feed), Poster Board (Manual Feed)	Roll (Double Roll), Cut Sheet (Manual Feed), Poster Board (Manual Feed)
Paper Feed Method		Friction Feed	
Maximum Roll Diameter		Max. 170 mm ⁴	
Maximum Roll Weight		6.8kg	
Paper Width (Roll)		254 – 610 mm	
Paper Width (Cut Sheet)		203 – 610 mm	
Paper Thickness (Roll)		0.07 – 0.8 mm	
Paper Thickness (Manual)		Cut Sheet: 0.07 – 0.8 mm / Poster Board: 0.8 – 1.5 mm	
Maximum Printable Length		91 m ⁵	
Borderless Sizes		254 mm (10"), 300 mm (11.8"), 330 mm (13"), 356 mm (14"), 406 mm (16"), 432 mm (17"), 500 mm (19"), 508 mm (20"), 515 mm (20.3"), 594 mm (23"), 610 mm (24")	
Roll Paper Remaining		The remaining amount is managed by the barcode printed on roll paper	
Connectivity			
Interface		SuperSpeed USB, 100BASE-TX/1000BASE-T/IEEE802.11b/g/n/ac, USB Memory Stick	
Printer Language		ESC/P raster	ESC/P raster, HP-GL/2*, HP RTL*, Adobe PostScript 3, Adobe PDF 1.7
USB Direct Print		Yes	
Memory		4 GB	
HDD (Optional)		SSD 960 GB	
Operating System			
PC System Requirement		Windows 10, 8.1, 8, 7, Windows Vista, Windows XP (32bit/64bit) Windows Server 2019/2016/2012 R2/2012/2008/2003 R2/2003 SP2 or later	
Mac System Requirement		Mac OS X 10.6.8 or later, Mac OS 11 or later	
Utility Software			
Bundled in CD		Windows - Printer driver - EpsonNet Setup - EpsonNet Print - EpsonNet Config SE - EPSON manuals - Manual Launcher - LFP Print Plug-in for Office	
Web Delivery		Epson Media Installer - EpsonNet SetupManager - Epson Device Admin - Epson Edge Dashboard - Epson Print Layout - Epson Print Automate - Order Controller Mac - Printer driver - EpsonNet Config SE - EPSON manuals - Epson Media Installer - Epson Edge Dashboard - Epson Print LayoutiOS/Android - Epson Smart Panel	
Electrical Specifications			
Voltage		AC 100 – 240 V, 50/60 Hz	
Rated Current		AC 100V 3.4AAC 100-240V 3.4-1.6A	
Power Consumption		Operating: Approx. 75 W, Ready: Approx. 32 W, Sleep: Approx. 2 W, Standby: Approx. 0.3 W	
Environmental Conditions			
Temperature		Operating: 10°C to 35°C / Storage: -20°C to 40°C	
Humidity		Operating: 20% to 80% (no condensation) Storage: 5% to 85% (no condensation)	
Dimensions & Weight			
Dimension (W x D x H)		1,365 x 499 x 975 mm	
Weight		Approx. 115.2 kg	Approx. 115.6 kg

¹ Might differ depends on applications/media.

² ISO/IEC 24790, Single weight matte paper, CAD/line drawing, speed, high speed=Off, finest detail=On.

³ Addressable.

⁴ Depending on the thickness of the paper. It is larger than the available outer diameter size. If roll paper is used, please confirm that it is within the outside diameter range.

⁵ Printable length is limited depending on restrictions of operating systems or applications.

Dimensions and Weight


SC-P6530E

Weight: Approx. 115.2 kg



SC-P6530D

Weight: Approx. 115.6 kg



WHAT'S IN THE BOX

- Printer
- Initial ink cartridge (110 mL)
- AC power cable
- Setup guide
- Software CD-ROM
- Maintenance box

OPTIONS

Production Stacker (24")

SSD Unit (C12C936671)

CONSUMABLE

Ink Cartridge

Photo Black	350 mL	C13T48Y100
Cyan	350 mL	C13T48Y200
Magenta	350 mL	C13T48Y300
Yellow	350 mL	C13T48Y400
Grey	350 mL	C13T48YE00
Matte Black	350 mL	C13T48Y800
Photo Black	700 mL	C13T48R100
Cyan	700 mL	C13T48R200
Magenta	700 mL	C13T48R300
Yellow	700 mL	C13T48R400
Grey	700 mL	C13T48RE00
Matte Black	700 mL	C13T48R800
Maintenance Tank		C13S210115
Borderless Maintenance Box		C13S210116
Printer Cutter Blade		C13S210117
Cleaning Stick		C13S090013

*It is recommended to do test before purchasing printer if HP-GL/2 or HP RTL direct print is used, because the support is dependent on application or data.

© 2024 Epson India Pvt. Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON is registered trademark of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.

Dealer's Stamp

Information correct at time of printing.
Printed February 2024.

SPECIFICATIONS

MODEL NUMBER	SC-P8530D	SC-P8530DM	SC-P8530DL
SKU Number	C11CJ50402	C11CJ51403	C11CJ75403
Printing Technology	PrecisionCore Inkjet Technology, Variable-Sized Droplet Technology		
Printing Method	PrecisionCore™ MicroTFP® Printhead		
Print Head	9,600 Nozzles		
Nozzle Configuration	Black		
	Colour		
Maximum Resolution	2,400 x 1,200 dpi		
Minimum Ink Droplet Volume	3.5 pl		
Printing Specifications			
Print Speed	B0 size Premium Glossy Photo Paper 170 gsm:		
	152 sec (Speed), 281 sec (Quality), 614 sec (Max Quality)		
	Plain Paper: 35 sec (Draft), 46 sec (Speed), 258 sec (High Quality)		
	Poster – B0 size Epson Premium Glossy Photo Paper 170gsm 1200dpi x 1200dpi:		
	Standard(sRGB)/Quality: 281 sec		
	Right: Min. 3 mm ¹ / Left : Min. 0 mm ¹		
	Top: Min. 3 mm ¹ / Bottom: Min. 1 mm ¹		
Margin	Roll Paper		
	Cut Sheet		
Scanning Specifications			
Max. Scan Speed		10 ips	
Max. Optical Resolution		600 dpi	
Scanning Specifications			
Max. Scan Speed	10 ips		
Max. Optical Resolution	600 dpi		
Copying Specifications			
Scaling		25 – 755%	
Max. Copy		99 copies	
Ink System			
Ink Type	Pigment Ink		
Ink Brand Name	UltraChrome Pro 6 Ink		
Colour	Cyan, Magenta, Yellow, Grey, Photo Black, Matte Black		
Ink Capacity		1,600 mL	
Ink Case		Ink Cartridge	Ink Supply Unit (Bulk Ink Solution)
Paper Handling			
Paper Path	Roll (Double Roll), Cut Sheet (Manual Feed), Poster Board (Manual Feed)		
Paper Feed Method	Friction Feed		
Maximum Roll Diameter	Max. 170 mm ²		
Maximum Roll Weight	12.5kg		
Paper Width (Roll)	254 – 1,118 mm		
Paper Width (Cut Sheet)	203 – 1,118 mm		
Paper Thickness (Roll)	0.07 – 0.8 mm		
Paper Thickness (Manual)	Cut Sheet: 0.07 – 0.8 mm / Poster Board: 0.8 – 1.5 mm		
Maximum Printable Length	91 m ³		
Borderless Sizes	254 mm (10"), 300 mm (11.8"), 330 mm (13"), 356 mm (14"), 406 mm (16"), 432 mm (17"), 500 mm (19"), 508 mm (20"), 515 mm (20.3"), 594 mm (23"), 610 mm (24"), 700 mm (27.5"), 728 mm (28.6"), 841 mm (33"), 914 mm (36"), 1030 mm (40.5"), 1188 mm (44")		
Roll Paper Remaining	The remaining amount is managed by the barcode printed on roll paper		
Connectivity			
Interface	SuperSpeed USB ¹ , 100BASE-TX /1000BASE-T/IEEE802.11b/g/n/ac		
Printer Language	ESC/P raster, HP-GL/2*, HP RTL*, Adobe PostScript 3, Adobe PDF 1.7		
USB Direct Print	Yes		
Memory	4 GB		
HDD (Optional)	SSD 960 GB		
Operating System			
PC System Requirement	Windows 10, 8.1, 8, 7, Windows Vista, Windows XP (32bit/64bit)		
	Windows Server 2019/2016/2012 R2/2012/2008/2003 R2/2003 SP2 or later		
Mac System Requirement	Mac OS X 10.6.8 or later, Mac OS 11 or later		
Utility Software			
Bundled in CD	Windows - Printer driver - EpsonNet Setup - EpsonNet Print - EpsonNet Config		
	SE - EPSON manuals - Manual Launcher - LFP Print Plug-in for Office - PS		
	Driver - PS Folder		
	Windows - Epson Media Installer - EpsonNet SetupManager - Epson Device		
	Admin - Epson Edge Dashboard - Epson Print Layout - Epson Print Automate -		
	Epson Edge Print (Option) - Epson Print Admin (Option) - Order Controller (Option)		
	Mac - Printer driver - EpsonNet Config SE - EPSON manuals - Epson Media		
	Installer - Epson Edge Dashboard - Epson Print Layout - PS DriveriOS/Android -		
	Epson Smart Panel		
Electrical Specifications			
Voltage	AC 100 – 240 V, 50/60 Hz		
Rated Current	AC 100V 3.4AAC 100-240V 3.4-1.6A		
Power Consumption	Operating: Approx. 70 W		Operating: Approx. 75 W
	Ready: Approx. 32 W		Ready: Approx. 32 W
	Sleep: Approx. 2.0 W		Sleep: Approx. 2.0 W
	Standby: Approx. 0.3 W		Standby: Approx. 0.3 W
Environmental Conditions			
Temperature	Operating: 10°C to 35°C / Storage: -20°C to 40°C		
Humidity	Operating: 20% to 80% (no condensation), Storage: 5% to 85% (no condensation)		
Dimensions & Weight			
Dimension (W x D x H)	1,848 x 499 x 975 mm		
Weight	Approx. 155 kg		Approx. 165 kg

¹ Might differ depends on applications/media.


² Depending on the thickness of the paper. It is larger than the available outer diameter size. If roll paper is used, please confirm that it is within the outside diameter range.

³ Printable length is limited depending on restrictions of operating systems or applications.

Dimensions and Weight


SC-P8530D / P8530DM

Weight: Approx. 155 kg



SC-P8530DL

Weight: Approx. 165 kg



WHAT'S IN THE BOX

- Printer
- Initial ink cartridge (110 mL)
- AC power cable
- Setup guide
- Software CD-ROM
- Maintenance box

OPTIONS

Roll Feed Spindle (44") (C12C936171)

Production Stacker (44") (C12C937131)

SSD Unit (C12C936671)

CONSUMABLE

Ink Cartridge

Photo Black	350 mL	C13T48Y100
Cyan	350 mL	C13T48Y200
Magenta	350 mL	C13T48Y300
Yellow	350 mL	C13T48Y400
Grey	350 mL	C13T48YE00
Matte Black	350 mL	C13T48Y800
Photo Black	700 mL	C13T48R100
Cyan	700 mL	C13T48R200
Magenta	700 mL	C13T48R300
Yellow	700 mL	C13T48R400
Grey	700 mL	C13T48RE00
Matte Black	700 mL	C13T48R800
Maintenance Tank		C13S210115
Borderless Maintenance Box		C13S210116
Printer Cutter Blade		C13S210117
Cleaning Stick		C13S090013

*It is recommended to do test before purchasing printer if HP-GL/2 or HP RTL direct print is used, because the support is dependent on application or data.

© 2024 Epson India Pvt. Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON is registered trademark of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.

Dealer's Stamp

Information correct at time of printing.
Printed February 2024.

EPSON

EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A, No.1,
Murphy Road, Ulsoor, Bangalore - 560 008.
Tel: 080-4566 5000 Fax: 080-4566 5005

Scan the QR code to contact an Epson representative close to you.



CONTACT EPSON TODAY! EMAIL: pravin@eid.epson.co.in



Epson Helpline: For product info or service - 1800 425 0011
For service: 1800 123 001 600 or 1860 3000 1600 (9 am - 6 pm) (Mon - Sat)
Email: lfp@epson-india.in

www.epson.co.in