



Presenting cost-effective borderless A3\* photo printing solutions perfectly suited for design drawing, stunning photos, and versatile media printing such as DVD/CD and PVC/ID card printing. Now with an integrated ink tank design, the printer is compact in size and fits easily into different spaces. The Epson L8050 and L18050 models also come with replaceable parts and can be easily maintained. Download Epson Smart Panel app to your mobile device and turn it into an intuitive control centre that enables you to power On/Off and set up your printer effortlessly.











Borderless Printing up to A3+\*

YEAR

 $\Box$ 













## **Quality Meets Productivity**

Enjoy superior quality photos made possible with 6 colour dye inks, coupled with fast print speed of up to 8.0 ipm

# Sustainability in Mind

Heat-Free Technology enables low power consumption and requires fewer replacement parts, minimising total environmental impact.

### Ease of Use

Epson Smart Panel mobile application facilitates print head cleaning, enabling easy maintenance and preventing ink wastage.

SPECIFICATIONS			Dimensions & Weight
Product Name	L8050	L18050	L8050
Printer Type	Print	1 = 10000	Weight: 6.0 kg
Printing			
Printing Technology	Micropiezo Printhead		150 mm
Nozzle Configuration	180 x 1 nozzles Black		
1102216 Goringaradori	180 x 1 per colour (Cyan, Magenta, Yellow, Light Cyan, Light Magenta)		
Print Direction	Bi-directional printing		403 mm
Maximum Resolution	5760 x 1440 dpi (with Variable-Sized Droplet Technology)		L18050
Minimum Ink Droplet Volume	1.5 pl		Weight: 8.0 kg
Print Speed*1	1.0 βι		
Draft Text - Memo, A4 (Black#1 / Colour#2)	Up to 22 ppm / 22 ppm		<b></b>
ISO 24734, A4 (Black / Colour)	Simplex: Up to 8.0 ipm / 8.0 ipm		150mm
ISO 24734, A3 (Black / Colour)	-   Simplex: Up to 3.0 ipm / 3.0 ipm		
First Page Out Time (Black / Colour)	Approx 14 app / 14 app	Approx. 14 sec / 14 sec	
Photo Default - 10 x 15 cm / 4 x 6" <sup>2 #3</sup>	Approx. 14 sec / 14 sec	Approx. 14 sec / 14 sec	523mm
(Border / Borderless)	A 05 / 05	A	323/11/1
Photo Default - A4 <sup>-2</sup>	Approx. 25 sec / 25 sec	Approx. 27 sec / 27 sec	
(Border / Borderless)			*1 Print speed (Pages Per Minute) is calculated when printed on A4 plain paper in the fastest mode, 10 x
Photo Default - A3 <sup>-2</sup>	Approx. 60 sec / 64 sec	Approx. 65 sec / 65 sec	15 cm photo print speed when printed on Epson
(Border / Borderless)		A	Premium Glossy Photo Paper. Print speed may vary depending on system configuration, print
Printer Language	- 	Approx. 110 sec / 115 sec	mode, document complexity, software, type of
CD/DVD Printing	ESC/P-R, ESC/P Raster		paper used and connectivity. Print speed does not include processing time on host computer.
PVC/ID card printing	Yes		militade processing time on most compatible.
, ,	Yes, 54 x 86 mm		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Automatic 2-sided printing	No		- Chin
Paper Handling			- NO
Paper Feed Method	Friction feed		424
Number of Paper Trays	1		
Paper Hold Capacity			#1 #2 #3
Input Capacity	Up to 100 sheets of A4 Plain Paper (80g/m²)	Up to 100 sheets of A3 Plain Paper (80g/m²)	Black Text Colour Photo 4R
	20 sheets of Premium Glossy Photo Paper	10 sheets of Premium Glossy Photo Paper	*2 When printed on Epson Premium Glossy Photo Paper.
Output Capacity	Up to 100 sheets of A4 Plain Paper	Up to 100 sheets of A3 Plain Paper	*3 Otherwise 3 mm top, left, right, bottom.
	Up to 30 sheets of Premium Glossy Photo Paper	Up to 30 sheets of Premium Glossy Photo Paper	*4 Default mode in accordance with ISO7779 for MFPs.
Paper Size	A4, Letter, 8 x 10", 5 x 7", 4 x 6",	A3+, A3, US B, 11 x 14", Legal, A4, Letter,	*5 In accordance with ISO 24711/24712. Actual yields will
	16:9 Wide, 3.5 x 5",	8 x 10", 5 x 7", 4 x 6", 16:9 Wide, 3.5 x 5",	vary considerably for reasons including images printed,
	User Defined (89 x 127 to 215.9 x 1200 mm)	User Defined (89 x 127 to 329 x 2000 mm)	print settings, temperature and humidity. Yields may be lower when printing infrequently or predominantly with
Maximum Paper Size	215.9 x 2000 mm (8.5 x 78.74")	329 x 2000 mm (12.95 x 78.74")	one ink colour. A variable amount of ink remains in the
Print Margin	0 mm top, left, right, bottom via custom se	ettings in printer driver <sup>*3</sup>	cartridges after the "replace cartridge" signal. Part of the ink from the first cartridges is used for priming the
Interface			printer. Ink is used for both printing and print head maintenance. All inks are used for both black and
USB	USB 2.0		colour printing.
Network	Wi-Fi IEEE 802.11b/a/n, Wi-Fi Direct	Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct	
Network Protocol		TCP/IPv4, TCP/IPv6	
Network Management Protocols	SNMP, HTTP, DHCP, APIPA, DDNS, mDNS, SLP, WSD, LLTD		Test Patterns provided in ISO/IEC 29103. Quoted yields are NOT based on ISO/IEC 29102. Quoted
			yields may vary depending on the images that you are printing, the paper type that you are using, the
Mobile and Cloud Printing			frequency of your prints and environmental
Epson Connect	Epson iPrint, Epson Email Print, Remote Print Driver		conditions such as temperature.  ^7 CD/DVD Printing
Other Mobile Solutions	Epson Smart Panel		Ÿ
Duinten Coffman			*8 PVC/ID card printing
Printer Software	Windows XP SP3 / XP Professional x64 S	Support only on inkjet coated CD/ DVD/ PVC /ID card.	
Operating System Compatibility	Windows Server 2003 / 2008 / 2012 / 2016 / 2019 / 2022 Only printing supported for Windows Server OS		
Mac OS X 10.9.5 or later			
Electrical Specifications			
Electrical Specifications	AC 000 040 V		
Rated Voltage	AC 220-240 V		
Rated Frequency	50 - 60 Hz		© 2023 Epson India Pvt Ltd. All Rights Reserved.
Power Consumption	40.14/		Reproduction in part or in whole, without the written
Operating	19 W		permission from Epson, is strictly prohibited. EPSON is a registered trademark of Seiko Epson Corporation.
Standby	4.4 W		All other products names and other company names
Sleep	0.6 W		used herein are for identification purposes only and are
Power Off	0.2 W		the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights
Noise Level			in those marks. Print samples shown are simulations
PC Printing / Premium Glossy Photo Paper	Sound Power (Black / Colour) 4.9 / 5.0 B(A),   Sound Power (Black / Colour) 4.9 / 5.0 B(A),		only. Specifications and product availability are subject
Best Photo	Sound Pressure (Black / Colour) 37 / 37 dB(A) Sound Pressure (Black / Colour) 40 / 40 dB(A)		to change without notice and may vary between countries. Please check with local Epson offices for
PC Printing / Plain Paper Default <sup>2</sup>	Sound Power (Black / Colour) 6.2 / 6.0 B(A),  Sound Power (Black / Colour) 6.3 / 6.1 B(A),		more information.
. 5 / many / man rapor boladit	Sound Pressure (Black / Colour) 50 / 47 dB(A)	Sound Pressure (Black / Colour) 5.5 / 6.1 B(A),	Apple (Ded and Dlage et al. 1916)
			Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a
Epson Consumable		ge Yield (4R)* Order Code	service mark of Apple Inc.
Black Ink Bottle	3,600 pages	C13T09D198	Android is a tradomark of Cooole Inc.
Cyan Ink Bottle		C13T09D298	Android is a trademark of Google Inc.
Magenta Ink Bottle		C13T09D398	Dealer's Stamp
Yellow Bottle	7,200 (Composite Yield) 2,100 (Cor	mposite Yield) C13T09D498	*

Information correct at time of printing Printed April 2023

C13T09D598

C13T09D698

Light Cyan Bottle

Light Magenta Bottle

**EPSON INDIA PVT. LTD.** 12th Floor, The Millenia, Tower A, No.1, Murphy Road, Ulsoor, Bangalore - 560 008. Tel: 080-4566 5000 I Fax: 080-4566 5005

Ahmedabad - 3314 8500/01, Chennai - 3967 7500, Ernakulam - 4012 315, Coimbatore - 98942 19200, Kolkata - 4603 4729, Mumbai - 3079 8200, New Delhi - 4107 3101, Pune - 3028 6000/05, Hyderabad - 4857 0032, Jaipur - 0141 4923119

