ECOTANK PRINTERS ECOTANK M3140/M3170/M3180





Efficiency meets productivity with the monochrome EcoTank M3140, M3170 and M3180 printers. Powered by PrecisionCore technology, these compact printers deliver laser-quality prints at fast print speeds of 20 ipm. Print well at very low costs of just 12 paise* per print while consuming up to 20X less power⁴ than mono laser printers. This level of power consumption also ensures the least environmental impact. A high print yield of 6,000 prints¹ per refill ensures seamless printing. What's more, these printers are 4-in-1 multifunctional printers, demonstrating how this range is rigorously built down to the last detail along with 3-years warranty coverage³ for peace of mind.

















nty of Etherne



ADF







M3140/M3170/M3180







Designed to support the Sustainable Development Goals (SDGs) set by the UN



Each printer comes bundled with a starter kit of 1 high capacity bottle of Epson genuine ink.

Cutting-edge Printhead Technology

Meet every deadline with swift printing as these printers enable high-quality printing at the speed of 20 ipm.

Multi-functional Edge

Enhance your productivity to a whole new level as these printers enable you to print, scan, copy and fax effortlessly.

Better for the Environment

Low power consumption and less replacement parts compared to laser printers mean less e-waste for a positive impact on the environment.

ECOTANK M3140/M3170/M3180



MODEL NUMBER	M3140	M3170	M3180
Printer Type	Print, Scan, Copy, Fax with ADF		
Printing	D O TH D		
Printing Technology	PrecisionCore™ Printhead		
Nozzle Configuration	400 x 2 nozzles Black		
Print Direction Maximum Resolution	Bi-directional printing 1200 x 2400 dpi (with Variable-Sized Droplet Technology)		
		zed Dropiet Technology)	
Minimum Ink Droplet Volume Print Speed ¹¹	2.8 pl		
	Un to 20 npm		
Draft Text - Memo, A4 (Black ^{#1}) ISO 24734, A4 (Black)	Up to 39 ppm Simplex: Up to 20 ipm, Duplex: 9	0 inm	
First Page Out Time (Black)	Approx. 6 sec (Simplex)	.o ipin	
Printer Language	ESC / P Raster (Factory Use), ES	C / P-R	
Automatic 2-sided printing	Yes	071 11	
Copying			
Copy Speed			
ISO 29183, A4, Simplex (Black)	Up to 17 ipm		
Copy Quality	Standard / Best		
Maximum Copies from Standalone	99 copies 25-400% Auto Fit Function		
Reduction/Enlargement			
Maximum Copy Resolution Maximum Copy Size	600 x 600 dpi, 1200 x 1200 dpi Legal (ADF)		
махітшті сору зіге	Legal (ADF)		
Scanning			
Scanner Type	Flatbed colour image scanner		
Sensor Type	CIS		
Optical Resolution	1200 x 2400 dpi		
Maximum Scan Area	216 x 297 mm (8.5 x 11.7")		
Scanner Bit Depth			
Colour	48-bit input, 24-bit output		
Grayscale	16-bit input, 8-bit output		
Black & White	16-bit input, 1-bit output		
Scan Speed (Flatbed/ADF)	40 aaa/7 inm		
Monochrome 200 dpi	12 sec/7 ipm		
Colour 200 dpi	27 sec/7 ipm		
Fax Function			
Type of Fax	Walk-up black-and-white and co	lour fax capability	
Receive Memory / Page Memory	2 MB, Page memory, Up to 180 pages (ITU-T No.1 chart)		
Error Correction Mode	TU-T T.30		
Fax Speed (Data Transfer Rate)	Up to 33.6 kbps, Approx. 3 sec/page		
Fax Resolution	Up to 200 x 200 dpi		
Transmission Paper Size			
Flatbed	Letter, A4		
ADF	Letter, A4, 8.5 x 13", Legal		
Receiving Paper Size	Letter, A4, Legal		
Speed Dial / Group Dial	Up to 100 numbers, 99 groups PC Fax (Transmission/Receive), Automatic redial, Address book, Transmit Reservation,		
Fax Feature			smit Reservation,
	Broadcast Fax (Mono Only), Polli	ng Reception, Fax Preview	
ADF Function	044 05 4 0		
Support Paper Thickness	64 to 95 g/m²		
Paper Capacity	35 (Legal: 10)		
Paper Handling			
Paper Feed Method	Friction feed		
Number of Paper Trays	2		
Paper Hold Capacity	·		
Input Capacity	Front Tray: 250 Sheets-A4 / Lette	r Plain Paper (80 g/m²); 10-sheets-E	invelope;
	Rear slot: 1 sheet-A4 paper		
Output Capacity	Up to 100 sheets		
Paper Size	Legal, Indian-Legal (215 x 345 mm), 8.5 x 13", Letter, A4, 16K (195 x 270 mm),		
	B5, A5, B6, A6, Hagaki (100 x 148 mm), Envelopes: #10, DL, C6		
Maximum Paper Size	215.9 x 1200 mm (8.5 x 47.24") Top / Rottom / Left / Right: 3		
Print Margin	Top / Bottom / Left / Right: 3		
Interface			
USB	Hi-speed USB		
Network	-	Ethernet, WiFi IEEE 802.11b/g/	/n, WiFi Direct
Network Protocol		TCP/IPv4, TCP/IPv6	
Network Management Protocols	-	SNMP, HTTP, DHCP, BOOTP, A	PIPA, PING, DDNS, mDNS, SLP, WSD, LLTD
Mobile and Cloud Printing			
Epson Connect	_	Epson iPrint, Email Print, Remo	ote Print Driver. Scan to Cloud
Other Mobile Solutions		Apple AirPrint™, Google Cloud	
		_	,
PCL Support	-	-	Yes
Control Panel		- 1	
Control Panel LCD Screen	2.4" LCD Touchscreen		
Printer Software			
Operating System Compatibility	Windows XP / Vista / 7 / 8 / 8.1 / 10 Windows Server 2003 / 2008 / 2012 / 2016		
		ons are supported for Windows Serv	ver OS
	Mac OS X 10.6.8 or later		
Electrical Specifications			
Rated Voltage	AC 220 - 240 V		
Rated Frequency	50 – 60 Hz		
Power Consumption			
Operating	12 W	_ _12 W	_12 W
Standby	5.4 W	5.4 W	5.6 W
Sleep	0.9 W	0.9 W	0.9 W
Power off	0.2 W	0.2 W	0.2 W
	_		
Noise Level (PC Printing)	0.0 B(A) 50 15 (A)		
Plain Paper Default*2	6.9 B(A), 56 dB (A)		
Consumables	Page Yield'3	Order Code	
Standard Black Ink Bottles	2,000	005S	
High Capacity Black Ink Bottles	6,000	005	-
Maintenance Box	-	-	

Dimensions & Weight

M3140 / M3170 / M3180 Weight: 7.2 kg (15.9 lb) / 7.3 kg (16.1 lb) / 7.3 kg (16.1 lb)



*1 Print speed (Pages Per Minute) is calculated when printed on A4 plain paper in the fastest mode. Print speed may vary depending on system configuration, print mode, document complexity, software, type of paper used and connectivity. Print speed does not include processing time on host computer.



#1 Black Text and graphics

- *2 Default mode in accordance with ISO7779 for MFPs.
- 3 Quoted yields are based on the ISO 24711/24712 patterns of mixed text and black-and-white graphics with Epson methodology. Quoted yields are based on the replacement ink bottles purchased. For print quality, part of the ink from the included bottles is used for printer startup so yields could be lower than those of replacement ink bottles. Actual yields will vary due to reasons including images printed, print settings, temperature and humidity. Yields may be lower when printing infrequently. Ink is used for both printing and printhead maintenance.

© 2019 Epson India Pvt. Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Selko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android is a trademark of Google Inc.

Dealer's Stamp

Information correct at time of printing Printed July 2019

EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A, No.1, Murphy Road, Ulsoor, Bangalore - 560 008. Tel: 080-4566 5000 Fax: 080-4566 5005

Regional Offices:

Ahmedabad - 3314 8500/01, Chennai - 3967 7500, Cochin - 4012 315, Coimbatore - 98942 19200, Kolkata - 4603 4714/15/29/30, Mumbai - 3079 8200, New Delhi - 3312 0300, Pune - 3028 6000/05, Hyderabad - 4857 0032, Jaipur - 78699 11699



