HOME THEATRE PROJECTORS EH-TW7100

EPSON



EH-TW7100 Home Theatre Projector

THE BIG SCREEN EXPERIENCE, AT A WHOLE DIFFERENT LEVEL.

The EH-TW7100 has been engineered to create the truest of cinematic experiences in the comfort of your home. 4K PRO-UHD enhancement and a high contrast ratio of 100,000:1 help deliver images in jaw-dropping detail. Equal white and colour brightness levels of 3,000 lumens ensure crystal-clear images irrespective of the ambient light. A wide range of connectivity options enable projection of content from smart devices, cameras, laptops and more.



3X Brighter Colours Epson's Proprietary 3LCD technology produces 3X brighter[#] colours than regular 1-chip DLP projectors.



Wider Lens Shift Range Freedom to project content from any surface/corner without compromising quality.

iProjection

The iProjection app turns a smart device into a remote control. Features include touch-control for easier navigation of menus.

SPECIFICATIONS EH-TW7100

FDSO

MODEL NUMBER		EH-TW7100	Supplied Accessories
Projection Technology		RGB liquid crystal shutter projection system	Supplied Accessories
Specifications o			Power Cable: 3 m
LĊD	Panel Size	1.55 cm (0.61") wide (D10)	Remote Control: Yes, w
	Native Resolution	1080p	Hernote Control. Tes, w
Projection Lens	Туре	Optical Zoom (Manual) / Focus (Manual)	
	F-Number	1.49 - 1.77	Optional Accessories
	Focal Length	18.2 - 29.2 mm	Spare Lamp: ELPLP85
	Zoom Ratio	1 - 1.62	
	Throw Ratio	1.32 - 2.15 (Wide - Tele)	Air Filter Set: ELPAF39
Lamp	Туре	250 W UHE	
Lamp	Life (Normal / Eco) ^{*1}	3,500 hours / 5,000 hours	Wireless LAN Unit: ELPAF
Scroon Size /Pro	pjected Distance)	3,000 110013 7 3,000 110013	
Zoom : Wide	Jected Distance	101.6 1070 cm (1.16 to 14.97 m)	
Zoom : Tele		<u>101.6 - 1270 cm (1.16 to 14.87 m)</u> 101.6 - 1270 cm (1.89 to 24.01 m)	
Brightness ^{*2}		101.0 - 1270 011 (1.09 to 24.01 11)	
3		3,000 lm	
Colour Light Output (Normal)		3,000 lm	
White Light Output (Normal) Contrast Ratio			
		100,000:1	EH-TW7100
Internal Speaker	r(s)		the second
Sound Output		Stereo: 10 W x 2	2 2
Geometric Correction		000 / 000	
Vertical / Horizontal Keystone		±30° / ±30°	
Auto Keystone Correction		N/A	
Quick Corner		Yes	
Lens Shift Rang			
Туре	With standard lens	Manual	
Vertical	H Center, with standard lens		
Horizontal	V Center, with standard lens	-24.0 % to +24.0 %	
Connectivity			
Analog Input	D-Sub 15pin	N/A	
	Composite (Yellow)	N/A	
	S-video	N/A	
	Component	N/A	
Digital Input	HDMI Type A	2	
Audio In	2 RCA (White x 1, Red x 1)	N/A	
Audio Out	Stereo Mini	1	
USB Interface	USB Type A	2 (The one port is for Wireless LAN, Firmware update, Copy OSD Settings. The another port is only	
		for Streaming Media Player with 2000 mA power supply).	
	USB Type B	1	
Network	Wired LAN	N/A	
literio	Wireless LAN	Optional	
Bluetooth speci		optional	
Version	lioutorio	Ver. 3.0	
Output		Class 2	
Communication distance		Approx. 10 m	
Supported profiles		A2DP	
Content protection		SCMS-T	
Frequency used		2.4 GHz band (2.402 to 2.480 GHz)	
Supported codecs		SBC, Qualcomm [®] aptX [™] audio	
Wireless Specifications		(Optional Wireless LAN Unit use)	
Supported Speed For Each Mode		IEEE 802.11b: 11 Mbps	
Supported Speed For Each Mode			
		IEEE 802.11g: 54 Mbps ¹³	
0	antina Maria	IEEE 802.11n: 130 Mbps ^{*3}	
Supported Connection Mode		Infrastructure, Access Point	
Wireless LAN Security		Quick: WPA2-PSK, Advanced: WPA/WPA2-PSK	
Supported Secur		NA	
Adjustment Fun			
Frame Interpolation		Off / Low / Normal / High (2D and 3D Mode)	
Detail Enhancem	ent	Yes (Range / Strength)	© 2025 Epson India Pv
Split Screen		N/A	Reserved. Reproductio
3D Features			without the written per
3D Display		Yes (Auto / 3D / 2D)	is strictly prohibited. EF
2D - 3D Conversion		N/A	trademark of Seiko Eps
3D Format		Side-by-Side / Top and Bottom	products names and of
3D Depth		-10 to +10	used herein are for ider
Operating Temperature		5 °C to 35 °C <41 °F to 95 °F> (over 2286 m / 7500 ft)	and are the trademarks
Operating Altitude		0 m to 3048 m <0 ft to 10000 ft> (over 1500 m / 4921 ft: with High altitude mode)	of their respective own any and all rights in tho
Direct Power On/Off		Yes	shown are simulations
Start-Up Period		19 seconds, Warm-up period: 30seconds	and product availability
Cool Down Period		7 seconds	without notice and may
Power Supply Voltage		100 - 240 V AC +/- 10%, 50/60 Hz	Please check with loca
	ption (220 - 240V)	· · · ·	information.
Lamp On (Norma		387 W / 297 W	
Standby (Network On / Off)		2.0 W/0.5 W	Apple (Dertand (D)
Dimension Excluding Feet (D X W X H)		310 x 410 x 157 mm	Apple, iPad and iPhone
Weight			Inc., registered in the U
Fan Noise (Normal / Eco)		Approx. 6.9 kg 35 dB / 24 dB	App Store is a service r
Warranty		2 Year for projector against standard manufacturing defects;	Android is a trademark
		1 Year or 1000 hrs on Lamp, whichever comes first	
1 Loron life will you (and a second	nmental conditions and usage. Lamo brightness decreases over time	Information correct as o

ower Cable: 3 m

emote Control: Yes, with Alkaline AA Battery x 2

ptional Accessories

/ireless LAN Unit: ELPAP10

H-TW7100



2025 Epson India Pvt. Ltd. All Rights eserved. Reproduction in part or in whole, eserved. Reproduction in part or in whole, ithout the written permission from Epson, strictly prohibited. EPSON is registered ademark of Seiko Epson Corporation. All other roducts names and other company names sed herein are for identification purposes only nd are the trademarks or registered trademarks nd are the trademarks or registered trademark f their respective owners. Epson disclaims ny and all rights in those marks. Print samples hown are simulations only. Specifications nd product availability are subject to change ithout notice and may vary between countries. lease check with local Epson offices for more formation.

pple, iPad and iPhone are trademarks of Apple nc., registered in the U.S. and other countries. pp Store is a service mark of Apple Inc.

ndroid is a trademark of Google Inc.

Information correct as of January 2025.

¹ Lamp life will vary depending upon mode selected, environmental conditions and usage, Lamp brightness decreases over time,

² Colour brightness (colour light output) and white brightness (white light output) will vary depending on usage conditions. Colour light output measured in accordance with IDMS 15:4; white light output measured in accordance with ISO 21118.

¹³ Maximum speed and range is achievable when used with same enhanced mode technology. Actual data rates, features and performance may vary depending on your computer system, the environment and other factors.


EPSON INDIA PVT. LTD.

11th Floor, Godrej Centre, Hebbal, Survey No.26, Bellary Road, Sahakar Nagar, Byatarayanapura, Bangalore 560 092, Karnataka. Tel: 080 6939 5000. Fax: 080 6939 5005

Regional Offices:

Ahmedabad 4037 0075, Chennai 4905 5177, Coimbatore 98942 19200, Ernakulam 4012 315, Hyderabad 4857 0032, Jaipur 4923 119, Kolkata 4603 4714/15/29/30, Mumbai 3079 8200, New Delhi 4107 3101, 4752 2414, Pune 2998 0641





www.epson.co.in

Dealer's Stamp